

COMP2610 / COMP6261 - Information Theory

Lecture 5: Bernoulli, Binomial, Maximum Likelihood and MAP

Assignment Project Exam Help

Robert Williamson

<https://powcoder.com>

Research School of Computer Science



Australian
National
University

Add WeChat powcoder

6 August 2018

Assignment Project Exam Help

- Examples of application of Bayes' rule
 - ▶ Formalizing problems in language of probability
 - ▶ Eating hamburgers, detecting terrorists, ...
- Frequentist vs Bayesian probabilities

Add WeChat powcoder

The Bayesian Inference Framework

Bayesian Inference

Bayesian inference provides us with a mathematical framework explaining how to change our (prior) beliefs in the light of new evidence

$$\begin{array}{c} \text{likelihood} \quad \text{prior} \\ \underbrace{p(X|Z)}_{\text{evidence}} \underbrace{p(Z)}_{\text{prior}} \\ \hline p(Z|X) \\ \text{posterior} \end{array}$$

<https://powcoder.com>

$$\text{Add WeChat } \frac{p(X|Z)p(Z)}{\sum_Z p(X|Z)p(Z)}$$

Prior: Belief that someone is sick

Likelihood: Probability of testing positive given someone is sick

Posterior: Probability of being sick given someone tests positive

This time

Assignment Project Exam Help

- The Bernoulli and binomial distribution (we will make much use of this henceforth in studying binary channels)

<https://powcoder.com>

- Estimating probabilities from data

Add WeChat powcoder

- Bayesian inference for parameter estimation

Outline

1 The Bernoulli Distribution

2 The Binomial Distribution

3 Parameter Estimation

4 Bayesian Parameter Estimation

5 Wrapping up

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

1 The Bernoulli Distribution

Assignment Project Exam Help

2 The Binomial Distribution

3 <https://powcoder.com>

4 Bayesian Parameter Estimation

Add WeChat powcoder

5 Wrapping up

The Bernoulli Distribution

Introduction

Consider a binary variable $X \in \{0, 1\}$. It could represent many things:

- Whether a coin lands heads or tails
- The presence/absence of a word in a document
- A transmitted bit in a message
- The success of a medical trial

Often, these outcomes (0 or 1) are not equally likely

What is a general way to model such an X ?

The Bernoulli Distribution

Definition

Assignment Project Exam Help

The variable X takes on the outcomes

$$X = \begin{cases} 1 & \text{probability } \theta \\ 0 & \text{probability } 1 - \theta \end{cases}$$

<https://powcoder.com>

Here, $0 \leq \theta \leq 1$ is a parameter representing the probability of success

For higher values of θ , it is more likely to see 1 than 0

Add WeChat powcoder

- e.g. a biased coin

The Bernoulli Distribution

Definition

By definition,

$$p(X = 1|\theta) = \theta$$

$$p(X = 0|\theta) = 1 - \theta$$

More succinctly,

$$p(X = x|\theta) = \theta^x(1 - \theta)^{1-x}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Bernoulli Distribution

Definition

By definition,

$$p(X = 1|\theta) = \theta$$

$$p(X = 0|\theta) = 1 - \theta$$

More succinctly,

$$p(X = x|\theta) = \theta^x(1 - \theta)^{1-x}$$

This is known as a Bernoulli distribution over binary outcomes:

$$p(X = x|\theta) = \text{Bern}(x|\theta) = \theta^x(1 - \theta)^{1-x}$$

Note the use of the conditioning symbol for θ ; will revisit later

The Bernoulli Distribution

Mean and Variance

The **expected value** (or mean) is given by:

$$\mathbb{E}[X|\theta] = \sum_{x \in \{0,1\}} x \cdot p(x|\theta)$$

$$= 1 \cdot p(X = 1|\theta) + 0 \cdot p(X = 0|\theta)$$

$$= \theta$$

<https://powcoder.com>

The **variance** (or squared standard deviation) is given by:

$$\mathbb{V}[X|\theta] = \mathbb{E}[(X - \mathbb{E}[X])^2]$$

$$= \mathbb{E}[(X - \theta)^2]$$

$$= (0 - \theta)^2 \cdot p(X = 0|\theta) + (1 - \theta)^2 \cdot p(X = 1|\theta)$$

$$= \theta(1 - \theta).$$

Add WeChat powcoder

Example: Binary Symmetric Channel

Suppose a sender transmits messages s that are sequences of bits

The receiver sees the bit sequence (message)


Assignment Project Exam Help

Due to noise in the channel, the message is flipped with probability

$$0 \leq f \leq 1$$


<https://powcoder.com>

Add WeChat powcoder



Example: Binary Symmetric Channel

We can think of r as the outcome of a **random variable**, with conditional distribution given by:



$$p(r=0|s=0) = 1-f$$
$$p(r=1|s=0) = f$$

$$p(r=0|s=1) = f$$

$$p(r=1|s=1) = 1-f$$

If E denotes whether an error occurred, clearly

$$p(E=e) = \text{Bern}(e|f), \quad e \in \{0, 1\}.$$

1 The Bernoulli Distribution

Assignment Project Exam Help

2 The Binomial Distribution

3 Parameter Estimation

<https://powcoder.com>

4 Bayesian Parameter Estimation

Add WeChat powcoder

5 Wrapping up

The Binomial Distribution

Introduction

Suppose we perform N independent Bernoulli trials

- e.g. we toss a coin N times
- e.g. we transmit a sequence of N bits across a noisy channel

Each trial has probability θ of success

What is the distribution of the number of times (m) that $X = 1$?

- e.g. the number of times we obtained m heads
- e.g. the number of errors in the transmitted sequence

The Binomial Distribution

Definition

Let

Assignment Project Exam Help

where $X_i \sim \text{Bern}(\theta)$.

Then Y has a binomial distribution with parameters N, θ .

$$p(Y = m) = \text{Bin}(m|N, \theta) = \binom{N}{m} \theta^m (1 - \theta)^{N-m}$$

Add WeChat powcoder

for $m \in \{0, 1, \dots, N\}$. Here

$$\binom{N}{m} = \frac{N!}{(N-m)!m!}$$

is the # of ways we can we obtain m heads out of N coin flips

The Binomial Distribution:

Mean and Variance

It is easy to show that:

$$\mathbb{E}[Y] = \sum_{m=0}^N m \cdot \text{Bin}(m|N, \theta) = N\theta$$

$$\mathbb{V}[Y] = \sum_{m=0}^N (m - \mathbb{E}[m])^2 \cdot \text{Bin}(m|N, \theta) = N\theta(1 - \theta)$$

- Follows from linearity of mean and variance

$$\mathbb{E}[Y] = \mathbb{E}\left[\sum_{i=1}^N X_i\right] = \sum_{i=1}^N \mathbb{E}[X_i] = N\theta$$

$$\mathbb{V}[Y] = \mathbb{V}\left[\sum_{i=1}^N X_i\right] = \sum_{i=1}^N \mathbb{V}[X_i] = N\theta(1 - \theta)$$

The Binomial Distribution:

Example

Ashton is an excellent off spinner. The probability of him getting a wicket during a cricket match is $\frac{1}{4}$. (That is, on each attempt, there is a $1/4$ chance he will get a wicket.)

His coach commands him to make 10 attempts of wickets in a particular game.


- 1 What is the probability that he will get exactly three wickets?
 $\text{Bin}(3|10, 0.25)$

- 2 What is the expected number of wickets he will get?
 $\mathbb{E}[Y]$, where $Y \sim \text{Bin}(\cdot|10, 0.25)$.

- 3 What is the probability that he will get at least one wicket?
 $\sum_{m=1}^{10} \text{Bin}(m|N = 10, \theta = 0.25) = 1 - \text{Bin}(m = 0|N = 10, \theta = 0.25)$

The Binomial Distribution:

Example: Distribution of the Number of Wickets



Histogram of the binomial distribution with $N = 10$ and $\theta = 0.25$. From Bishop (PRML, 2006)

1 The Bernoulli Distribution

Assignment Project Exam Help

2 The Binomial Distribution

3 Parameter Estimation

<https://powcoder.com>

4 Bayesian Parameter Estimation

Add WeChat powcoder

5 Wrapping up

The Bernoulli Distribution: Parameter Estimation

Consider the set of observations $\mathcal{D} = \{x_1, \dots, x_n\}$ with $x_i \in \{0, 1\}$

- The outcomes of a sequence of coin flips

- Whether or not there are errors in a transmitted bit string

Each observation is the outcome of a random variable X , with distribution

$$p(X = x) = \text{Bern}(x|\theta) = \theta^x (1 - \theta)^{1-x}$$

for some parameter θ

The Bernoulli Distribution: Parameter Estimation

We know that

Assignment Project Exam Help

$$X \sim \text{Bern}(x|\theta) = \theta^x (1 - \theta)^{1-x}$$

But often, we don't know what the value of θ is

- The probability of a coin toss resulting in heads
- The probability of the word defence appearing in a document about sports

What would be a reasonable estimate for θ from \mathcal{D} ?

The Bernoulli Distribution: Parameter Estimation:

Maximum Likelihood

Assignment Project Exam Help

Say that we observe

$\mathcal{D} = \{0, 0, 0, 1, 0, 0, 1, 0, 0, 0\}$
<https://powcoder.com>

Intuitively, which seems more plausible: $\theta = \frac{1}{2}$? $\theta = \frac{1}{5}$?

Add WeChat [powcoder](https://powcoder.com)

The Bernoulli Distribution: Parameter Estimation:

Maximum Likelihood

Say that we observe

$$\mathcal{D} = \{0, 0, 0, 1, 0, 0, 1, 0, 0, 0\}$$

If it were true that $\theta = \frac{1}{2}$, then the probability of this sequence would be

<https://powcoder.com>

$$p(\mathcal{D}|\theta) = \prod_{i=1}^{10} p(x_i|\theta)$$

Add WeChat [powcoder](https://powcoder.com)

$$= \prod_{i=1}^{10} \frac{1}{2}$$

$$= \frac{1}{2^{10}}$$

$$\approx 0.001.$$

The Bernoulli Distribution: Parameter Estimation:

Maximum Likelihood

Say that we observe

$$\mathcal{D} = \{0, 0, 0, 1, 0, 0, 1, 0, 0, 0\}$$

If it were true that $\theta = \frac{1}{5}$, then the probability of this sequence would be

$$\begin{aligned} p(\mathcal{D}|\theta) &= \prod_{i=1}^{10} p(x_i|\theta) \\ &= \left(\frac{1}{5}\right)^2 \cdot \left(\frac{4}{5}\right)^8 \\ &\approx 0.007. \end{aligned}$$

The Bernoulli Distribution: Parameter Estimation:

Maximum Likelihood

We can write down how likely \mathcal{D} is under the Bernoulli model. Assuming independent observations.

$$p(\mathcal{D}|\theta) = \prod_{i=1}^N p(x_i|\theta) = \prod_{i=1}^N \theta^{x_i} (1-\theta)^{1-x_i}$$

We call $L(\theta) = p(\mathcal{D}|\theta)$ the **likelihood** function

Add WeChat powcoder

The Bernoulli Distribution: Parameter Estimation:

Maximum Likelihood

We can write down how likely \mathcal{D} is under the Bernoulli model. Assuming independent observations.

$$p(\mathcal{D}|\theta) = \prod_{i=1}^N p(x_i|\theta) = \prod_{i=1}^N \theta^{x_i} (1-\theta)^{1-x_i}$$

We call $L(\theta) = p(\mathcal{D}|\theta)$ the **likelihood** function

Maximum likelihood principle: We want to maximize this function wrt θ

The parameter for which the observed sequence has the highest probability

The Bernoulli Distribution: Parameter Estimation:

Maximum Likelihood

Maximising $p(\mathcal{D}|\theta)$ is equivalent to maximising $\mathcal{L}(\theta) = \log p(\mathcal{D}|\theta)$

Assignment Project Exam Help

$$\mathcal{L}(\theta) = \log p(\mathcal{D}|\theta) = \sum_{i=1}^N \log p(x_i|\theta) = \sum_{i=1}^N [x_i \log \theta + (1 - x_i) \log(1 - \theta)]$$

<https://powcoder.com>

Add WeChat powcoder

The Bernoulli Distribution: Parameter Estimation:

Maximum Likelihood

Maximising $p(\mathcal{D}|\theta)$ is equivalent to maximising $\mathcal{L}(\theta) = \log p(\mathcal{D}|\theta)$

Assignment Project Exam Help

$$\mathcal{L}(\theta) = \log p(\mathcal{D}|\theta) = \sum_{i=1}^N \log p(x_i|\theta) = \sum_{i=1}^N [x_i \log \theta + (1 - x_i) \log(1 - \theta)]$$

<https://powcoder.com>

Setting $\frac{d\mathcal{L}}{d\theta} = 0$ we obtain:

$$\theta_{\text{ML}} = \frac{1}{N} \sum_{i=1}^N x_i$$

Add WeChat powcoder

The Bernoulli Distribution: Parameter Estimation:

Maximum Likelihood

Maximising $p(\mathcal{D}|\theta)$ is equivalent to maximising $\mathcal{L}(\theta) = \log p(\mathcal{D}|\theta)$

$$\mathcal{L}(\theta) = \log p(\mathcal{D}|\theta) = \sum_{i=1}^N \log p(x_i|\theta) = \sum_{i=1}^N [x_i \log \theta + (1 - x_i) \log(1 - \theta)]$$

Setting $\frac{d\mathcal{L}}{d\theta} = 0$ we obtain:

$$\theta_{\text{ML}} = \frac{1}{N} \sum_{i=1}^N x_i$$

The proportion of times $x = 1$ in the dataset \mathcal{D} !

The Bernoulli Distribution:

Parameter Estimation — Issues with Maximum Likelihood

Consider the following scenarios:

- After $N = 3$ coin flips we obtained 3 ‘tails’
 - ▶ What is the estimate of the probability of a coin flip resulting in ‘heads’?
- In a small set of documents about sports, the words *defence* never appeared
 - ▶ What are the consequences when predicting whether a document is about sports (using Bayes’ rule)?

Add WeChat powcoder

The Bernoulli Distribution:

Parameter Estimation — Issues with Maximum Likelihood

Consider the following scenarios:

- After $N = 3$ coin flips we obtained 3 ‘tails’
 - ▶ What is the estimate of the probability of a coin flip resulting in ‘heads’?
- In a small set of documents about sports, the words *defence* never appeared
 - ▶ What are the consequences when predicting whether a document is about sports (using Bayes’ rule)?

These issues are usually referred to as **overfitting**

- Need to “smooth” out our parameter estimates
- Alternatively, we can do Bayesian inference by considering **priors** over the parameters

1 The Bernoulli Distribution

Assignment Project Exam Help

2 The Binomial Distribution

3 Parameter Estimation
<https://powcoder.com>

4 Bayesian Parameter Estimation

Add WeChat powcoder

5 Wrapping up

The Bernoulli Distribution:

Parameter Estimation: Bayesian Inference

Recall:

$$\underbrace{p(\theta|X)}_{\text{posterior}} = \frac{\underbrace{p(X|\theta)}_{\text{likelihood}} \underbrace{p(\theta)}_{\text{prior}}}{\underbrace{p(X)}_{\text{evidence}}}$$

<https://powcoder.com>

If we treat θ as a random variable, we may have some **prior** belief $p(\theta)$ about its value

- e.g. we believe θ is probably close to 0.5

Add WeChat powcoder

Our **prior** on θ quantifies what we believe θ is likely to be, **before** looking at the data

Our **posterior** on θ quantifies what we believe θ is likely to be, **after** looking at the data

The Bernoulli Distribution:

Parameter Estimation: Bayesian Inference

The likelihood of X given θ is

Assignment Project Exam Help

$$\text{Bern}(x|\theta) = \theta^x(1 - \theta)^{1-x}$$

<https://powcoder.com>

For the prior, it is mathematically convenient to express it as a Beta distribution:

$$\text{Beta}(\theta|a, b) = \frac{1}{Z(a, b)} \theta^{a-1} (1 - \theta)^{b-1},$$





Add WeChat powcoder

where $Z(a, b)$ is a suitable normaliser

We can tune a, b to reflect our belief in the range of likely values of θ

Beta Prior

Examples



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Beta Prior and Binomial Likelihood:

Beta Posterior Distribution

Recall that for $\mathcal{D} = \{x_1, \dots, x_N\}$, the likelihood under a Bernoulli model is:

$p(\mathcal{D}|\theta) = \theta^m (1-\theta)^\ell$, **Assignment Project Exam Help**

where $m = \#(x = 1)$ and $\ell \stackrel{\text{def}}{=} N - m = \#(x = 0)$.

<https://powcoder.com>

Add WeChat powcoder

Beta Prior and Binomial Likelihood:

Beta Posterior Distribution

Recall that for $\mathcal{D} = \{x_1, \dots, x_N\}$, the likelihood under a Bernoulli model is:

Assignment Project Exam Help

where $m = \#(x = 1)$ and $\ell \stackrel{\text{def}}{=} N - m = \#(x = 0)$.

For the prior $p(\theta|a, b) = \text{Beta}(\theta|a, b)$ we can obtain the posterior:

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned} p(\theta|\mathcal{D}, a, b) &= \frac{p(\mathcal{D}|\theta)p(\theta|a, b)}{p(\mathcal{D}|a, b)} \\ &= \frac{p(\mathcal{D}|\theta)p(\theta|a, b)}{\int_0^1 p(\mathcal{D}|\theta)p(\theta|a, b)d\theta} \\ &= \text{Beta}(\theta|m + a, \ell + b). \end{aligned}$$

Beta Prior and Binomial Likelihood:

Beta Posterior Distribution

Recall that for $\mathcal{D} = \{x_1, \dots, x_N\}$, the likelihood under a Bernoulli model is:

Assignment $p(\mathcal{D}|\theta) = \theta^m (1-\theta)^\ell$, Exam Help

where $m = \#(x = 1)$ and $\ell \stackrel{\text{def}}{=} N - m = \#(x = 0)$.

For the prior $p(\theta|a, b) = \text{Beta}(\theta|a, b)$ we can obtain the posterior:

<https://powcoder.com>

$$p(\theta|\mathcal{D}, a, b) = \frac{p(\mathcal{D}|\theta)p(\theta|a, b)}{p(\mathcal{D}|a, b)}$$

Add WeChat [powcoder](https://powcoder.com)

$$\begin{aligned} &= \frac{p(\mathcal{D}|\theta)p(\theta|a, b)}{\int_0^1 p(\mathcal{D}|\theta)p(\theta|a, b)d\theta} \\ &= \text{Beta}(\theta|m + a, \ell + b). \end{aligned}$$

Can use this as our new prior if we see more data!

Beta Prior and Binomial Likelihood:

Beta Posterior Distribution

Now suppose we choose θ_{MAP} to maximise $p(\theta|\mathcal{D})$

(MAP= Maximum A Posteriori)

One can show that

$$\theta_{\text{MAP}} = \frac{m + a - 1}{N + a + b - 2}$$

cf. the estimate that did not use any prior,

$$\theta_{\text{ML}} = \frac{m}{N}$$

The prior parameters a and b can be seen as adding some “fake” trials!

What values of a and b ensure $\theta_{\text{MAP}} = \theta_{\text{ML}}$? $a = b = 1$. Make sense?

(Note that the choice of the beta distribution was not accidental here — it is the “conjugate prior” for the binomial distribution.)

1 The Bernoulli Distribution

Assignment Project Exam Help

2 The Binomial Distribution

3 Parameter Estimation

<https://powcoder.com>

4 Bayesian Parameter Estimation

Add WeChat powcoder

5 Wrapping up

Assignment Project Exam Help

- Distributions involving binary random variables
 - ▶ Bernoulli distribution

<https://powcoder.com>

- ▶ Binomial distribution
- Bayesian inference: Full posterior on the parameters
 - ▶ Beta prior and binomial likelihood \rightarrow Beta posterior
- Reading: Mackay §23.1 and §23.5; Bishop §2.1 and §2.2

Add WeChat powcoder

Next time

Assignment Project Exam Help

- Entropy <https://powcoder.com>

Add WeChat powcoder