COMP2610 / COMP6261 Information Theory

Lecture 2: First Steps and Basic Probability

Assignment Project Exam Help

Robert C. Williamson

https://powcoder.com

Research School of Computer Science
The Australian National University

Australian
National
University

Add WeChat powcoder

July 24, 2018

Outline

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

A General Communication System



Assignment Project Exam Help
https://powcoder.com

Source : The information source that generates the message to be communicated

Add WeChat powcoder

Encoder : Operates on the message to produce a signal suitable for transmission

Channel : The medium used to transmit the signal

Decoder : Reconstructs the message from the signal

Destination : The entity that receives the message

Communication over Noisy Channels

Assignment Project Exam Help

A channel is some medium for transmitting messages

A noisy channel is a channel that potentially introduces errors in the sender's message

https://powcoder.com

The Problem of Communication

"The fundamental problem of communication is that of reproducing at one point either exactly or approximately a message selected at another point." (Claude Shannon, 1948)

Add WeChat powcoder

Example: Telephone Network

Assignment Project Exam Help



https://powcoder.com

Add WeChat powcoder

Source : Aditya

Encoder : Telephone handset

Channel : Analogue telephone line

Decoder : Telephone handset

Destination : Mark

Examples of Noisy Communication Channels

Other examples of noisy channels:

- A radio communication link
- VDSL NBN connection
- The complete link from camera, through editing, Netflix, the rest of the internet, VDSL link to home, wifi to TV screen
- Reproducing cells
- A magnetic hard disk drive
  - Channel does not need to involve physical movement

What would the other components be for each of these channels?

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Uncertainty in Communication

Assignment Project Exam Help

We cannot avoid uncertainty when

1. Dealing with noise (imperfections) in the channel

https://powcoder.com

2. "Compressing" the messages (compare a high-resolution photograph of a manuscript with the typed text that captures the essence; or a transcript of a spoken utterance)

Add WeChat powcoder

Channel Noise

Assignment Project Exam Help

A noisy channel introduces errors in sender's message

https://powcoder.com

Thus, receiver is uncertain that the message is what the sender intended

How to model, quantify, and mitigate this uncertainty?

Add WeChat powcoder

Message Compression – I

Cover and Thomas, Example 1.1.2

Assignment Project Exam Help

- Suppose we'd like to relay the outcome of an 8 horse race to a friend
  - We wish to convey one of $\{$ `A`, `B`, ..., `H` $\}$
- Suppose we encode the message as a binary string. A natural coding scheme is

https://powcoder.com

$$\begin{aligned} \texttt{A} &\rightarrow \texttt{000} \\ \texttt{B} &\rightarrow \texttt{001} \\ \texttt{C} &\rightarrow \texttt{010} \\ &\vdots \\ \texttt{H} &\rightarrow \texttt{111} \end{aligned}$$

Add WeChat powcoder

Message Compression – II

Cover and Thomas, Example 1.1.2

- Now say the probabilities of the horses winning are $(1/2, 1/4, 1/8, 1/16, 1/64, 1/64, 1/64, 1/64)$
- Encoding messages based on their probability of the being chosen will give shorter expected lengths:

$$\begin{aligned}
\mathtt{A} &\rightarrow \mathtt{0} \\
\mathtt{B} &\rightarrow \mathtt{10} \\
\mathtt{C} &\rightarrow \mathtt{110} \\
\mathtt{D} &\rightarrow \mathtt{1110} \\
\mathtt{E} &\rightarrow \mathtt{11110} \\
\mathtt{F} &\rightarrow \mathtt{111100} \\
\mathtt{G} &\rightarrow \mathtt{111101} \\
\mathtt{H} &\rightarrow \mathtt{111111}
\end{aligned}$$

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

What is “Information”?

Assignment Project Exam Help

For noise correction and message compression, we will need to quantify the information contained in a message

Roughly, “information” measures how much:

https://powcoder.com

- Unexpected data a message contains

Add WeChat powcoder

- The receiver’s uncertainty is reduced on seeing the message

The Case for Probability

We run into the notion of uncertainty when trying to pin down:

1. How to deal with channel noise
2. How to compress messages
3. What "information" means

To make progress, we need to formalise uncertainty

We will do this using probability theory

We now commence our *review* of probability; this will be hard going if you have not met it before!

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Probability: Example

Quantification and Manipulation of Uncertainty (Bishop, PRML, 2006)

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder



Probability: Example

Quantification and Manipulation of Uncertainty (Bishop, PRML, 2006)

1. Pick a box at random

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder



Probability: Example

Quantification and Manipulation of Uncertainty (Bishop, PRML, 2006)

1. Pick a box at random
2. From the selected box, pick a fruit (apple or orange) at random

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder



Probability: Example

Quantification and Manipulation of Uncertainty (Bishop, PRML, 2006)

1. Pick a box at random
2. From the selected box, pick a fruit (apple or orange) at random
3. Observe the fruit type and return it back to the original box

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder



Probability: Example

Quantification and Manipulation of Uncertainty (Bishop, PRML, 2006) — Cont'd

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder



- Identity of the box is a random variable $B \in \{r, b\}$
- Identity of the fruit is a random variable $F \in \{a, o\}$

Probability: Example

Quantification and Manipulation of Uncertainty (Bishop, PRML, 2006) — Cont'd

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder



- Identity of the box is a random variable $B \in \{r, b\}$
- Identity of the fruit is a random variable $F \in \{a, o\}$

Probability of an event: Proportion of times it happens out of a large number of trials

Probability: Example

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder



Suppose we repeat the selection process many times, and ended up picking up the blue box 60% of the time and the red box 40% of the time

- $p(B = r) = 0.4$, $p(B = b) = 0.6$

Probability: Basic Properties

By definition, $0 \leq p(B = b) \leq 1$ and $0 \leq p(B = r) \leq 1$

Assignment Project Exam Help

Outcomes are mutually exclusive:

$$\begin{aligned} p(B = r \texttt{ AND } B = b) &= p(B = r, B = b) \\ &= 0 \end{aligned}$$

https://powcoder.com

Outcomes are jointly exhaustive:

Add WeChat powcoder

$$\begin{aligned} p(B = r \texttt{ OR } B = b) &= p(B = r) + p(B = b) - p(B = r \texttt{ AND } B = b) \\ &= p(B = r) + p(B = b) \\ &= 1 \end{aligned}$$

Probability

What Types of Questions Can We Answer?

Assignment Project Exam Help

- What is the probability of picking the red box, and an apple within that box?

https://powcoder.com

- What is the (overall) probability of picking up an apple?

Add WeChat powcoder

- Given that we selected a red box, what is the probability of selecting an apple?

We can answer these and more complex questions by using the *rules of probability*.

Joint Probability

What is the probability of selecting the red box and selecting an apple?

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Joint Probability

What is the probability of selecting the red box and selecting an apple?

Assignment Project Exam Help

Joint Probability of a Set of Events

The proportion of times these events happened together out of the total number of trials.

https://powcoder.com

Add WeChat powcoder

Joint Probability

What is the probability of selecting the red box and selecting an apple?

Assignment Project Exam Help

Joint Probability of a Set of Events

The proportion of times these events happened together out of the total number of trials.

https://powcoder.com

If we repeated our experiment many (say $N = 100$) times, and in 10 of the trials we saw $B = r$ and $F = a$, then we may estimate

Add WeChat powcoder

$$\begin{aligned} p(B = r \texttt{ AND } F = a) &= p(B = r, F = a) \\ &= \frac{10}{100} \\ &= 0.1 \end{aligned}$$

Marginal Probability

What is the probability of an apple being picked, regardless of the box we selected?

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Marginal Probability

What is the probability of an apple being picked, regardless of the box we selected?

Assignment Project Exam Help

Marginal Probability of an Event

The proportion of times that this event happened out of the total number of trials.

https://powcoder.com

Add WeChat powcoder

Marginal Probability

What is the probability of an apple being picked, regardless of the box we selected?

Assignment Project Exam Help

Marginal Probability of an Event

The proportion of times that this event happened out of the total number of trials.

https://powcoder.com

Remember that we selected a red box and an apple in 10 out of 100 trials

Say that in 45 of the trials, we selected a blue box and an apple

Add WeChat powcoder

So, irrespective of B, an apple was selected $45 + 10 = 55$ times, and:

$$p(F = a) = \frac{55}{100} = \frac{11}{20}$$

Conditional Probability

What is the probability of an apple being picked up, given that a red box was selected?

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Conditional Probability

What is the probability of an apple being picked up, given that a red box was selected?

Conditional Probability of an Event

The conditional probability of an event X with respect to an event Y is the proportion of times that X happens out of the times that Y happens.

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Conditional Probability

What is the probability of an apple being picked up, given that a red box was selected?

Conditional Probability of an Event

The conditional probability of an event X with respect to an event Y is the proportion of times that X happens out of the times that Y happens.

Assignment Project Exam Help

https://powcoder.com

The trials where we selected a blue box are irrelevant, whether or not an apple was selected

We selected a red box and an apple 10 out of 100 times

Add WeChat powcoder

We selected a red box (regardless of the fruit) 40 out of 100 times

$$p(F = a \,\texttt{GIVEN}\, B = r) = p(F = a | B = r) = \frac{10}{40} = \frac{1}{4}$$

Conditional Probability

What is the probability of an apple being picked up, given that a red box was selected?

Conditional Probability of an Event

The conditional probability of an event X with respect to an event Y is the proportion of times that X happens out of the times that Y happens.

Assignment Project Exam Help

https://powcoder.com

The trials where we selected a blue box are irrelevant, whether or not an apple was selected

We selected a red box and an apple 10 out of 100 times

Add WeChat powcoder

We selected a red box (regardless of the fruit) 40 out of 100 times

$$p(F = a \,\texttt{GIVEN}\, B = r) = p(F = a|B = r) = \frac{10}{40} = \frac{1}{4}$$

Can we write this in terms of the joint and marginal probabilities?

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Joint, Marginal and Conditional Probabilities:

A More General Formulation (1)

Consider the more general case of two random variables:

$X \in \{x_1, x_2, \ldots, x_M\}$ and $Y \in \{y_1, y_2, \ldots, y_L\}$

Assignment Project Exam Help



https://powcoder.com

Add WeChat powcoder

N : Total number of trials

Joint, Marginal and Conditional Probabilities:

A More General Formulation (1)

Consider the more general case of two random variables:

$X \in \{x_1, x_2, \ldots, x_m\}$ and $Y \in \{y_1, y_2, \ldots, y_L\}$

Assignment Project Exam Help



https://powcoder.com
Add WeChat powcoder

N : Total number of trials

n_{ij} : $\sharp(X = x_i, Y = y_j)$ = $\sharp$ of times that x_i and y_i happen

Joint, Marginal and Conditional Probabilities:

A More General Formulation (1)

Consider the more general case of two random variables:

$X \in \{x_1, x_2, \ldots, x_I\}$ and $Y \in \{y_1, y_2, \ldots, y_J\}$

Assignment Project Exam Help



https://powcoder.com

Add WeChat powcoder

N : Total number of trials

n_{ij} : $\sharp(X = x_i, Y = y_j)$ = $\sharp$ of times that x_i and y_i happen

c_i : $\sharp(X = x_i) = \sum_j n_{ij}$ = $\sharp$ of times that x_i happens

Joint, Marginal and Conditional Probabilities:

A More General Formulation (1)

Consider the more general case of two random variables:

$X \in \{x_1, x_2, \ldots, x_I\}$ and $Y \in \{y_1, y_2, \ldots, y_J\}$

Assignment Project Exam Help
https://powcoder.com



Add WeChat powcoder

N : Total number of trials

n_{ij} : $\sharp(X = x_i, Y = y_j)$ = $\sharp$ of times that x_i and y_i happen

c_i : $\sharp(X = x_i) = \sum_j n_{ij}$ = $\sharp$ of times that x_i happens

r_j : $\sharp(Y = y_j) = \sum_i n_{ij}$ = $\sharp$ of times that y_j happens

Joint, Marginal and Conditional Probabilities:

A More General Formulation (2)



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

By definition:

$$p(X = x_i, Y = y_j) = \frac{n_{ij}}{N} \text{ (Joint)}$$

$$p(X = x_i) = \frac{c_i}{N} \text{ (Marginal)}$$

$$p(Y = y_j) = \frac{r_j}{N} \text{ (Marginal)}$$

$$p(Y = y_j | X = x_i) = \frac{n_{ij}}{c_i} \text{ (Conditional)}$$

Joint, Marginal and Conditional Probabilities:

A More General Formulation (1)

Assignment Project Exam Help

Bins and fruit example:

https://powcoder.com

	Orange	Apple
Blue	15	45
Red	30	10

Add WeChat powcoder

Verify the computations from previous section with this table.

Joint, Marginal and Conditional Probabilities:

A More General Formulation (3)



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Observe:

$$p(X = x_i) = \frac{\sum_j n_{ij}}{N}$$
$$= \sum_j p(X = x_i, Y = y_j)$$

$$p(Y = y_j | X = x_i) = \frac{n_{ij}}{c_i} = \frac{n_{ij}}{N} \Big/ \frac{c_i}{N}$$
$$= p(X = x_i, Y = y_j)/p(X = x_i)$$

The Rules of Probability

Sum Rule / Marginalization :

$$p(X = x_i) = \sum_j p(X = x_i, Y = y_j)$$

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

The Rules of Probability

Sum Rule / Marginalization :

$$p(X = x_i) = \sum_j p(X = x_i, Y = y_j)$$

Assignment Project Exam Help

Product Rule :

$$p(X = x_i, Y = y_j) = p(Y = y_j | X = x_i) p(X = x_i)$$

https://powcoder.com

Add WeChat powcoder

The Rules of Probability

Sum Rule / Marginalization :

$$p(X = x_i) = \sum_j p(X = x_i, Y = y_j)$$

Assignment Project Exam Help

Product Rule :

$$p(X = x_i, Y = y_j) = p(Y = y_j | X = x_i) p(X = x_i)$$

https://powcoder.com

and by symmetry:

$$p(Y = y_j, X = x_i) = p(X = x_i | Y = y_j) p(Y = y_j)$$

Add WeChat powcoder

The Rules of Probability

Sum Rule / Marginalization :

$$p(X = x_i) = \sum_j p(X = x_i, Y = y_j)$$

Assignment Project Exam Help

Product Rule :

$$p(X = x_i, Y = y_j) = p(Y = y_j | X = x_i) p(X = x_i)$$

https://powcoder.com

and by symmetry:

$$p(Y = y_j, X = x_i) = p(X = x_i | Y = y_j) p(Y = y_j)$$

Add WeChat powcoder

Therefore:

$$P(X = x_i) = \sum_j P(X = x_i, Y = y_j) = \sum_j P(X = x_i | Y = y_j) P(Y = y_j)$$

An Illustration of a Distribution over Two Variables



joint

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

An Illustration of a Distribution over Two Variables



joint marginal

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

An Illustration of a Distribution over Two Variables



joint



marginal



marginal

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

An Illustration of a Distribution over Two Variables



joint



marginal



marginal



conditional

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Joint, Marginal and Conditional Probabilities:

An even More General Formulation

Assignment Project Exam Help

Given D random variables $X_1, \ldots, X_D$:

$$p(X_1, \ldots, X_{i-1}, X_{i+1}, \ldots, X_D) = \sum_{X_i} p(X_1, \ldots, X_D)$$

https://powcoder.com

Add WeChat powcoder

Joint, Marginal and Conditional Probabilities:

An even More General Formulation

Assignment Project Exam Help

Given D random variables $X_1, \ldots, X_D$

$$p(X_1, \ldots, X_{i-1}, X_{i+1}, \ldots, X_D) = \sum_{X_i} p(X_1, \ldots, X_D)$$

https://powcoder.com

Chain Rule: We can also express:

$$p(X_1, X_2) = p(X_1)p(X_2|X_1)$$

What are we using here?

Add WeChat powcoder

Joint, Marginal and Conditional Probabilities:

An even More General Formulation

Assignment Project Exam Help

Given D random variables $X_1, \ldots, X_D$:

$$p(X_1, \ldots, X_{i-1}, X_{i+1}, \ldots, X_D) = \sum_{X_i} p(X_1, \ldots, X_D)$$

https://powcoder.com

Chain Rule: We can also express:

$$p(X_1, X_2) = p(X_1)p(X_2|X_1)$$

What are we using here?

Add WeChat powcoder

$$p(X_1, X_2, X_3) = p(X_1, X_2)p(X_3|X_1, X_2) = p(X_1)p(X_2|X_1)p(X_3|X_1, X_2)$$

Joint, Marginal and Conditional Probabilities:

An even More General Formulation

Assignment Project Exam Help

Given D random variables $X_1, \ldots, X_D$:

$$p(X_1, \ldots, X_{i-1}, X_{i+1}, \ldots, X_D) = \sum_{X_i} p(X_1, \ldots, X_D)$$

https://powcoder.com

Chain Rule: We can also express:

$$p(X_1, X_2) = p(X_1)p(X_2|X_1)$$

What are we using here?

Add WeChat powcoder

$$p(X_1, X_2, X_3) = p(X_1, X_2)p(X_3|X_1, X_2) = p(X_1)p(X_2|X_1)p(X_3|X_1, X_2)$$

$$p(X_1, \ldots, X_D) = p(X_1)p(X_2|X_1)p(X_3|X_2, X_1)\ldots p(X_D|X_1, \ldots, X_{D-1})$$

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Summary

Assignment Project Exam Help

- General architecture for communication systems

- Why we need probability

https://powcoder.com

- Probability theory: joint, marginal and conditional distribution

Add WeChat powcoder

- Reading: Mackay § 2.1 and § 2.2; Bishop § 1.2

Exercise

Coming Back to our Original Example

Given: $p(B = r) = 0.4$, $p(B = b) = 0.6$

Assume the fruit are selected uniformly from each box

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder



- Write down all conditional probabilities $P(F|B)$
- Evaluate the overall probabilities $P(F)$

Next time

Assignment Project Exam Help

- More on joint, marginal and conditional distributions

https://powcoder.com

- When can we say that X, Y do not influence each other?

Add WeChat powcoder

- What, if anything, does $p(X = x|Y = y)$ tell us about $p(Y = y|X = x)$?

Next time

Assignment Project Exam Help

- Sign-up for tutorials open at 9am wednesday 25 July. Will offer **three** tutorials. If we need more, I will add.

https://powcoder.com

- Class rep.

Add WeChat powcoder