

COMP2610 – Information Theory

Lecture 12: The Source Coding Theorem

Assignment Project Exam Help

Robert C. Williamson

<https://powcoder.com>

Research School of Computer Science



Australian
National
University

Add WeChat powcoder

28 August 2018

Last time

Basic goal of compression

Key concepts: codes and their types, raw bit content, essential bit content

Assignment Project Exam Help

Informal statement of source coding theorem

<https://powcoder.com>


Add WeChat powcoder

A General Communication Game (Recap)

Data compression is the process of replacing a message with a smaller message which can be reliably converted back to the original.

- Want small messages **on average** when outcomes are from a **fixed, known, but uncertain** source (e.g., coin flips with known bias)

<https://powcoder.com>



Definitions (Recap)

Source Code

Given an ensemble X , the function $c : \mathcal{A}_X \rightarrow \mathcal{B}$ is a **source code** for X .

The number of symbols in $c(x)$ is the **length** $l(x)$ of the code word for x .

The **extension** of c is defined by $c(x_1 \dots x_n) = c(x_1) \dots c(x_n)$.

<https://powcoder.com>

Add WeChat powcoder

Definitions (Recap)

Source Code

Given an ensemble X , the function $c : \mathcal{A}_X \rightarrow \mathcal{B}$ is a **source code** for X .
The number of symbols in $c(x)$ is the **length** $l(x)$ of the code word for x .
The **extension** of c is defined by $c(x_1 \dots x_n) = c(x_1) \dots c(x_n)$.

Smallest δ -sufficient subset

Let X be an ensemble and for $\delta \geq 0$ define S_δ to be the **smallest** subset of \mathcal{A}_X such that

$$P(x \in S_\delta) \geq 1 - \delta$$

Add WeChat powcoder

Definitions (Recap)

Source Code

Given an ensemble X , the function $c : \mathcal{A}_X \rightarrow \mathcal{B}$ is a **source code** for X . The number of symbols in $c(x)$ is the **length** $l(x)$ of the code word for x . The **extension** of c is defined by $c(x_1 \dots x_n) = c(x_1) \dots c(x_n)$.

Smallest δ -sufficient subset

Let X be an ensemble and for $\delta \geq 0$ define S_δ to be the **smallest** subset of \mathcal{A}_X such that

$$P(x \in S_\delta) \geq 1 - \delta$$

Essential Bit Content

Let X be an ensemble then for $\delta \geq 0$ the **essential bit content** of X is

$$H_\delta(X) \stackrel{\text{def}}{=} \log_2 |S_\delta|$$

Essential Bit Content (Recap)

Intuitively, construct S_δ by removing elements of X in ascending order of probability, till we have reached the $1 - \delta$ threshold

x	$P(x)$
a	1/4
b	1/4
c	1/4
d	3/16
e	1/64
f	1/64
g	1/64
h	1/64

- Outcomes ranked (high–low) by $P(x = a_i)$
removed to make set S_δ with $P(x \in S_\delta) \geq 1 - \delta$
- $\delta = 0 : S_\delta = \{a, b, c, d, e, f, g, h\}$

<https://powcoder.com>

Add WeChat powcoder

Essential Bit Content (Recap)

Intuitively, construct S_δ by removing elements of X in ascending order of probability, till we have reached the $1 - \delta$ threshold

x	$P(x)$
a	1/4
b	1/4
c	1/4
d	3/16
e	1/64
f	1/64
g	1/64

- Outcomes ranked (high–low) by $P(x = a_i)$
removed to make set S_δ with $P(x \in S_\delta) \geq 1 - \delta$
- $\delta = 0 : S_\delta = \{a, b, c, d, e, f, g, h\}$
 $\delta = 1/64 : S_\delta = \{a, b, c, d, e, f, g\}$

Essential Bit Content (Recap)

Intuitively, construct S_δ by removing elements of X in ascending order of probability, till we have reached the $1 - \delta$ threshold

x	$P(x)$
a	1/4
b	1/4
c	1/4
d	3/16

- Outcomes ranked (high–low) by $P(x = a_i)$
removed to make set S_δ with $P(x \in S_\delta) \geq 1 - \delta$

$$\delta = 0 : S_\delta = \{a, b, c, d, e, f, g, h\}$$

$$\delta = 1/64 : S_\delta = \{a, b, c, d, e, f, g\}$$

$$\delta = 1/16 : S_\delta = \{a, b, c, d\}$$

Add WeChat powcoder

Essential Bit Content (Recap)

Intuitively, construct S_δ by removing elements of X in ascending order of probability, till we have reached the $1 - \delta$ threshold

x	$P(x)$
a	1/4

- Outcomes ranked (high–low) by $P(x = a_i)$
removed to make set S_δ with $P(x \in S_\delta) \geq 1 - \delta$

$$\delta = 0 : S_\delta = \{a, b, c, d, e, f, g, h\}$$

$$\delta = 1/64 : S_\delta = \{a, b, c, d, e, f, g\}$$

$$\delta = 1/16 : S_\delta = \{a, b, c, d\}$$

$$\delta = 3/4 : S_\delta = \{a\}$$

Lossy Coding (Recap)

Consider a coin with $P(\text{Heads}) = 0.9$

Assignment Project Exam Help

If we are happy to fail on up to 2% of the sequences we can ignore any sequence of 10 outcomes with more than 3 tails

<https://powcoder.com>

There are only $176 < 2^8$ sequences with 3 or fewer tails

So, we can just code those, and ignore the rest!

- Coding 10 outcomes with 2% failure doable with 8 bits, or 0.8 bits/outcome

Add WeChat powcoder

This time

Recap: typical sets

Formal statement of source coding theorem

Proof of source coding theorem

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Source Coding Theorem

(Theorem 4.1 in MacKay)

Our aim this week is to understand this:

The Source Coding Theorem

Let X be an ensemble with entropy $H = H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

$\left| \frac{1}{N} \log_2 \frac{1}{P(X^N)} - H \right| < \epsilon$
<https://powcoder.com>

Add WeChat powcoder

The Source Coding Theorem

(Theorem 4.1 in MacKay)

Our aim this week is to understand this:

The Source Coding Theorem

Let X be an ensemble with entropy $H = H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

$$\left| \frac{1}{N} \log_2 \left(\frac{1}{N} \sum_{i=1}^N p_i^N \right) - H \right| < \epsilon.$$

In English:

- Given outcomes drawn from X ...

Add WeChat powcoder

The Source Coding Theorem

(Theorem 4.1 in MacKay)

Our aim this week is to understand this:

The Source Coding Theorem

Let X be an ensemble with entropy $H = H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

$\left| \frac{1}{N} \log_2 \left(\frac{P(X^N)}{2^{NH}} \right) - H \right| < \epsilon$

<https://powcoder.com>

In English:

- Given outcomes drawn from X ...
- ... no matter what *reliability* $1 - \delta$ and *tolerance* ϵ you choose ...

Add WeChat powcoder

The Source Coding Theorem

(Theorem 4.1 in MacKay)

Our aim this week is to understand this:

The Source Coding Theorem

Let X be an ensemble with entropy $H = H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

$\left| \frac{1}{N} \log_2 \frac{P(X^N)}{2^{NH}} - H \right| < \epsilon$
<https://powcoder.com>

In English:

- Given outcomes drawn from X ...
- ... no matter what *reliability* $1 - \delta$ and *tolerance* ϵ you choose ...
- ... there is always a length N_0 so sequences X^N longer than this ...

Add WeChat powcoder

The Source Coding Theorem

(Theorem 4.1 in MacKay)

Our aim this week is to understand this:

The Source Coding Theorem

Let X be an ensemble with entropy $H = H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

<https://powcoder.com>

In English:

- Given outcomes drawn from X ...
- ... no matter what *reliability* $1 - \delta$ and *tolerance* ϵ you choose ...
- ... there is always a length N_0 so sequences X^N longer than this ...
- ... have an average essential bit content $\frac{1}{N} H_\delta(X^N)$ within ϵ of $H(X)$

Add WeChat powcoder

The Source Coding Theorem

(Theorem 4.1 in MacKay)

Our aim this week is to understand this:

The Source Coding Theorem

Let X be an ensemble with entropy $H = H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

<https://powcoder.com>

In English:

- Given outcomes drawn from X ...
- ... no matter what *reliability* $1 - \delta$ and *tolerance* ϵ you choose ...
- ... there is always a length N_0 so sequences X^N longer than this ...
- ... have an average essential bit content $\frac{1}{N} H_\delta(X^N)$ within ϵ of $H(X)$

$H_\delta(X^N)$ measures the *fewest* number of bits needed to uniformly code *smallest* set of N -outcome sequence S_δ with $P(x \in S_\delta) \geq 1 - \delta$.

1 Introduction

- Quick Review

Assignment Project Exam Help

2 Extended Ensembles

- Definition and Properties
- Essential Bit Content
- The Asymptotic Equipartition Property

<https://powcoder.com>

3 The Source Coding Theorem

- Typical Sets
- Statement of the Theorem

Add WeChat powcoder

Extended Ensembles (Review)

Instead of coding single outcomes, we now consider coding **blocks** and sequences of blocks

Example (Coin Flips).

hhhhthhththh \rightarrow hh hh th ht ht hh (6 \times 2 outcome blocks)

\rightarrow hhh hth hth thh (4 \times 3 outcome blocks)

\rightarrow hhhh thht hthh (3 \times 4 outcome blocks)

Add WeChat powcoder

Extended Ensembles (Review)

Instead of coding single outcomes, we now consider coding **blocks** and sequences of blocks

Example (Coin Flips):

hhhhthhththh \rightarrow hh hh th ht ht hh (6 \times 2 outcome blocks)

\rightarrow hhh hth hth thh (4 \times 3 outcome blocks)

\rightarrow hhhh thht htth (3 \times 4 outcome blocks)

Extended Ensemble

The **extended ensemble** of blocks of size N is denoted X^N . Outcomes from X^N are denoted $\mathbf{x} = (x_1, x_2, \dots, x_N)$. The **probability** of \mathbf{x} is defined to be $P(\mathbf{x}) = P(x_1)P(x_2) \dots P(x_N)$.

Extended Ensembles (Review)

Instead of coding single outcomes, we now consider coding **blocks** and sequences of blocks

Example (Coin Flips):

hhhhthhththh \rightarrow hh hh th ht ht hh (6 \times 2 outcome blocks)

\rightarrow hhh hth hth thh (4 \times 3 outcome blocks)

\rightarrow hhhh thht htth (3 \times 4 outcome blocks)

<https://powcoder.com>

Extended Ensemble

The **extended ensemble** of blocks of size N is denoted X^N . Outcomes from X^N are denoted $\mathbf{x} = (x_1, x_2, \dots, x_N)$. The **probability** of \mathbf{x} is defined to be $P(\mathbf{x}) = P(x_1)P(x_2) \dots P(x_N)$.

What is the entropy of X^N ?

Extended Ensembles (Review)

Example: Bent Coin



Let X be an ensemble with outcomes

$\mathcal{A}_X = \{h, t\}$ with $p_h = 0.9$ and $p_t = 0.1$.

Consider X^4 – i.e., 4 flips of the coin.

$\mathcal{A}_{X^4} = \{hhhh, hhht, hthh, \dots, tttt\}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Extended Ensembles (Review)

Example: Bent Coin



Let X be an ensemble with outcomes

$\mathcal{A}_X = \{h, t\}$ with $p_h = 0.9$ and $p_t = 0.1$.

Consider X^4 – i.e., 4 flips of the coin.

$\mathcal{A}_{X^4} = \{hhhh, hhht, hthh, \dots, tttt\}$

What is the probability of

- Four heads? $P(hhhh) = (0.9)^4 \approx 0.656$
- Four tails? $P(tttt) = (0.1)^4 = 0.0001$

Add WeChat powcoder

Extended Ensembles (Review)

Example: Bent Coin



Let X be an ensemble with outcomes

$\mathcal{A}_X = \{h, t\}$ with $p_h = 0.9$ and $p_t = 0.1$.

Consider X^4 – i.e., 4 flips of the coin.

$\mathcal{A}_{X^4} = \{hhhh, hhht, hthh, \dots, tttt\}$

What is the probability of

- Four heads? $P(hhhh) = (0.9)^4 \approx 0.656$
- Four tails? $P(tttt) = (0.1)^4 = 0.0001$

What is the entropy and raw bit content of X^4 ?


- The outcome set size is $|\mathcal{A}_{X^4}| = |\{0000, 0001, 0010, \dots, 1111\}| = 16$
- Raw bit content: $H_0(X^4) = \log_2 |\mathcal{A}_{X^4}| = 4$
- Entropy: $H(X^4) = 4H(X) = 4 \cdot (-0.9 \log_2 0.9 - 0.1 \log_2 0.1) = 1.88$

Essential Bit Content of Extended Ensembles

What if we use a **lossy uniform code** on the extended ensemble?

Assignment Project Exam Help

\mathbf{x}	$P(\mathbf{x})$	\mathbf{x}	$P(\mathbf{x})$
hhhh	0.656	thht	0.008
hhht	0.073	thth	0.008
hhth	0.073	tthh	0.008
hthh	0.073	httt	0.001
thhh	0.073	ttht	0.001
htht	0.008	ttth	0.001
htth	0.008	ttth	0.001
hhtt	0.008	tttt	0.000




$$\delta = 0 \text{ gives } H_\delta(X^4) = \log_2 16 = 4$$

Essential Bit Content of Extended Ensembles

What if we use a **lossy uniform code** on the extended ensemble?

Assignment Project Exam Help

\mathbf{x}	$P(\mathbf{x})$	\mathbf{x}	$P(\mathbf{x})$
hhhh	0.656	thht	0.008
hhht	0.073	thth	0.008
hhth	0.073	tthh	0.008
hthh	0.0073	httt	0.001
thhh	0.073	ttht	0.001
htht	0.008	ttth	0.001
htth	0.008		
hhtt	0.008		



$$\delta = 0.0001 \text{ gives } H_\delta(X^4) = \log_2 15 = 3.91$$


Essential Bit Content of Extended Ensembles

What if we use a **lossy uniform code** on the extended ensemble?

Assignment Project Exam Help

\mathbf{x}	$P(\mathbf{x})$	\mathbf{x}	$P(\mathbf{x})$
hhhh	0.656	thht	0.008
hhht	0.073	thth	0.008
hhth	0.073	tthh	0.008
hthh	0.073		
thhh	0.073		
htht	0.008		
htth	0.008		
hhtt	0.008		

$H_\delta(X^4)$



$$\delta = 0.005 \text{ gives } H_\delta(X^4) = \log_2 11 = 3.46$$


Essential Bit Content of Extended Ensembles

What if we use a **lossy uniform code** on the extended ensemble?

Assignment Project Exam Help

\mathbf{x}	$P(\mathbf{x})$
hhhh	0.656
hhht	0.073
hhth	0.073
hthh	0.073
thhh	0.073

$H_\delta(X^4)$



<https://powcoder.com>

Add WeChat powcoder

$$\delta = 0.05 \text{ gives } H_\delta(X^4) = \log_2 5 = 2.32$$


Essential Bit Content of Extended Ensembles

What if we use a **lossy uniform code** on the extended ensemble?

Assignment Project Exam Help

\mathbf{x}	$P(\mathbf{x})$
hhhh	0.656
hhht	0.073
hhth	0.073

$H_\delta(X^4)$



<https://powcoder.com>

Add WeChat powcoder

$$\delta = 0.25 \text{ gives } H_\delta(X^4) = \log_2 3 = 1.6$$

Essential Bit Content of Extended Ensembles


What if we use a **lossy uniform code** on the extended ensemble?

Assignment Project Exam Help

x	P(x)	y	P(y)
hhhh	0.656		
hhht	0.073		
hhth	0.073		

<https://powcoder.com>

Add WeChat powcoder




$$\delta = 0.25 \text{ gives } H_\delta(X^4) = \log_2 3 = 1.6$$

Unlike entropy, $H_\delta(X^4) \neq 4H_\delta(X) = 0$

Essential Bit Content of Extended Ensembles

What happens as N increases?



Recall that the entropy of a single coin flip with $p_h = 0.9$ is $H(X) \approx 0.47$

Essential Bit Content of Extended Ensembles

Some Intuition

Assignment Project Exam Help

Why does the curve flatten for large N ?

Recall that for $N = 1000$ e.g., sequences with 900 heads are considered typical

<https://powcoder.com>

Such sequences occupy most of the probability mass, and are roughly equally likely

Add WeChat powcoder


As we increase δ , we will quickly encounter these sequences, and make small, roughly equal sized changes to $|S_\delta|$

Typical Sets and the AEP (Review)

\mathbf{x}	$\log_2(P(\mathbf{x}))$
...1.....1...1...11.....1.....1.....1.....1.....11..	-50.1
.....1.....1.....1.....1.....1.....1.....1.....1.....	-37.3
.....1.....1.....1.....1.....1.....1.....1.....1.....	-37.3
...1.....1.....1.....1.....1.....1.....1.....1.....	-56.4
.....1.....1.....1.....1.....1.....1.....1.....1.....	-56.4
.....1.....1.....1.....1.....1.....1.....1.....1.....	-53.2
.....1.....1.....1.....1.....1.....1.....1.....1.....	-43.7
.....1.....1.....1.....1.....1.....1.....1.....1.....	-46.8
.....1.....1.....1.....1.....1.....1.....1.....1.....	-56.4
.....1.....1.....1.....1.....1.....1.....1.....1.....	-37.3
.....1.....1.....1.....1.....1.....1.....1.....1.....	-43.7
.....1.....1.....1.....1.....1.....1.....1.....1.....	-56.4
.....1.....1.....1.....1.....1.....1.....1.....1.....	-37.3
.....1.....1.....1.....1.....1.....1.....1.....1.....	-56.4
.....1.....1.....1.....1.....1.....1.....1.....1.....	-59.5
.....1.....1.....1.....1.....1.....1.....1.....1.....	-46.8

<https://powcoder.com>

Add WeChat powcoder



Typical Sets and the AEP (Review)

Typical Set

For “closeness” $\beta > 0$, the typical set $T_{N\beta}$ for X^N is

$$T_{N\beta} \stackrel{\text{def}}{=} \left\{ \mathbf{x} : \left| -\frac{1}{N} \log_2 P(\mathbf{x}) - H(X) \right| < \beta \right\}$$

The name “typical” is used since $\mathbf{x} \in T_{N\beta}$ will have roughly $p_1 N$ occurrences of symbol a_1 , $p_2 N$ of a_2 , \dots , $p_K N$ of a_K .

Add WeChat powcoder

Typical Sets and the AEP (Review)

Typical Set

For “closeness” $\epsilon > 0$, the typical set $T_{N\epsilon}$ for X^N is

$$T_{N\epsilon} \stackrel{\text{def}}{=} \left\{ \mathbf{x} : \left| -\frac{1}{N} \log_2 P(\mathbf{x}) - H(X) \right| < \epsilon \right\}$$

The name “typical” is used since $\mathbf{x} \in T_{N\epsilon}$ will have roughly $p_1 N$ occurrences of symbol a_1 , $p_2 N$ of a_2 , \dots , $p_K N$ of a_K .

Asymptotic Equipartition Property (Informal)

As $N \rightarrow \infty$, $\log_2 P(x_1, \dots, x_N)$ is close to $-NH(X)$ with high probability.

For large block sizes “almost all sequences are typical” (i.e., in $T_{N\epsilon}$).

1 Introduction

- Quick Review

Assignment Project Exam Help

2 Extended Ensembles

- Definition and Properties
- Essential Bit Content
- The Asymptotic Equipartition Property

<https://powcoder.com>

3 The Source Coding Theorem

- Typical Sets
- Statement of the Theorem

Add WeChat powcoder


The Source Coding Theorem

The Source Coding Theorem

Let X be an ensemble with entropy $H = H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

$$\left| \frac{1}{N} H_\delta(X^N) - H \right| < \epsilon.$$

<https://powcoder.com>



- Given a **tiny** probability of error δ , the average bits per outcome can be made as close to H as required.
- Even if we allow a **large** probability of error, we **cannot** compress more than H bits per outcome for large sequences.

Warning: proof ahead

Assignment Project Exam Help



I don't expect you to reproduce the following proof

- I present it as it sheds some light on why the result is true

And it is a remarkable and fundamental result

- You are expected to **understand** and **be able to apply** the theorem

<https://powcoder.com>
Add WeChat powcoder

Proof of the SCT

The absolute value of a difference being bounded (e.g., $|x - y| \leq \epsilon$) says two things:

- 1 When $x - y$ is positive, it says $x - y < \epsilon$ which means $x < y + \epsilon$
- 2 When $x - y$ is negative, it says $-(x - y) < \epsilon$ which means $x < y - \epsilon$

$|x - y| < \epsilon$ is equivalent to $y - \epsilon < x < y + \epsilon$

<https://powcoder.com>

Add WeChat powcoder

Proof of the SCT

The absolute value of a difference being bounded (e.g., $|x - y| \leq \epsilon$) says two things:

- 1 When $x - y$ is positive, it says $x - y < \epsilon$ which means $x < y + \epsilon$
- 2 When $x - y$ is negative, it says $-(x - y) < \epsilon$ which means $x < y - \epsilon$


$|x - y| < \epsilon$ is equivalent to $y - \epsilon < x < y + \epsilon$

<https://powcoder.com>

Using this, we break down the claim of the SCT into two parts: showing that for any ϵ and δ we can find N large enough so that:

Part 1: $\frac{1}{N} H_\delta(X^N) < H + \epsilon$

Part 2: $\frac{1}{N} H_\delta(X^N) > H - \epsilon$



Proof the SCT

Idea

Proof Idea: As N increases

- $T_{N\beta}$ has $\sim 2^{NH(x)}$ elements

- almost all \mathbf{x} are in $T_{N\beta}$

- S_δ and $T_{N\beta}$ increasingly overlap

- so $\log_2 |S_\delta| \sim NH$

Basically, we look to encode all typical sequences uniformly, and relate that to the essential bit content

Proof of the SCT (Part 1)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) < H(X) + \epsilon$.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Proof of the SCT (Part 1)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) < H(X) + \epsilon$.

Assignment Project Exam Help

Recall (see Lecture 10) for the typical set $T_{N\beta}$ we have for any N, β that

$$|T_{N\beta}| \leq 2^{N(H(X)+\beta)} \quad (1)$$

and, by the AEF, for any β as $N \rightarrow \infty$ we have $P(x \in T_{N\beta}) \rightarrow 1$.

So for any $\delta > 0$ we can always find an N such that $P(x \in T_{N\beta}) \geq 1 - \delta$.

Add WeChat powcoder

Proof of the SCT (Part 1)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) < H(X) + \epsilon$.

Recall (see Lecture 10) for the typical set $T_{N\beta}$ we have for any N, β that

$$|T_{N\beta}| \leq 2^{N(H(X)+\beta)} \quad (1)$$

and, by the AEF, for any β as $N \rightarrow \infty$ we have $P(x \in T_{N\beta}) \rightarrow 1$.

So for any $\delta > 0$ we can always find an N such that $P(x \in T_{N\beta}) \geq 1 - \delta$.

Now recall the definition of the *smallest δ -sufficient subset* S_δ : it is the **smallest** subset of outcomes such that $P(x \in S_\delta) \geq 1 - \delta$ so $|S_\delta| \leq |T_{N\beta}|$.

Proof of the SCT (Part 1)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) < H(X) + \epsilon$.

Recall (see Lecture 10) for the *typical* set $T_{N\beta}$ we have for any N, β that

$$|T_{N\beta}| \leq 2^{N(H(X)+\beta)} \quad (1)$$

and, by the AEP, for any β as $N \rightarrow \infty$ we have $P(x \in T_{N\beta}) \rightarrow 1$.

So for any $\delta > 0$ we can always find an N such that $P(x \in T_{N\beta}) \geq 1 - \delta$.

Now recall the definition of the *smallest* δ -sufficient subset S_δ : it is the **smallest** subset of outcomes such that $P(x \in S_\delta) \geq 1 - \delta$ so $|S_\delta| \leq |T_{N\beta}|$.

So, given any δ and β we can find an N large enough so that, by (1)

$$|S_\delta| \leq |T_{N\beta}| \leq 2^{N(H(X)+\beta)}$$

Proof of the SCT (Part 1)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) < H(X) + \epsilon$.

Recall (see Lecture 10) for the *typical set* $T_{N\beta}$ we have for any N, β that

$$|T_{N\beta}| \leq 2^{N(H(X)+\beta)} \quad (1)$$

and, by the AEP, for any β as $N \rightarrow \infty$ we have $P(x \in T_{N\beta}) \rightarrow 1$.

So for any $\delta > 0$ we can always find an N such that $P(x \in T_{N\beta}) \geq 1 - \delta$.

Now recall the definition of the *smallest δ -sufficient subset* S_δ : it is the **smallest** subset of outcomes such that $P(x \in S_\delta) \geq 1 - \delta$ so $|S_\delta| \leq |T_{N\beta}|$.

So, given any δ and β we can find an N large enough so that, by (1)

$$\log_2 |S_\delta| \leq \log_2 |T_{N\beta}| \leq N(H(X) + \beta)$$

Proof of the SCT (Part 1)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) < H(X) + \epsilon$.

Recall (see Lecture 10) for the *typical* set $T_{N\beta}$ we have for any N, β that

$$|T_{N\beta}| \leq 2^{N(H(X)+\beta)} \quad (1)$$

and, by the AEP, for any β as $N \rightarrow \infty$ we have $P(x \in T_{N\beta}) \rightarrow 1$.

So for any $\delta > 0$ we can always find an N such that $P(x \in T_{N\beta}) \geq 1 - \delta$.

Now recall the definition of the *smallest* δ -sufficient subset S_δ : it is the **smallest** subset of outcomes such that $P(x \in S_\delta) \geq 1 - \delta$ so $|S_\delta| \leq |T_{N\beta}|$.

So, given any δ and β we can find an N large enough so that, by (1)

$$H_\delta(X^N) = \log_2 |S_\delta| \leq \log_2 |T_{N\beta}| \leq N(H(X) + \beta)$$

Setting $\beta = \epsilon$ and dividing through by N gives result.

Proof of the SCT (Part 2)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) > H(X) - \epsilon$.

Suppose this was **not** the case – that is, for every N we have

Assignment Project Exam Help

$$\frac{1}{N}H_\delta(X^N) \leq H(X) - \epsilon \iff |S_\delta| \leq 2^{N(H(X)-\epsilon)}$$

<https://powcoder.com>

Add WeChat powcoder

Proof of the SCT (Part 2)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) > H(X) - \epsilon$.

Suppose this was **not** the case – that is, for every N we have

$$\frac{1}{N}H_\delta(X^N) \leq H(X) - \epsilon \iff |S_\delta| \leq 2^{N(H(X)-\epsilon)}$$

Let's look at what this says about $P(x \in S_\delta)$ by writing

$$P(x \in S_\delta) = P(x \in S_\delta \cap T_{N\beta}) + P(x \in S_\delta \cap \overline{T_{N\beta}})$$

$$\leq |S_\delta| 2^{-N(H-\beta)} + P(x \in \overline{T_{N\beta}})$$

since every $x \in T_{N\beta}$ has $P(x) \leq 2^{-N(H-\beta)}$ and $S_\delta \cap \overline{T_{N\beta}} \subset \overline{T_{N\beta}}$.

Proof of the SCT (Part 2)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) > H(X) - \epsilon$.

Suppose this was **not** the case – that is, for every N we have

$$\frac{1}{N}H_\delta(X^N) \leq H(X) - \epsilon \iff |S_\delta| \leq 2^{N(H(X)-\epsilon)}$$

Let's look at what this says about $P(x \in S_\delta)$ by writing

$$P(x \in S_\delta) = P(x \in S_\delta \cap T_{N\beta}) + P(x \in S_\delta \cap \overline{T_{N\beta}})$$

$$\leq |S_\delta| 2^{-N(H-\beta)} + P(x \in \overline{T_{N\beta}})$$

since every $x \in T_{N\beta}$ has $P(x) \leq 2^{-N(H-\beta)}$ and $S_\delta \cap \overline{T_{N\beta}} \subset \overline{T_{N\beta}}$.

So

$$P(x \in S_\delta) \leq 2^{N(H-\epsilon)} 2^{-N(H-\beta)} + P(x \in \overline{T_{N\beta}})$$

Proof of the SCT (Part 2)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) > H(X) - \epsilon$.

Suppose this was **not** the case – that is, for every N we have

$$\frac{1}{N}H_\delta(X^N) \leq H(X) - \epsilon \iff |S_\delta| \leq 2^{N(H(X)-\epsilon)}$$

Let's look at what this says about $P(x \in S_\delta)$ by writing

$$P(x \in S_\delta) = P(x \in S_\delta \cap T_{N\beta}) + P(x \in S_\delta \cap \overline{T_{N\beta}})$$

$$\leq |S_\delta| 2^{-N(H-\beta)} + P(x \in \overline{T_{N\beta}})$$

since every $x \in T_{N\beta}$ has $P(x) \leq 2^{-N(H-\beta)}$ and $S_\delta \cap \overline{T_{N\beta}} \subset \overline{T_{N\beta}}$.

So

$$P(x \in S_\delta) \leq 2^{-N(H-H+\epsilon-\beta)} + P(x \in \overline{T_{N\beta}})$$

Proof of the SCT (Part 2)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) > H(X) - \epsilon$.

Suppose this was **not** the case – that is, for every N we have

$$\frac{1}{N}H_\delta(X^N) \leq H(X) - \epsilon \iff |S_\delta| \leq 2^{N(H(X)-\epsilon)}$$

Let's look at what this says about $P(x \in S_\delta)$ by writing

$$P(x \in S_\delta) = P(x \in S_\delta \cap T_{N\beta}) + P(x \in S_\delta \cap \overline{T_{N\beta}})$$

$$\leq |S_\delta| 2^{-N(H-\beta)} + P(x \in \overline{T_{N\beta}})$$

since every $x \in T_{N\beta}$ has $P(x) \leq 2^{-N(H-\beta)}$ and $S_\delta \cap \overline{T_{N\beta}} \subset \overline{T_{N\beta}}$.

So

$$P(x \in S_\delta) \leq 2^{-N(\epsilon-\beta)} + P(x \in \overline{T_{N\beta}}) \rightarrow 0 \text{ as } N \rightarrow \infty$$

since $P(x \in T_{N\beta}) \rightarrow 1$.

Proof of the SCT (Part 2)

For $\epsilon > 0$ and $\delta > 0$, want N large enough so $\frac{1}{N}H_\delta(X^N) > H(X) - \epsilon$.

Suppose this was **not** the case – that is, for every N we have

$$\frac{1}{N}H_\delta(X^N) \leq H(X) - \epsilon \iff |S_\delta| \leq 2^{N(H(X)-\epsilon)}$$

Let's look at what this says about $P(x \in S_\delta)$ by writing

$$P(x \in S_\delta) = P(x \in S_\delta \cap T_{N\beta}) + P(x \in S_\delta \cap \overline{T_{N\beta}})$$

$$\leq |S_\delta| 2^{-N(H-\beta)} + P(x \in \overline{T_{N\beta}})$$

since every $x \in T_{N\beta}$ has $P(x) \leq 2^{-N(H-\beta)}$ and $S_\delta \cap \overline{T_{N\beta}} \subset \overline{T_{N\beta}}$.

So

$$P(x \in S_\delta) \leq 2^{-N(\epsilon-\beta)} + P(x \in \overline{T_{N\beta}}) \rightarrow 0 \text{ as } N \rightarrow \infty$$

since $P(x \in T_{N\beta}) \rightarrow 1$. But $P(x \in S_\delta) \geq 1 - \delta$, by defn. **Contradiction**

Interpretation of the SCT

The Source Coding Theorem

Let X be an ensemble with entropy $H \equiv H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

$$\left| \frac{1}{N} H(X^N) - H \right| < \epsilon.$$

<https://powcoder.com>

If you want to uniformly code blocks of N symbols drawn i.i.d. from X

- If you use **more than $NH(X)$ bits per block** you can do so without almost no loss of information as $N \rightarrow \infty$
- If you use **less than $NH(X)$ bits per block** you will almost certainly **lose information** as $N \rightarrow \infty$

Interpretation of the SCT

The Source Coding Theorem

Let X be an ensemble with entropy $h = H(X)$ bits. Given $\epsilon > 0$ and $0 < \delta < 1$, there exists a positive integer N_0 such that for all $N > N_0$

$$\left| \frac{1}{N} H_\delta(X^N) - H \right| < \epsilon$$

Making the error probability $\delta \approx 1$ doesn't really help

- We're still "stuck with" coding the typical sequences

Assumes we deal with X^N

- If outcomes are **dependent**, entropy $H(X)$ need not be the limit
- We won't look at such extensions

Implications of SCT

How practical is it to perform coding inspired by the SCT?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Implications of SCT

How practical is it to perform coding inspired by the SCT?

Not very!

- Theorem might require huge block sizes N_0
- We'd need lookup tables of size $|S_\delta(X^{N_0})| \sim 2^{N_0 \cdot H(X)}$

<https://powcoder.com>

Add WeChat powcoder

Implications of SCT

How practical is it to perform coding inspired by the SCT?

Not very!

- Theorem might require huge block sizes N_0
- We'd need lookup tables of size $|S_\delta(X^{N_0})| \sim 2^{N_0 \cdot H(X)}$

Can we design more practical compression algorithms?

- And will the entropy still feature with the fundamental limit?

Add WeChat powcoder

Next time

We move towards more practical compression ideas

Prefix and Uniquely Decodable variable-length codes

Assignment Project Exam Help

The **Kraft Inequality**

<https://powcoder.com>

Add WeChat powcoder