

COMP284 Scripting Languages

Lecture 17: JavaScript (Part 4)

Handouts (8 on 1)

Ullrich Hustadt

Department of Computer Science
School of Electrical Engineering, Electronics, and Computer Science
University of Liverpool

Dynamic web pages using JavaScript

Window object: Properties and methods

Navigator object

Properties of a **navigator object** include

navigator.appName	the web browser's name
navigator.appVersion	the web browser's version

Example: Load different style sheets depending on browser

```
<html><head><title>Navigator example</title>
<script type="text/javascript">
if (navigator.appName == 'Netscape') {
    document.writeln('<link rel=stylesheet type="text/css" ' +
        href="Netscape.css">')
} else if (navigator.appName == 'Opera') {
    document.writeln('<link rel=stylesheet type="text/css" ' +
        href="Opera.css">')
} else {
    document.writeln('<link rel=stylesheet type="text/css" ' +
        href="Others.css">')
}
</script></head>
```

COMP284 Scripting Languages

Lecture 17

Slide L17 - 4

Contents

- Dynamic web pages using JavaScript
 - Window and Document objects
 - Window object: Properties and methods
 - Dialog boxes
 - Input validation
 - Document object and Document Object Model
- Event-driven Programs
 - Introduction
 - Events

COMP284 Scripting Languages

Lecture 17

Slide L17 - 3

Dynamic web pages using JavaScript

Window object: Properties and methods

Window object

Methods provided by a **window object** include

- open(url, name [, features])**
 - opens a new browser window/tab
 - returns a reference to a window object
 - url** is the URL to access in the new window; can be the empty string
 - name** is a name given to the window for later reference
 - features** is a string that determines various window features

The standard sequence for the creation of a new windows is **not**:

```
// new instance of 'Window' class
var newWin = new Window(...)
newWin.document.write('<html>...</html>')
instead it is
```

```
// new window created by using 'open' with an existing one
var newWin = window.open(...)
newWin.document.write('<html>...</html>')
```

COMP284 Scripting Languages

Lecture 17

Slide L17 - 5

Window and Document objects

JavaScript provides two objects that are essential to the creation of **dynamic web pages** and **interactive web applications**:

window object

- a JavaScript object that represents a browser window or tab
- automatically created with every instance of a `<body>` or `<frameset>` tag
- allows properties of a window to be accessed and manipulated
 - JavaScript provides methods that allow window objects to be created and manipulated
 - Example: `window.open('http://www.csc.liv.ac.uk','Home')`
- whenever an object method or property is referenced in a script without an object name and dot prefix it is assumed by JavaScript to be a member of the **window object**
- Example: We can write `alert()` instead of `window.alert()`

COMP284 Scripting Languages

Lecture 17

Slide L17 - 2

Dynamic web pages using JavaScript

Window object: Properties and methods

Window object

Methods provided by a **window object** include

- close()**
 - closes a browser window/tab
- focus()**
 - give focus to a window (bring the window to the front)
- blur()**
 - removes focus from a window (moves the window behind others)
- print()**
 - prints (sends to a printer) the contents of the current window

COMP284 Scripting Languages

Lecture 17

Slide L17 - 6

Window object

- A **window object** represents an open window in a browser.
- If a document contain **frames**, then there is
 - one window object, **window**, for the HTML document
 - and one additional window object for each frame, accessible via an array **window.frames**
- A **window object** has **properties** including

document	document object for the window
history	history object for the window
location	location object (current URL) for the window
navigator	navigator (web browser) object for the window
opener	reference to the window that created the window
innerHeight	inner height of a window's content area
innerWidth	inner width of a window's content area
closed	boolean value indicating whether the window is (still) open

COMP284 Scripting Languages

Lecture 17

Slide L17 - 3

Dynamic web pages using JavaScript

Window object: Properties and methods

Window object: Example

```
<html><head><title>Window handling</title>
<script type="text/javascript">
function Help() {
    var OutputWindow = window.open('', 'Help', 'resizable=1');
    with (OutputWindow.document) {
        open()
        writeln("<!DOCTYPE html><html><head><title>Help</title>\<br>
</head><body>This might be a context-sensitive help\<br>
message, depending on the application and state of the\<br>
page.</body></html>");
        close()
    }
}
</script></head><body>
<form name="ButtonForm" id="ButtonForm" action="">
<p>
    <input type="button" value="Click for Help"
        onclick="Help();">
</p>
</form></body></html>
```

COMP284 Scripting Languages

Lecture 17

Slide L17 - 7

Dynamic web pages using JavaScriptDialog boxes

Window object: Dialog boxes

- Often we only want to open a new window in order to
 - display a message
 - ask for confirmation of an action
 - request an input
- For these purposes, the `window` object in JavaScript provides pre-defined methods for the handling of `dialog boxes` (`windows` for simple dialogs):
 - `null alert(message_string)`
 - `bool confirm(message_string)`
 - `string prompt(message_string, default)`

COMP284 Scripting LanguagesLecture 17Slide L17 – 8

Dynamic web pages using JavaScriptDialog boxes

Window object: Dialog boxes

- `prompt()` always returns a string, even if the user enters a number
- To `convert` a string to number the following functions can be used:
 - `number parseInt(string [,base])`
 - converts `string` to an integer number wrt numeral system `base`
 - only converts up to the first invalid character in `string`
 - if the first non-whitespace character in `string` is not a digit, returns `NaN`
 - `number parseFloat(string)`
 - converts `string` to a floating-point number
 - only converts up to the first invalid character in `string`
 - if the first non-whitespace character in `string` is not a digit, returns `NaN`
 - `number Number(string)`
 - returns `NaN` if `string` contains an invalid character

COMP284 Scripting LanguagesLecture 17Slide L17 – 12


Dynamic web pages using JavaScriptDialog boxes

Window object: Dialog boxes

- `null alert(message_string)`
 - creates a message box displaying `message_string`
 - the box contains an 'OK' button that the user will have to click (alternatively, the message box can be closed) for the execution of the remaining code to proceed

Example:

```
alert("Local time: " + (new Date).toString())
```



COMP284 Scripting LanguagesLecture 17Slide L17 – 8

Dynamic web pages using JavaScriptDialog boxes

Dialog boxes: Example

```
<html>
<head><title>Interaction example</title></head>
<body>
<script type="text/javascript">
do {
    string = prompt("How many items do you want to buy?")
    quantity = parseInt(string)
} while (isNaN(quantity) || quantity <= 0)
do {
    string = prompt("How much does an item cost?")
    price = parseFloat(string)
} while (isNaN(price) || price <= 0)
buy = confirm("You will have to pay " +
    (price * quantity) + "£. Do you want to proceed?")
if (buy) alert("Purchase made")
</script>
</body></html>
```

<http://cgi.csc.liv.ac.uk/~ullrich/COMP284/examples/jsPrompt.html>

COMP284 Scripting LanguagesLecture 17Slide L17 – 13


Dynamic web pages using JavaScriptDialog boxes

Window object: Dialog boxes

- `bool confirm(message_string)`
 - creates a message box displaying `message_string`
 - the box contains two buttons 'Cancel' and 'OK'
 - the function returns `true` if the user selects 'OK', `false` otherwise

Example:

```
var answer = confirm("Are you sure?")
```



COMP284 Scripting LanguagesLecture 17Slide L17 – 10

Dynamic web pages using JavaScriptInput validation

User input validation

A common use of JavaScript is the `validation` of user input in a HTML form before it is processed:

- check that required fields have not been left empty
- check that fields only contain allowed characters or comply to a certain grammar
- check that values are within allowed bounds

```
<form method="post" action="process.php"
onSubmit="return validate(this)">
<label>User name: <input type="text" name="user"></label>
<label>Email address: <input type="text" name="email"></label>
<input type="submit" name="submit">
</form>
<script>
function validate(form) {
    fail = validateUser(form.user.value)
    fail += validateEmail(form.email.value)
    if (fail == "") return true
    else { alert(fail); return false }
}
</script>
```

COMP284 Scripting LanguagesLecture 17Slide L17 – 14


Dynamic web pages using JavaScriptDialog boxes

Window object: Dialog boxes

- `string prompt(message_string, default)`
 - creates a dialog box displaying `message_string` and an input field
 - if a second argument `default` is given, `default` will be shown in the input field
 - the box contains two buttons 'Cancel' and 'OK'
 - if the user selects 'OK' then the current value entered in the input field is returned as a string, otherwise `null` is returned

Example:

```
var userName =
prompt("What is your name?",
    "")
```



COMP284 Scripting LanguagesLecture 17Slide L17 – 11

Dynamic web pages using JavaScriptInput validation

User input validation

```
1 function validateUser(field) {
2   if (field == "") return "No username entered\n"
3   else if (field.length < 5)
4     return "Username too short\n"
5   else if (/^[^a-zA-Z0-9_-]/.test(field))
6     return "Invalid character in username\n"
7   else return ""
8 }
9
10 function validateEmail(field) {
11   if (field == "") return "No email entered\n"
12   else if (!((field.indexOf(".") > 0) &&
13     (field.indexOf("@") > 0)) ||
14     /^[^a-zA-Z0-9._-]/.test(field))
15     return "Invalid character in email\n"
16   else return ""
17 }
```

<http://cgi.csc.liv.ac.uk/~ullrich/COMP284/examples/jsValidate.html>

COMP284 Scripting LanguagesLecture 17Slide L17 – 15

Window and Document objects

JavaScript provides two objects that are essential to the creation of **dynamic web pages** and **interactive web applications**:

document object

- an object-oriented representation of a web page (HTML document) that is displayed in a window
- allows interaction with the **Document Object Model (DOM)** of a page

Example: `document.writeln()` adds content to a web page

Document Object Model

A platform- and language-neutral interface that allows programs and scripts to dynamically access and update the content, structure and style of HTML, XHTML and XML documents

Accessing HTML elements: Names (2)

Accessing HTML elements by giving them **names** and using **paths** within the Document Object Model tree structure is still problematic

~ If that tree structure changes, then those **paths** no longer work

Example:

Changing the previous form to

```
<form name="form1" action="">
<div class="field" name="fdiv">
<label>Temperature in Fahrenheit:</label>
<input type="text" name="fahrenheit" size=10 value="0" />
</div>
<div class="field" name="cdiv">
<label>Temperature in Celsius:</label>
<input type="text" name="celsius" size="10" value="" />
</div>
</form>
```

means that `document.form1.celsius` no longer works as there is now a `div` element between form and text field, we would now need to use `document.form1.cdiv.celsius`


Document Object Model

Example:

The HTML table below

```
<table>
<tbody>
<tr>
<td>Shady Grove</td>
<td>Aeolian</td>
</tr>
<tr>
<td>Over the River, Charlie</td>
<td>Dorian</td>
</tr>
</tbody>
</table>
```

is parsed into the following DOM



Arnaud Le Hors, et al. editors: Document Object Model (DOM) Level 3 Core Specification, Version 1.0, W3C Recommendation 07 April 2004. World Wide Web Consortium, 2004.
https://www.w3.org/TR/DOM-Level-3-Core/ [accessed 9 January 2017]

Accessing HTML elements: IDs

A more reliable way is to give each HTML element an ID (using the **id** attribute) and to use `getElementById` to retrieve a HTML element by its ID

Example:

```
<form id="form1" action="">
<label>Temperature in Fahrenheit:</label>
<input type="text" id="fahrenheit" size="10" value="0"><br>
<label>Temperature in Celsius:</label>
<input type="text" id="celsius" size="10" value="">
</form>
```

Then

- `document.getElementById('celsius')`
Refers to the HTML element with ID celsius in document
- `document.getElementById('celsius').value`
Refers to the attribute value in the HTML element with ID celsius in document

Accessing HTML elements: Object methods


Example:

```
// access the tbody element from the table element
var myBodyElement = myTableElement.firstChild;

// access its second tr element; the list of children starts at 0 (not 1).
var mySecondTrElement = myBodyElement.childNodes[1];

// remove its first td element
mySecondTrElement.removeChild(mySecondTrElement.firstChild);

// change the text content of the remaining td element
mySecondTrElement.firstChild.firstChild.data = "Peter";
```



Manipulating HTML elements

It is not only possible to access HTML elements, but also possible to change them in the fly

```
<html><head><title>Manipulating HTML elements</title>
<style>
td.RedBG { background: #f00; }
</style>
<script>
function changeBackground1(id) {
document.getElementById(id).style.background = "#00f";
document.getElementById(id).innerHTML = "blue";
}
function changeBackground2(id) {
document.getElementById(id).cell.className = "RedBG";
document.getElementById(id).cell.innerHTML = "red";
}
</script></head><body>
<table border="1"><tr>
<td id="0" onclick="changeBackground1('0');">white</td>
<td id="1" onclick="changeBackground2('1');">white</td>
</tr></table></body></html>
```

<http://cgi.csc.liv.ac.uk/~ullrich/COMP284/examples/jsBG.html>

Accessing HTML elements: Names (1)

Instead of using methods such as `firstChild` and `childNodes[n]`, it is possible to assign **names** to denote the children of a HTML element

Example:

```
<form name="form1" action="">
<label>Temperature in Fahrenheit:</label>
<input type="text" name="fahrenheit" size="10" value="0"><br>
<label>Temperature in Celsius:</label>
<input type="text" name="celsius" size="10" value="">
</form>
```

Then – `document.form1`

Refers to the whole form

– `document.form1.celsius`

Refers to the text field named celsius in `document.form1`

– `document.form1.celsius.value`

Refers to the attribute value in the text field named celsius in `document.form1`

Event-driven JavaScript Programs

- The JavaScript programs we have seen so far were all **executed sequentially**
- programs have a particular starting point
- programs are executed step-by-step, involving control structures and function execution
- programs reach a point at which their execution stops

Event-driven Programs

Introduction

Event-Driven JavaScript Programs

- Web applications are event-driven
 - they react to events such as mouse clicks and key strokes

User interacts with page

An event is triggered

The page's appearance is updated/modified as a result

A handler runs in response

Click me!

Click me!

Click me!

EVENT!

function myEvent() {
...
}

Controller

View

Model

Computation Data

nickywalters: What is Event Driven Programming?
SlideShare, 7 September 2014.
<https://tinyurl.com/ya58zbe9> [accessed 5/11/2017]

- With JavaScript,
 - we can define event handler functions for a wide variety of events
 - event handler functions can manipulate the document object (changing the web page in situ)

COMP284 Scripting LanguagesLecture 17Slide L17 – 24

Event-driven Programs

Events

Events: Focus / Change

- A focus event occurs when a form field receives input focus by tabbing with the keyboard or clicking with the mouse
 - onFocus attribute
- A change event occurs when a select, text, or textarea field loses focus and its value has been modified
 - onChange attribute

Example:

```
<form name="form1" method="post" action="process.php">  
  <select name="select" required  
    onChange="document.form1.submit();">  
    <option value="">Select a name</option>  
    <option value="200812345">Tom Beck</option>  
    <option value="200867890">Jim Kent</option>  
  </select>  
</form>
```

COMP284 Scripting LanguagesLecture 17Slide L17 – 28

Event-driven Programs

Introduction

Event Handlers and HTML Elements

- HTML events are things, mostly user actions, that happen to HTML elements
- Event handlers are JavaScript functions that process events
- Event handlers must be associated with HTML elements for specific events
- This can be done via attributes

```
<input type="button" value="Help" onclick="Help()">
```
- Alternatively, a JavaScript function can be used to add a handler to an HTML element

```
// All good browsers  
window.addEventListener("load", Hello)  
// MS IE browser  
window.attachEvent("onload", Hello)
```

More than one event handler can be added this way to the same element for the same event

COMP284 Scripting LanguagesLecture 17Slide L17 – 25

Event-driven Programs

Events

Events: Focus / Change

- A focus event occurs when a form field receives input focus by tabbing with the keyboard or clicking with the mouse
 - onFocus attribute
- A change event occurs when a select, text, or textarea field loses focus and its value has been modified
 - onChange attribute

```
<form>  
<label>Temperature in Fahrenheit:</label>  
<input type="text" id="fahrenheit" size="10" value="0"  
  onchange="document.getElementById('celsius').value =  
    FahrenheitToCelsius(parseFloat(  
      document.getElementById('fahrenheit').value)).toFixed(1);"  
  ></input>  
<label>Temperature in Celsius:</label>  
<input type="text" id="celsius"  
  size="10" value="" onfocus="blur();"></form>
```

<http://cgi.csc.liv.ac.uk/~ullrich/COMP519/examples/jsOnchange.html>

COMP284 Scripting LanguagesLecture 17Slide L17 – 29

Event-driven Programs

Introduction

Event Handlers and HTML Elements

- As our scripts should work with as many browsers as possible, we need to detect which method works:

```
if (window.addEventListener) {  
  window.addEventListener("load", Hello)  
} else {  
  window.attachEvent("onload", Hello)  
}
```
- Event handlers can also be removed

```
if (window.removeEventListener) {  
  window.removeEventListener("load", Hello)  
} else {  
  window.detachEvent("onload", Hello)  
}
```

COMP284 Scripting LanguagesLecture 17Slide L17 – 26

Event-driven Programs

Events

Events: Blur / Click

- A blur event occurs when an HTML element loses focus
 - onBlur attribute
- A click event occurs when an object on a form is clicked
 - onClick attribute

Example:

```
<html><head><title>OnClick Example</title></head><body>  
<form name="form1" action="">  
  Enter a number here:  
  <input type="text" size="12" id="number" value="3.1">  
  <br><br>  
  <input type="button" value="Double"  
    onclick="document.getElementById('number').value =  
      parseFloat(document.getElementById('number').value)  
        * 2;">  
</form></body></html>
```

<http://cgi.csc.liv.ac.uk/~ullrich/COMP284/examples/jsOnClick.html>

COMP284 Scripting LanguagesLecture 17Slide L17 – 30

Event-driven Programs

Introduction

Events: Load

- An (on)load event occurs when an object has been loaded
- Typically, event handlers for onload events are associated with the window object or the body element of an HTML document

```
<html>  
  <head>  
    <title>Onload Example</title>  
    <script type="text/javascript">  
      function Hello() { alert("Welcome to my page!") }  
    </script>  
  </head>  
  <body onload="Hello()">  
    <p>Content of the web page</p>  
  </body>  
</html>
```

<http://cgi.csc.liv.ac.uk/~ullrich/COMP519/examples/jsOnload.html>

COMP284 Scripting LanguagesLecture 17Slide L17 – 27

Event-driven Programs

Events

Events: MouseOver / Select / Submit

- A keydown event occurs when the user presses a key
 - onkeydown attribute
- A mouseOver event occurs once each time the mouse pointer moves over an HTML element from outside that element
 - onMouseOver attribute
- A select event occurs when a user selects some of the text within a text or textarea field
 - onSelect attribute
- A submit event occurs when a user submits a form
 - onSubmit attribute

COMP284 Scripting LanguagesLecture 17Slide L17 – 31

<div>Event-driven ProgramsEvents</div> <div>Events and DOM</div> <div><ul style="list-style-type: none">When an event occurs, an event object is created<ul style="list-style-type: none">an event object has attributes and methodsevent objects can be created by your code independent of an event occurringIn most browsers, the event object is passed to event handler functions as an argumentIn most versions of Microsoft Internet Explorer, the most recent event can only be accessed via window.event<pre><html><body onKeyPress="processKey(event)"> <script> function processKey(e) { e = e window.event document.getElementById("key").innerHTML = String.fromCharCode(e.keyCode)+' has been pressed' } </script> <!-- key code will appear in the paragraph below --> <p id="key"></p> </body></html></pre><div>COMP284 Scripting LanguagesLecture 17Slide L17 – 32</div></div>	
<div>Event-driven ProgramsEvents</div> <div>Revision</div> <div><p>Read</p><ul style="list-style-type: none">Chapter 17: JavaScript and PHP Validation and Error HandlingChapter 18: Using Ajax<p>of</p><p>R. Nixon: Learning PHP, MySQL, and JavaScript. O'Reilly, 2009.</p><ul style="list-style-type: none">Mozilla Developer Network and individual contributors: Document Object Model (DOM), 18 March 2014. https://developer.mozilla.org/en/docs/DOM [accessed 18 March 2014].W3Schools: JavaScript and HTML DOM Reference, 18 March 2014. http://www.w3schools.com/jsref/ [accessed 18 March 2014].<div>COMP284 Scripting LanguagesLecture 17Slide L17 – 33</div></div>	

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder