

COMP30026 Models of Computation

Context-Free Languages

Assignment Project Exam Help

<https://powcoder.com>

Bach Le / Anna Kalenkova

Lecture Week 8 Part 2

Add WeChat powcoder

Semester 2, 2021

A Bit of History

Finite-state machines go back to McCulloch and Pitts (1943), who wanted to model the working of neurons and synapses.

Assignment Project Exam Help

The formalism that we use today is from Moore (1956).

Kleene (1956) established the connections between regular expressions and finite-state automata.


<https://powcoder.com>

We now turn to **context-free grammars**.

Add WeChat powcoder
These go back to Post's "productions" and Chomsky's grammar formalism (1956).

Chomsky, a linguist, proposed a range of formalisms in grammar form for the description of natural language syntax.

Machines vs Languages



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Context-Free Grammars in Computer Science

In the 60's, computer scientists started adopting context-free free grammars to describe syntax of programming languages.

They are frequently referred to as Backus-Naur Formalism (BNF).

Standard tools for parsing owe much to this formalism, which indirectly has helped make parsing a routine task.

It is extensively used to specify syntax of programming languages, data formats (XML, JSON), etc.

Pushdown automata are to context-free grammars what finite-state automata are to regular languages.

Context-Free Grammars

We have already used the formalism of context-free grammars. To specify the syntax of regular expressions we gave a **grammar**, much

like

Assignment Project Exam Help

$$R \rightarrow 0$$

$$R \rightarrow 1$$

$$R \rightarrow \text{eps}$$

$$R \rightarrow \text{empty}$$

$$R \rightarrow R \cup R$$

$$R \rightarrow R R$$

$$R \rightarrow R^*$$

<https://powcoder.com>

Add WeChat powcoder

Hence a grammar is a set of **substitution rules**, or **productions**. We have the shorthand notation

$$R \rightarrow 0 \mid 1 \mid \text{eps} \mid \text{empty} \mid R \cup R \mid R R \mid R^*$$

Derivations, Sentences and Sentential Forms

A simpler example is this grammar G :

$$\begin{aligned} A &\rightarrow 0A0 \\ A &\rightarrow 1A1 \\ A &\rightarrow \epsilon \end{aligned}$$

Using the two rules as a rewrite system, we get **derivations** such as

$$A \Rightarrow 0A0$$

$$\Rightarrow 00A00$$

$$\Rightarrow 001A100$$

$$\Rightarrow 00100100$$

A is called a **variable**. Other symbols (here 0 and 1) are **terminals**. We refer to a valid string of terminals (such as 00100100) as a **sentence**. The intermediate strings that mix variables and terminals are **sentential forms**.

Context-Free Languages

Clearly a grammar determines a formal language.

Assignment Project Exam Help

The language of G is written $L(G)$.

$$L(G) = \{ww^R \mid w \in \{0,1\}^*\}$$

<https://powcoder.com>

A language which can be generated by some context-free grammar is a **context-free language** (CFL).

Add WeChat powcoder

It should be clear that some of the languages that we found not to be regular **are** context-free, for example

$$\{0^n1^n \mid n \geq 1\}$$

Context-Free Grammars Formally

A context-free grammar (CFG) G is a 4-tuple (V, Σ, R, S) , where

- 1 V is a finite set of **variables**,
- 2 Σ is a finite set of **terminals**,
- 3 R is a finite set of **rules**, each consisting of a variable (the left hand side) and a string in $(V \cup \Sigma)^*$ (the right-hand side),
- 4 S is the **start variable**.

The binary relation \Rightarrow on $(V \cup \Sigma)^*$ is defined as follows.

Let $u, v, w \in (V \cup \Sigma)^*$. Then $uAw \Rightarrow uvw$ iff $A \rightarrow v$ is a rule in R . That is, \Rightarrow captures a single derivation step.

Let \Rightarrow^* be the **reflexive transitive closure** of \Rightarrow .

$$L(G) = \{s \in \Sigma^* \mid S \Rightarrow^* s\}$$

Right/Left Regular Grammars (Not Examinable)

Right regular grammar:

Left regular grammar:

Assignment Project Exam Help

$$A \rightarrow a A$$

$$A \rightarrow \epsilon$$

$$A \rightarrow b B$$

$$B \rightarrow b B$$

$$B \rightarrow \epsilon$$

$$A \rightarrow A b$$

$$A \rightarrow \epsilon$$


$$A \rightarrow B a$$

$$B \rightarrow B a$$

$$B \rightarrow \epsilon$$

<https://powcoder.com>

Add WeChat powcoder



A Context-Free Grammar for Numeric Expressions

Here is a grammar with three variables, 14 terminals, and 15 rules:

Assignment Project Exam Help

$$E \rightarrow T \mid T + E$$

$$T \rightarrow F \mid F * T$$

$$F \rightarrow 0 \mid 1 \mid \dots \mid 9 \mid (E)$$

<https://powcoder.com>

When the start variable is unspecified, it is assumed to be the variable of the first rule.

Add WeChat powcoder

An example sentence in the language is


$$(3 + 7) * 2$$

The grammar ensures that $*$ binds tighter than $+$.

Assignment Project Exam Help

<https://powcoder.com> A parse tree for $(3 + 7) * 2$

Add WeChat powcoder



Parse Trees

There are different derivations leading to the sentence $(3 + 7) * 2$, all corresponding to the parse tree above. They differ in the order in which we choose to replace variables. Here is the **leftmost** derivation:

$$E \Rightarrow T$$

$$\Rightarrow F * T$$

$$\Rightarrow (E) * T$$

$$\Rightarrow (T + E) * T$$

$$\Rightarrow (F + E) * T$$

$$\Rightarrow (3 + E) * T$$

$$\Rightarrow (3 + T) * T$$

$$\Rightarrow (3 + F) * T$$

$$\Rightarrow (3 + 7) * T$$

$$\Rightarrow (3 + 7) * F$$

$$\Rightarrow (3 + 7) * 2$$

$$E \rightarrow T \mid T + E$$

$$T \rightarrow F \mid F * T$$

$$F \rightarrow 0 \mid 1 \mid \dots \mid 9 \mid (E)$$

<https://powcoder.com>

Add WeChat powcoder

Ambiguity


Consider the grammar

$$E \rightarrow E + E \mid E * E \mid (E) \mid 0 \mid 1 \mid \dots \mid 9$$

Assignment Project Exam Help

This grammar allows not only different derivations, but different
parse trees for $3 + 7 * 2$:

<https://powcoder.com>



Assignment Project Exam Help

A grammar that has different parse trees for some sentence is
ambiguous.

<https://powcoder.com>

Sometimes we can find a better grammar (as in our example) which is not ambiguous, and which generates the same language.

Add WeChat powcoder