

# COMP302: Programming Languages and Paradigms

## Assignment Project Exam Help

Prof. Brigitte Pientka (Sec 01)

[bpientka@cs.mcgill.ca](mailto:bpientka@cs.mcgill.ca)

Francisco Ferreira (Sec 02)


[fferre8@cs.mcgill.ca](mailto:fferre8@cs.mcgill.ca)

<https://powcoder.com>

School of Computer Science  
McGill University


Week 5-1, Fall 2017

## Add WeChat powcoder



## Assignment Project Exam Help





# Assignment Project Exam Help

"I find languages that support just one programming paradigm constraining."

- Bjarne Stroustrup

<https://powcoder.com>

## Add WeChat powcoder

So far:

Assignment Project Exam Help

Expressions in OCaml have characteristics:

- An expression has a type
- An expression evaluates to a value (or diverges).

<https://powcoder.com>  
Add WeChat powcoder

Today:

Expressions in OCaml may also have an *effect*.

## Recall: Variable Bindings and Overshadowing

Example 1:

```
1 let (k : int) = 4;;  
2 let (k : int) = 2 in k * 1;;  
3 k;;
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Recall: Variable Bindings and Overshadowing

Example 1:

```
1 let (k : int) = 4;;  
2 let (k : int) = 2 in k * k;;  
3 k;;
```

Example 2:

```
1 let pi = 3.14;;  
2 let area (r:float) = pi *. r *. r;;  
3  
4 let a2 = area (2.0)  
5  
6 let (pi : float) = 6.0;;  
7  
8 let b1 = area (2.0) = a2  
9  
10 let area (r:float) = pi *. r *. r;;  
11 let b2 = area (2.0) = a2
```

# Assignment Project Exam Help

How to program with state?  
<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

How to program with state?  
<https://powcoder.com>

– Demo –

Add WeChat powcoder



- How to allocate state?

# Assignment Project Exam Help

Allocates a reference cell with the name `x` in memory  
and initializes it with 0.

<https://powcoder.com>

Add WeChat powcoder

- How to allocate state?

# Assignment Project Exam Help

Allocates a reference cell with the name `x` in memory and initializes it with 0.

- <https://powcoder.com>

# Add WeChat powcoder

# How to program with state? – Allocate and Compare

- How to allocate state?

## Assignment Project Exam Help

Allocates a reference cell with the name `x` in memory and initializes it with 0.

- <https://powcoder.com>

Compare their address: `r == s`

Succeeds, if both `r` and `s` are names for the same location in memory.

## Add WeChat powcoder

Compare their content: `r = s`

Succeeds, if both reference cells store the same value.

## How to program with state? – Read and Write

- How to read value stored in a reference cell?

1 `!x`      Read value that is stored in the reference cell with name `x`.

1 `let {contents = x} = r`      Pattern match on value that is stored in the reference cell with name `x`.

- How to update the value stored in a reference cell?

1 `x := 3`

Writes the value in the reference cell with the name `x`  
The previously stored value is overwritten.

# Assignment Project Exam Help

– Demo –  
<https://powcoder.com>

Add WeChat powcoder

```
1 let imperative_fact n =  
2   begin  
3     let result = ref 1 in  
4     let i = ref 0 in  
5     let rec loop () =  
6       if !i = n then ()  
7       else (i := !i + 1; result := !result * !i; loop ())  
8     in  
9     (loop (); !result)  
10  end
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
1 let imperative_fact n =  
2   begin  
3     let result = ref 1 in  
4     let i = ref 0 in  
5     let rec loop () =  
6       if !i = n then ()  
7       else (i := !i + 1; result := !result * !i; loop ())  
8     in  
9     (loop (); !result)  
10  end
```

## Add WeChat powcoder

- More complicated than the purely functional version
- Considered bad style in a functional language
- Harder to reason about its correctness

```
1 let counter = ref 0
2
3 (* newName () ==> a, where a is a new name *)
4 (* Names are described by strings and an nat. *)
5 let newName () =
6   (counter := !counter + 1;
7    "a" ^ string_of_int (!counter))
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder