



Assignment Project Exam Help

Algorithms:
<https://powcoder.com>
COMP3121/9101

Add WeChat powcoder

School of Computer Science and Engineering
University of New South Wales

9. STRING MATCHING ALGORITHMS

Assignment Project Exam Help

- Assume that you want to find out if a string $B = b_0b_1 \dots b_{m-1}$ appears as a (contiguous) substring of a much longer string $A = a_0a_1 \dots a_{n-1}$.

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- Assume that you want to find out if a string $B = b_0b_1 \dots b_{m-1}$ appears as a (contiguous) substring of a much longer string $A = a_0a_1 \dots a_{n-1}$.
- The “naïve” string matching algorithm does not work well if B is much longer than what can fit in a single register; we need something cleverer.

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- Assume that you want to find out if a string $B = b_0b_1 \dots b_{m-1}$ appears as a (contiguous) substring of a much longer string $A = a_0a_1 \dots a_{n-1}$.
- The “naïve” string matching algorithm does not work well if B is much longer than what can fit in a single register; we need something cleverer.
- We now show how hashing can be combined with recursion to produce an efficient string matching algorithm.

<https://powcoder.com>
Add WeChat powcoder

- We compute a hash value for the string $B = b_0b_1b_2 \dots b_m$ in the following way.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- We compute a hash value for the string $B = b_0b_1b_2 \dots b_m$ in the following way.
- We will assume that strings A and B are in an alphabet \mathcal{A} with d many symbols in total.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- We compute a hash value for the string $B = b_0b_1b_2 \dots b_m$ in the following way.
- We will assume that strings A and B are in an alphabet \mathcal{A} with d many symbols in total.
- Thus, we can identify each string with a sequence of integers by mapping each symbol s_i into a corresponding integer i :

$A = \{s_0, s_1, s_2, \dots, s_{m-1}\} \rightarrow \{0, 1, 2, \dots, d-1\}$

<https://powcoder.com>

Add WeChat powcoder

Rabin - Karp Algorithm

- We compute a hash value for the string $B = b_0b_1b_2 \dots b_m$ in the following way.
- We will assume that strings A and B are in an alphabet \mathcal{A} with d many symbols in total.
- Thus, we can identify each string with a sequence of integers by mapping each symbol s_i into a corresponding integer i :

$$A = \{s_0, s_1, s_2, \dots, s_{n-1}\} \rightarrow \{0, 1, 2, \dots, d-1\}$$

- To any string $B = b_0b_1 \dots b_{m-1}$ we can now associate an integer whose digits in base d are integers corresponding to each symbol in B :

$$h(B) = h(b_0b_1b_2 \dots b_{m-1}) = d^{m-1}b_0 + d^{m-2}b_1 + \dots + d \cdot b_{m-2} + b_{m-1}$$

Rabin - Karp Algorithm

- We compute a hash value for the string $B = b_0b_1b_2 \dots b_m$ in the following way.
- We will assume that strings A and B are in an alphabet \mathcal{A} with d many symbols in total.
- Thus, we can identify each string with a sequence of integers by mapping each symbol s_i into a corresponding integer i :

$$A = \{s_0, s_1, s_2, \dots, s_{n-1}\} \longrightarrow \{0, 1, 2, \dots, d-1\}$$

- To any string $B = b_0b_1 \dots b_{m-1}$ we can now associate an integer whose digits in base d are integers corresponding to each symbol in B :

$$h(B) = h(b_0b_1b_2 \dots b_{m-1}) = d^{m-1}b_0 + d^{m-2}b_1 + \dots + d \cdot b_{m-2} + b_{m-1}$$

- This can be done efficiently using the Horner's rule:

$$h(B) = b_{m-1} + d(b_{m-2} + d(b_{m-3} + d(b_{m-4} + \dots + d(b_1 + d \cdot b_0)))) \dots$$

Rabin - Karp Algorithm

- We compute a hash value for the string $B = b_0b_1b_2 \dots b_m$ in the following way.
- We will assume that strings A and B are in an alphabet \mathcal{A} with d many symbols in total.
- Thus, we can identify each string with a sequence of integers by mapping each symbol s_i into a corresponding integer i :

$$A = \{s_0, s_1, s_2, \dots, s_{n-1}\} \longrightarrow \{0, 1, 2, \dots, d-1\}$$

- To any string $B = b_0b_1 \dots b_{m-1}$ we can now associate an integer whose digits in base d are integers corresponding to each symbol in B :

$$h(B) = h(b_0b_1b_2 \dots b_{m-1}) = d^{m-1}b_0 + d^{m-2}b_1 + \dots + d \cdot b_{m-2} + b_{m-1}$$

- This can be done efficiently using the Horner's rule:

$$h(B) = b_{m-1} + d(b_{m-2} + d(b_{m-3} + d(b_{m-4} + \dots + d(b_1 + d \cdot b_0)))) \dots$$

- Next we choose a large prime number p such that $(d+1)p$ still fits into a single register and define the hash value of B as $H(B) = h(B) \bmod p$.

- Recall that $A = a_0a_1a_2a_3 \dots a_s a_{s+1} \dots a_{s+m-1} \dots a_{N-1}$ where $N \gg m$.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Recall that $A = a_0a_1a_2a_3 \dots a_s a_{s+1} \dots a_{s+m-1} \dots a_{N-1}$ where $N \gg m$.
- We want to find efficiently all s such that the string of length m of the form $a_s a_{s+1} \dots a_{s+m-1}$ and string $b_0 b_1 \dots b_{m-1}$ are equal.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Rabin - Karp Algorithm

- Recall that $A = a_0a_1a_2a_3 \dots a_sa_{s+1} \dots a_{s+m-1} \dots a_{N-1}$ where $N \gg m$.
- We want to find efficiently all s such that the string of length m of the form $a_sa_{s+1} \dots a_{s+m-1}$ and string $b_0b_1 \dots b_{m-1}$ are equal.
- For each contiguous substring $A_s = a_sa_{s+1} \dots a_{s+m-1}$ of string A we also compute its hash value as

$$H(A_s) = (d^{m-1}a_s + d^{m-2}a_{s+1} + \dots + d^1a_{s+m-2} + a_{s+m-1}) \bmod p$$

<https://powcoder.com>

Add WeChat powcoder

Rabin - Karp Algorithm

- Recall that $A = a_0a_1a_2a_3 \dots a_s a_{s+1} \dots a_{s+m-1} \dots a_{N-1}$ where $N \gg m$.
- We want to find efficiently all s such that the string of length m of the form $a_s a_{s+1} \dots a_{s+m-1}$ and string $b_0 b_1 \dots b_{m-1}$ are equal.
- For each contiguous substring $A_s = a_s a_{s+1} \dots a_{s+m-1}$ of string A we also compute its hash value as

$$H(A_s) = (d^{m-1}a_s + d^{m-2}a_{s+1} + \dots + d^1a_{s+m-2} + a_{s+m-1}) \bmod p$$

<https://powcoder.com>

- We can now compare the hash values $H(B)$ and $H(A_s)$ and do a symbol-by-symbol matching only if $H(B) = H(A_s)$.

Add WeChat powcoder

Rabin - Karp Algorithm

- Recall that $A = a_0a_1a_2a_3 \dots a_s a_{s+1} \dots a_{s+m-1} \dots a_{N-1}$ where $N \gg m$.
- We want to find efficiently all s such that the string of length m of the form $a_s a_{s+1} \dots a_{s+m-1}$ and string $b_0 b_1 \dots b_{m-1}$ are equal.
- For each contiguous substring $A_s = a_s a_{s+1} \dots a_{s+m-1}$ of string A we also compute its hash value as

$$H(A_s) = (d^{m-1}a_s + d^{m-2}a_{s+1} + \dots + d^1a_{s+m-2} + a_{s+m-1}) \bmod p$$

<https://powcoder.com>

- We can now compare the hash values $H(B)$ and $H(A_s)$ and do a symbol-by-symbol matching only if $H(B) = H(A_s)$.
- Clearly, such an algorithm would be faster than the naïve symbol-by-symbol comparison only if we can compute the hash values of substrings A_s faster than what it takes to compare strings B and A_s character by character.

[Add WeChat powcoder](#)

Rabin - Karp Algorithm

- Recall that $A = a_0a_1a_2a_3 \dots a_s a_{s+1} \dots a_{s+m-1} \dots a_{N-1}$ where $N \gg m$.
- We want to find efficiently all s such that the string of length m of the form $a_s a_{s+1} \dots a_{s+m-1}$ and string $b_0 b_1 \dots b_{m-1}$ are equal.
- For each contiguous substring $A_s = a_s a_{s+1} \dots a_{s+m-1}$ of string A we also compute its hash value as

$$H(A_s) = (d^{m-1}a_s + d^{m-2}a_{s+1} + \dots + d^1a_{s+m-2} + a_{s+m-1}) \bmod p$$

<https://powcoder.com>

- We can now compare the hash values $H(B)$ and $H(A_s)$ and do a symbol-by-symbol matching only if $H(B) = H(A_s)$.
- Clearly, such an algorithm would be faster than the naïve symbol-by-symbol comparison only if we can compute the hash values of substrings A_s faster than what it takes to compare strings B and A_s character by character.
- This is where recursion comes into play: we do not have to compute the hash value $H(A_{s+1})$ of $A_{s+1} = a_{s+1}a_{s+2} \dots a_{s+m}$ “from scratch”, but we can compute it efficiently from the hash value $H(A_s)$ of $A_s = a_s a_{s+1} \dots a_{s+m-1}$ as follows.

Since Assignment Project Exam Help

$$H(A_s) = (d^{m-1}a_s + d^{m-2}a_{s+1} + \dots d^1a_{s+m-2} + a_{s+m-1}) \bmod p$$

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

$$H(A_s) = (d^{m-1}a_s + d^{m-2}a_{s+1} + \dots d^1a_{s+m-2} + a_{s+m-1}) \bmod p$$

by multiplying both sides by d we obtain

$$\begin{aligned} d \cdot H(A_s) \bmod p &= \\ &= (d^m a_s + d^{m-1} a_{s+1} + \dots d \cdot a_{s+m-1}) \bmod p \\ &= (d^m a_s + (d^{m-1} a_{s+1} + \dots d^2 a_{s+m-2} + d a_{s+m-1} + a_{s+m}) \bmod p + a_{s+m}) \bmod p \\ &= (d^m a_s + H(A_{s+1}) \cdot a_{s+m}) \bmod p \end{aligned}$$

- Consequently,

$$H(A_{s+1}) = (d \cdot H(A_s) - d^m a_s + a_{s+m}) \bmod p.$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Consequently,

$$H(A_{s+1}) = (d \cdot H(A_s) - d^m a_s + a_{s+m}) \bmod p.$$

Assignment Project Exam Help

- Note that

$$(d^m a_s) \bmod p = ((d^m \bmod p) a_s) \bmod p$$

and that the value $d^m \bmod p$ can be precomputed and stored.

<https://powcoder.com>

Add WeChat powcoder

- Consequently,

$$H(A_{s+1}) = (d \cdot H(A_s) - d^m a_s + a_{s+m}) \bmod p.$$

Assignment Project Exam Help

- Note that

$$(d^m a_s) \bmod p = ((d^m \bmod p) a_s) \bmod p$$

and that the value $d^m \bmod p$ can be precomputed and stored.

- Also, $(-d^m a_s + a_{s+m}) \bmod p < p$

<https://powcoder.com>

Add WeChat powcoder

- Consequently,

$$H(A_{s+1}) = (d \cdot H(A_s) - d^m a_s + a_{s+m}) \bmod p.$$

- Note that

$$(d^m a_s) \bmod p = ((d^m \bmod p) a_s) \bmod p$$

and that the value $d^m \bmod p$ can be precomputed and stored.

- Also, $(-d^m a_s + a_{s+m}) \bmod p < p$

- Thus, since $H(A_s) < p$ we obtain

$$d \cdot H(A_s) + (-d^m a_s + a_{s+m}) \bmod p < (d+1)p$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Consequently,

$$H(A_{s+1}) = (d \cdot H(A_s) - d^m a_s + a_{s+m}) \bmod p.$$

- Note that

$$(d^m a_s) \bmod p = ((d^m \bmod p) a_s) \bmod p$$

and that the value $d^m \bmod p$ can be precomputed and stored.

- Also, $(-d^m a_s + a_{s+m}) \bmod p < p$

- Thus, since $H(A_s) < p$ we obtain

$$d \cdot H(A_s) + (-d^m a_s + a_{s+m}) \bmod p < (d+1)p$$

- Thus, since we chose p such that $(d+1)p$ fits in a register, all the values and the intermediate results for the above expression also fit in a single register.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Consequently,

$$H(A_{s+1}) = (d \cdot H(A_s) - d^m a_s + a_{s+m}) \bmod p.$$

Assignment Project Exam Help

- Note that

$$(d^m a_s) \bmod p = ((d^m \bmod p) a_s) \bmod p$$

and that the value $d^m \bmod p$ can be precomputed and stored.

- Also, $(-d^m a_s + a_{s+m}) \bmod p < p$

- Thus, since $H(A_s) < p$ we obtain

$$d \cdot H(A_s) + (-d^m a_s + a_{s+m}) \bmod p < (d+1)p$$

- Thus, since we chose p such that $(d+1)p$ fits in a register, all the values and the intermediate results for the above expression also fit in a single register.
- Thus, for every s except $s = 0$ the value of $H(A_s)$ can be computed in constant time independent of the length of the strings A and B .

- Thus, we first compute $H(B)$ and $H(A_0)$ using the Horner's rule.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Thus, we first compute $H(B)$ and $H(A_0)$ using the Horner's rule.

• Subsequent values of $H(A_s)$ for $s > 0$ are computed in constant time using the above recursion.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Thus, we first compute $H(B)$ and $H(A_0)$ using the Horner's rule.

Assignment Project Exam Help

- Subsequent values of $H(A_s)$ for $s > 0$ are computed in constant time using the above recursion.
- $H(A_s)$ is compared with $H(B)$ and if they are equal the strings A_s and B are compared by brute force character by character to see if they are equal.

<https://powcoder.com>

Add WeChat powcoder

- Thus, we first compute $H(B)$ and $H(A_0)$ using the Horner's rule.

• Subsequent values of $H(A_s)$ for $s > 0$ are computed in constant time using the above recursion.

- $H(A_s)$ is compared with $H(B)$ and if they are equal the strings A_s and B are compared by brute force character by character to see if they are equal.

- Since p was chosen large, the false positives when $H(A_s) = H(B)$ but $A_s \neq B$ are very unlikely, which makes the algorithm run fast in practice.

- Thus, we first compute $H(B)$ and $H(A_0)$ using the Horner's rule.

• Subsequent values of $H(A_s)$ for $s > 0$ are computed in constant time using the above recursion.

- $H(A_s)$ is compared with $H(B)$ and if they are equal the strings A_s and B are compared by brute force character by character to see if they are equal.

- Since p was chosen large, the false positives when $H(A_s) = H(B)$ but $A_s \neq B$ are very unlikely, which makes the algorithm run fast in practice.

- However, as always when we use hashing, we cannot guarantee the worst case performance.

- Thus, we first compute $H(B)$ and $H(A_0)$ using the Horner's rule.

• Subsequent values of $H(A_s)$ for $s > 0$ are computed in constant time using the above recursion.

- $H(A_s)$ is compared with $H(B)$ and if they are equal the strings A_s and B are compared by brute force character by character to see if they are equal.

- Since p was chosen large, the false positives when $H(A_s) = H(B)$ but $A_s \neq B$ are very unlikely, which makes the algorithm run fast in practice.

- However, as always when we use hashing, we cannot guarantee the worst case performance.

- So we now look for algorithms whose worst case performance can be guaranteed.

- A string matching finite automaton for a string S with k symbols has $k + 1$ many states $0, 1, \dots, k$ which correspond to the number of characters matched thus far and a transition function $\delta(s, c)$ where s is a state and c is a character read at the moment.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- A string matching finite automaton for a string S with k symbols has $k + 1$ many states $0, 1, \dots, k$ which correspond to the number of characters matched thus far and a transition function $\delta(s, c)$ where s is a state and c is a character read at the moment.
- We first look at the case when such $\delta(s, c)$ is given by a pre-constructed table.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


String matching finite automata

- A string matching finite automaton for a string S with k symbols has $k + 1$ many states $0, 1, \dots, k$ which correspond to the number of characters matched thus far and a transition function $\delta(s, c)$ where s is a state and c is a character read at the moment.
- We first look at the case when such $\delta(s, c)$ is given by a pre-constructed table.
- To make things easier to describe, we consider the string $S = ababaca$. The table defining $\delta(s, c)$ would then be

<https://powcoder.com>

Add WeChat powcoder

state	input			
	a	b	c	
0	1	0	0	a
1	1	2	0	b
2	3	0	0	a
3	1	4	0	b
4	5	0	0	a
5	1	4	6	c
6	7	0	0	a
7	1	2	0	



state transition diagram for string *ababaca*

- How do we compute the transition function δ , i.e., how do we fill the table?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- How do we compute the transition function δ , i.e., how do we fill the table?

Assignment Project Exam Help

- Let B_k denote the prefix of the string B consisting of the first k characters of string B .

<https://powcoder.com>

Add WeChat powcoder

- How do we compute the transition function δ , i.e., how do we fill the table?

Assignment Project Exam Help

- Let B_k denote the prefix of the string B consisting of the first k characters of string B .
- If we are at a state k this means that so far we have matched the prefix B_k ; if we now see an input character a , then $o(k, a)$ is the largest m such that the prefix B_m of string B is the suffix of the string $B_k a$.

Add WeChat powcoder

- How do we compute the transition function δ , i.e., how do we fill the table?

- Let B_k denote the prefix of the string B consisting of the first k characters of string B .

- If we are at a state k this means that so far we have matched the prefix B_k ; if we now see an input character a , then $\delta(k, a)$ is the largest m such that the prefix B_m of string B is the suffix of the string $B_k a$.

- Thus, if a happens to be $B[k+1]$, then $m = k+1$ and so $\delta(k, a) = k+1$ and $B_k a = B_{k+1}$.

- How do we compute the transition function δ , i.e., how do we fill the table?


Assignment Project Exam Help

- Let B_k denote the prefix of the string B consisting of the first k characters of string B .
- If we are at a state k this means that so far we have matched the prefix B_k ; if we now see an input character a , then $\delta(k, a)$ is the largest m such that the prefix B_m of string B is the suffix of the string $B_k a$.
- Thus, if a happens to be $B[k+1]$, then $m = k+1$ and so $\delta(k, a) = k+1$ and $B_k a = B_{k+1}$.
- We do that by matching the string against itself: we can recursively compute a function $\pi(k)$ which for each k returns the largest integer m such that the prefix B_m of B is a proper suffix of B_k .

The Knuth-Morris-Pratt algorithm

Assignment Project Exam Help

```
1: function  
2:    $m \leftarrow \text{length}[B]$   
3:   let  $\pi[1..m]$  be a new array  
4:    $\pi[1] = 0$   
5:    $k = 0$   
6:   for  $q = 2$  to  $m$  do  
7:     while  $k > 0$  and  
8:        $B[k + 1] \neq B[q]$   
9:        $k = \pi[k]$   
10:    if  $B[k + 1] = B[q]$   
11:       $k = k + 1$   
12:     $\pi[q] = k$   
13:  return  $\pi$   
14: end function
```



<https://powcoder.com>

Add WeChat powcoder

Assume that length of B is n and that we have already found that $\pi[q-1] = k$; to compute $\pi[q]$ we check if $B[q] = B[k+1]$; if true then $\pi[q] = k+1$; if not true then we find $\pi[k] = p$; if now $B[q] = B[p+1]$ then $\pi[q] = p+1$.

The Knuth-Morris-Pratt algorithm

- We can now do our search for string B in a longer string A :

```
1: function KMP-Matcher( $A, B$ )
2:    $n \leftarrow \text{length}[A]$ 
3:    $m \leftarrow \text{length}[B]$ 
4:    $\pi \leftarrow \text{Compute-Prefix-Function}(B)$ 
5:    $q = 0$ 
6:   for  $i = 1$  to  $n$  do
7:     while  $q > 0$  and  $B[q + 1] \neq A[i]$ 
8:        $q = \pi[q]$ 
9:     if  $B[q + 1] == A[i]$ 
10:       $q = q + 1$ 
11:     if  $q == m$ 
12:       print pattern occurs with shift  $i - m$ 
13:        $q = \pi[q]$ 
14:   end for
15: end function
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Sometimes we are not interested in finding just the perfect matches, but also in matches that might have a few errors such as a few insertions, deletions and replacements.

- So assume that we have a very long string

$A = a_0 a_1 a_2 a_3 \dots a_s a_{s+1} \dots a_{s+m-1} \dots a_{N-1}$, a shorter string

$B = b_0 b_1 b_2 \dots b_{m-1}$ where $m \ll N$ and an integer $k \ll m$. We are interested in finding all matches for B in A which allow up to k many errors.

- Idea: split B into $k + 1$ consecutive subsequences of (approximately) equal length. Then any match in A with at most k errors must contain a subsequence which is a perfect match for a subsequence of B . Thus, we look for all perfect matches for all of $k + 1$ subsequences of B and for every hit we test by brute force if the remaining parts of B have sufficient number of matches in the appropriate parts of A .

Assignment Project Exam Help

On a rectangular table there are 25 non-overlapping round coins of equal size placed in such a way that it is not possible to add another coin without overlapping any of the existing coins and without the coin falling off the table (for a coin to stay on the table its centre must be within the table). Show that it is possible to completely cover the table with 100 coins (of course with overlapping of coins).

<https://powcoder.com>
Add WeChat powcoder