



Assignment Project Exam Help

Algorithms
<https://powcoder.com>
COMP3121/9101

Add WeChat powcoder

School of Computer Science and Engineering
University of New South Wales

4. FAST LARGE INTEGER MULTIPLICATION - part A

Basics revisited: how do we multiply two numbers?

- The primary school algorithm:

Assignment Project Exam Help

```
X X X X <- first input integer
* X X X X <- second input integer
-----
X X X X
X X X X \ O(n^2) intermediate operations:
X X X X / O(n^2) elementary multiplications
X X X X / + O(n^2) elementary additions
-----
X X X X X X X X <- result of length 2n
```

<https://powcoder.com>

Add WeChat powcoder

Basics revisited: how do we multiply two numbers?

- The primary school algorithm:

Assignment Project Exam Help

```
X X X X <- first input integer
* X X X X <- second input integer
-----
X X X X
X X X X \ 0(n^2) intermediate operations:
X X X X / 0(n^2) elementary multiplications
X X X X / + 0(n^2) elementary additions
-----
X X X X X X X X <- result of length 2n
```

<https://powcoder.com>

Add WeChat powcoder

- Can we do it faster than in n^2 many steps??

The Karatsuba trick

- Take the two input numbers A and B , and split them into two halves:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick

- Take the two input numbers A and B , and split them into two halves:

$$A = A_1 2^{\frac{n}{2}} + A_0 \quad A = \underbrace{X \dots X}_{n/2 \text{ bits}} \dots \underbrace{X \dots X}_{n/2 \text{ bits}}$$

$$B = B_1 2^{\frac{n}{2}} + B_0$$

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick

- Take the two input numbers A and B , and split them into two halves:

$$A = A_1 2^{\frac{n}{2}} + A_0 \quad A = \underbrace{X \dots X}_{n/2 \text{ bits}} \dots \underbrace{X \dots X}_{n/2 \text{ bits}}$$

$$B = B_1 2^{\frac{n}{2}} + B_0$$

<https://powcoder.com>

- AB can now be calculated as follows:

Add WeChat powcoder

The Karatsuba trick

- Take the two input numbers A and B , and split them into two halves:

$$A = A_1 2^{\frac{n}{2}} + A_0 \quad A = \underbrace{A_1 \dots A_1}_{n/2 \text{ bits}} \dots \underbrace{A_0 \dots A_0}_{n/2 \text{ bits}}$$

$$B = B_1 2^{\frac{n}{2}} + B_0$$

<https://powcoder.com>

- AB can now be calculated as follows:

$$AB = A_1 B_1 2^n + (A_1 B_0 + A_0 B_1) 2^{\frac{n}{2}} + A_0 B_0$$

Add WeChat powcoder

The Karatsuba trick

- Take the two input numbers A and B , and split them into two halves:

$$A = A_1 2^{\frac{n}{2}} + A_0 \quad A = \underbrace{\overbrace{X \dots X}^{A_1}}_{n/2 \text{ bits}} \cdot \underbrace{\overbrace{X \dots X}^{A_0}}_{n/2 \text{ bits}}$$

$$B = B_1 2^{\frac{n}{2}} + B_0$$

<https://powcoder.com>

- AB can now be calculated as follows:

$$AB = (A_1 B_1 2^n + (A_1 B_0 + A_0 B_1) 2^{\frac{n}{2}} + A_0 B_0)$$

$$= A_1 B_1 2^n + ((A_1 + A_0)(B_1 + B_0) - A_1 B_1 - A_0 B_0) 2^{\frac{n}{2}} + A_0 B_0$$

- We have saved one multiplication, now we have only three: $A_0 B_0$, $A_1 B_1$ and $(A_1 + A_0)(B_1 + B_0)$.

$AB =$

$$A_1 B_1 2^n + ((A_1 + A_0)(B_1 + B_0) - A_1 B_1 - A_0 B_0) 2^{\frac{n}{2}} + A_0 B_0$$

```
1: function MULT( $A, B$ )
2:   if  $|A| = |B| = 1$  then return  $AB$ 
3:   else
4:      $A_1 \leftarrow \text{MoreSignificantPart}(A);$ 
5:      $A_0 \leftarrow \text{LessSignificantPart}(A);$ 
6:      $B_1 \leftarrow \text{MoreSignificantPart}(B);$ 
7:      $B_0 \leftarrow \text{LessSignificantPart}(B);$ 
8:      $U \leftarrow A_0 + A_1;$ 
9:      $V \leftarrow B_0 + B_1;$ 
10:     $X \leftarrow \text{MULT}(A_0, B_0);$ 
11:     $W \leftarrow \text{MULT}(A_1, B_1);$ 
12:     $Y \leftarrow \text{MULT}(U, V);$ 
13:    return  $W 2^n + (Y - X - W) 2^{n/2} + X$ 
14:   end if
15: end function
```

- How many steps does this algorithm take? (remember, addition is in linear time!)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick

- How many steps does this algorithm take? (remember, addition is in linear time!)

- Recurrence: $T(n) = 3T(\frac{n}{5}) + cn$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick

- How many steps does this algorithm take? (remember, addition is in linear time!)

• Recurrence: $T(n) = 3T(\frac{n}{2}) + cn$

$$a = 3; \quad b = 2; \quad f(n) = cn; \quad n^{\log_b a} = n^{\log_2 3}$$

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick

- How many steps does this algorithm take? (remember, addition is in linear time!)

- Recurrence: $T(n) = 3T(\frac{n}{2}) + cn$

$$a = 3; \quad b = 2; \quad f(n) = cn; \quad n^{\log_b a} = n^{\log_2 3}$$

- since $1.5 < \log_2 3 < 1.6$ we have

$$f(n) = cn = O(n^{\log_2 3 - \varepsilon}) \quad \text{for any } 0 < \varepsilon < 0.5$$

Add WeChat powcoder

The Karatsuba trick

- How many steps does this algorithm take? (remember, addition is in linear time!)

• Recurrence: $T(n) = 3T(\frac{n}{2}) + cn$

$$a = 3; \quad b = 2; \quad f(n) = cn; \quad n^{\log_b a} = n^{\log_2 3}$$

- since $1.5 < \log_2 3 < 1.6$ we have

$$f(n) = cn = O(n^{\log_2 3 - \varepsilon}) \quad \text{for any } 0 < \varepsilon < 0.5$$

- Thus, the first case of the Master Theorem applies.

The Karatsuba trick

- How many steps does this algorithm take? (remember, addition is in linear time!)

• Recurrence: $T(n) = 3T(\frac{n}{2}) + cn$

$$a = 3; \quad b = 2; \quad f(n) = cn; \quad n^{\log_b a} = n^{\log_2 3}$$

- since $1.5 < \log_2 3 < 1.6$ we have

$$f(n) = cn = O(n^{\log_2 3 - \varepsilon}) \quad \text{for any } 0 < \varepsilon < 0.5$$

- Thus, the first case of the Master Theorem applies.
- Consequently,

$$T(n) = \Theta(n^{\log_2 3}) < \Theta(n^{1.585})$$

without going through the messy calculations!

- Can we do better if we break the numbers in more than two pieces?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Can we do better if we break the numbers in more than two pieces?
- Lets try breaking the numbers A, B into 3 pieces; then with $k \doteq n/3$ we obtain

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- Can we do better if we break the numbers in more than two pieces?
- Lets try breaking the numbers A, B into 3 pieces; then with

$k \doteq n/3$ we obtain

$$A = \underbrace{XXX \dots XX}_{k \text{ bits of } A_2} \underbrace{XXX \dots XX}_{k \text{ bits of } A_1} \underbrace{XXX \dots XX}_{k \text{ bits of } A_0}$$

<https://powcoder.com>

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- Can we do better if we break the numbers in more than two pieces?
- Lets try breaking the numbers A, B into 3 pieces; then with

$k \doteq n/3$ we obtain

$$A = \underbrace{XXX \dots XX}_{k \text{ bits of } A_2} \underbrace{XXX \dots XX}_{k \text{ bits of } A_1} \underbrace{XXX \dots XX}_{k \text{ bits of } A_0}$$

i.e., $A = A_2 2^{2k} + A_1 2^k + A_0$

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- Can we do better if we break the numbers in more than two pieces?
- Lets try breaking the numbers A, B into 3 pieces; then with

$k \doteq n/3$ we obtain

$$A = \underbrace{XXX \dots XX}_{k \text{ bits of } A_2} \underbrace{XXX \dots XX}_{k \text{ bits of } A_1} \underbrace{XXX \dots XX}_{k \text{ bits of } A_0}$$

i.e., $A = A_2 2^{2k} + A_1 2^k + A_0$

$$B = B_2 2^{2k} + B_1 2^k + B_0$$

Generalizing Karatsuba's algorithm

- Can we do better if we break the numbers in more than two pieces?
- Lets try breaking the numbers A, B into 3 pieces; then with

$k \doteq n/3$ we obtain

$$A = \underbrace{XXX \dots XX}_{k \text{ bits of } A_2} \underbrace{XXX \dots XX}_{k \text{ bits of } A_1} \underbrace{XXX \dots XX}_{k \text{ bits of } A_0}$$

i.e., $A = A_2 2^{2k} + A_1 2^k + A_0$

$$B = B_2 2^{2k} + B_1 2^k + B_0$$

- So,

$$AB = A_2 B_2 2^{4k} + (A_2 B_1 + A_1 B_2) 2^{3k} + (A_2 B_0 + A_1 B_1 + A_0 B_2) 2^{2k} + (A_1 B_0 + A_0 B_1) 2^k + A_0 B_0$$

The Karatsuba trick

$$AB = \underbrace{A_2B_2}_{C_4} 2^{4k} + \underbrace{(A_2B_1 + A_1B_2)}_{C_3} 2^{3k} + \underbrace{(A_2B_0 + A_1B_1 + A_0B_2)}_{C_2} 2^{2k} + \underbrace{(A_1B_0 + A_0B_1)}_{C_1} 2^k + \underbrace{A_0B_0}_{C_0}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick

$$AB = \underbrace{A_2B_2}_{C_4} 2^{4k} + \underbrace{(A_2B_1 + A_1B_2)}_{C_3} 2^{3k} + \underbrace{(A_2B_0 + A_1B_1 + A_0B_2)}_{C_2} 2^{2k} + \underbrace{(A_1B_0 + A_0B_1)}_{C_1} 2^k + \underbrace{A_0B_0}_{C_0}$$

Assignment Project Exam Help

- we need only 5 coefficients:

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick

$$AB = \underbrace{A_2 B_2}_{C_4} 2^{4k} + \underbrace{(A_2 B_1 + A_1 B_2)}_{C_3} 2^{3k} + \underbrace{(A_2 B_0 + A_1 B_1 + A_0 B_2)}_{C_2} 2^{2k} + \underbrace{(A_1 B_0 + A_0 B_1)}_{C_1} 2^k + \underbrace{A_0 B_0}_{C_0}$$

Assignment Project Exam Help

- we need only 5 coefficients:

$$C_4 = A_2 B_2$$

$$C_3 = A_2 B_1 + A_1 B_2$$

$$C_2 = A_2 B_0 + A_1 B_1 + A_0 B_2$$

$$C_1 = A_1 B_0 + A_0 B_1$$

$$C_0 = A_0 B_0$$

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick

$$AB = \underbrace{A_2B_2}_{C_4} 2^{4k} + \underbrace{(A_2B_1 + A_1B_2)}_{C_3} 2^{3k} + \underbrace{(A_2B_0 + A_1B_1 + A_0B_2)}_{C_2} 2^{2k} + \underbrace{(A_1B_0 + A_0B_1)}_{C_1} 2^k + \underbrace{A_0B_0}_{C_0}$$

Assignment Project Exam Help

- we need only 5 coefficients:

$$C_4 = A_2B_2$$

$$C_3 = A_2B_1 + A_1B_2$$

$$C_2 = A_2B_0 + A_1B_1 + A_0B_2$$

$$C_1 = A_1B_0 + A_0B_1$$

$$C_0 = A_0B_0$$

Add WeChat powcoder

- Can we get these with 5 multiplications only?

The Karatsuba trick

$$AB = \underbrace{A_2B_2}_{C_4} 2^{4k} + \underbrace{(A_2B_1 + A_1B_2)}_{C_3} 2^{3k} + \underbrace{(A_2B_0 + A_1B_1 + A_0B_2)}_{C_2} 2^{2k} + \underbrace{(A_1B_0 + A_0B_1)}_{C_1} 2^k + \underbrace{A_0B_0}_{C_0}$$

Assignment Project Exam Help

- we need only 5 coefficients:

$$C_4 = A_2B_2$$

$$C_3 = A_2B_1 + A_1B_2$$

$$C_2 = A_2B_0 + A_1B_1 + A_0B_2$$

$$C_1 = A_1B_0 + A_0B_1$$

$$C_0 = A_0B_0$$

Add WeChat powcoder

- Can we get these with 5 multiplications only?
- Should we perhaps look at

$$(A_2 + A_1 + A_0)(B_2 + B_1 + B_0) =$$

$$A_0B_0 + A_1B_0 + A_2B_0 + A_0B_1 + A_1B_1 + A_2B_1 + A_0B_2 + A_1B_2 + A_2B_2 \quad ???$$

The Karatsuba trick

$$AB = \underbrace{A_2B_2}_{C_4} 2^{4k} + \underbrace{(A_2B_1 + A_1B_2)}_{C_3} 2^{3k} + \underbrace{(A_2B_0 + A_1B_1 + A_0B_2)}_{C_2} 2^{2k} + \underbrace{(A_1B_0 + A_0B_1)}_{C_1} 2^k + \underbrace{A_0B_0}_{C_0}$$

Assignment Project Exam Help

- we need only 5 coefficients:

$$C_4 = A_2B_2$$

$$C_3 = A_2B_1 + A_1B_2$$

$$C_2 = A_2B_0 + A_1B_1 + A_0B_2$$

$$C_1 = A_1B_0 + A_0B_1$$

$$C_0 = A_0B_0$$

Add WeChat powcoder

- Can we get these with 5 multiplications only?
- Should we perhaps look at

$$(A_2 + A_1 + A_0)(B_2 + B_1 + B_0) =$$

$$A_0B_0 + A_1B_0 + A_2B_0 + A_0B_1 + A_1B_1 + A_2B_1 + A_0B_2 + A_1B_2 + A_2B_2 \quad ???$$

- Not clear at all how to get $C_0 - C_4$ with 5 multiplications only ...

The Karatsuba trick: slicing into 3 pieces

- We now look for a method for getting these coefficients without any guesswork!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- We now look for a method for getting these coefficients without any guesswork!

Let $A = A_2 2^{2k} + A_1 2^k + A_0$

$$B = B_2 2^{2k} + B_1 2^k + B_0$$

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- We now look for a method for getting these coefficients without any guesswork!

Assignment Project Exam Help

$$A = A_2 2^{2k} + A_1 2^k + A_0$$
$$B = B_2 2^{2k} + B_1 2^k + B_0$$

- We form the naturally corresponding polynomials

$$P_A(x) = A_2 x^2 + A_1 x + A_0;$$

$$P_B(x) = B_2 x^2 + B_1 x + B_0.$$

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- We now look for a method for getting these coefficients without any guesswork!

Assignment Project Exam Help

$$A = A_2 2^{2k} + A_1 2^k + A_0$$

$$B = B_2 2^{2k} + B_1 2^k + B_0$$

- We form the naturally corresponding polynomials

$$P_A(x) = A_2 x^2 + A_1 x + A_0;$$

$$P_B(x) = B_2 x^2 + B_1 x + B_0.$$

- Note that

$$A = A_2 (2^k)^2 + A_1 2^k + A_0 = P_A(2^k);$$

$$B = B_2 (2^k)^2 + B_1 2^k + B_0 = P_B(2^k).$$

The Karatsuba trick: slicing into 3 pieces

- If we manage to compute somehow the product polynomial

$$P_C(x) = P_A(x)P_B(x) = C_4x^4 + C_3x^3 + C_2x^2 + C_1x + C_0$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- If we manage to compute somehow the product polynomial

$$P_C(x) = P_A(x)P_B(x) = C_4 x^4 + C_3 x^3 + C_2 x^2 + C_1 x + C_0$$

with only 5 multiplications, we can then obtain the product of numbers A and B simply as

$$A \cdot B = P_A(2^k)P_B(2^k) = P_C(2^k) = C_4 2^{4k} + C_3 2^{3k} + C_2 2^{2k} + C_1 2^k + C_0,$$

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- If we manage to compute somehow the product polynomial

$$P_C(x) = P_A(x)P_B(x) = C_4x^4 + C_3x^3 + C_2x^2 + C_1x + C_0$$

with only 5 multiplications, we can then obtain the product of numbers A and B simply as

$$A \cdot B = P_A(2^k)P_B(2^k) = P_C(2^k) = C_42^{4k} + C_32^{3k} + C_22^{2k} + C_12^k + C_0,$$

- Note that the right hand side involves only shifts and additions.

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- If we manage to compute somehow the product polynomial

$$P_C(x) = P_A(x)P_B(x) = C_4 x^4 + C_3 x^3 + C_2 x^2 + C_1 x + C_0$$

with only 5 multiplications, we can then obtain the product of numbers A and B simply as

$$A \cdot B = P_A(2^k)P_B(2^k) = P_C(2^k) = C_4 2^{4k} + C_3 2^{3k} + C_2 2^{2k} + C_1 2^k + C_0,$$

- Note that the right hand side involves only shifts and additions.
- Since the product polynomial $P_C(x) = P_A(x)P_B(x)$ is of degree 4 we need 5 values to uniquely determine $P_C(x)$.

The Karatsuba trick: slicing into 3 pieces

- If we manage to compute somehow the product polynomial

$$P_C(x) = P_A(x)P_B(x) = C_4x^4 + C_3x^3 + C_2x^2 + C_1x + C_0$$

with only 5 multiplications, we can then obtain the product of numbers A and B simply as

$$A \cdot B = P_A(2^k)P_B(2^k) = P_C(2^k) = C_42^{4k} + C_32^{3k} + C_22^{2k} + C_12^k + C_0,$$

- Note that the right hand side involves only shifts and additions.
- Since the product polynomial $P_C(x) = P_A(x)P_B(x)$ is of degree 4 we need 5 values to uniquely determine $P_C(x)$.
- We choose the smallest possible 5 integer values (smallest by their absolute value),

The Karatsuba trick: slicing into 3 pieces

- If we manage to compute somehow the product polynomial

$$P_C(x) = P_A(x)P_B(x) = C_4x^4 + C_3x^3 + C_2x^2 + C_1x + C_0$$

with only 5 multiplications, we can then obtain the product of numbers A and B simply as

$$A \cdot B = P_A(2^k)P_B(2^k) = P_C(2^k) = C_42^{4k} + C_32^{3k} + C_22^{2k} + C_12^k + C_0,$$

- Note that the right hand side involves only shifts and additions.
- Since the product polynomial $P_C(x) = P_A(x)P_B(x)$ is of degree 4 we need 5 values to uniquely determine $P_C(x)$.
- We choose the smallest possible 5 integer values (smallest by their absolute value), i.e., $-2, -1, 0, 1, 2$.

The Karatsuba trick: slicing into 3 pieces

- If we manage to compute somehow the product polynomial

$$P_C(x) = P_A(x)P_B(x) = C_4x^4 + C_3x^3 + C_2x^2 + C_1x + C_0$$

with only 5 multiplications, we can then obtain the product of numbers A and B simply as

$$A \cdot B = P_A(2^k)P_B(2^k) = P_C(2^k) = C_42^{4k} + C_32^{3k} + C_22^{2k} + C_12^k + C_0,$$

- Note that the right hand side involves only shifts and additions.
- Since the product polynomial $P_C(x) = P_A(x)P_B(x)$ is of degree 4 we need 5 values to uniquely determine $P_C(x)$.
- We choose the smallest possible 5 integer values (smallest by their absolute value), i.e., $-2, -1, 0, 1, 2$.
- Thus, we compute $P_A(-2), P_A(-1), P_A(0), P_A(1), P_A(2)$
 $P_B(-2), P_B(-1), P_B(0), P_B(1), P_B(2)$

The Karatsuba trick: slicing into 3 pieces

- For $P_A(x) = A_2x^2 + A_1x + A_0$ we have

$$P_A(-2) = A_2(-2)^2 + A_1(-2) + A_0 = 4A_2 - 2A_1 + A_0$$

$$P_A(-1) = A_2(-1)^2 + A_1(-1) + A_0 = A_2 - A_1 + A_0$$

$$P_A(0) = A_20^2 + A_10 + A_0 = A_0$$

$$P_A(1) = A_21^2 + A_11 + A_0 = A_2 + A_1 + A_0$$

$$P_A(2) = A_22^2 + A_12 + A_0 = 4A_2 + 2A_1 + A_0.$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- For $P_A(x) = A_2x^2 + A_1x + A_0$ we have

$$P_A(-2) = A_2(-2)^2 + A_1(-2) + A_0 = 4A_2 - 2A_1 + A_0$$

$$P_A(-1) = A_2(-1)^2 + A_1(-1) + A_0 = A_2 - A_1 + A_0$$

$$P_A(0) = A_20^2 + A_10 + A_0 = A_0$$

$$P_A(1) = A_21^2 + A_11 + A_0 = A_2 + A_1 + A_0$$

$$P_A(2) = A_22^2 + A_12 + A_0 = 4A_2 + 2A_1 + A_0.$$

- Similarly, for $P_B(x) = B_2x^2 + B_1x + B_0$ we have

$$P_B(-2) = B_2(-2)^2 + B_1(-2) + B_0 = 4B_2 - 2B_1 + B_0$$

$$P_B(-1) = B_2(-1)^2 + B_1(-1) + B_0 = B_2 - B_1 + B_0$$

$$P_B(0) = B_20^2 + B_10 + B_0 = B_0$$

$$P_B(1) = B_21^2 + B_11 + B_0 = B_2 + B_1 + B_0$$

$$P_B(2) = B_22^2 + B_12 + B_0 = 4B_2 + 2B_1 + B_0.$$

The Karatsuba trick: slicing into 3 pieces

- For $P_A(x) = A_2x^2 + A_1x + A_0$ we have

$$P_A(-2) = A_2(-2)^2 + A_1(-2) + A_0 = 4A_2 - 2A_1 + A_0$$

$$P_A(-1) = A_2(-1)^2 + A_1(-1) + A_0 = A_2 - A_1 + A_0$$

$$P_A(0) = A_20^2 + A_10 + A_0 = A_0$$

$$P_A(1) = A_21^2 + A_11 + A_0 = A_2 + A_1 + A_0$$

$$P_A(2) = A_22^2 + A_12 + A_0 = 4A_2 + 2A_1 + A_0.$$

- Similarly, for $P_B(x) = B_2x^2 + B_1x + B_0$ we have

$$P_B(-2) = B_2(-2)^2 + B_1(-2) + B_0 = 4B_2 - 2B_1 + B_0$$

$$P_B(-1) = B_2(-1)^2 + B_1(-1) + B_0 = B_2 - B_1 + B_0$$

$$P_B(0) = B_20^2 + B_10 + B_0 = B_0$$

$$P_B(1) = B_21^2 + B_11 + B_0 = B_2 + B_1 + B_0$$

$$P_B(2) = B_22^2 + B_12 + B_0 = 4B_2 + 2B_1 + B_0.$$

- These evaluations involve only additions because $2A = A + A$; $4A = 2A + 2A$.

The Karatsuba trick: slicing into 3 pieces

- Having obtained $P_A(-2), P_A(-1), P_A(0), P_A(1), P_A(2)$ and $P_B(-2), P_B(-1), P_B(0), P_B(1), P_B(2)$ we can now obtain $P_C(-2), P_C(-1), P_C(0), P_C(1), P_C(2)$ with only 5 multiplications of large numbers:

$$\begin{aligned}P_C(-2) &= P_A(-2)P_B(-2) \\ &= (A_0 - 2A_1 + 4A_2)(B_0 - 2B_1 + 4B_2)\end{aligned}$$

$$\begin{aligned}P_C(-1) &= P_A(-1)P_B(-1) \\ &= (A_0 - A_1 + A_2)(B_0 - B_1 + B_2)\end{aligned}$$

$$\begin{aligned}P_C(0) &= P_A(0)P_B(0) \\ &= A_0B_0\end{aligned}$$

$$\begin{aligned}P_C(1) &= P_A(1)P_B(1) \\ &= (A_0 + A_1 + A_2)(B_0 + B_1 + B_2)\end{aligned}$$

$$\begin{aligned}P_C(2) &= P_A(2)P_B(2) \\ &= (A_0 + 2A_1 + 4A_2)(B_0 + 2B_1 + 4B_2)\end{aligned}$$

The Karatsuba trick: slicing into 3 pieces

- Thus, if we represent the product $C(x) = P_A(x)P_B(x)$ in the coefficient form as $C(x) = C_4x^4 + C_3x^3 + C_2x^2 + C_1x + C_0$ we get

$$C_4(-2)^4 + C_3(-2)^3 + C_2(-2)^2 + C_1(-2) + C_0 = P_C(-2) = P_A(-2)P_B(-2)$$
$$C_4(-1)^4 + C_3(-1)^3 + C_2(-1)^2 + C_1(-1) + C_0 = P_C(-1) = P_A(-1)P_B(-1)$$

$$C_40^4 + C_30^3 + C_20^2 + C_1 \cdot 0 + C_0 = P_C(0) = P_A(0)P_B(0)$$

$$C_41^4 + C_31^3 + C_21^2 + C_1 \cdot 1 + C_0 = P_C(1) = P_A(1)P_B(1)$$

$$C_42^4 + C_32^3 + C_22^2 + C_1 \cdot 2 + C_0 = P_C(2) = P_A(2)P_B(2).$$

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- Thus, if we represent the product $C(x) = P_A(x)P_B(x)$ in the coefficient form as $C(x) = C_4x^4 + C_3x^3 + C_2x^2 + C_1x + C_0$ we get

$$\begin{aligned} C_4(-2)^4 + C_3(-2)^3 + C_2(-2)^2 + C_1(-2) + C_0 &= P_C(-2) = P_A(-2)P_B(-2) \\ C_4(-1)^4 + C_3(-1)^3 + C_2(-1)^2 + C_1(-1) + C_0 &= P_C(-1) = P_A(-1)P_B(-1) \end{aligned}$$

$$C_40^4 + C_30^3 + C_20^2 + C_1 \cdot 0 + C_0 = P_C(0) = P_A(0)P_B(0)$$

$$C_41^4 + C_31^3 + C_21^2 + C_1 \cdot 1 + C_0 = P_C(1) = P_A(1)P_B(1)$$

$$C_42^4 + C_32^3 + C_22^2 + C_1 \cdot 2 + C_0 = P_C(2) = P_A(2)P_B(2).$$

- Simplifying the left side we obtain

$$16C_4 - 8C_3 + 4C_2 - 2C_1 + C_0 = P_C(-2)$$

$$C_4 - C_3 + C_2 - C_1 + C_0 = P_C(-1)$$

$$C_0 = P_C(0)$$

$$C_4 + C_3 + C_2 + C_1 + C_0 = P_C(1)$$

$$16C_4 + 8C_3 + 4C_2 + 2C_1 + C_0 = P_C(2)$$

The Karatsuba trick: slicing into 3 pieces

- Solving this system of linear equations for C_0, C_1, C_2, C_3, C_4 produces (as an exercise solve this system by hand, using the Gaussian elimination)

$$C_0 = P_C(0)$$

$$C_1 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{3} - \frac{2P_C(1)}{3} - \frac{P_C(2)}{12}$$

$$C_2 = -\frac{P_C(-2)}{24} + \frac{2P_C(-1)}{3} - \frac{5P_C(0)}{4} + \frac{2P_C(1)}{3} - \frac{P_C(2)}{24}$$

$$C_3 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{6} - \frac{P_C(0)}{6} + \frac{P_C(2)}{12}$$

$$C_4 = \frac{P_C(-2)}{24} - \frac{P_C(-1)}{6} + \frac{P_C(0)}{4} - \frac{P_C(1)}{6} + \frac{P_C(2)}{24}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- Solving this system of linear equations for C_0, C_1, C_2, C_3, C_4 produces (as an exercise solve this system by hand, using the Gaussian elimination)

$$C_0 = P_C(0)$$

$$C_1 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{3} - \frac{2P_C(1)}{3} - \frac{P_C(2)}{12}$$

$$C_2 = -\frac{P_C(-2)}{24} + \frac{2P_C(-1)}{3} - \frac{5P_C(0)}{4} + \frac{2P_C(1)}{3} - \frac{P_C(2)}{24}$$

$$C_3 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{6} - \frac{P_C(0)}{6} + \frac{P_C(2)}{12}$$

$$C_4 = \frac{P_C(-2)}{24} - \frac{P_C(-1)}{6} + \frac{P_C(0)}{4} - \frac{P_C(1)}{6} + \frac{P_C(2)}{24}$$

- Note that these expressions do not involve any multiplications of TWO large numbers and thus can be done in linear time.

The Karatsuba trick: slicing into 3 pieces

- Solving this system of linear equations for C_0, C_1, C_2, C_3, C_4 produces (as an exercise solve this system by hand, using the Gaussian elimination)

$$C_0 = P_C(0)$$

$$C_1 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{3} + \frac{2P_C(0)}{3} - \frac{P_C(1)}{12}$$

$$C_2 = -\frac{P_C(-2)}{24} + \frac{2P_C(-1)}{3} - \frac{5P_C(0)}{4} + \frac{2P_C(1)}{3} - \frac{P_C(2)}{24}$$

$$C_3 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{6} + \frac{P_C(0)}{6} - \frac{P_C(1)}{12}$$

$$C_4 = \frac{P_C(-2)}{24} - \frac{P_C(-1)}{6} + \frac{P_C(0)}{4} - \frac{P_C(1)}{6} + \frac{P_C(2)}{24}$$

- Note that these expressions do not involve any multiplications of TWO large numbers and thus can be done in linear time.
- With the coefficients C_0, C_1, C_2, C_3, C_4 obtained, we can now form the polynomial $P_C(x) = C_0 + C_1x + C_2x^2 + C_3x^3 + C_4x^4$.

The Karatsuba trick: slicing into 3 pieces

- Solving this system of linear equations for C_0, C_1, C_2, C_3, C_4 produces (as an exercise solve this system by hand, using the Gaussian elimination)

$$C_0 = P_C(0)$$

$$C_1 = \frac{P_C(-2) - P_C(-1)}{12} - \frac{P_C(-1) - P_C(0)}{3} - \frac{P_C(0) - P_C(1)}{3} - \frac{P_C(1) - P_C(2)}{12}$$

$$C_2 = -\frac{P_C(-2)}{24} + \frac{2P_C(-1)}{3} - \frac{5P_C(0)}{4} + \frac{2P_C(1)}{3} - \frac{P_C(2)}{24}$$

$$C_3 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{6} - \frac{P_C(0)}{6} + \frac{P_C(1)}{12}$$

$$C_4 = \frac{P_C(-2)}{24} - \frac{P_C(-1)}{6} + \frac{P_C(0)}{4} - \frac{P_C(1)}{6} + \frac{P_C(2)}{24}$$

- Note that these expressions do not involve any multiplications of TWO large numbers and thus can be done in linear time.
- With the coefficients C_0, C_1, C_2, C_3, C_4 obtained, we can now form the polynomial $P_C(x) = C_0 + C_1x + C_2x^2 + C_3x^3 + C_4x^4$.
- We can now compute $P_C(2^k) = C_0 + C_12^k + C_22^{2k} + C_32^{3k} + C_42^{4k}$ in linear time, because computing $P_C(2^k)$ involves only binary shifts of the coefficients plus $O(k)$ additions.

The Karatsuba trick: slicing into 3 pieces

- Solving this system of linear equations for C_0, C_1, C_2, C_3, C_4 produces (as an exercise solve this system by hand, using the Gaussian elimination)

$$C_0 = P_C(0)$$

$$C_1 = \frac{P_C(-2) - P_C(-1)}{12} - \frac{P_C(-1) - 2P_C(0)}{3} - \frac{P_C(0) - P_C(1)}{3} + \frac{P_C(1) - P_C(2)}{12}$$

$$C_2 = -\frac{P_C(-2)}{24} + \frac{2P_C(-1)}{3} - \frac{5P_C(0)}{4} + \frac{2P_C(1)}{3} - \frac{P_C(2)}{24}$$

$$C_3 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{6} - \frac{P_C(0)}{6} + \frac{P_C(1)}{12}$$

$$C_4 = \frac{P_C(-2)}{24} - \frac{P_C(-1)}{6} + \frac{P_C(0)}{4} - \frac{P_C(1)}{6} + \frac{P_C(2)}{24}$$

- Note that these expressions do not involve any multiplications of two large numbers and thus can be done in linear time.
- With the coefficients C_0, C_1, C_2, C_3, C_4 obtained, we can now form the polynomial $P_C(x) = C_0 + C_1x + C_2x^2 + C_3x^3 + C_4x^4$.
- We can now compute $P_C(2^k) = C_0 + C_12^k + C_22^{2k} + C_32^{3k} + C_42^{4k}$ in linear time, because computing $P_C(2^k)$ involves only binary shifts of the coefficients plus $O(k)$ additions.
- Thus we have obtained $A \cdot B = P_A(2^k)P_B(2^k) = P_C(2^k)$ with only 5 multiplications!

The Karatsuba trick: slicing into 3 pieces

- Solving this system of linear equations for C_0, C_1, C_2, C_3, C_4 produces (as an exercise solve this system by hand, using the Gaussian elimination)

$$C_0 = P_C(0)$$

$$C_1 = \frac{P_C(-2) - P_C(-1)}{12} - \frac{P_C(-1) - 2P_C(0)}{3} - \frac{P_C(0) - P_C(1)}{3} + \frac{P_C(1) - P_C(2)}{12}$$

$$C_2 = -\frac{P_C(-2)}{24} + \frac{2P_C(-1)}{3} - \frac{5P_C(0)}{4} + \frac{2P_C(1)}{3} - \frac{P_C(2)}{24}$$

$$C_3 = \frac{P_C(-2)}{12} - \frac{P_C(-1)}{6} - \frac{P_C(0)}{6} + \frac{P_C(1)}{12}$$

$$C_4 = \frac{P_C(-2)}{24} - \frac{P_C(-1)}{6} + \frac{P_C(0)}{4} - \frac{P_C(1)}{6} + \frac{P_C(2)}{24}$$

- Note that these expressions do not involve any multiplications of 4W0 large numbers and thus can be done in linear time.
- With the coefficients C_0, C_1, C_2, C_3, C_4 obtained, we can now form the polynomial $P_C(x) = C_0 + C_1x + C_2x^2 + C_3x^3 + C_4x^4$.
- We can now compute $P_C(2^k) = C_0 + C_12^k + C_22^{2k} + C_32^{3k} + C_42^{4k}$ in linear time, because computing $P_C(2^k)$ involves only binary shifts of the coefficients plus $O(k)$ additions.
- Thus we have obtained $A \cdot B = P_A(2^k)P_B(2^k) = P_C(2^k)$ with only 5 multiplications! Here is the complete algorithm:

1: **function** MULT(A, B)
 2: obtain A_0, A_1, A_2 and B_0, B_1, B_2 such that $A = A_2 2^{2^k} + A_1 2^k + A_0$; $B = B_2 2^{2^k} + B_1 2^k + B_0$;
 3: form polynomials $P_A(x) = A_2 x^2 + A_1 x + A_0$; $P_B(x) = B_2 x^2 + B_1 x + B_0$;
 4:

$$P_A(-2) \leftarrow 4A_2 - 2A_1 + A_0$$

$$P_B(-2) \leftarrow 4B_2 - 2B_1 + B_0$$

$$P_A(-1) \leftarrow A_2 - A_1 + A_0$$

$$P_B(-1) \leftarrow B_2 - B_1 + B_0$$

$$P_A(0) \leftarrow A_0$$

$$P_B(0) \leftarrow B_0$$

$$P_A(1) \leftarrow A_2 + A_1 + A_0$$

$$P_B(1) \leftarrow B_2 + B_1 + B_0$$

$$P_A(2) \leftarrow 4A_2 + 2A_1 + A_0$$

$$P_B(2) \leftarrow 4B_2 + 2B_1 + B_0$$

5: $P_C(-2) \leftarrow \text{MULT}(P_A(-2), P_B(-2));$ $P_C(-1) \leftarrow \text{MULT}(P_A(-1), P_B(-1));$
 $P_C(0) \leftarrow \text{MULT}(P_A(0), P_B(0));$
 $P_C(1) \leftarrow \text{MULT}(P_A(1), P_B(1));$ $P_C(2) \leftarrow \text{MULT}(P_A(2), P_B(2));$

6: $C_0 \leftarrow P_C(0);$ $C_1 \leftarrow \frac{P_C(-2)}{12} - \frac{2P_C(-1)}{3} + \frac{2P_C(1)}{3} - \frac{P_C(2)}{12}$

$$C_2 \leftarrow -\frac{P_C(-2)}{24} + \frac{2P_C(-1)}{3} - \frac{5P_C(0)}{4} + \frac{2P_C(1)}{6} - \frac{P_C(2)}{24}$$

$$C_3 \leftarrow -\frac{P_C(-2)}{12} + \frac{P_C(-1)}{6} - \frac{P_C(1)}{6} + \frac{P_C(2)}{12}$$

$$C_4 \leftarrow \frac{P_C(-2)}{24} - \frac{P_C(-1)}{6} + \frac{P_C(0)}{4} - \frac{P_C(1)}{6} + \frac{P_C(2)}{24}$$

7: form $P_C(x) = C_4 x^4 + C_3 x^3 + C_2 x^2 + C_1 x + C_0$; compute
 $P_C(2^k) = C_4 2^{4k} + C_3 2^{3k} + C_2 2^{2k} + C_1 2^k + C_0$
 8: **return** $P_C(2^k) = A \cdot B$.

9: **end function**

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- How fast is this algorithm?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- How fast is this algorithm?

Assignment Project Exam Help

- We have replaced a multiplication of two n bit numbers with 5 multiplications of $n/3$ bit numbers with an overhead of additions, shifts and the similar, all doable in linear time cn ;

<https://powcoder.com>

Add WeChat powcoder

- How fast is this algorithm?

- We have replaced a multiplication of two n bit numbers with 5 multiplications of $n/3$ bit numbers with an overhead of additions, shifts and the similar, all doable in linear time cn ;
- thus,

$$T(n) = 5T\left(\frac{n}{3}\right) + cn$$

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- How fast is this algorithm?

- We have replaced a multiplication of two n bit numbers with 5 multiplications of $n/3$ bit numbers with an overhead of additions, shifts and the similar, all doable in linear time cn ;
- thus,

$$T(n) = 5T\left(\frac{n}{3}\right) + cn$$

- We now apply the Master Theorem:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- How fast is this algorithm?

- We have replaced a multiplication of two n bit numbers with 5 multiplications of $n/3$ bit numbers with an overhead of additions, shifts and the similar, all doable in linear time cn ;
- thus,

$$T(n) = 5T\left(\frac{n}{3}\right) + cn$$

- We now apply the Master Theorem:

we have $a = 5$, $b = 3$, so we consider $n^{\log_3 5} = n^{\log_3 5} \approx n^{1.46}$.

The Karatsuba trick: slicing into 3 pieces

- How fast is this algorithm?

- We have replaced a multiplication of two n bit numbers with 5 multiplications of $n/3$ bit numbers with an overhead of additions, shifts and the similar, all doable in linear time cn ;
- thus,

$$T(n) = 5T\left(\frac{n}{3}\right) + cn$$

- We now apply the Master Theorem:

we have $a = 5$, $b = 3$, so we consider $n^{\log_3 5} = n^{\log_3 5} \approx n^{1.46}$.

- Clearly, the first case of the MT applies and we get $T(n) = O(n^{\log_3 5}) < O(n^{1.47})$.

The Karatsuba trick: slicing into 3 pieces

- Recall that the original Karatsuba algorithm runs in time

$$n^{\log_2 3} \approx n^{1.58} > n^{1.47}.$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- Recall that the original Karatsuba algorithm runs in time

$$n^{\log_2 3} \approx n^{1.58} > n^{1.47}.$$

- Thus, we got a significantly faster algorithm.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- Recall that the original Karatsuba algorithm runs in time

$$n^{\log_2 3} \approx n^{1.58} > n^{1.47}.$$

- Thus, we got a significantly faster algorithm.

- Then why not slice numbers A and B into even larger number of slices?
Maybe we can get even faster algorithm?

Add WeChat powcoder

The Karatsuba trick: slicing into 3 pieces

- Recall that the original Karatsuba algorithm runs in time

$$n^{\log_2 3} \approx n^{1.58} > n^{1.47}.$$

- Thus, we got a significantly faster algorithm.

- Then why not slice numbers A and B into even larger number of slices? Maybe we can get even faster algorithm?

- The answer is, in a sense, BOTH yes and no, so let's see what happens if we slice numbers into $p + 1$ many (approximately) equal slices, where $p = 1, 2, 3, \dots$

The **general case** - slicing the input numbers A, B into $p + 1$ many slices

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Generalizing Karatsuba's algorithm

The general case - slicing the input numbers A, B into $p + 1$ many slices

- For simplicity, let us assume A and B have exactly $(p + 1)k$ bits (otherwise one of the slices will have to be shorter):

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Generalizing Karatsuba's algorithm

The general case - slicing the input numbers A, B into $p + 1$ many slices

- For simplicity, let us assume A and B have exactly $(p + 1)k$ bits (otherwise one of the slices will have to be shorter):

- Note: p is a fixed (smallish) number, a fixed parameter of our design – $p + 1$ is the number of slices we are going to make, but k depends on the input values A and B and can be arbitrarily large!

<https://powcoder.com>

Add WeChat powcoder

Generalizing Karatsuba's algorithm

The general case - slicing the input numbers A, B into $p + 1$ many slices

- For simplicity, let us assume A and B have exactly $(p + 1)k$ bits (otherwise one of the slices will have to be shorter):
- Note: p is a fixed (smallish) number, a fixed parameter of our design – $p + 1$ is the number of slices we are going to make, but k depends on the input values A and B and can be arbitrarily large!
- Slice A, B into $p + 1$ pieces each:

$$A = A_p 2^{kp} + A_{p-1} 2^{k(p-1)} + \dots + A_0$$

$$B = B_p 2^{kp} + B_{p-1} 2^{k(p-1)} + \dots + B_0$$

Add WeChat powcoder

Generalizing Karatsuba's algorithm

The general case - slicing the input numbers A, B into $p + 1$ many slices


- For simplicity, let us assume A and B have exactly $(p + 1)k$ bits (otherwise one of the slices will have to be shorter):

- Note: p is a fixed (smallish) number, a fixed parameter of our design – $p + 1$ is the number of slices we are going to make, but k depends on the input values A and B and can be arbitrarily large!

- Slice A, B into $p + 1$ pieces each:

$$A = A_p 2^{kp} + A_{p-1} 2^{k(p-1)} + \dots + A_0$$

$$B = B_p 2^{kp} + B_{p-1} 2^{k(p-1)} + \dots + B_0$$



A divided into $p+1$ slices each slice k bits = $(p+1)k$ bits in total

Generalizing Karatsuba's algorithm

- We form the naturally corresponding polynomials:

$$P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \cdots + A_0$$

$$P_B(x) = B_r x^r + B_{r-1} x^{r-1} + \cdots + B_0$$

- As before, we have:

$$A = P_A(2^k); \quad B = P_B(2^k); \quad AB = P_A(2^k)P_B(2^k) = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- We form the naturally corresponding polynomials:

$$P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \cdots + A_0$$

$$P_B(x) = B_p x^p + B_{p-1} x^{p-1} + \cdots + B_0$$

- As before, we have:

$$A = P_A(2^k); \quad B = P_B(2^k); \quad AB = P_A(2^k)P_B(2^k) = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

- Since

$$AB = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- We form the naturally corresponding polynomials:

$$P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \cdots + A_0$$

$$P_B(x) = B_p x^p + B_{p-1} x^{p-1} + \cdots + B_0$$

- As before, we have:

$$A = P_A(2^k); \quad B = P_B(2^k); \quad AB = P_A(2^k)P_B(2^k) = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

- Since

$$AB = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

we adopt the following strategy:

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- We form the naturally corresponding polynomials:

$$P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \cdots + A_0$$

$$P_B(x) = B_r x^r + B_{r-1} x^{r-1} + \cdots + B_0$$

- As before, we have:

$$A = P_A(2^k); \quad B = P_B(2^k); \quad AB = P_A(2^k)P_B(2^k) = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

- Since

$$AB = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

we adopt the following strategy:

- we will first figure out how to multiply polynomials fast to obtain

$$P_C(x) = P_A(x) \cdot P_B(x);$$

Generalizing Karatsuba's algorithm

- We form the naturally corresponding polynomials:

$$P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \cdots + A_0$$

$$P_B(x) = B_r x^r + B_{r-1} x^{r-1} + \cdots + B_0$$

- As before, we have:

$$A = P_A(2^k); \quad B = P_B(2^k); \quad AB = P_A(2^k)P_B(2^k) = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

- Since

$$AB = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

we adopt the following strategy:

- we will first figure out how to multiply polynomials fast to obtain

$$P_C(x) = P_A(x) \cdot P_B(x);$$

- then we evaluate $P_C(2^k)$.

Generalizing Karatsuba's algorithm

- We form the naturally corresponding polynomials:

$$P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \cdots + A_0$$

$$P_B(x) = B_p x^p + B_{p-1} x^{p-1} + \cdots + B_0$$

- As before, we have:

$$A = P_A(2^k); \quad B = P_B(2^k); \quad AB = P_A(2^k)P_B(2^k) = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

- Since

$$AB = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

we adopt the following strategy:

- we will first figure out how to multiply polynomials fast to obtain

$$P_C(x) = P_A(x) \cdot P_B(x);$$

- then we evaluate $P_C(2^k)$.

- Note that $P_C(x) = P_A(x) \cdot P_B(x)$ is of degree $2p$:

Generalizing Karatsuba's algorithm

- We form the naturally corresponding polynomials:

$$P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \cdots + A_0$$

$$P_B(x) = B_p x^p + B_{p-1} x^{p-1} + \cdots + B_0$$

- As before, we have:

$$A = P_A(2^k); \quad B = P_B(2^k); \quad AB = P_A(2^k)P_B(2^k) = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

- Since

$$AB = (P_A(x) \cdot P_B(x))|_{x=2^k}$$

we adopt the following strategy:

- we will first figure out how to multiply polynomials fast to obtain

$$P_C(x) = P_A(x) \cdot P_B(x);$$

- then we evaluate $P_C(2^k)$.

- Note that $P_C(x) = P_A(x) \cdot P_B(x)$ is of degree $2p$:

$$P_C(x) = \sum_{j=0}^{2p} C_j x^j$$

Generalizing Karatsuba's algorithm

- Example:

$$(A_3x^3 + A_2x^2 + A_1x + A_0)(B_3x^3 + B_2x^2 + B_1x + B_0) =$$

$$\begin{aligned} & A_3B_3x^6 + (A_3B_2 + A_2B_3)x^5 + (A_3B_1 + A_2B_2 + A_1B_3)x^4 \\ & + (A_3B_0 + A_2B_1 + A_1B_2 + A_0B_3)x^3 + (A_2B_0 + A_1B_1 + A_0B_2)x^2 \\ & + (A_1B_0 + A_0B_1)x + A_0B_0 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- Example:

$$(A_3x^3 + A_2x^2 + A_1x + A_0)(B_3x^3 + B_2x^2 + B_1x + B_0) =$$

$$\begin{aligned} & A_3B_3x^6 + (A_3B_2 + A_2B_3)x^5 + (A_3B_1 + A_2B_2 + A_1B_3)x^4 \\ & + (A_3B_0 + A_2B_1 + A_1B_2 + A_0B_3)x^3 + (A_2B_0 + A_1B_1 + A_0B_2)x^2 \\ & + (A_1B_0 + A_0B_1)x + A_0B_0 \end{aligned}$$

- In general: for

$$\begin{aligned} P_A(x) &= A_px^p + A_{p-1}x^{p-1} + \cdots + A_0 \\ P_B(x) &= B_px^p + B_{p-1}x^{p-1} + \cdots + B_0 \end{aligned}$$

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- Example:

$$(A_3x^3 + A_2x^2 + A_1x + A_0)(B_3x^3 + B_2x^2 + B_1x + B_0) =$$

$$\begin{aligned} & A_3B_3x^6 + (A_3B_2 + A_2B_3)x^5 + (A_3B_1 + A_2B_2 + A_1B_3)x^4 \\ & + (A_3B_0 + A_2B_1 + A_1B_2 + A_0B_3)x^3 + (A_2B_0 + A_1B_1 + A_0B_2)x^2 \\ & + (A_1B_0 + A_0B_1)x + A_0B_0 \end{aligned}$$

- In general: for

$$P_A(x) = A_px^p + A_{p-1}x^{p-1} + \dots + A_0$$

$$P_B(x) = B_px^p + B_{p-1}x^{p-1} + \dots + B_0$$

we have

Add WeChat powcoder

Generalizing Karatsuba's algorithm

- Example:

$$(A_3x^3 + A_2x^2 + A_1x + A_0)(B_3x^3 + B_2x^2 + B_1x + B_0) =$$

$$\begin{aligned} & A_3B_3x^6 + (A_3B_2 + A_2B_3)x^5 + (A_3B_1 + A_2B_2 + A_1B_3)x^4 \\ & + (A_3B_0 + A_2B_1 + A_1B_2 + A_0B_3)x^3 + (A_2B_0 + A_1B_1 + A_0B_2)x^2 \\ & + (A_1B_0 + A_0B_1)x + A_0B_0 \end{aligned}$$

- In general: for

$$P_A(x) = A_px^p + A_{p-1}x^{p-1} + \cdots + A_0$$

$$P_B(x) = B_px^p + B_{p-1}x^{p-1} + \cdots + B_0$$

we have

$$P_A(x) \cdot P_B(x) = \sum_{j=0}^{2p} \left(\sum_{i+k=j} A_i B_k \right) x^j = \sum_{j=0}^{2p} C_j x^j$$

Generalizing Karatsuba's algorithm

- Example:

$$(A_3x^3 + A_2x^2 + A_1x + A_0)(B_3x^3 + B_2x^2 + B_1x + B_0) =$$

$$\begin{aligned} & A_3B_3x^6 + (A_3B_2 + A_2B_3)x^5 + (A_3B_1 + A_2B_2 + A_1B_3)x^4 \\ & + (A_3B_0 + A_2B_1 + A_1B_2 + A_0B_3)x^3 + (A_2B_0 + A_1B_1 + A_0B_2)x^2 \\ & + (A_1B_0 + A_0B_1)x + A_0B_0 \end{aligned}$$

- In general: for

$$P_A(x) = A_px^p + A_{p-1}x^{p-1} + \dots + A_0$$

$$P_B(x) = B_px^p + B_{p-1}x^{p-1} + \dots + B_0$$

we have

$$P_A(x) \cdot P_B(x) = \sum_{j=0}^{2p} \left(\sum_{i+k=j} A_i B_k \right) x^j = \sum_{j=0}^{2p} C_j x^j$$

- We need to find the coefficients $C_j = \sum_{i+k=j} A_i B_k$ without performing $(p+1)^2$ many multiplications necessary to get all products of the form $A_i B_k$.

A VERY IMPORTANT DIGRESSION:

If you have two sequences $\vec{A} = (A_0, A_1, \dots, A_{p-1}, A_p)$ and $\vec{B} = (B_0, B_1, \dots, B_{m-1}, B_m)$, and if you form the two corresponding polynomials

$$\begin{aligned} P_A(x) &= A_0 + A_1x + \dots + A_{p-1}x^{p-1} + A_px^p \\ P_B(x) &= B_0 + B_1x + \dots + B_{m-1}x^{m-1} + B_mx^m \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A VERY IMPORTANT DIGRESSION:

If you have two sequences $\vec{A} = (A_0, A_1, \dots, A_{p-1}, A_p)$ and $\vec{B} = (B_0, B_1, \dots, B_{m-1}, B_m)$, and if you form the two corresponding polynomials

$$\begin{aligned} P_A(x) &= A_0 + A_1x + \dots + A_{p-1}x^{p-1} + A_px^p \\ P_B(x) &= B_0 + B_1x + \dots + B_{m-1}x^{m-1} + B_mx^m \end{aligned}$$

and if you multiply these two polynomials to obtain their product

$$P_A(x) \cdot P_B(x) = \sum_{j=0}^{n+p} \left(\sum_{i+k=j} A_i B_k \right) x^j = \sum_{j=0}^{n+p} C_j x^j$$

Add WeChat powcoder

A VERY IMPORTANT DIGRESSION:

If you have two sequences $\vec{A} = (A_0, A_1, \dots, A_{p-1}, A_p)$ and $\vec{B} = (B_0, B_1, \dots, B_{m-1}, B_m)$, and if you form the two corresponding polynomials

$$\begin{aligned} P_A(x) &= A_0 + A_1x + \dots + A_{p-1}x^{p-1} + A_px^p \\ P_B(x) &= B_0 + B_1x + \dots + B_{m-1}x^{m-1} + B_mx^m \end{aligned}$$

Assignment Project Exam Help

and if you multiply these two polynomials to obtain their product

$$P_A(x) \cdot P_B(x) = \sum_{j=0}^{p+m} \left(\sum_{i+k=j} A_i B_k \right) x^j = \sum_{j=0}^{p+m} C_j x^j$$

https://powcoder.com

then the sequence $\vec{C} = (C_0, C_1, \dots, C_{p+m})$ of the coefficients of the product polynomial, with these coefficients given by

$$C_j = \sum_{i+k=j} A_i B_k, \quad \text{for } 0 \leq j \leq p+m,$$

Add WeChat powcoder

is **extremely important** and is called the **LINEAR CONVOLUTION** of sequences \vec{A} and \vec{B} and is denoted by $\vec{C} = \vec{A} \star \vec{B}$.

AN IMPORTANT DIGRESSION:

- For example, if you have an audio signal and you want to emphasise the bass sounds, you would pass the sequence of discrete samples of the signal through a digital filter which amplifies the low frequencies more than the medium and the high audio frequencies.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

AN IMPORTANT DIGRESSION:

- For example, if you have an audio signal and you want to emphasise the bass sounds, you would pass the sequence of discrete samples of the signal through a digital filter which amplifies the low frequencies more than the medium and the high audio frequencies.
- This is accomplished by computing the linear convolution of the sequence of discrete samples of the signal with a sequence of values which correspond to that filter, called *the impulse response* of the filter.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

AN IMPORTANT DIGRESSION:

- For example, if you have an audio signal and you want to emphasise the bass sounds, you would pass the sequence of discrete samples of the signal through a digital filter which amplifies the low frequencies more than the medium and the high audio frequencies.
- This is accomplished by computing the linear convolution of the sequence of discrete samples of the signal with a sequence of values which correspond to that filter, called *the impulse response* of the filter.
- This means that the samples of the output sound are simply the coefficients of the product of two polynomials.

<https://powcoder.com>

Add WeChat powcoder

AN IMPORTANT DIGRESSION:

- For example, if you have an audio signal and you want to emphasise the bass sounds, you would pass the sequence of discrete samples of the signal through a digital filter which amplifies the low frequencies more than the medium and the high audio frequencies.
- This is accomplished by computing the linear convolution of the sequence of discrete samples of the signal with a sequence of values which correspond to that filter, called *the impulse response* of the filter.
- This means that the samples of the output sound are simply the coefficients of the product of two polynomials:
 - ① polynomial $P_A(x)$ whose coefficients A_i are the samples of the input signal;

Add WeChat powcoder

AN IMPORTANT DIGRESSION:

- For example, if you have an audio signal and you want to emphasise the bass sounds, you would pass the sequence of discrete samples of the signal through a digital filter which amplifies the low frequencies more than the medium and the high audio frequencies.
- This is accomplished by computing the linear convolution of the sequence of discrete samples of the signal with a sequence of values which correspond to that filter, called *the impulse response* of the filter.
- This means that the samples of the output sound are simply the coefficients of the product of two polynomials:
 - ① polynomial $P_A(x)$ whose coefficients A_i are the samples of the input signal;
 - ② polynomial $P_B(x)$ whose coefficients B_k are the samples of the so called impulse response of the filter (they depend of what kind of filtering you want to do).

AN IMPORTANT DIGRESSION:

- For example, if you have an audio signal and you want to emphasise the bass sounds, you would pass the sequence of discrete samples of the signal through a digital filter which amplifies the low frequencies more than the medium and the high audio frequencies.
- This is accomplished by computing the linear convolution of the sequence of discrete samples of the signal with a sequence of values which correspond to that filter, called *the impulse response* of the filter.
- This means that the samples of the output sound are simply the coefficients of the product of two polynomials:
 - ① polynomial $P_A(x)$ whose coefficients A_i are the samples of the input signal;
 - ② polynomial $P_B(x)$ whose coefficients B_k are the samples of the so called impulse response of the filter (they depend of what kind of filtering you want to do).
- Convolutions are bread-and-butter of signal processing, and for that reason it is **extremely important** to find fast ways of multiplying two polynomials of possibly very large degrees.

AN IMPORTANT DIGRESSION:

- For example, if you have an audio signal and you want to emphasise the bass sounds, you would pass the sequence of discrete samples of the signal through a digital filter which amplifies the low frequencies more than the medium and the high audio frequencies.
- This is accomplished by computing the linear convolution of the sequence of discrete samples of the signal with a sequence of values which correspond to that filter, called *the impulse response* of the filter.
- This means that the samples of the output sound are simply the coefficients of the product of two polynomials:
 - ① polynomial $P_A(x)$ whose coefficients A_i are the samples of the input signal;
 - ② polynomial $P_B(x)$ whose coefficients B_k are the samples of the so called impulse response of the filter (they depend of what kind of filtering you want to do).
- Convolutions are bread-and-butter of signal processing, and for that reason it is **extremely important** to find fast ways of multiplying two polynomials of possibly very large degrees.
- In signal processing these degrees can be greater than 1000.

AN IMPORTANT DIGRESSION:

- For example, if you have an audio signal and you want to emphasise the bass sounds, you would pass the sequence of discrete samples of the signal through a digital filter which amplifies the low frequencies more than the medium and the high audio frequencies.
- This is accomplished by computing the linear convolution of the sequence of discrete samples of the signal with a sequence of values which correspond to that filter, called *the impulse response* of the filter.
- This means that the samples of the output sound are simply the coefficients of the product of two polynomials:
 - ① polynomial $P_A(x)$ whose coefficients A_i are the samples of the input signal;
 - ② polynomial $P_B(x)$ whose coefficients B_k are the samples of the so called impulse response of the filter (they depend of what kind of filtering you want to do).
- Convolutions are bread-and-butter of signal processing, and for that reason it is **extremely important** to find fast ways of multiplying two polynomials of possibly very large degrees.
- In signal processing these degrees can be greater than 1000.
- This is the main reason for us to study methods of fast computation of convolutions (aside of finding products of large integers, which is what we are doing at the moment).

- Every polynomial $P_A(x)$ of degree p is uniquely determined by its values at any $p + 1$ distinct input values x_0, x_1, \dots, x_p :

Assignment Project Exam Help

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_p, P_A(x_p))\}$$

<https://powcoder.com>

Add WeChat powcoder

Coefficient vs value representation of polynomials

- Every polynomial $P_A(x)$ of degree p is uniquely determined by its values at any $p + 1$ distinct input values x_0, x_1, \dots, x_p :

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_p, P_A(x_p))\}$$

- For $P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \dots + A_0$, these values can be obtained via a matrix multiplication:

$$\begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} \quad (1)$$

Coefficient vs value representation of polynomials

- Every polynomial $P_A(x)$ of degree p is uniquely determined by its values at any $p + 1$ distinct input values x_0, x_1, \dots, x_p :

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_p, P_A(x_p))\}$$

- For $P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \dots + A_0$, these values can be obtained via a matrix multiplication:

$$\begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} \quad (1)$$

- It can be shown that if x_i are all distinct then this matrix is invertible.

Coefficient vs value representation of polynomials

- Every polynomial $P_A(x)$ of degree p is uniquely determined by its values at any $p + 1$ distinct input values x_0, x_1, \dots, x_p :

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_p, P_A(x_p))\}$$

- For $P_A(x) = A_p x^p + A_{p-1} x^{p-1} + \dots + A_0$, these values can be obtained via a matrix multiplication:

$$\begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} \quad (1)$$

- It can be shown that if x_i are all distinct then this matrix is invertible.
- Such a matrix is called *the Vandermonde matrix*.

- Thus, if all x_i are all distinct, given any values $P_A(x_0), P_A(x_1), \dots, P_A(x_p)$ the coefficients A_0, A_1, \dots, A_p of the polynomial $P_A(\cdot)$ are uniquely determined:

$$\begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} \quad (2)$$

Add WeChat powcoder

- Thus, if all x_i are all distinct, given any values $P_A(x_0), P_A(x_1), \dots, P_A(x_p)$ the coefficients A_0, A_1, \dots, A_p of the polynomial $P_A(\cdot)$ are uniquely determined:

$$\begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} \quad (2)$$

<https://powcoder.com>

- Equations (1) and (2) show how we can commute between:

Add WeChat powcoder

Coefficient vs value representation of polynomials - ctd.

- Thus, if all x_i are all distinct, given any values $P_A(x_0), P_A(x_1), \dots, P_A(x_p)$ the coefficients A_0, A_1, \dots, A_p of the polynomial $P_A(x)$ are uniquely determined:

$$\begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} \quad (2)$$

- Equations (1) and (2) show how we can commute between:

- 1 a representation of a polynomial $P_A(x)$ via its coefficients A_p, A_{p-1}, \dots, A_0 , i.e. $P_A(x) = A_p x^p + \dots + A_1 x + A_0$

- Thus, if all x_i are all distinct, given any values $P_A(x_0), P_A(x_1), \dots, P_A(x_p)$ the coefficients A_0, A_1, \dots, A_p of the polynomial $P_A(x)$ are uniquely determined:

$$\begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} \quad (2)$$

- Equations (1) and (2) show how we can commute between:

- a representation of a polynomial $P_A(x)$ via its coefficients A_p, A_{p-1}, \dots, A_0 , i.e. $P_A(x) = A_p x^p + \dots + A_1 x + A_0$
- a representation of a polynomial $P_A(x)$ via its values

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_p, P_A(x_p))\}$$

Coefficient vs value representation of polynomials- ctd.

- If we fix the inputs x_0, x_1, \dots, x_p then commuting between a representation of a polynomial $P_A(x)$ via its coefficients and a representation via its values at these points is done via the following two matrix multiplications, with matrices made up from constants:

$$\begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix};$$

Add WeChat powcoder

Coefficient vs value representation of polynomials- ctd.

- If we fix the inputs x_0, x_1, \dots, x_p then commuting between a representation of a polynomial $P_A(x)$ via its coefficients and a representation via its values at these points is done via the following two matrix multiplications, with matrices made up from constants:

$$\begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix};$$

$$\begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix}^{-1} \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix}.$$

Coefficient vs value representation of polynomials- ctd.

- If we fix the inputs x_0, x_1, \dots, x_p then commuting between a representation of a polynomial $P_A(x)$ via its coefficients and a representation via its values at these points is done via the following two matrix multiplications, with matrices made up from constants:

$$\begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix} \begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix};$$

$$\begin{pmatrix} A_0 \\ A_1 \\ \vdots \\ A_p \end{pmatrix} = \begin{pmatrix} 1 & x_0 & x_0^2 & \dots & x_0^p \\ 1 & x_1 & x_1^2 & \dots & x_1^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_p & x_p^2 & \dots & x_p^p \end{pmatrix}^{-1} \begin{pmatrix} P_A(x_0) \\ P_A(x_1) \\ \vdots \\ P_A(x_p) \end{pmatrix}.$$

- Thus, for fixed input values x_0, \dots, x_p this switch between the two kinds of representations is done in **linear time**!

Our strategy to multiply polynomials fast:

- 1 Given two polynomials of degree at most p ,

$$P_A(x) = A_p x^p + \dots + A_0; \quad P_B(x) = B_p x^p + \dots + B_0$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Our strategy to multiply polynomials fast:

- 1 Given two polynomials of degree at most p ,

$$P_A(x) = A_px^p + \dots + A_0; \quad P_B(x) = B_px^p + \dots + B_0$$

convert them into value representation at $2p+1$ distinct points x_0, x_1, \dots, x_{2p} .

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_{2p}, P_A(x_{2p}))\}$$

$$P_B(x) \leftrightarrow \{(x_0, P_B(x_0)), (x_1, P_B(x_1)), \dots, (x_{2p}, P_B(x_{2p}))\}$$

<https://powcoder.com>

Add WeChat powcoder

Our strategy to multiply polynomials fast:

- 1 Given two polynomials of degree at most p ,

$$P_A(x) = A_px^p + \dots + A_0; \quad P_B(x) = B_px^p + \dots + B_0$$

convert them into value representation at $2p + 1$ distinct points x_0, x_1, \dots, x_{2p} .

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_{2p}, P_A(x_{2p}))\}$$

$$P_B(x) \leftrightarrow \{(x_0, P_B(x_0)), (x_1, P_B(x_1)), \dots, (x_{2p}, P_B(x_{2p}))\}$$

- **Note:** since the product of the two polynomials will be of degree $2p$ we need the values of $P_A(x)$ and $P_B(x)$ at $2p + 1$ points, rather than just $p + 1$ points!

Add WeChat powcoder

Our strategy to multiply polynomials fast:

- 1 Given two polynomials of degree at most p ,

$$P_A(x) = A_px^p + \dots + A_0; \quad P_B(x) = B_px^p + \dots + B_0$$

convert them into value representation at $2p + 1$ distinct points x_0, x_1, \dots, x_{2p} .

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_{2p}, P_A(x_{2p}))\}$$

$$P_B(x) \leftrightarrow \{(x_0, P_B(x_0)), (x_1, P_B(x_1)), \dots, (x_{2p}, P_B(x_{2p}))\}$$

- **Note:** since the product of the two polynomials will be of degree $2p$ we need the values of $P_A(x)$ and $P_B(x)$ at $2p + 1$ points, rather than just $p + 1$ points!

- 2 Multiply these two polynomials point-wise, using $2p + 1$ multiplications only.

Our strategy to multiply polynomials fast:

- 1 Given two polynomials of degree at most p ,

$$P_A(x) = A_px^p + \dots + A_0; \quad P_B(x) = B_px^p + \dots + B_0$$

convert them into value representation at $2p + 1$ distinct points x_0, x_1, \dots, x_{2p} .

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_{2p}, P_A(x_{2p}))\}$$

$$P_B(x) \leftrightarrow \{(x_0, P_B(x_0)), (x_1, P_B(x_1)), \dots, (x_{2p}, P_B(x_{2p}))\}$$

- Note: since the product of the two polynomials will be of degree $2p$ we need the values of $P_A(x)$ and $P_B(x)$ at $2p + 1$ points, rather than just $p + 1$ points!

- 2 Multiply these two polynomials point-wise, using $2p + 1$ multiplications only.

$$P_A(x)P_B(x) \leftrightarrow \{(x_0, \underbrace{P_A(x_0)P_B(x_0)}_{P_C(x_0)}), (x_1, \underbrace{P_A(x_1)P_B(x_1)}_{P_C(x_1)}), \dots, (x_{2p}, \underbrace{P_A(x_{2p})P_B(x_{2p})}_{P_C(x_{2p})})\}$$

Our strategy to multiply polynomials fast:

- 1 Given two polynomials of degree at most p ,

$$P_A(x) = A_px^p + \dots + A_0; \quad P_B(x) = B_px^p + \dots + B_0$$

convert them into value representation at $2p+1$ distinct points x_0, x_1, \dots, x_{2p} .

$$P_A(x) \leftrightarrow \{(x_0, P_A(x_0)), (x_1, P_A(x_1)), \dots, (x_{2p}, P_A(x_{2p}))\}$$

$$P_B(x) \leftrightarrow \{(x_0, P_B(x_0)), (x_1, P_B(x_1)), \dots, (x_{2p}, P_B(x_{2p}))\}$$

- Note: since the product of the two polynomials will be of degree $2p$ we need the values of $P_A(x)$ and $P_B(x)$ at $2p+1$ points, rather than just $p+1$ points!

- 2 Multiply these two polynomials point-wise, using $2p+1$ multiplications only.

$$P_A(x)P_B(x) \leftrightarrow \{(x_0, \underbrace{P_A(x_0)P_B(x_0)}_{P_C(x_0)}), (x_1, \underbrace{P_A(x_1)P_B(x_1)}_{P_C(x_1)}), \dots, (x_{2p}, \underbrace{P_A(x_{2p})P_B(x_{2p})}_{P_C(x_{2p})})\}$$

- 3 Convert such value representation of $P_C(x) = P_A(x)P_B(x)$ back to coefficient form

$$P_C(x) = C_{2p}x^{2p} + C_{2p-1}x^{2p-1} + \dots + C_1x + C_0;$$

- What values should we choose for $x_0, x_1, \dots, x_{2p}??$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- What values should we choose for $x_0, x_1, \dots, x_{2p}??$
- Key idea: use $2p + 1$ smallest possible integer values!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Fast multiplication of polynomials - continued

- What values should we choose for x_0, x_1, \dots, x_{2p} ??
- Key idea: use $2p + 1$ smallest possible integer values!

Assignment $\{-p, \dots, p-1\}, \dots, \{-1, 0, 1, \dots, p-1, p\}$ Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Fast multiplication of polynomials - continued

- What values should we choose for x_0, x_1, \dots, x_{2p} ??
- Key idea: use $2p + 1$ smallest possible integer values!

Assignment Project Exam Help

- So we find the values $P_A(m)$ and $P_B(m)$ for all m such that $-p \leq m \leq p$.

<https://powcoder.com>

Add WeChat powcoder

Fast multiplication of polynomials - continued

- What values should we choose for x_0, x_1, \dots, x_{2p} ??
- Key idea: use $2p + 1$ smallest possible integer values!

Assignment Project Exam Help

- So we find the values $P_A(m)$ and $P_B(m)$ for all m such that $-p \leq m \leq p$.
- Remember that $p + 1$ is the number of slices we split the input numbers A, B .

<https://powcoder.com>

Add WeChat powcoder

Fast multiplication of polynomials - continued

- What values should we choose for x_0, x_1, \dots, x_{2p} ??
- Key idea: use $2p + 1$ smallest possible integer values!

Assignment Project Exam Help

- So we find the values $P_A(m)$ and $P_B(m)$ for all m such that $-p \leq m \leq p$.
- Remember that $p + 1$ is the number of slices we split the input numbers A, B .
- Multiplication of a large number with k bits by a constant integer d can be done in time linear in k because it is reducible to $d - 1$ additions:

$$d \cdot A = \underbrace{A + A + \dots + A}_{d-1 \text{ times}}$$

Add WeChat powcoder

Fast multiplication of polynomials - continued

- What values should we choose for $x_0, x_1, \dots, x_{2p}??$
- Key idea: use $2p + 1$ smallest possible integer values!

Assignment Project Exam Help

- So we find the values $P_A(m)$ and $P_B(m)$ for all m such that $-p \leq m \leq p$.
- Remember that $p + 1$ is the number of slices we split the input numbers A, B .
- Multiplication of a large number with k bits by a constant integer d can be done in time linear in k because it is reducible to $d - 1$ additions:

$$d \cdot A = \underbrace{A + A + \dots + A}_{d \text{ times}}$$

Add WeChat powcoder

- Thus, all the values

$$P_A(m) = A_p m^p + A_{p-1} m^{p-1} + \dots + A_0 : \quad -p \leq m \leq p,$$

$$P_B(m) = B_p m^p + B_{p-1} m^{p-1} + \dots + B_0 : \quad -p \leq m \leq p.$$

can be found in time linear in the number of bits of the input numbers!

Fast multiplication of polynomials - ctd.

- We now perform $2p + 1$ **multiplications of large numbers** to obtain

$P_A(-p)P_B(-p), \dots, P_A(-1)P_B(-1), P_A(0)P_B(0), P_A(1)P_B(1), \dots, P_A(p)P_B(p)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Fast multiplication of polynomials - ctd.

- We now perform $2p + 1$ **multiplications of large numbers** to obtain

$$P_A(-p)P_B(-p), \dots, P_A(-1)P_B(-1), P_A(0)P_B(0), P_A(1)P_B(1), \dots, P_A(p)P_B(p)$$

Assignment Project Exam Help

- For $P_C(x) = P_A(x)P_B(x)$ these products are $2p + 1$ many values of $P_C(x)$:

$$P_C(-p) = P_A(-p)P_B(-p), \dots, P_C(0) = P_A(0)P_B(0), \dots, P_C(p) = P_A(p)P_B(p)$$

<https://powcoder.com>

Add WeChat powcoder

Fast multiplication of polynomials - ctd.

- We now perform $2p + 1$ **multiplications of large numbers** to obtain

$$P_A(-p)P_B(-p), \dots, P_A(-1)P_B(-1), P_A(0)P_B(0), P_A(1)P_B(1), \dots, P_A(p)P_B(p)$$

Assignment Project Exam Help

- For $P_C(x) = P_A(x)P_B(x)$ these products are $2p + 1$ many values of $P_C(x)$:

$$P_C(-p) = P_A(-p)P_B(-p), \dots, P_C(0) = P_A(0)P_B(0), \dots, P_C(p) = P_A(p)P_B(p)$$

- Let C_0, C_1, \dots, C_{2p} be the coefficients of the product polynomial $C(x)$, i.e., let

$$P_C(x) = C_{2p}x^{2p} + C_{2p-1}x^{2p-1} + \dots + C_0,$$

Add WeChat powcoder

Fast multiplication of polynomials - ctd.

- We now perform $2p + 1$ **multiplications of large numbers** to obtain

$$P_A(-p)P_B(-p), \dots, P_A(-1)P_B(-1), P_A(0)P_B(0), P_A(1)P_B(1), \dots, P_A(p)P_B(p)$$

Assignment Project Exam Help

- For $P_C(x) = P_A(x)P_B(x)$ these products are $2p + 1$ many values of $P_C(x)$:

$$P_C(-p) = P_A(-p)P_B(-p), \dots, P_C(0) = P_A(0)P_B(0), \dots, P_C(p) = P_A(p)P_B(p)$$

- Let C_0, C_1, \dots, C_{2p} be the coefficients of the product polynomial $C(x)$, i.e., let

$$P_C(x) = C_{2p}x^{2p} + C_{2p-1}x^{2p-1} + \dots + C_0,$$

- We now have:

$$C_{2p}(-p)^{2p} + C_{2p-1}(-p)^{2p-1} + \dots + C_0 = P_C(-p)$$

$$C_{2p}(-(p-1))^{2p} + C_{2p-1}(-(p-1))^{2p-1} + \dots + C_0 = P_C(-(p-1))$$

$$\vdots$$

$$C_{2p}(p-1)^{2p} + C_{2p-1}(p-1)^{2p-1} + \dots + C_0 = P_C(p-1)$$

$$C_{2p}p^{2p} + C_{2p-1}p^{2p-1} + \dots + C_0 = P_C(p)$$

Fast multiplication of polynomials - ctd.

- This is just a system of linear equations, that can be solved for C_0, C_1, \dots, C_{2p} :

$$\begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix} \begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p-1} \\ C_{2p} \end{pmatrix} = \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}$$

<https://powcoder.com>

Add WeChat powcoder

Fast multiplication of polynomials - ctd.

- This is just a system of linear equations, that can be solved for C_0, C_1, \dots, C_{2p} :

$$\begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix} \begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p-1} \\ C_{2p} \end{pmatrix} = \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}$$

- i.e., we can obtain C_0, C_1, \dots, C_{2p} as

$$\begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p} \end{pmatrix} = \begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix}^{-1} \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}$$

Fast multiplication of polynomials - ctd.

- This is just a system of linear equations, that can be solved for C_0, C_1, \dots, C_{2p} :

$$\begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix} \begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p-1} \\ C_{2p} \end{pmatrix} = \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}$$

- i.e., we can obtain C_0, C_1, \dots, C_{2p} as

$$\begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p} \end{pmatrix} = \begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix}^{-1} \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}.$$

- But the inverse matrix also involves only constants depending on p only;

Fast multiplication of polynomials - ctd.

- This is just a system of linear equations, that can be solved for C_0, C_1, \dots, C_{2p} :

$$\begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix} \begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p-1} \\ C_{2p} \end{pmatrix} = \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}$$

- i.e., we can obtain C_0, C_1, \dots, C_{2p} as

$$\begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p} \end{pmatrix} = \begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix}^{-1} \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}$$

- But the inverse matrix also involves only constants depending on p only;
- Thus the coefficients C_i can be obtained in linear time.

Fast multiplication of polynomials - ctd.

- This is just a system of linear equations, that can be solved for C_0, C_1, \dots, C_{2p} :

$$\begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix} \begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p-1} \\ C_{2p} \end{pmatrix} = \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}$$

- i.e., we can obtain C_0, C_1, \dots, C_{2p} as

$$\begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p} \end{pmatrix} = \begin{pmatrix} 1 & -p & (-p)^2 & \dots & (-p)^{2p} \\ 1 & -(p-1) & (-(p-1))^2 & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & p-1 & (p-1)^2 & \dots & (p-1)^{2p} \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix}^{-1} \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p-1) \\ P_C(p) \end{pmatrix}$$

- But the inverse matrix also involves only constants depending on p only;
- Thus the coefficients C_i can be obtained in linear time.
- So here is the algorithm we have just described:

```

1: function MULT( $A, B$ )
2:   if  $|A| = |B| < p + 1$  then return  $AB$ 
3:   else
4:     obtain  $p + 1$  slices  $A_0, A_1, \dots, A_p$  and  $B_0, B_1, \dots, B_p$  such that

```

$$A = A_p 2^{p \cdot k} + A_{p-1} 2^{(p-1) \cdot k} + \dots + A_0$$

$$B = B_p 2^{p \cdot k} + B_{p-1} 2^{(p-1) \cdot k} + \dots + B_0$$

$$P_A(x) = A_p x^p + A_{p-1} x^{(p-1)} + \dots + A_0$$

$$P_B(x) = B_p x^p + B_{p-1} x^{(p-1)} + \dots + B_0$$

```

6:   for  $m = -p$  to  $m = p$  do
7:     compute  $P_A(m)$  and  $P_B(m)$ ;
8:      $P_C(m) \leftarrow \text{MULT}(P_A(m), P_B(m))$ 
9:   end for
10:  compute  $C_0, C_1, \dots, C_{2p}$  via

```

$$\begin{pmatrix} C_0 \\ C_1 \\ \vdots \\ C_{2p} \end{pmatrix} = \begin{pmatrix} 1 & (-p) & \dots & (-p)^{2p} \\ 1 & -(p-1) & \dots & (-(p-1))^{2p} \\ \vdots & \vdots & \ddots & \vdots \\ 1 & p & p^2 & \dots & p^{2p} \end{pmatrix}^{-1} \begin{pmatrix} P_C(-p) \\ P_C(-(p-1)) \\ \vdots \\ P_C(p) \end{pmatrix}.$$

```

11:   form  $P_C(x) = C_{2p} x^{2p} + \dots + C_0$  and compute  $P_C(2^k)$ 
12:   return  $P_C(2^k) = A \cdot B$ 
13: end if
14: end function

```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

How fast is our algorithm?

- it is easy to see that the values of the two polynomials we are multiplying have at most $k + s$ bits where s is a constant which depends on p but does NOT depend on k :

$$P_A(m) = A_p m^p + A_{p-1} m^{p-1} + \dots + A_0 \quad -p \leq m \leq p.$$

Assignment Project Exam Help

This is because each A_k is smaller than 2^k because each A_k has k bits; thus

$$|P_A(m)| < p^p(p+1) \times 2^k \Rightarrow \log_2 |P_A(m)| < \log_2(p^p(p+1)) + k = s + k$$

<https://powcoder.com>

Add WeChat powcoder

How fast is our algorithm?

- it is easy to see that the values of the two polynomials we are multiplying have at most $k + s$ bits where s is a constant which depends on p but does NOT depend on k :

$$P_A(m) = A_p m^p + A_{p-1} m^{p-1} + \dots + A_0 \quad -p \leq m \leq p.$$

This is because each A_i is smaller than 2^k because each A_k has k bits; thus

$$|P_A(m)| < p^p(p+1) \times 2^k \Rightarrow \log_2 |P_A(m)| < \log_2(p^p(p+1)) + k = s + k$$

- Thus, we have reduced a multiplication of two $k(p+1)$ digit numbers to $2p+1$ multiplications of $k+s$ digit numbers plus a linear overhead (of additions splitting the numbers etc.)

Add WeChat powcoder

How fast is our algorithm?

- it is easy to see that the values of the two polynomials we are multiplying have at most $k + s$ bits where s is a constant which depends on p but does NOT depend on k :

$$P_A(m) = A_p m^p + A_{p-1} m^{p-1} + \dots + A_0 \quad -p \leq m \leq p.$$

This is because each A_i is smaller than 2^k because each A_k has k bits; thus

$$|P_A(m)| < p^p(p+1) \times 2^k \Rightarrow \log_2 |P_A(m)| < \log_2(p^p(p+1)) + k = s + k$$

- Thus, we have reduced a multiplication of two $k(p+1)$ digit numbers to $2p+1$ multiplications of $k+s$ digit numbers plus a linear overhead (of additions splitting the numbers etc.)
- So we get the following recurrence for the complexity of $\text{MULT}(A, B)$:

Add WeChat powcoder

How fast is our algorithm?

- it is easy to see that the values of the two polynomials we are multiplying have at most $k + s$ bits where s is a constant which depends on p but does NOT depend on k :

$$P_A(m) = A_p m^p + A_{p-1} m^{p-1} + \dots + A_0 \quad -p \leq m \leq p.$$

This is because each A_i is smaller than 2^k because each A_k has k bits; thus

$$|P_A(m)| < p^p(p+1) \times 2^k \Rightarrow \log_2 |P_A(m)| < \log_2(p^p(p+1)) + k = s + k$$

- Thus, we have reduced a multiplication of two $k(p+1)$ digit numbers to $2p+1$ multiplications of $k+s$ digit numbers plus a linear overhead (of additions splitting the numbers etc.)
- So we get the following recurrence for the complexity of $\text{MULT}(A, B)$:

$$T((p+1)k) = (2p+1)T(k+s) + ck$$

How fast is our algorithm?

- it is easy to see that the values of the two polynomials we are multiplying have at most $k + s$ bits where s is a constant which depends on p but does NOT depend on k :

$$P_A(m) = A_p m^p + A_{p-1} m^{p-1} + \cdots + A_0 \quad -p \leq m \leq p.$$

This is because each A_i is smaller than 2^k because each A_k has k bits; thus

$$|P_A(m)| < p^p(p+1) \times 2^k \Rightarrow \log_2 |P_A(m)| < \log_2(p^p(p+1)) + k = s + k$$

- Thus, we have reduced a multiplication of two $k(p+1)$ digit numbers to $2p+1$ multiplications of $k+s$ digit numbers plus a linear overhead (of additions splitting the numbers etc.)
- So we get the following recurrence for the complexity of $\text{MULT}(A, B)$:

$$T((p+1)k) = (2p+1)T(k+s) + ck$$

- Let $n = (p+1)k$. Then

$$T(n) = \underbrace{(2p+1)}_a T\left(\underbrace{\frac{n}{p+1}}_b + s\right) + \frac{c}{p+1} n$$

How fast is our algorithm?

- it is easy to see that the values of the two polynomials we are multiplying have at most $k + s$ bits where s is a constant which depends on p but does NOT depend on k :

$$P_A(m) = A_p m^p + A_{p-1} m^{p-1} + \dots + A_0 \quad -p \leq m \leq p.$$

This is because each A_i is smaller than 2^k because each A_k has k bits; thus

$$|P_A(m)| < p^p (p+1) \times 2^k \Rightarrow \log_2 |P_A(m)| < \log_2 (p^p (p+1)) + k = s + k$$

- Thus, we have reduced a multiplication of two $k(p+1)$ digit numbers to $2p+1$ multiplications of $k+s$ digit numbers plus a linear overhead (of additions splitting the numbers etc.)
- So we get the following recurrence for the complexity of $\text{MULT}(A, B)$:

$$T((p+1)k) = (2p+1)T(k+s) + ck$$

- Let $n = (p+1)k$. Then

$$T(n) = \underbrace{(2p+1)}_a T\left(\underbrace{\frac{n}{p+1}}_b + s\right) + \frac{c}{p+1} n$$

- Since s is constant, its impact can be neglected.

How fast is our algorithm?

$$T(n) = \underbrace{(2p+1)}_a T\left(\underbrace{\frac{n}{p+1}}_b + s\right) + \frac{c}{p+1} n$$

Assignment Project Exam Help

- Since $\log_b a = \log_{p+1}(2p+1) > 1$, we can choose a small ε such that also $\log_b a - \varepsilon > 1$.

<https://powcoder.com>

Add WeChat powcoder

How fast is our algorithm?

$$T(n) = \underbrace{(2p+1)}_a T\left(\underbrace{\frac{n}{p+1}}_b + s\right) + \frac{c}{p+1} n$$

Assignment Project Exam Help

- Since $\log_b a = \log_{p+1}(2p+1) > 1$, we can choose a small ε such that also $\log_b a - \varepsilon > 1$.

<https://powcoder.com>

- Consequently, for such an ε we would have $f(n) = c/(p+1) n = O(n^{\log_b a - \varepsilon})$.

Add WeChat powcoder

How fast is our algorithm?

$$T(n) = \underbrace{(2p+1)}_a T\left(\underbrace{\frac{n}{p+1}}_b + s\right) + \frac{c}{p+1} n$$

Assignment Project Exam Help

- Since $\log_b a = \log_{p+1}(2p+1) > 1$, we can choose a small ε such that also $\log_b a - \varepsilon > 1$.

<https://powcoder.com>

- Consequently, for such an ε we would have $f(n) = c/(p+1)n = O(n^{\log_b a - \varepsilon})$.
- Thus, with $a = 2p+1$ and $b = p+1$ the first case of the Master Theorem applies;

Add WeChat powcoder

How fast is our algorithm?

$$T(n) = \underbrace{(2p+1)}_a T\left(\underbrace{\frac{n}{p+1}}_b + s\right) + \frac{c}{p+1} n$$

Assignment Project Exam Help

- Since $\log_b a = \log_{p+1}(2p+1) > 1$, we can choose a small ε such that also $\log_b a - \varepsilon > 1$.

<https://powcoder.com>

- Consequently, for such an ε we would have $f(n) = c/(p+1)n = O(n^{\log_b a - \varepsilon})$.
- Thus, with $a = 2p+1$ and $b = p+1$ the first case of the Master Theorem applies;
- so we get.

Add WeChat powcoder

$$T(n) = \Theta\left(n^{\log_b a}\right) = \Theta\left(n^{\log_{p+1}(2p+1)}\right)$$

- Note that

$$n^{\log_{p+1}(2p+1)} < n^{\log_{p+1} 2(p+1)} = n^{\log_{p+1} 2 + \log_{p+1}(p+1)}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Note that

$$n^{\log_{p+1}(2p+1)} < n^{\log_{p+1} 2(p+1)} = n^{\log_{p+1} 2 + \log_{p+1}(p+1)}$$

Assignment Project Exam Help

- Thus, by choosing a sufficiently large p , we can get a run time arbitrarily close to linear time!

<https://powcoder.com>

Add WeChat powcoder

- Note that

$$n^{\log_{p+1}(2p+1)} < n^{\log_{p+1} 2(p+1)} = n^{\log_{p+1} 2 + \log_{p+1}(p+1)}$$

Assignment Project Exam Help

- Thus, by choosing a sufficiently large p , we can get a run time arbitrarily close to linear time!

<https://powcoder.com>

- How large does p have to be, in order to get an algorithm which runs in time $n^{1.1}$?

Add WeChat powcoder

- Note that

$$n^{\log_{p+1}(2p+1)} < n^{\log_{p+1} 2(p+1)} = n^{\log_{p+1} 2 + \log_{p+1}(p+1)}$$

Assignment Project Exam Help

- Thus, by choosing a sufficiently large p , we can get a run time arbitrarily close to linear time!

<https://powcoder.com>

- How large does p have to be, in order to get an algorithm which runs in time $n^{1.1}$?

Add WeChat powcoder

$$n^{1.1} = n^{1 + \frac{1}{\log_2(p+1)}} \rightarrow \frac{1}{\log_2(p+1)} = \frac{1}{10} \rightarrow p+1 = 2^{10}$$

- Note that

$$n^{\log_{p+1}(2p+1)} < n^{\log_{p+1} 2(p+1)} = n^{\log_{p+1} 2 + \log_{p+1}(p+1)}$$

Assignment Project Exam Help

- Thus, by choosing a sufficiently large p , we can get a run time arbitrarily close to linear time!

<https://powcoder.com>

- How large does p have to be, in order to get an algorithm which runs in time $n^{1.1}$?

Add WeChat powcoder

- Thus, we would have to slice the input numbers into $2^{10} = 1024$ pieces!!

- We would have to evaluate polynomials $P_A(x)$ and $P_B(x)$ both of degree p at values up to p .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- We would have to evaluate polynomials $P_A(x)$ and $P_B(x)$ both of degree p at values up to p .

• However, $p = 2^{10}$, so evaluating $P_A(p) = A_p p^p + \dots + A_0$ involves multiplication of A_p with $p^p = (2^{10})^{2^{10}} \approx 1.27 \times 10^{307}$.

<https://powcoder.com>

Add WeChat powcoder

- We would have to evaluate polynomials $P_A(x)$ and $P_B(x)$ both of degree p at values up to p .

- However, $p = 2^{10}$, so evaluating $P_A(p) = A_p p^p + \dots + A_0$ involves multiplication of A_p with $p^p = (2^{10})^{2^{10}} \approx 1.27 \times 10^{307}$.

- Thus, while evaluations of $P_A(x)$ and $P_B(x)$ for $x = -p \dots p$ can **theoretically** all be done in linear time, $T(p) = cp$, the constant c is absolutely enormous.

Add WeChat powcoder

- We would have to evaluate polynomials $P_A(x)$ and $P_B(x)$ both of degree p at values up to p .

- However, $p = 2^{10}$, so evaluating $P_A(p) = A_p p^p + \dots + A_0$ involves multiplication of A_p with $p^p = (2^{10})^{2^{10}} \approx 1.27 \times 10^{307}$.

- Thus, while evaluations of $P_A(x)$ and $P_B(x)$ for $x = -p \dots p$ can **theoretically** all be done in linear time, $T(p) = cp$, the constant c is absolutely enormous.

- Consequently, slicing the input numbers in more than just a few slices results in a hopelessly slow algorithm, despite the fact that the asymptotic bounds improve as we increase the number of slices!

- We would have to evaluate polynomials $P_A(x)$ and $P_B(x)$ both of degree p at values up to p .

- However, $p = 2^{10}$, so evaluating $P_A(p) = A_p p^p + \dots + A_0$ involves multiplication of A_p with $p^p = (2^{10})^{2^{10}} \approx 1.27 \times 10^{307}$.

- Thus, while evaluations of $P_A(x)$ and $P_B(x)$ for $x = -p \dots p$ can **theoretically** all be done in linear time, $T(p) = cp$, the constant c is absolutely enormous.

- Consequently, slicing the input numbers in more than just a few slices results in a hopelessly slow algorithm, despite the fact that the asymptotic bounds improve as we increase the number of slices!

- The moral is: **In practice, asymptotic estimates are useless if the size of the constants hidden by the O -notation are not estimated and found to be reasonably small!!!**

- **Crucial question:** Are there numbers x_0, x_1, \dots, x_p such that the size of x_i^p does not grow uncontrollably?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- **Crucial question:** Are there numbers x_0, x_1, \dots, x_p such that the size of x_i^p does not grow uncontrollably?
- Answer: YES; they are the complex numbers z_i lying on the unit circle, i.e., such that $|z_i| = 1$!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- **Crucial question:** Are there numbers x_0, x_1, \dots, x_p such that the size of x_i^p does not grow uncontrollably?
- Answer: YES; they are the complex numbers z_i lying on the unit circle, i.e., such that $|z_i| = 1$!

Assignment Project Exam Help

- This motivates us to consider values of polynomials at inputs which are equally spaced complex numbers all lying on the unit circle.

<https://powcoder.com>

Add WeChat powcoder

- **Crucial question:** Are there numbers x_0, x_1, \dots, x_p such that the size of x_i^p does not grow uncontrollably?
- Answer: YES; they are the complex numbers z_i lying on the unit circle, i.e., such that $|z_i| = 1$!

Assignment Project Exam Help

- This motivates us to consider values of polynomials at inputs which are equally spaced complex numbers all lying on the unit circle.
- The sequence of such values is called **the discrete Fourier transform (DFT)** of the sequence of the coefficients of the polynomial being evaluated.

<https://powcoder.com>

Add WeChat powcoder

- **Crucial question:** Are there numbers x_0, x_1, \dots, x_p such that the size of x_i^p does not grow uncontrollably?
- Answer: YES; they are the complex numbers z_i lying on the unit circle, i.e., such that $|z_i| = 1$!

Assignment Project Exam Help

- This motivates us to consider values of polynomials at inputs which are equally spaced complex numbers all lying on the unit circle.
- The sequence of such values is called **the discrete Fourier transform (DFT)** of the sequence of the coefficients of the polynomial being evaluated.
- We will present a very fast algorithm for computing these values, called **the Fast Fourier Transform**, abbreviated as **FFT**.

Add WeChat powcoder

- **Crucial question:** Are there numbers x_0, x_1, \dots, x_p such that the size of x_i^p does not grow uncontrollably?
- Answer: YES; they are the complex numbers z_i lying on the unit circle, i.e., such that $|z_i| = 1$!

Assignment Project Exam Help

- This motivates us to consider values of polynomials at inputs which are equally spaced complex numbers all lying on the unit circle.
- The sequence of such values is called **the discrete Fourier transform (DFT)** of the sequence of the coefficients of the polynomial being evaluated.
- We will present a very fast algorithm for computing these values, called **the Fast Fourier Transform**, abbreviated as **FFT**.
- The Fast Fourier Transform is **the most executed algorithm today** and is thus arguably **the most important algorithm of all**.

<https://powcoder.com>

Add WeChat powcoder

- **Crucial question:** Are there numbers x_0, x_1, \dots, x_p such that the size of x_i^p does not grow uncontrollably?
- Answer: YES; they are the complex numbers z_i lying on the unit circle, i.e., such that $|z_i| = 1$!

Assignment Project Exam Help

- This motivates us to consider values of polynomials at inputs which are equally spaced complex numbers all lying on the unit circle.
- The sequence of such values is called **the discrete Fourier transform (DFT)** of the sequence of the coefficients of the polynomial being evaluated.
- We will present a very fast algorithm for computing these values, called **the Fast Fourier Transform**, abbreviated as **FFT**.
- The Fast Fourier Transform is **the most executed algorithm today** and is thus arguably **the most important algorithm of all**.
- Every mobile phone performs thousands of FFT runs each second, for example to compress your speech signal or to compress images taken by your camera, to mention just a few uses of the FFT.

<https://powcoder.com>

Add WeChat powcoder

PUZZLE!

The warden meets with 23 new prisoners when they arrive. He tells them, “You may meet today and plan a strategy. But after today, you will be in isolated cells and will have no communication with one another. In the prison there is a switch room, which contains two light switches labeled A and B, each of which can be in either the on or the off position. I am not telling you their present positions. The switches are not connected to anything. After today, from time to time whenever I feel so inclined, I will select one prisoner at random and escort him to the switch room. This prisoner will select one of the two switches and reverse its position. He must move one, but only one, of the switches. He can’t move both but he can’t move none either. Then he will be led back to his cell. No one else will enter the switch room until I lead the next prisoner there, and he’ll be instructed to do the same thing. I’m going to choose prisoners at random. I may choose the same guy three times in a row, or I may jump around and come back. But, given enough time, everyone would eventually visit the switch room many times. At any time anyone of you may declare to me: “We have all visited the switch room. If it is true, then you will all be set free. If it is false, and somebody has not yet visited the switch room, you will be fed to the alligators.”

What is the strategy the prisoners can devise to gain their freedom?