

$$f(n) = \begin{cases} 0 & \text{if } n = 0 \\ 2n - 1 + f(n-1) & \text{if } n > 0 \end{cases}$$

$$\underline{f(n) = n^2}$$

$(n \in \mathbb{N})$
for all n

Base Case $(n=0)$

WTP) $f(0) = 0^2$

$$f(0) = 0 \quad (1)$$


$$= 0^2 \quad \square$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Inductive Case $(n=k+1)$

I.H) $f(k) = k^2$ 

WTP) $f(k+1) = (k+1)^2$

$$\begin{aligned} f(k+1) &= 2(k+1) - 1 + f(k) \quad (2) \\ &= 2k + 2 - 1 + f(k) \\ &= 2k + 1 + \underline{f(k)} \\ &= 2k + 1 + k^2 \quad \text{(I.H)} \\ &= k^2 + 2k + 1 \\ &= (k+1)^2 \quad \square \end{aligned}$$


```

sum :: [Int] -> Int
sum [] = 0 -- 1
sum (x:xs) = x + sum xs -- 2

foldr :: (a -> b -> b) -> b -> [a] -> b
foldr f z [] = z -- A
foldr f z (x:xs) = x `f` foldr f z xs -- B

```

Sum ls = foldr (+) 0 ls

GOAL ↑

Base Case (ls = [])

WTP) $\text{sum } [] = 0$

$= 0$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$= \text{foldr } (+) 0 [] \quad \square$

①

A²

Inductive Case (ls = x:xs)

I.H) $\text{sum } xs = \text{foldr } (+) 0 xs \leftarrow$

WTP) $\text{sum } (x:xs) = \text{foldr } (+) 0 (x:xs)$

$\text{sum } (x:xs) = x + \text{sum } xs$

$\approx x + \text{foldr } (+) 0 xs$

$= \text{foldr } (+) 0 (x:xs) \quad \square$

②

I.H

B²