

Assignment Project Exam Help

COMP6443 - Topic 3

<https://powcoder.com>
Add WeChat powcoder

A NOTE ON ETHICS / LEGALITY

- UNSW hosting this course is an extremely important step forward.
- We expect a high standard of professionalism from you, meaning:
 - Respect the property of others and the university
 - Always abide by the law and university regulations
 - Be considerate of others to ensure everyone has an equal learning experience
- Always check that you have written permission before performing a security test on a system

PLEASE BE SUPER CAREFUL WHENEVER YOU'RE GENERATING NETWORK TRAFFIC

Recap

Authentication,
Sessions
Access Control

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Today's lecture

Assignment Project Exam Help

<https://powcoder.com>
Don't trust anyone's Name
Add WeChat powcoder

Today's lecture

User input = **Assignment Project Exam Help** → How user input is action actioned
<https://powcoder.com>

Abhijeth

Australia, Sydney

Add WeChat powcoder

```
mysql_connect_error());  
}  
  
$id = $_GET['id'];  
$id = mysql_real_escape_string($conn,$id);  
$sql = "SELECT * FROM products where ID=".$id;  
$result = mysql_query($conn, $sql);  
  
if (mysql_num_rows($result) > 0) {  
    // output data of each row  
    while($row = mysql_fetch_assoc($result)) {  
        echo "ID: ".$row["ID"]. " - Name: ".$  
$row["name"]. " - Price: ".$row["price"]. "<br>";  
    }  
}
```



PROBING FOR VULNS

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SQLI 101

```
select * from users where username='admin' and  
password='hunter2' limit 1;
```

<https://powcoder.com>

```
select * from users where username='admin' and  
password='x' or '1'='1' limit 1;
```

The database engine is not designed to tell the difference between **code** and **data**. As discussed - it is generally a bad idea when **control** and **data** share the same **band**.

SQLI IN PRACTICE

Assignment Project Exam Help

~ all hail the demo gods ~
<https://powcoder.com>

Add WeChat powcoder

SQLI “TELLS”: or 1=1

```
SELECT * FROM PRODUCTS WHERE PRODUCTNAME='x' OR '1'='1';
```

Not all products meet the first condition, but **ALL** meet the second (1 is always equal to 1) so **ALL** records are returned!

```
PRODUCTS (11337 found):
```

```
Product 1
```

```
Product 2
```

```
Product 3...
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SQLI “TELLS”: and 1=1

```
SELECT * FROM PRODUCTS WHERE PRODUCTNAME='shirt' AND  
'1'='1';
```

Assignment Project Exam Help

The SAME legit record(s) should be returned as the un.injected equivalent, as the product condition is still met.

PRODUCTS (3 found):

shirt (red)

shirt (blue)

shirt (green)

Add WeChat powcoder

```
SELECT * FROM PRODUCTS WHERE PRODUCTNAME='shirt' AND  
'1'='0';
```

Now, if **NO** records are now returned, we can be sure our injection is being processed.

SQLI “TELLS”: COMMENTS

```
SELECT * FROM USERS WHERE name='x' -- ' LIMIT 1;
```

Assignment Project Exam Help

Imagine if there is an unfavourable appendix on the end of a query, you can comment it out using the relevant DBMS `inline comment` syntax.

<https://powcoder.com>

Add WeChat powcoder

The above query will then instead be processed like this:

```
SELECT * FROM USERS WHERE name='x';
```

Now, instead of returning one record - will return ALL records that meet the condition in the query.

EXPLORING SQLI

Assignment Project Exam Help

~ all hail the demo gods ~
<https://powcoder.com>
test time: ~15 mins

Add WeChat powcoder

SQLI: FURTHER OS INTERACTION

- SELECT INTO OUTFILE / LOAD DATA INFILE
 - LOAD DATA INFILE 'data.txt' INTO TABLE db2.my_table;
 - SELECT a,b,a+b INTO OUTFILE '/tmp/result.txt' FIELDS TERMINATED BY ',' OPTIONALLY ENCLOSED BY '"' LINES TERMINATED BY '\n' FROM test_table;
 - SELECT _utf8'Hello world!' INTO DUMPFILE '/tmp/world';
 - SELECT LOAD_FILE('/tmp/world') AS world;
- exec master.dbo.xp_cmdshell 'dtsrun -E -Sserver1 -N"Export Invoices"'
- that's right - under certain circumstances you can directly pop a shell on a vulnerable server running MSSQL as the DBMS.

BLIND SQLI

- **Blind** SQLi is when you can't directly exfiltrate data by selecting it into a column
 - You can make the database do something depending on if a condition is true
 - "Is the first letter of the password 'a'? If yes, sleep for 5 seconds, otherwise, do nothing"
 - From this exploit primitive, build a binary search tree.
 - Dump data from the DB via error codes / time delays alone

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
SELECT PRODUCT_COLOR FROM PRODUCTS WHERE PRODUCTID=$PRODUCT
```

BLIND SQLI

- Boolean-Based Blind:

`https://www.example.com/items.php?id=1' and (select 1
from users where (select password from users where
username like '%admin%' limit 0,1) like '<GUESS>%') --`

<https://powcoder.com>

- Time-Based Blind:

`https://www.example.com/items.php?id=1' UNION SELECT
IF(SUBSTRING(user_password,1,1) =
CHAR(50),BENCHMARK(5000000,ENCODE('MSG','by 5
seconds'))),null) FROM users WHERE user_id = 1;`

SQLI IN REST APIS?

```
http://application/apiv3/Users/?req_id=1' AND '1' LIKE '1
```

Assignment Project Exam Help

```
[{"user": "admin", "id": "1", "firstName": "Admin"}]
```

<https://powcoder.com>

```
http://application/apiv3/Users/?req_id=1' AND '1' LIKE '2
```

Add WeChat powcoder

```
[]
```

generally apis (ESPECIALLY APIs for mobile apps) have little if not no protection against SQLi. these are great targets for testing for SQLi.

WHAT ABOUT NOSQL?

Assignment Project Exam Help



Add WeChat powcoder

```
db.users.find({username: username, password:
password})
{"username": {"$gt": ""}, "password": {"$gt":
""} }
```

[DEFENSIVE] PREVENTING SQLI

- SQL Injection comes from the confusion of **code** and **data**
- Parameterised queries force the SQL engine to cleanly segregate **code** and **data**

DON'T: Construct SQL Queries through string

concatenation:

```
c.execute("SELECT * FROM USERS WHERE USERNAME = '" +  
username + "' AND PASSWORD = '" + password + "'");
```

Instead, used parameterised queries

```
c.execute("SELECT * FROM USERS WHERE USERNAME = ? AND  
PASSWORD = ?", (username, password));
```

[DEFENSIVE] PREVENTING SQLI

- Other methods to prevent SQLi:
 - SQL Escaping: Replace control characters in user input with safe substitutes
 - Stored Procedures
 - If nothing else can be used, only allow a whitelist of characters in the user input
- Most SQL Libraries for programming languages will have a way to securely execute SQL queries

[DEFENSIVE] REDUCING ATTACK SURFACE

- Application Layer
 - Handle your error messages gracefully
 - Filter user input
 - Use parameterised queries where possible
- Database Layer
 - Minimise the privilege level of your database user
 - Prevent arbitrary connections to your database server

tl;dr: trust nothing

THE **MAGIC** OF SQLMAP

Assignment Project Exam Help

~~~all hail the dem gods~~~  
<https://powcoder.com>

est. duration: 10 mins

Add WeChat powcoder

*Running this tool is generally not legal, unless you have explicit authorisation to test a target. Be ethical, don't be unethical.*

# Local File Inclusion DEMO

Assignment Project Exam Help

~ all hail the demo gods ~  
<https://powcoder.com>

Add WeChat powcoder

# [DEFENSIVE] PREVENTING PATH TRAVERSAL

- Don't trust a path provided by the user, it can lead to LFI
- Resolve the final path of the file and ensure it is in a safe directory

DON'T

```
open(userpath, "r")
```

DO

```
UPLOAD_DIR = "/app/uploads/"
if os.path.dirname(os.realpath(os.path.join(UPLOAD_DIR,
userpath))) != UPLOAD_DIR:
    # DIRECTORY TRAVERSAL DETECTED!
    exit()
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# COMMAND INJECTION DEMO

Assignment Project Exam Help

~ all hail the demo gods ~  
<https://powcoder.com>

Add WeChat powcoder



# [DEFENSIVE] PREVENTING CMD INJECTION

- Command Injection comes from the confusion of **code** and **data**

DON'T

Assignment Project Exam Help

```
os.system("ping "+host)
```

DO



Add WeChat powcoder

```
subprocess.call(["ping", host])
```

# Moral of the story

Assignment Project Exam Help  
User input → How user input is securely  
interpreted → How user input is secured  
<https://powcoder.com>

Add WeChat powcoder



```
$id = $_GET['id'];  
  
$stmt = $conn->prepare( "SELECT * FROM product  
ID=?" );  
  
$stmt->bind_param("i",$id);  
  
$stmt->execute();  
  
$stmt->store_result();  
  
$num_of_rows = $stmt->num_rows;  
  
$stmt->bind_result($id,$name,$price);
```



# WEEK 4 ASSESSMENT

| COMP6443 - Core Challenges                                                                                                                                                                                                            | COMP6843 - Extension Challenges                                                                                                                                                           | Total Flags                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>This is the flags you will need to get for a credit</p> <ul style="list-style-type: none"><li>• The pay-portal flag</li><li>• 1 of the support flags</li><li>• 3 of the bigapp flags</li><li>• 1 of the feedifier flags.</li></ul> | <p>The core requirements plus at least:</p> <ul style="list-style-type: none"><li>• 4 of the bigapp flags.</li><li>• 1 of the feedifier flags.</li><li>• 1 of the letters flag.</li></ul> | <p>This is the total flags you will need to find if you wish to receive full marks in this challenge</p> <ul style="list-style-type: none"><li>• 1 pay-portal flag</li><li>• 2 support flags</li><li>• 7 of the bigapp flags</li><li>• 1 feedifier flag</li><li>• 2 letter flags</li><li>• 1 bfd flag</li><li>• 1 gcc flag</li><li>• 1 signin flag</li></ul> |

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Please call out if you get stuck.

Support one another, your tutors are here to help!

# READING MATERIAL (REFERENCE)

- OWASP Input validation cheat sheet
  - [https://cheatsheetseries.owasp.org/cheatsheets/Input\\_Validation\\_Cheat\\_Sheet.html](https://cheatsheetseries.owasp.org/cheatsheets/Input_Validation_Cheat_Sheet.html)
- Pentester Lab <https://powcoder.com>
  - [https://pentesterlab.com/exercises/from\\_sql\\_i\\_to\\_shell](https://pentesterlab.com/exercises/from_sql_i_to_shell)
- SQLMap
  - <https://github.com/sqlmapproject/sqlmap>
- Anatomy of an attack: SQLi to Shell
  - <http://resources.infosecinstitute.com/anatomy-of-an-attack-gaining-reverse-shell-from-sql-injection/>

# Assignment Project Exam Help

THANKS FOR LISTENING TO US

<https://powcoder.com>

RANT:

questions? slack / email

Add WeChat powcoder