

# Spelling Correction and the Noisy Channel

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

The Spelling  
Correction Task

# Applications for spelling correction


Word processing



Phones



Web search



Showing results for natural language processing  
Search instead for natural language processing

# Spelling Tasks

- Spelling Error Detection
- Spelling Error Correction:
  - Autocorrect <https://powcoder.com>
  - hte→the [Add WeChat powcoder](#)
  - Suggest a correction
  - Suggestion lists

# Types of spelling errors

- Non-word Errors
  - *graffe* → *giraffe*
- Real-word Errors
  - Typographical errors
    - *three* → *there*
  - Cognitive Errors (homophones)
    - *piece* → *peace*,
    - *too* → *two*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Rates of spelling errors

- 26%:** Web queries Wang et al. 2003
- 13%:** Retyping, no backspace: Whitelaw et al. English&German
- 7%:** Words corrected retyping on phone-sized organizer
- 2%:** Words uncorrected on organizer Soukoreff & MacKenzie 2003
- 1-2%:** Retyping: Kane and Wobbrock 2007, Gruden et al. 1983

# Non-word spelling errors

- Non-word spelling error detection:
  - Any word not in a **dictionary** is an error
  - The larger the dictionary the better
- Non-word spelling error correction:
  - Generate **candidates**: real words that are similar to error
  - Choose the one which is best:
    - Shortest weighted edit distance
    - Highest noisy channel probability

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Real word spelling errors

- For each word  $w$ , generate candidate set:
  - Find candidate words with similar *pronunciations*
  - Find candidate words with similar *spelling*
  - Include  $w$  in candidate set
- Choose best candidate
  - Noisy Channel
  - Classifier

# Spelling Correction and the Noisy Channel

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The Spelling  
Correction Task




# Spelling Correction and the Noisy Channel

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat [powcoder](https://powcoder.com)  
The Noisy Channel  
Model of Spelling

# Noisy Channel Intuition



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Noisy Channel

- We see an observation  $x$  of a misspelled word
- Find the correct word  $w$

$$\begin{aligned}\hat{w} &= \operatorname{argmax}_{w \in V} P(w | x) \\ &= \operatorname{argmax}_{w \in V} \frac{P(x | w)P(w)}{P(x)} \\ &= \operatorname{argmax}_{w \in V} P(x | w)P(w)\end{aligned}$$

# History: Noisy channel for spelling proposed around 1990

- **IBM**

- Mays, Eric, Fred J. Damerau and Robert L. Mercer. 1991. Context based spelling correction. *Information Processing and Management*, 23(5), 517–522

<https://powcoder.com>  
Add WeChat powcoder

- **AT&T Bell Labs**

- Kernighan, Mark D., Kenneth W. Church, and William A. Gale. 1990. A spelling correction program based on a noisy channel model. *Proceedings of COLING 1990*, 205-210

# Non-word spelling error example

Assignment Project Exam Help  
**acress**

<https://powcoder.com>

Add WeChat powcoder

# Candidate generation

- Words with similar spelling
  - Small edit distance to error
- Words with similar pronunciation
  - Small edit distance of pronunciation to error

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Damerau-Levenshtein edit distance

- Minimal edit distance between two strings, where edits are:
  - Insertion
  - Deletion
  - Substitution
  - Transposition of two adjacent letters

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Words within 1 of across

Error	Candidate	Correct	Error	Type
acress	actress	t	-	deletion
acress	cress	-	a	insertion
acress	caress	ca	ac	transposition
acress	access	c	r	substitution
acress	across	o	e	substitution
acress	acres	-	s	insertion
acress	acres	-	s	insertion



# Candidate generation

- 80% of errors are within edit distance 1
- Almost all errors within edit distance 2
- Also allow insertion of space or hyphen
  - `thisidea` → `this idea`
  - `inlaw` → `in-law`

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Language Model

- Use any of the language modeling algorithms we've learned
- Unigram, bigram, trigram
- Web-scale spelling correction
  - Stupid backoff

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Unigram Prior probability

Counts from 404,253,213 words in Corpus of Contemporary English (COCA)

Assignment Project Exam Help

word	Frequency of word	P(word)
actress	9,321	.0000230573
cress	220	.0000005442
caress	686	.0000016969
access	37,038	.0000916207
across	120,844	.0002989314
acres	12,874	.0000318463

<https://powcoder.com>

Add WeChat powcoder

# Channel model probability

- Error model probability, Edit probability
- *Kernighan, Church, Gale 1990*
- <https://powcoder.com>
- Misspelled word  $x = x_1, x_2, x_3, \dots, x_m$
- Correct word  $w = w_1, w_2, w_3, \dots, w_n$
- $P(x|w)$  = probability of the edit
  - (deletion/insertion/substitution/transposition)

# Computing error probability: confusion matrix

```
del[x,y]:      count(xy typed as x)
ins[x,y]:      count(x typed as xy)
sub[x,y]:      count(x typed as y)
trans[x,y]:    count(xy typed as yx)
```

Assignment Project Exam Help  
<https://powcoder.com>  
Add WeChat powcoder

Insertion and deletion conditioned on previous character

# Confusion matrix for spelling errors

sub[X, Y] = Substitution of X (incorrect) for Y (correct)

X	Y (correct)																									
	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
a	0	0	7	1	342	0	0	2	118	0	1	0	0	3	76	0	0	1	35	9	9	0	1	0	5	0
b	0	0	9	9	2	2	3	1	0	0	0	5	11	5	0	10	0	0	2	1	0	0	8	0	0	0
c	6	5	0	16	0	9	5	0	0	0	1	0	7	9	1	19	2	5	19	40	1	3	7	1	1	0
d	1	10	13	0	11	0	5	5	0	0	2	3	7	3	0	0	48	30	22	0	0	4	0	2	0	0
e	388	0	3	11	0	2	2	0	89	0	0	3	0	5	93	0	0	14	12	6	15	0	1	0	18	0
f	0	15	0	3	1	0	5	2	0	0	0	3	4	1	0	0	0	6	4	12	0	0	2	0	0	0
g	4	1	11	11	9	2	0	0	0	1	1	3	0	0	2	1	3	5	13	21	0	0	1	0	3	0
h	1	8	0	3	0	0	0	0	0	0	0	1	0	12	18	2	3	0	1	11	0	0	2	0	0	0
i	103	0	0	0	146	0	0	0	0	0	0	6	6	0	49	0	0	0	2	1	47	0	2	1	15	0
j	0	1	1	9	0	0	1	0	0	0	0	2	1	0	0	0	0	5	0	0	0	0	0	0	0	0
k	1	2	8	4	1	1	2	5	0	0	0	0	5	0	2	0	0	6	0	0	0	4	0	0	0	3
l	2	10	1	4	0	4	5	6	13	0	1	0	0	14	2	5	0	11	10	2	0	0	0	0	0	0
m	1	3	7	8	0	2	0	6	0	4	14	0	18	0	0	0	0	0	15	13	3	2	2	3	0	0
n	2	7	6	5	3	0	1	19	1	0	4	35	78	0	0	7	0	28	5	7	0	0	1	2	0	2
o	91	1	1	3	116	0	0	0	25	0	2	0	0	0	0	14	0	2	4	14	39	0	0	0	18	0
p	0	11	1	2	0	6	5	0	2	9	0	2	7	6	15	0	0	1	3	6	0	4	1	0	0	0
q	0	0	1	0	0	0	27	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
r	0	14	0	30	12	2	2	8	2	0	5	8	4	20	1	14	0	0	12	22	4	0	0	1	0	0
s	11	8	27	33	35	4	0	1	0	1	0	27	0	6	1	7	0	14	0	15	0	0	5	3	20	1
t	3	4	9	42	7	5	19	5	0	1	0	14	9	5	5	6	0	11	37	0	0	2	19	0	7	6
u	20	0	0	0	44	0	0	0	64	0	0	0	0	2	43	0	0	4	0	0	0	0	2	0	8	0
v	0	0	7	0	0	3	0	0	0	0	0	1	0	0	1	0	0	8	3	0	0	0	0	0	0	0
w	2	2	1	0	1	0	0	2	0	0	1	0	0	0	0	7	0	6	3	3	1	0	0	0	0	0
x	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	9	0	0	0	0	0	0	0	0
y	0	0	2	0	15	0	1	7	15	0	0	0	2	0	6	1	0	7	36	8	5	0	0	1	0	0
z	0	0	0	7	0	0	0	0	0	0	0	7	5	0	0	0	0	2	21	3	0	0	0	3	0	0

# Generating the confusion matrix

- Peter Norvig's list of errors
- Peter Norvig's list of counts of single-edit errors

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Channel model

Kernighan, Church, Gale 1990

$$P(x|w) = \begin{cases} \frac{\text{del}[w_{i-1}, w_i]}{\text{count}[w_{i-1} w_i]}, & \text{if deletion} \\ \frac{\text{ins}[w_{i-1}, x_i]}{\text{count}[w_{i-1}]}, & \text{if insertion} \\ \frac{\text{sub}[x_i, w_i]}{\text{count}[w_i]}, & \text{if substitution} \\ \frac{\text{trans}[w_i, w_{i+1}]}{\text{count}[w_i w_{i+1}]}, & \text{if transposition} \end{cases}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Channel model for across

Candidate Correction	Correct Letter	Error Letter	x w	P(x word)
actress	t	-	c ct	.000117
cress	-	a	a #	.00000144
caress	ca	ac	ac ca	.00000164
access	c	r	r c	.00000009
across	o	e	e o	.00000093
acres	-	s	es e	.0000321
acres	-	s	ss s	.0000342

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Noisy channel probability for across

Candidate Correction	Correct Letter	Error Letter	$x w$	$P(x word)$	$P(word)$	$10^9 * P(x w)P(w)$
actress	t	-	c ct	.000117	.0000231	2.7
cress	-	a	a #	.00000144	.000000544	.00078
caress	ca	ac	ac ca	.00000164	.00000170	.0028
access	c	r	r c	.00000209	.00000916	.019
across	o	e	e o	.0000093	.000299	2.8
acres	-	s	es e	.0000321	.0000318	1.0
acres	-	s	ss s	.0000342	.0000318	1.0

# Noisy channel probability for across

Candidate Correction	Correct Letter	Error Letter	$x w$	$P(x word)$	$P(word)$	$10^9 * P(x w)P(w)$
actress	t	-	c ct	.000117	.0000231	2.7
cress	-	a	a #	.00000144	.000000544	.00078
caress	ca	ac	ac ca	.00000164	.00000170	.0028
access	c	r	r c	.00000209	.00000916	.019
<b>across</b>	<b>o</b>	<b>e</b>	<b>e o</b>	<b>.0000093</b>	<b>.000299</b>	<b>2.8</b>
acres	-	s	es e	.0000321	.0000318	1.0
acres	-	s	ss s	.0000342	.0000318	1.0

# Using a bigram language model

- "a stellar and versatile **actress** whose combination of sass and glamour..."
- Counts from the Corpus of Contemporary American English with add-1 smoothing
- $P(\text{actress} | \text{versatile}) = .000021$   $P(\text{whose} | \text{actress}) = .0010$
- $P(\text{across} | \text{versatile}) = .000021$   $P(\text{whose} | \text{across}) = .000006$
- $P(\text{"versatile actress whose"}) = .000021 * .0010 = 210 \times 10^{-10}$
- $P(\text{"versatile across whose"}) = .000021 * .000006 = 1 \times 10^{-10}$

# Using a bigram language model

- "a stellar and versatile **acress** whose combination of sass and glamour..."
- Counts from the Corpus of Contemporary American English with add-1 smoothing
- $P(\text{actress} | \text{versatile}) = .000021$   $P(\text{whose} | \text{actress}) = .0010$
- $P(\text{across} | \text{versatile}) = .000021$   $P(\text{whose} | \text{across}) = .000006$
- $P(\text{"versatile actress whose"}) = .000021 * .0010 = 210 \times 10^{-10}$
- $P(\text{"versatile across whose"}) = .000021 * .000006 = 1 \times 10^{-10}$

# Evaluation

- Some spelling error test sets
  - [Wikipedia's list of common English misspelling](#)
  - [Aspell filtered version of that list](#)
  - [Birkbeck spelling error corpus](#)
  - [Peter Norvig's list of errors \(includes Wikipedia and Birkbeck, for training or testing\)](#)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Spelling Correction and the Noisy Channel

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat [powcoder](https://powcoder.com)  
The Noisy Channel  
Model of Spelling

# Spelling Correction and the Noisy Channel

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Real-Word Spelling  
Correction



# Real-word spelling errors

- ...leaving in about fifteen **minuets** to go to her house.
- The design **an** construction of the system...
- Can they **lave** him my messages?
- The study was conducted mainly **be** John Black.

Add WeChat powcoder

- 25-40% of spelling errors are real words [Kukich 1992](#)

# Solving real-world spelling errors

- For each word in sentence
  - Generate *candidate set*
    - the word itself
    - all single-letter edits that are English words
    - words that are homophones
- Choose best candidates
  - Noisy channel model
  - Task-specific classifier

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder


# Noisy channel for real-word spell correction

- Given a sentence  $w_1, w_2, w_3, \dots, w_n$
- Generate a set of candidates for each word  $w_i$ 
  - $\text{Candidate}(w_1) = \{w_1, w'_1, w''_1, w'''_1, \dots\}$
  - $\text{Candidate}(w_2) = \{w_2, w'_2, w''_2, w'''_2, \dots\}$
  - $\text{Candidate}(w_n) = \{w_n, w'_n, w''_n, w'''_n, \dots\}$
- Choose the sequence  $W$  that maximizes  $P(W)$

# Noisy channel for real-word spell correction



# Noisy channel for real-word spell correction



# Simplification: One error per sentence

- Out of all possible sentences with one word replaced
  - $w_1, w''_2, w_3, w_4$  two off the
  - $w_1, w_2, w'_3, w_4$  two of the
  - $w'''_1, w_2, w_3, w_4$  too of the
  - ...
- Choose the sequence  $W$  that maximizes  $P(W)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Where to get the probabilities

- Language model
    - Unigram
    - Bigram
    - Etc
  - Channel model
- Assignment Project Exam Help
- <https://powcoder.com>
- Add WeChat powcoder
- Same as for non-word spelling correction
  - Plus need probability for no error,  $P(w|w)$

# Probability of no error

- What is the channel probability for a correctly typed word?
- $P(\text{"the"} | \text{"the"})$

<https://powcoder.com>

- Obviously this depends on the application.
  - .90 (1 error in 10 words)
  - .95 (1 error in 20 words)
  - .99 (1 error in 100 words)
  - .995 (1 error in 200 words)



# Peter Norvig's "thew" example

x	w	x w	P(x w)	P(w)	$10^9 P(x w)P(w)$
thew	the	ew e	0.0000007	0.02	144
thew	thew		0.95	0.000000009	90
thew	thaw	e a	0.001	0.0000001	0.7
thew	threw	h hr	0.0000008	0.0000004	0.03
thew	thwe	ew we	0.0000003	0.000000004	0.0001