



THE UNIVERSITY OF
MELBOURNE

COMP90038

Algorithms and Complexity

Assignment Project Exam Help

Lecture 5: Brute Force Methods
(with thanks to Harald Søndergaard)

<https://powcoder.com>

Add WeChat powcoder

Toby Murray



toby.murray@unimelb.edu.au



DMD 8.17 (Level 8, Doug McDonnell Bldg)



<http://people.eng.unimelb.edu.au/tobym>



@tobycmurray

Compulsory Quizzes

- **Remember:** you need to **complete** 8 of the quizzes to pass the hurdle
- By “completing” a quiz, we mean **getting all answers right (100%) in one sitting**
Assignment Project Exam Help
<https://powcoder.com>
- You can have as many attempts as you need, but on at least one of those attempts you need to score 100%
Add WeChat powcoder
- The first compulsory quiz (for week 2) closes **tomorrow**

Brute Force Algorithms

- Straightforward problem solving approach, usually based directly on the problem's statement.
- Exhaustive search for solutions is a prime example.
 - Selection sort <https://powcoder.com>
 - String matching [Add WeChat powcoder](#)
 - Closest pair
 - Exhaustive search for combinatorial solutions
 - Graph traversal

Example: Selection Sort



THE UNIVERSITY OF
MELBOURNE

```
function SELSORT( $A[\cdot]$ ,  $n$ )  
  for  $i \leftarrow 0$  to  $n - 2$  do  
     $min \leftarrow i$   
    for  $j \leftarrow i + 1$  to  $n - 1$  do  
      if  $A[j] < A[min]$  then  
         $min \leftarrow j$   
     $t \leftarrow A[i]$  // swap  $A[i]$  and  $A[min]$   
     $A[i] \leftarrow A[min]$   
     $A[min] \leftarrow t$ 
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

// swap $A[i]$ and $A[min]$

Example: Selection Sort



THE UNIVERSITY OF
MELBOURNE

```
function SELSORT( $A[\cdot]$ ,  $n$ )  
  for  $i \leftarrow 0$  to  $n - 2$  do  
     $min \leftarrow i$   
    for  $j \leftarrow i + 1$  to  $n - 1$  do  
      if  $A[j] < A[min]$  then  
         $min \leftarrow j$   
     $t \leftarrow A[i]$  // swap  $A[i]$  and  $A[min]$   
     $A[i] \leftarrow A[min]$   
     $A[min] \leftarrow t$ 
```

Time Complexity:

Example: Selection Sort



```
function SELSORT( $A[\cdot]$ ,  $n$ )  
  for  $i \leftarrow 0$  to  $n - 2$  do  
     $min \leftarrow i$   
    for  $j \leftarrow i + 1$  to  $n - 1$  do  
      if  $A[j] < A[min]$  then  
         $min \leftarrow j$   
     $t \leftarrow A[i]$  // swap  $A[i]$  and  $A[min]$   
     $A[i] \leftarrow A[min]$   
     $A[min] \leftarrow t$ 
```

Time Complexity: $\Theta(n^2)$

Example: Selection Sort

```
function SELSORT( $A[\cdot]$ ,  $n$ )  
  for  $i \leftarrow 0$  to  $n - 2$  do  
     $min \leftarrow i$   
    for  $j \leftarrow i + 1$  to  $n - 1$  do  
      if  $A[j] < A[min]$  then  
         $min \leftarrow j$   
     $t \leftarrow A[i]$  // swap  $A[i]$  and  $A[min]$   
     $A[i] \leftarrow A[min]$   
     $A[min] \leftarrow t$ 
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Time Complexity: $\Theta(n^2)$

We will soon meet better sorting algorithms

Properties of Sorting Algorithms

- A Sorting algorithm is:
 - **in-place** if it does not require additional memory except, perhaps, for a few units of memory
 - **stable** if it preserves the relative order of elements with identical keys
 - **input-insensitive** if its running time is fairly independent of input properties other than size

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Properties of Selection Sort



THE UNIVERSITY OF
MELBOURNE

- While running time is quadratic, selection sort makes only about **n exchanges**.
- So: **selection sort is a good algorithm for sorting small collections of large records.**
[Assignment Project Exam Help
https://powcoder.com](https://powcoder.com)
- In-place?
[Add WeChat powcoder](#)
- Stable?
- Input-insensitive?

Properties of Selection Sort



THE UNIVERSITY OF
MELBOURNE

- While running time is quadratic, selection sort makes only about **n exchanges**.
- So: **selection sort is a good algorithm for sorting small collections of large records.**
Assignment Project Exam Help
<https://powcoder.com>
- In-place? *yes*
Add WeChat powcoder
- Stable?
- Input-insensitive?

Properties of Selection Sort



THE UNIVERSITY OF
MELBOURNE

- While running time is quadratic, selection sort makes only about **n exchanges**.
- So: **selection sort is a good algorithm for sorting small collections of large records.**
Assignment Project Exam Help
<https://powcoder.com>
- In-place? *yes*
Add WeChat powcoder
- Stable? *?*
- Input-insensitive?

Properties of Selection Sort



THE UNIVERSITY OF
MELBOURNE

- While running time is quadratic, selection sort makes only about **n exchanges**.
- So: **selection sort is a good algorithm for sorting small collections of large records.**
Assignment Project Exam Help
<https://powcoder.com>
- In-place? *yes*
Add WeChat powcoder
- Stable? *?*
- Input-insensitive? *yes*

Selection Sort Stability

key: 4 val: ab	key: 3 val: bc	key: 4 val: de	key: 3 val: fg
-------------------	-------------------	-------------------	-------------------

0 1 2 3
↑
A[i]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Selection Sort Stability

key: 4 val: ab	key: 3 val: bc	key: 4 val: de	key: 3 val: fg
-------------------	-------------------	-------------------	-------------------

0 1 2 3
↑
A[i]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Selection Sort Stability

key: 3 val: bc	key: 4 val: ab	key: 4 val: de	key: 3 val: fg
-------------------	-------------------	-------------------	-------------------

0 1 2 3
↑
A[i]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Selection Sort Stability

key: 3 val: bc	key: 4 val: ab	key: 4 val: de	key: 3 val: fg
-------------------	-------------------	-------------------	-------------------

0

1

2

3

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

↑
A[i]

Selection Sort Stability

key: 3 val: bc	key: 4 val: ab	key: 4 val: de	key: 3 val: fg
-------------------	-------------------	-------------------	-------------------

0

1

2

3

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

↑
A[i]

Selection Sort Stability

key: 3 val: bc	key: 3 val: fg	key: 4 val: de	key: 4 val: ab
-------------------	-------------------	-------------------	-------------------

0

1

2

3

↑
A[i]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Selection Sort Stability

key: 3 val: bc	key: 3 val: fg	key: 4 val: de	key: 4 val: ab
-------------------	-------------------	-------------------	-------------------

0

1

2

3

↑
A[i]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

the relative order
of the two "4" records
has changed!

Properties of Selection Sort



THE UNIVERSITY OF
MELBOURNE

- While running time is quadratic, selection sort makes only about **n exchanges**.
- So: **selection sort is a good algorithm for sorting small collections of large records.**
Assignment Project Exam Help
<https://powcoder.com>
- In-place? *yes*
Add WeChat powcoder
- Stable? *no*
- Input-insensitive? *yes*

Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

- **Pattern** p : a string of m characters to search **for**
- **Text** t : a long string of n characters to search **in**
- We use i to run through the text and j to run through the pattern

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
for  $i \leftarrow 0$  to  $n - m$  do  
   $j \leftarrow 0$   
  while  $j < m$  and  $p[j] = t[i + j]$  do  
     $j \leftarrow j + 1$   
  if  $j = m$  then  
    return  $i$   
return  $-1$ 
```

Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

for $i \leftarrow 0$ to $n - m$ **do**

$j \leftarrow 0$

while $j < m$ and $p[j] = t[i + j]$ **do**

$j \leftarrow j + 1$

if $j = m$ **then**

return i

return -1

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

t:

N	O	B	O	D	Y		K	N	O	W	S
0	1	2	3	4	5	6	7	8	9	10	11

m

p:

N	O	T
0	1	2

n

Brute Force String Matching




THE UNIVERSITY OF
MELBOURNE

```
for  $i \leftarrow 0$  to  $n - m$  do  
     $j \leftarrow 0$   
    while  $j < m$  and  $p[j] = t[i + j]$  do  
         $j \leftarrow j + 1$   
    if  $j = m$  then  
        return  $i$   
return  $-1$ 
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

for $i \leftarrow 0$ to $n - m$ **do**

$j \leftarrow 0$

while $j < m$ and $p[j] = t[i + j]$ **do**

$j \leftarrow j + 1$

if $j = m$ **then**

return i

return -1

$t[i+j]$



$t[i]$



t:

N	O	B	O	D	Y		K	N	O	W	S
---	---	---	---	---	---	--	---	---	---	---	---

0

1

2

3

4

5

6

7

8

9

10

11

m

p:

N	O	T
---	---	---

0

1

2

n



$p[j]$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

for $i \leftarrow 0$ to $n - m$ **do**

$j \leftarrow 0$

while $j < m$ and $p[j] = t[i + j]$ **do**

$j \leftarrow j + 1$

if $j = m$ **then**


return i

return -1

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

for $i \leftarrow 0$ to $n - m$ **do**

$j \leftarrow 0$

while $j < m$ and $p[j] = t[i + j]$ **do**

$j \leftarrow j + 1$

if $j = m$ **then**

return i

return -1

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

t:

N	O	B	O	D	Y		K	N	O	W	S
0	1	2	3	4	5	6	7	8	9	10	11

n

p:

N	O	T
0	1	2

m

$p[j]$

Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

for $i \leftarrow 0$ to $n - m$ **do**

$j \leftarrow 0$

while $j < m$ and $p[j] = t[i + j]$ **do**

$j \leftarrow j + 1$

if $j = m$ **then**

return i

return -1

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$t[i]$
↓

t:

N	O	B	O	D	Y		K	N	O	W	S
0	1	2	3	4	5	6	7	8	9	10	11

n

p:

N	O	T
0	1	2

m

Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

for $i \leftarrow 0$ to $n - m$ **do**

$j \leftarrow 0$

while $j < m$ and $p[j] = t[i + j]$ **do**

$j \leftarrow j + 1$

if $j = m$ **then**


return i

return -1

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

```
for  $i \leftarrow 0$  to  $n - m$  do  
     $j \leftarrow 0$   
    while  $j < m$  and  $p[j] = t[i + j]$  do  
         $j \leftarrow j + 1$   
    if  $j = m$  then  
        return  $i$   
return  $-1$ 
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

t:

N	O	B	O	D	Y		K	N	O	W	S
0	1	2	3	4	5	6	7	8	9	10	11

n

p:

N	O	T
0	1	2

m

Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

for $i \leftarrow 0$ to $n - m$ **do**

$j \leftarrow 0$

while $j < m$ and $p[j] = t[i + j]$ **do**

$j \leftarrow j + 1$

if $j = m$ **then**


return i

return -1

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

```
for  $i \leftarrow 0$  to  $n - m$  do  
     $j \leftarrow 0$   
    while  $j < m$  and  $p[j] = t[i + j]$  do  
         $j \leftarrow j + 1$   
    if  $j = m$  then  
        return  $i$   
return  $-1$ 
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

t:

N	O	B	O	D	Y		K	N	O	W	S
0	1	2	3	4	5	6	7	8	9	10	11

n

p:

N	O	T
0	1	2

m

Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

for $i \leftarrow 0$ to $n - m$ **do**

$j \leftarrow 0$

while $j < m$ and $p[j] = t[i + j]$ **do**

$j \leftarrow j + 1$

if $j = m$ **then**

Assignment Project Exam Help

return i

<https://powcoder.com>

return -1

Add WeChat powcoder

t:

N	O	B	O	D	Y		K	N	O	W	S
0	1	2	3	4	5	6	7	8	9	10	11

n

p:

N	O	T
0	1	2

m

Analysing Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Analysing Brute Force String Matching



THE UNIVERSITY OF
MELBOURNE

Basic operation:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Analysing Brute Force String Matching



Basic operation: comparison $p[j] = t[i+j]$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Analysing Brute Force String Matching



Basic operation: comparison $p[j] = t[i+j]$

For each $n - m + 1$ positions in t
we make up to m comparisons

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Analysing Brute Force String Matching

Basic operation: comparison $p[j] = t[i+j]$

For each $n - m + 1$ positions in t
we make up to m comparisons

Assignment Project Exam Help

Assuming m much larger than n : $O(mn)$ comparisons.

Add WeChat powcoder

Analysing Brute Force String Matching

Basic operation: comparison $p[j] = t[i+j]$

For each $n - m + 1$ positions in t
we make up to m comparisons

Assignment Project Exam Help

Assuming m much larger than n : $O(mn)$ comparisons.

Add WeChat powcoder

But for **random text** over reasonably large alphabet
(e.g. English), **average** running time is linear in n

Analysing Brute Force String Matching

Basic operation: comparison $p[j] = t[i+j]$

For each $n - m + 1$ positions in t
we make up to m comparisons

Assignment Project Exam Help

Assuming m much larger than n : $O(mn)$ comparisons.

<https://powcoder.com>
Add WeChat powcoder

But for **random text** over reasonably large alphabet
(e.g. English), **average** running time is linear in n

There are better algorithms, for smaller alphabets such as binary strings or strings of DNA nucleobases. But for many purposes, the brute-force algorithm is acceptable.

Brute Force Geometric Algorithms: Closest Pair

- **Problem:** Given n points in k -dimensional space, find a pair of points with minimal separating Euclidean distance.


Assignment Project Exam Help

- The brute force approach considers each pair in turn (except that once it has found the distance from x to y , it does not need to consider the distance from y to x).
<https://powcoder.com>
Add WeChat powcoder
- For simplicity, we look at the 2-dimensional case, the points being $(x_0, y_0), (x_1, y_1), \dots, (x_{n-1}, y_{n-1})$.

Closest Pair Problem (2D)




THE UNIVERSITY OF
MELBOURNE



Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE



Brute Force Closest Pair

Try all combinations (x_i, y_i) and (x_j, y_j) with $i < j$:


```
min  $\leftarrow \infty$   
for  $i \leftarrow 0$  to  $n - 2$  do  
  for  $j \leftarrow i + 1$  to  $n - 1$  do  
     $d \leftarrow \text{sqrt}((x_i - x_j)^2 + (y_i - y_j)^2)$   $\triangleright$  Distance for this pair  
    if  $d < \text{min}$  then  
       $\text{min} \leftarrow d$   $\triangleright$  Smallest distance so far  
       $p_1 \leftarrow i$   $\triangleright$  Remember this (i,j) combination  
       $p_2 \leftarrow j$   
return  $p_1, p_2$ 
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Closest Pair Problem (2D)




THE UNIVERSITY OF
MELBOURNE



Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE



$i=0$ $\min=\infty$

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE



$i=0$ $\min=\infty$

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder


Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE



Closest Pair Problem (2D)



$i=0$ $\min=5$

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE



$i=0$ $\min=5$

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE



$i=0$ $\min=5$

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Closest Pair Problem (2D)




THE UNIVERSITY OF
MELBOURNE



Closest Pair Problem (2D)




THE UNIVERSITY OF
MELBOURNE



Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE



$i=1$ $\min=5$

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Closest Pair Problem (2D)



THE UNIVERSITY OF
MELBOURNE




$i=1$ $\min=4$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Closest Pair Problem (2D)



$i=1$ $\min=4$

and so on until

Assignment Project Exam Help

$i=3$ and $j=4$

<https://powcoder.com>

(which will find the minimum here)

Add WeChat powcoder

Analysing Brute Force Closest Pair Algorithm

- Not hard to see that the algorithm is
- Note, however, that we can speed up the algorithm considerably, by utilising the monotonicity of the square root function
- Does that contradict the claim?
- Later we will see a clever divide and conquer approach leads to a $\Theta(n \log n)$ algorithm

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Analysing Brute Force Closest Pair Algorithm

- Not hard to see that the algorithm is $\Theta(n^2)$
- Note, however, that we can speed up the algorithm considerably, by utilising the monotonicity of the square root function
<https://powcoder.com>
Add WeChat powcoder
- Does that contradict the claim?
- Later we will see a clever divide and conquer approach leads to a $\Theta(n \log n)$ algorithm

Analysing Brute Force Closest Pair Algorithm

- Not hard to see that the algorithm is $\Theta(n^2)$
- Note, however, that we can speed up the algorithm considerably, by utilising the monotonicity of the square root function
 $a < b \implies \sqrt{a} < \sqrt{b}$

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder
- Does that contradict the claim?
- Later we will see a clever divide and conquer approach leads to a $\Theta(n \log n)$ algorithm

Analysing Brute Force Closest Pair Algorithm

- Not hard to see that the algorithm is $\Theta(n^2)$
- Note, however, that we can speed up the algorithm considerably, by utilising the monotonicity of the square root function
 $a < b \implies \sqrt{a} < \sqrt{b}$

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder
- Does that contradict the $\Theta(n^2)$ claim?
- Later we will see a clever divide and conquer approach leads to a $\Theta(n \log n)$ algorithm

Brute Force Summary

- Simple, easy to program, widely applicable.
- Standard approach for small tasks.
[Assignment Project Exam Help](#)
- Reasonable algorithms for some problems.
<https://powcoder.com>
[Add WeChat powcoder](#)
- **But:** Generally inefficient—does not scale well.
- Use brute force for prototyping, or when it is known that input remains small.


Exhaustive Search

- Problem type:
 - Combinatorial decision or optimization problems
 - Search for an element with a particular property
 - Domain grows exponentially, for example all permutations
<https://powcoder.com>
- The brute-force approach—generate and test:
 - Systematically construct all possible solutions
 - Evaluate each, keeping track of the best so far
 - When all potential solutions have been examined, return the best found

Add WeChat powcoder

Example 1: Travelling Salesperson (TSP)


- Find the shortest **tour** (visiting each node exactly once before returning to the start) in a *weighted, undirected* graph.



Side Note: Graph Concepts



THE UNIVERSITY OF
MELBOURNE



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Side Note: Graph Concepts




THE UNIVERSITY OF
MELBOURNE



Side Note: Graph Concepts




THE UNIVERSITY OF
MELBOURNE



Side Note: Graph Concepts




THE UNIVERSITY OF
MELBOURNE



Side Note: Graph Concepts




THE UNIVERSITY OF
MELBOURNE



Side Note: Graph Concepts




THE UNIVERSITY OF
MELBOURNE



Side Note: Graph Concepts




THE UNIVERSITY OF
MELBOURNE



Side Note: Graph Concepts




THE UNIVERSITY OF
MELBOURNE



This graph is undirected since edges do not have directions associated with them.

Example 1: Travelling Salesperson (TSP)

- Find the shortest **tour** (visiting each node exactly once before returning to the start) in a *weighted, undirected* graph.



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Tours

$a - b - c - d - a$:	18
$a - b - d - c - a$:	11
$a - c - b - d - a$:	23
$a - c - d - b - a$:	11
$a - d - b - c - a$:	23
$a - d - c - b - a$:	18

Example 2: Knapsack

- Given n items with
 - Weights: w_1, w_2, \dots, w_n
 - Values: v_1, v_2, \dots, v_n
 - Knapsack of capacity W
- find the most valuable selection of items whose combined weight does not exceed W

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Knapsack Example



THE UNIVERSITY OF
MELBOURNE



Knapsack: Example

Set	Weight	Value	Set	Weight	Value
\emptyset	0	0	{2, 3}	7	52
{1}	7	42	{2, 4}	8	37
{2}	3	12	{3, 4}	9	65
{3}	4	40	{1, 2, 3}	14	NF
{4}	5	25	{1, 2, 4}	15	NF
{1, 2}	10	54	{1, 3, 4}	16	NF
{1, 3}	11	NF	{2, 3, 4}	12	NF
{1, 4}	12	NF	{1, 2, 3, 4}	19	NF

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

NF means “not feasible”: exhausts the capacity of the knapsack.

Later we'll find a better algorithm based on
dynamic programming

Comments on Exhaustive Search

- Exhaustive search algorithms have acceptable running times **only for very small instances.**
- In many cases there are better alternatives, for example, Eulerian tours, shortest paths, minimum spanning trees, . <https://powcoder.com>
Assignment Project Exam Help
- But for some problems, it is **known** that there is essentially no better alternative.
Add WeChat powcoder
- For a large class of important problems, it **appears** that there is no better alternative, but we have no proof either way.


Hamiltonian Tours

- The Hamiltonian tour problem is this:
- In a given undirected graph, is there a simple tour (a path that visits each **node** exactly once, except it returns to the starting node)?

Assignment Project Exam Help

- Is there a Hamiltonian tour of this graph?

Add WeChat powcoder



Eulerian Tours




- The Eulerian tour problem is this:
- In a given undirected graph, is there a path which visits each **edge** exactly once?

Assignment Project Exam Help

- Is there a Eulerian tour of this graph?

<https://powcoder.com>

Add WeChat powcoder



Hard and Easy Problems

- Recall that by a **problem** we usually mean a parametric problem: an infinite family of problem “instances”.
- Sometimes our intuition about the difficulty of problems is not very reliable. The Hamiltonian Tour problem and the Eulerian Tour problem look very similar, but one is hard and the other is easy. We shall see more examples of this phenomenon later.
<https://powcoder.com>
- For many important **optimization** problems we do not know of solutions that are essentially better than exhaustive search (a whole raft of **NP-complete** problems, including TSP, knapsack).
Add WeChat powcoder
- In those cases we may look for **approximation algorithms** that are fast and still find solutions that are reasonably close to the optimal.
- We plan to return to this idea in Week 12.

Next Up

Assignment Project Exam Help

- **Recursion** as a problem solving technique

<https://powcoder.com>

Add WeChat powcoder