

Lecture 14:
Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression

Prediction

k — Nearest

Neighbour

Naive Bayes

Summary

Lecture 14: Classification

COMP90049

Knowledge Technologies

<https://powcoder.com>

Sarah Erfani and Karin Verspoor, CIS

Add WeChat powcoder

Semester 2, 2017



THE UNIVERSITY OF
MELBOURNE

What is Classification?

Classification involves predicting a discrete class or classes.
Those classes are defined in advance.

Binary (yes/no)

- Deciding whether a lone application is risky or not
- Predict whether a dwelling is an apartment or house based on its characteristics
- Predict whether a child will play or not, given weather.
- Will a student skip class on Friday?

Multi-class

- Categorise a document into newspaper sections (news, sports, entertainment, health)
- Recognise images of digits (0-9)
- Discriminating between different species of e.g. a kind of plant or an insect.
- Predicting type of cancer from gene expression data.

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary

■ Given:

- 1 a fixed representation language of *attributes*
- 2 a fixed set of pre-classified *training instances*
- 3 a fixed set of classes C
- 4 a “learner” algorithm which can identify patterns in the training instances

■ Estimate:

the category of a novel input $x : c(x) \in C$

■ Model:

discover the function that predicts the label $c(x)$ given a previously unseen x

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression


Prediction

k - Nearest

Neighbour

Naive Bayes

Summary



The goal of learning from examples is not to **memorise** but rather to **generalise**, e.g., predict.

Example: Supervised Learning (Regression)

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k — Nearest


Neighbour

Naive Bayes

Summary

Can we predict housing prices?

Housing price prediction.



<https://powcoder.com>

Add WeChat powcoder

A friend has a house which is 750 square feet – how much can he expect to get?

(draw a straight line vs. fit a curve)

Linear regression captures a relationship between two variables or attributes.

It makes the assumption that there is a *linear* relationship between the two variables.

- 1 An outcome variable (aka response variable, dependent variable, or label)
- 2 x - predictor (aka independent variable, explanatory variable, or feature)

At its most basic, the relationship can be expressed as a *line* (a deterministic function).

$$y = f(x)$$

$$y = \beta_0 + \beta_1 * x$$

$$y = \beta \cdot x \text{ (given } x_0 = 1)$$

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary

Linear functions are more basic than non-linear functions
(mathematically)

They capture that changes in one variable correlate linearly with changes in another variable.

For some variables, this makes sense.

[The more umbrellas you sell, the more money you make. How much money you make is directly proportional to how many umbrellas you sell.]

Applicability: Regression can be applied when all variables/attributes are real numbers.

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression


Prediction

k — Nearest

Neighbour

Naïve Bayes

Summary



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

From Schutt & O'Neil, *Doing Data Science*

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression


Prediction

k — Nearest

Neighbour

Naïve Bayes

Summary



Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

From Schutt & O'Neil, *Doing Data Science*

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naïve Bayes

Summary

Want to choose the *best* line.

Operationally, the line that minimises the distance between a points and the line.

Recall Euclidean distance: $d(A, B) = \sqrt{\sum_{i=1}^n (a_i - b_i)^2}$

Least squares estimation: find the line that minimises the sum of the squares of the vertical distances between approximated/predicted \hat{y}_i s and observed y_i s. Put another way, we want to find the β that produces \hat{y}_i for each x_i that is closest to the known y_i .

Minimise the Residual Sum of Squares (RSS)
(aka Sum of Squares Due to Error (SSE)):

$$RSS(\beta) = \sum_i (y_i - \beta x_i)^2$$

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary


Armed with a linear model $y = \beta_0 + \beta_1 * x$, we can straightforwardly predict a continuous valued output for y given a value of x .

We derive that linear model by estimating it from training examples.

Given examples $(x_0, y_0), (x_1, y_1), \dots (x_n, y_n)$, we determine β through least squares estimation.

<https://powcoder.com>

Add WeChat powcoder



Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods


Linear Regression

Prediction

k -Nearest
Neighbour

Naive Bayes

Summary



Given class assignments for existing data points, classify a new point (black).

- (a) According to the class membership of the K closest data points.
- (b) For $k = 1$, the induced decision boundary.

See: Charles Elkan, UCSD, 2011 lecture notes (posted on LMS)

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k – Nearest
Neighbour

Naïve Bayes

Summary

[1-NN]: Classify the test input according to the class of the closest training instance.

[k -NN]: Classify the test input according to the majority class of the k nearest training instances.

[weighted k -NN]: Classify the test input according to the weighted accumulative class of the k nearest training instances, where weights are based on similarity of the input to each of the k neighbours.

[offset-weighted k -NN]: Classify the test input according to the weighted accumulative class of the k nearest training instances, where weights are based on similarity of the input to each of the k neighbours, factoring in an offset to indicate the prior expectation of a test input being classified as being a member of that class.

k -Nearest Neighbour classification implementation

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k -Nearest
Neighbour

Naive Bayes

Summary

The most naive neighbour search implementation involves the brute-force computation of distances between all pairs of points in the dataset.

For N samples in D dimensions, this approach scales as $O(DN^2)$.

- Efficient brute-force neighbours searches can be very competitive for small data samples.
- However, as the number of samples N grows, the brute-force approach quickly becomes infeasible.

Alternative: tree-based data structures

- These structures attempt to reduce the required number of distance calculations by efficiently encoding aggregate distance information for the sample.
- The basic idea is that if point A is very distant from point B, and point B is very close to point C, then we know that points A and C are very distant, without having to explicitly calculate their distance.
- In this way, the computational cost of a nearest neighbours search can be reduced to $O(DN \log(N))$ or better.

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k -Nearest
Neighbour

Naive Bayes

Summary

The nearest neighbour approach corresponds to classification by “hyper-spheres” (or “hyper-ellipsoids”)



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression


Prediction

k -Nearest
Neighbour

Naive Bayes

Summary

The nearest neighbour approach corresponds to classification by “hyper-spheres” (or “hyper-ellipsoids”)



Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression


Prediction

k -Nearest
Neighbour

Naive Bayes

Summary

The nearest neighbour approach corresponds to classification by “hyper-spheres” (or “hyper-ellipsoids”)



Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k — Nearest
Neighbour

Naive Bayes

Summary

Strengths

■ Simple

- Can handle arbitrarily many classes (multi-class and multi-label)

Weaknesses

- We need a useful distance function, which may not be obvious to design for some sets.
- We need some sort of averaging or voting function for combining the labels of multiple training examples, which may also not be obvious to design.
- Expensive (in terms of index accesses)
- Everything is done at run time (lazy learner)
- Prone to bias
- Arbitrary k value

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression

Prediction

k — Nearest

Neighbour

Naive Bayes

Summary

Assignment Project Exam Help

- Learning and classification methods based on probability theory
- Build a *generative model* that approximates how data is produced
- Categorisation produces a posterior probability distribution over the possible categories given a description of an instance

Add WeChat powcoder

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary

Assignment Project Exam Help

$$P(C, X) = P(C|X)P(X) = P(X|C)P(C)$$

<https://powcoder.com>

$$P(C|X) = \frac{P(X|C)P(C)}{P(X)}$$

Add WeChat powcoder

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary

- Task: classify an instance $X = \langle x_1, x_2, \dots, x_n \rangle$ according to one of the classes $c_j \in C$

$$\begin{aligned} c &= \operatorname{argmax}_{c_j \in C} P(c_j | x_1, x_2, \dots, x_n) \\ &= \operatorname{argmax}_{c_j \in C} \frac{P(x_1, x_2, \dots, x_n | c_j) P(c_j)}{P(x_1, x_2, \dots, x_n)} \\ &= \operatorname{argmax}_{c_j \in C} P(x_1, x_2, \dots, x_n | c_j) P(c_j) \end{aligned}$$

$$\text{posterior } P(c_j | x_1, x_2, \dots, x_n) = \frac{\text{likelihood} * \text{prior}}{\text{evidence}}$$

- Predicts X belongs to c_i iff the probability $P(c_i | X)$ is the highest among all the $P(c_k | X)$ for all the K classes
- Since $P(x_1, x_2, \dots, x_n)$ is constant for all classes, only $P(x_1, x_2, \dots, x_n | c_j) P(c_j)$ needs to be maximised.

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression


Prediction

k — Nearest

Neighbour

Naïve Bayes

Summary



<https://powcoder.com>

Must determine the probability of *each combination of values* (given a class).

For large n , Add WeChat powcoder

- 1 Typically not enough data to estimate this accurately.
- 2 Common to encounter the situation where there are no training examples for a particular combination.
- 3 This would likely lead to over-fitting (biased to combinations for which there are examples).

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary

Assignment Project Exam Help

- $P(c_j)$

- can be estimated from the frequency of classes in the training examples [*maximum likelihood estimate*]

- $P(x_1, x_2, \dots, x_n | c_j)$

- $O(|X|^n | C|)$ parameters (cannot be estimated in practice)

<https://powcoder.com>

- Naive Bayes Conditional Independence Assumption:

- assume that the probability of observing the conjunction of attributes is equal to the product of the individual probabilities $P(x_i | c_j)$ [hence "naive"]

Add WeChat powcoder

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary

Assignment Project Exam Help

- Applying the conditional independence assumption:

$$\begin{aligned} C &= \operatorname{argmax}_{c_j \in C} P(x_1, x_2, \dots, x_n | c_j) P(c_j) \\ &= \operatorname{argmax}_{c_j \in C} P(c_j) \prod_i P(x_i | c_j) \end{aligned}$$

Add WeChat powcoder

Naive Bayes Example

Given a training data set, what are the probabilities we need to estimate?

Headache	Sore	Temperature	Cough	Diagnosis
severe	mild	high	yes	Flu
no	severe	normal	yes	Cold
mild	mild	normal	yes	Flu
mild	no	normal	no	Cold
severe	severe	normal	yes	Flu

Ann comes to the clinic with severe headache, no soreness, normal temperature and with cough. What does she have? Choose the case with highest probability.

$$P(\text{Flu} | \text{Headache} = \text{severe}, \text{Sore} = \text{no}, \text{Temperature} = \text{normal}, \text{Cough} = \text{yes}) \\ \sim P(\text{Flu}) * P(\text{Headache} = \text{severe} | \text{Flu}) * P(\text{Sore} = \text{no} | \text{Flu}) * P(\text{Temperature} = \text{normal} | \text{Flu}) * P(\text{Cough} = \text{yes} | \text{Flu})$$

$$P(\text{Cold} | \text{Headache} = \text{severe}, \text{Sore} = \text{no}, \text{Temperature} = \text{normal}, \text{Cough} = \text{yes}) \\ \sim P(\text{Cold}) * P(\text{Headache} = \text{severe} | \text{Cold}) * P(\text{Sore} = \text{no} | \text{Cold}) * P(\text{Temperature} = \text{normal} | \text{Cold}) * P(\text{Cough} = \text{yes} | \text{Cold})$$

Estimating probabilities

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification

Definition

Methods

Linear Regression

Prediction

k - Nearest

Neighbour

Naive Bayes

Summary

$$P(Flu) = 3/5$$

$$P(Headache = severe|Flu) = 2/3$$

$$P(Headache = mild|Flu) = 1/3$$

$$P(Headache = no|Flu) = 0/3 (= e)$$

$$P(Sore = severe|Flu) = 1/3$$

$$P(Sore = mild|Flu) = 2/3$$

$$P(Sore = no|Flu) = 0/3 (= e)$$

$$P(Temp = high|Flu) = 1/3$$

$$P(Temp = normal|Flu) = 2/3$$

$$P(Cough = yes|Flu) = 3/3$$

$$P(Cough = no|Flu) = 0/3 (= e)$$

$$P(Cold) = 2/5$$

$$P(Headache = severe|Cold) = 0/2 (= e)$$

$$P(Headache = mild|Cold) = 1/2$$

$$P(Headache = no|Cold) = 1/2$$

$$P(Sore = severe|Cold) = 1/2$$

$$P(Sore = mild|Cold) = 0/2 (= e)$$

$$P(Sore = no|Cold) = 1/2$$

$$P(Temp = high|Cold) = 0/2 (= e)$$

$$P(Temp = normal|Cold) = 2/2$$

$$P(Cough = yes|Cold) = 1/2$$

$$P(Cough = no|Cold) = 1/2$$

Set $0/y$ to e , a small value like 10^{-7} (or less than $\frac{1}{n}$ where n is the number of training instances)

$$\begin{aligned} P(Flu|Headache = severe, Sore = no, Temperature = normal, Cough = yes) \\ \sim P(Flu) * P(Headache = severe|Flu) * P(Sore = no|Flu) * P(Temperature = normal|Flu) * P(Cough = yes|Flu) \\ = 3/5 * 2/3 * e * 2/3 * 3/3 = 0.26e \end{aligned}$$

$$\begin{aligned} P(Cold|Headache = severe, Sore = no, Temperature = normal, Cough = yes) \\ \sim P(Cold) * P(Headache = severe|Cold) * P(Sore = no|Cold) * P(Temperature = normal|Cold) * P(Cough = yes|Cold) \\ = 2/5 * e * 1/2 * 1 * 1/2 = 0.1e \end{aligned}$$

Diagnosis is Flu

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression

Prediction

k — Nearest

Neighbour

Naive Bayes

Summary

Assignment Project Exam Help

Naive Bayes (NB) Classifier is very simple to build, extremely fast to make decisions, and easy to change the probabilities when the new data becomes available.

<https://powcoder.com>

- Works well in many application areas.
- Scales easily for large number of dimensions (100s) and data sizes.
- Easy to explain the reason for the decision made.
- One should apply NB first before launching into more sophisticated classification techniques.

Add WeChat powcoder

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression

Prediction

k - Nearest
Neighbour

Naive Bayes

Summary

Assignment Project Exam Help

- How does the k-nearest neighbour method operate, and what are some of the variants on the original algorithm?
- How does the Naive Bayes algorithm work? What assumptions are required to make the computation tractable?

Add WeChat powcoder

Lecture 14: Classification

COMP90049
Knowledge
Technologies

Classification
Definition

Methods

Linear Regression
Prediction
 k — Nearest
Neighbour
Naive Bayes

Summary

Assignment Project Exam Help

Charles Elkan, UCSD, lecture notes

<http://csweb.ucsd.edu/~felk/lec503winter2010/nearestn.pdf>

Witten, Frank, Hall (2011) Data Mining. Chapter 4. (kD — *tree*, ball tree)

Add WeChat powcoder