

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Functional Dependency

Functional Dependency

A “good” database schema should not lead to *update anomalies*.

- update anomalies,
- functional dependencies,
- Armstrong Axioms,
- closures.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Update Anomalies

Redundancy in a database means storing a piece of data more than once.

Redundancy is often useful for efficiency and semantic reasons, but creates the potential for consistency problems.

A poor *redundancy control* may cause update anomalies.

Consider the example relation below (adapted from “An Introduction to Database Systems” by Desai):

STUDENTS					
Name	Course	Phone_no	Major	Prof	Grade
Jones	353	237-4539	Comp Sci	Smith	A
Ng	329	427-7390	Chemistry	Turner	B
Jones	328	237-4539	Comp Sci	Clark	B
Martin	456	388-5183	Physics	James	A
Dulles	293	371-6259	Decision Sci	Cook	C
Duke	491	823-7293	Mathematics	Lamb	B
Duke	356	823-7293	Mathematics	Bond	UN
Jones	492	237-4539	Comp Sci	Cross	UN
Baxter	379	839-0827	English	Broes	C

Modification anomalies: e.g. Jones's phone number appears 3 times. When a phone number is changed, it must be changed in all 3 places, or the data will be inconsistent.

Update Anomalies

Insertion anomalies:

- If Jones enrolls in another course, and a different phone number is entered, again the data will be inconsistent.

Assignment Project Exam Help

- Also, if the only way that the association between course and professor is stored in this relation, we can only enter the association when someone enrolls in the course.

<https://powcoder.com>

Add WeChat powcoder

Deletion anomalies: If the last student in a course is deleted, the association between professor and course is lost.

Functional dependencies

A function f from S_1 to S_2 has the property

if $x, y \in S_1$ and $x = y$, then $f(x) = f(y)$.

A generalization of keys to avoid design flaws violating the above rule.

Let X and Y be sets of attributes in R .

X (*functionally*) determines Y $X \rightarrow Y$, iff $t_1[X] = t_2[X]$ implies $t_1[Y] = t_2[Y]$.

i.e., $f(t(X)) = t[Y]$

We also say $X \rightarrow Y$ is a *functional* dependency, and that Y is *functionally* dependent on X .

X is called the *left side*, Y the *right side* of the dependency.

Examples

- For every Name, there is a unique Phone_no and Major, assume Name is unique;
- For every Course, there is a unique Prof;
- For every Name and Course, there is a unique Grade.

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

In this example:

$$\{Name\} \rightarrow \{Phone_no, Major\}$$
$$\{Course\} \rightarrow \{Prof\}$$
$$\{Name, Course\} \rightarrow \{Grade\}$$

We can also show these in a diagram like this one:



Notice that other FD's follow from these:

$$\{Name\} \rightarrow \{Major\}$$
$$\{Course, Grade\} \rightarrow \{Prof, Grade\}$$

Functional dependencies

Let F be a set of FD's.

Definition 1: $X \rightarrow Y$ is inferred from F (or that F infers $X \rightarrow Y$), written in

$F \models X \rightarrow Y$
Assignment Project Exam Help

if any relation instance satisfying F must also satisfy $X \rightarrow Y$.

Impossible to list every relation to verify if $X \rightarrow Y$ is inferred from F .

A set ρ of derivation rules are required, such that:

a $X \rightarrow Y$ is inferred from F according to Definition 1 iff it can be derived using ρ .

Armstrong's axioms (1974)

Notation: If X and Y are sets of attributes, we write XY for their union.

e.g. $X = \{A, B\}$, $Y = \{B, C\}$, $XY = \{A, B, C\}$

F1 (Reflexivity) If $X \subseteq Y$ then $X \rightarrow Y$

F2 (Augmentation) $\{X \rightarrow Y\} \models XZ \rightarrow YZ$

F3 (Transitivity) $\{X \rightarrow Y, Y \rightarrow Z\} \models X \rightarrow Z$

F4 (Additivity) $\{X \rightarrow Y, X \rightarrow Z\} \models X \rightarrow YZ$.

F5 (Projectivity) $\{X \rightarrow YZ\} \models X \rightarrow Y$.

F6 (Pseudotransitivity) $\{X \rightarrow Y, YZ \rightarrow W\} \models XZ \rightarrow W$.

Example: Given $F = \{A \rightarrow B, A \rightarrow C, BC \rightarrow D\}$, derive $A \rightarrow D$:

1. $A \rightarrow B$ (given)

2. $A \rightarrow C$ (given)

3. $A \rightarrow BC$ (by F4, from 1 and 2)

4. $BC \rightarrow D$ (given)

5. $A \rightarrow D$ (by F3, from 3 and 4)

F4 (Additivity) $\{X \rightarrow Y, X \rightarrow Z\} \models X \rightarrow YZ$.

F5 (Projectivity) $\{X \rightarrow YZ\} \models X \rightarrow Y$.

F6 (Pseudotransitivity) $\{X \rightarrow Y, YZ \rightarrow W\} \models XZ \rightarrow W$.

In fact, F4, F5, and F6 can be derived from F1-F3.

Assignment Project Exam Help

Example: Prove $\{X \rightarrow Y, X \rightarrow Z\} \models X \rightarrow YZ$.

<https://powcoder.com>

1) $X \rightarrow Y$ is given.

Add WeChat powcoder

2) $XX \rightarrow XY$ (by F2); that is, $X \rightarrow XY$

3) $X \rightarrow Z$ is given.

4) $XY \rightarrow YZ$ (by F2)

5) $X \rightarrow YZ$ (by F3, 2) and 4))

Armstrong's axioms

We can prove that Armstrong's axioms are sound and complete:

Sound: if F derives $A \rightarrow B$ by using Armstrong's axioms, then $F \models A \rightarrow B$ by Definition 1.

Complete: if $F \models M \rightarrow N$ by Definition 1, then F derives $M \rightarrow N$ by using Armstrong's axioms.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Algorithm to Check a FD

Given F , how do we check if $X \rightarrow Y$ is in F^+ ?

F^+ denotes the smallest set of FD's that

- contains F , and

<https://powcoder.com>

- is *closed* under Armstrong's axioms.

Add WeChat powcoder

F^+ is the *closure* of F .

$$F = \{ A \rightarrow B, B \rightarrow C, A \rightarrow C \}$$

$$F^+ = \{ AB \rightarrow A, AB \rightarrow B, AB \rightarrow C, AC \rightarrow A, AC \rightarrow B, AC \rightarrow C, ABC \rightarrow A, ABC \rightarrow B, ABC \rightarrow C, AB \rightarrow AB, AB \rightarrow BC, AB \rightarrow AC, \dots \}$$

Assignment Project Exam Help

F^+ always has an exponential size regarding $|F|$.

<https://powcoder.com>

Add WeChat powcoder

Too expensive to compute F^+ to verify a membership.

Instead we can compute the *closure* X^+ of X under F , X^+ is the largest set of attributes functionally determined by X .

Assignment Project Exam Help

It can be proven (using additivity) that

S1:
$$X^+ = \bigcup_{\forall X \rightarrow A \in F} A.$$

S2:
$$X \rightarrow Y \in F^+ \text{ iff (if and only if) } Y \subseteq X^+.$$

Example:

$F = \{ A \rightarrow B, BC \rightarrow D, A \rightarrow C \}$, compute $\{A\}^+$

1st scan of F:

$X^+ := \{A\}$

$X^+ := \{A, B\}$

$X^+ := \{A, B, C\}$

Assignment Project Exam Help

2nd scan of F: <https://powcoder.com>

$X^+ := \{A, B, C, D\}$

Add WeChat powcoder

3rd scan of F: no change, therefore the algorithm terminates.

$\{A\}^+ := \{A, B, C, D\}$

Algorithm to compute X^+

$X^+ := X;$

change := true;

while change do

begin

change := false;

for each FD $W \rightarrow Z$ in F do

begin

if $(W \subseteq X^+) \text{ and } (Z \not\subseteq X^+)$ then do

begin

$X^+ := X^+ \cup Z;$

change := true;

end

end

end

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Algorithm to Compute a Candidate Key

Given a relational schema R and a set F of functional dependencies on R .

A key X of R must have the property that $X^+ = R$.

Assignment Project Exam Help
Algorithm to compute a candidate key

<https://powcoder.com>

Step 1: Assign X a superkey in F .

Add WeChat powcoder

Step 2: Iteratively remove attributes from X while retaining the property $X^+ =$

R till no reduction on X .

The remaining X is a key.

Example:

$R = \{A, B, C, D\}$ and $F = \{A \rightarrow B, BC \rightarrow D, A \rightarrow C\}$

$X = \{A, B, C\}$ if the left hand side of F is a super key.

A cannot be removed because $\{BC\}^+ = \{B, C, D\} \neq R$

B can be removed because $\{AC\}^+ = \{A, B, C, D\} = R$

→ $X = \{A, C\}$

C can be further removed because $\{A\}^+ = \{A, B, C, D\}$

→ $X = \{A\}$