# COMP9334
# Capacity Planning for Computer Systems and Networks

## Week 5B_1: Discrete-event simulation (3).
## Comparing two systems.

# Discrete event simulations so far

- You have learnt:
  - How to write simulation program
  - You know you cannot get exact mean response time from simulation but you can get a confidence interval
  - You can reduce the width of the confidence interval by
    - Simulate for longer
    - Increase the number of independent replications

- Today, you will learn how you can compare two systems in a statistically sound way

- Before that, we show you that comparing systems can be tricky

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

# Problem: How do we compare 2 alternative choices?

- Week 4B's Revision Problem #2. The question asks you to simulate each of the following 2 queues 10 times:
    - M/M/1 queue with $\lambda = 0.9$ and $\mu = 1$
    - M/M/2 queue with $\lambda = 0.9$ and $\mu = 0.5$

# Comparing two systems: motivation

- An application of simulation is to compare two systems

- For example, in Week 4B's revision question, you used simulation to compare the mean response time of
  - System 1: M/M/1 queue with $\lambda = 0.9$ and $\mu = 1$
  - System 2: M/M/2 queue with $\lambda = 0.9$ and $\mu = 0.5$ for both server

- If you use analytical method, you can find the steady state mean response time of both systems exactly and you compare two numbers

- If you use simulation, you get a confidence interval for each system instead. How do you compare them?

# Example: Comparing two systems

- Let us assume our goal is to use simulation to compare:
  - System 1: M/M/1 queue with $\lambda = 0.9$ and $\mu = 1$
  - System 2: M/M/2 queue with $\lambda = 0.9$ and $\mu = 0.5$ for both server

- For each system we carry out 3 independent replications
  - That is, we use 3 sets of independent random numbers together

- After removing the transient, the estimated mean response times are:
  - System 1: 6.8769, 8.5769, 10.6340
  - System 2: 8.8087, 7.4616, 9.1565

- In order to compare them, let us pair up these results
  - 1st experiment for System 1 with 1st experiment for System 2
  - 2nd experiment for System 1 with 2nd experiment for System 2 etc.

# A paired-*t* confidence interval

- Let us summarise the data in a table
  - EMRT = estimated mean response time

| | EMRT System 1 | EMRT System 2 | EMRT System 2 - EMRT System 1 |
|---|---|---|---|
| Rep. 1 | 6.8769 | 8.8087 | 1.9318 |
| Rep. 2 | 8.5769 | 7.4616 | -1.1154 |
| Rep. 3 | 10.6340 | 9.1565 | -1.4775 |

- We compute the 100 (1-$\alpha$)% confidence interval of the difference between 2 systems (= last column)

- Let us denote the computed confidence interval by [p,q]
  - Case 1: p,q > 0 ➜ System 1 is better than System 2 with probability (1-$\alpha$)
  - Case 2: p,q < 0 ➜ System 2 is better than System 1 with probability (1-$\alpha$)
  - Case 3: q > 0 & p < 0 ➜ Systems 1 and 2 are not different with probability (1-$\alpha$)

# Example: Paired-*t* confidence interval

- We compute the 95% confidence interval of the data showed in the last slide, the confidence interval is:
  - [-4.8721,4.4314]

- Therefore, with 95% probability that the mean response times of the two systems are not different

- Hmmm, we have proven from queueing theory that System 1 has a better mean response time than System 2, but our simulation does not seem to be able to distinguish them.

- What can we do?

# Let us increase the number of replications

- Since increasing the number of replications can reduce the width of the confidence interval, let us try that.

- Let us try 5, 10, 20, 30 replications

| # independent replications | 95% Confidence interval of EMRT System 2 - EMRT System 1 |
|---|---|
| 5 | [-4.9540, 5.0242] |
| 10 | [-1.5347, 2.8020] |
| 20 | [-1.2724, 1.9870] |
| 30 | [-0.6001, 1.8046] |

- Increasing the number of replications does reduce the width of the confidence interval

- However, we still cannot conclude which system is better

# Let us have a look at how we did our experiments …

- We did our experiment with independent random numbers

| Job # | arrival time | service time |
|-------|-------------|--------------|
| 1 | 0.6329 | 0.3431 |
| 2 | 3.6392 | 0.4319 |
| 3 | 4.3919 | 0.1549 |
| … | … | … |

**Arrivals**

**System 1**

$\mu = 1$

**Identical probability distribution but different numbers**

**Different probability distribution but independently generated**

| Job # | arrival time | service time |
|-------|-------------|--------------|
| 1 | 0.2548 | 0.3228 |
| 2 | 4.1194 | 0.3877 |
| 3 | 6.4435 | 0.0728 |
| … | … | …. |

**Arrivals**

**System 2**

$\mu = 0.5$

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

# Common random numbers method

- An alternative is to compare two systems under similar condition

| Job # | arrival time | service time |
|-------|--------------|--------------|
| 1 | 0.6329 | 0.3432 |
| 2 | 3.6392 | 0.4320 |
| 3 | 4.3919 | 0.1050 |
| ... | ... | .... |

**System 1**

Arrivals

$\mu = 1$

Assignment Project Exam Help

https://powcoder.com

**=**

**Multiply by 2**

Add WeChat powcoder

| Job # | arrival time | service time |
|-------|--------------|--------------|
| 1 | 0.6329 | 0.6864 |
| 2 | 3.6392 | 0.8640 |
| 3 | 4.3919 | 0.2100 |
| ... | ... | .... |

**System 2**

Arrivals

1

2

$\mu = 0.5$

# Common random numbers method

- A method to reduce the variance when comparing two alternative systems is to subject them to similar experimental condition

- In each replication, generate only one arrival time and one service time sequence
  - Apply this to both systems
  - Note: Service time may need to be adjusted according to service rate

- In next replication, generate a new arrival time and a new service time sequence
  - Apply this to both systems

- This method can reduce the variance if the behaviour of the two systems is positively correlated

# Applying common random numbers to our problem (1)

- Let us apply the common random numbers method to compare

  - System 1: M/M/1 queue with $\lambda$ = 0.9 and $\mu$ = 1
  - System 2: M/M/2 queue with $\lambda$ = 0.9 and $\mu$ = 0.5 for both server

- Let us carry out 5 replications

- In each replication, we generate one arrival time sequence and one service time sequence (adjusted by service rate) and apply to both systems

# Applying common random numbers to our problem (2)

- Let us compare the estimated mean response time (EMRT) from the 5 replications:

| | EMRT System 1 | EMRT System 2 | EMRT System 2 - EMRT System 1 |
|---|---|---|---|
| Rep. 1 | 8.3022 | 8.8087 | 0.5065 |
| Rep. 2 | 6.8809 | 7.4616 | 0.5807 |
| Rep. 3 | 8.5769 | 9.1565 | 0.5796 |
| Rep. 4 | 10.6340 | 11.3409 | 0.7069 |
| Rep. 5 | 16.2648 | 16.6485 | 0.3837 |

- Observation: The EMRT of System 2 is higher than that of System 1 in all 5 replications
- If we compute the 95% confidence interval of the last column, we get [0.4046,0.6983]
- There is a 95% probability that System 1 is better than System 2

# Comparing two methods

- Let us compare using common random number (CRN) method or not

| # independent replications | 95% Confidence interval of EMRT System 2 - EMRT System 1 | |
|---|---|---|
| | Not using CRN | Using CRN |
| 5 | [-4.9540, 5.0242] | [0.4046, 0.6983] |
| 10 | [-1.5347, 2.8020] | [0.4705, 0.6103] |
| 20 | [-1.2724, 1.9870] | [0.5127, 0.5942] |
| 30 | [-0.6001, 1.8046] | [0.5026, 0.5786] |

- Observations
  - By using CRN, all 95% confidence interval does not include 0
  - The width of the confidence interval for CRN method is a lot lower!

# Approximate visual test

- Let us assume that you know the mean response time and its confidence interval (CI) for 2 systems: **System 1** and **System 2**

- Consider the following 3 possibilities:

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

**Mean**

Sys 1    Sys 2

**CIs do not overlap Mean of System 1 > Mean of Sys. 2**

**Mean**

Sys 1    Sys 2

**CIs overlap and mean of a system is in the CI of the other: System are *not* different**

**Mean**

Sys 1    Sys 2

**CIs overlap and mean of any one is not in the CI of the other: do *t*-test**

# Ex: Multicast protocol design for wireless mesh networks

- Comparing 3 multicast protocols (WCMA, **SPT** and **RCAM**) for wireless mesh networks
- The thin vertical line shows the confidence interval
- What conclusion can you draw?



- Source: Chou et al, "Maximizing Broadcast and Multicast Traffic Load through Link-Rate Diversity in Wireless Mesh Networks", you can download it from my web site: http://www.cse.unsw.edu.au/~ctchou/

# Simulation tools and some applications (1)

- You do not always have to write your own simulation programs from scratch

- There are plenty of simulation tools available
  - Many with GUI

Assignment Project Exam Help

- Simulation tools are used in a lot in computer networking research

https://powcoder.com

Add WeChat powcoder

  - Protocol #1 is the existing protocol, you have designed Protocol #2. You want to see whether Protocol #2 is better or not.

  - You have two options (Option #1 and Option #2) to design a network. Which option is better?

# Simulation tools and some applications (2)

- Some examples of publicly available simulation tools
  - General purpose: OMNet++
    - http://www.omnetpp.org/
  - For networking research: ns3
    - http://www.isi.edu/nsnam/ns/
- Some commercial tools
  - For network design: OPNET, Qualnet
    - http://www.opnet.com/
    - http://web.scalable-networks.com/content/qualnet

- **Important note: These tools save you time in writing simulation program but don't forget that you still need to analyse your simulation results using statistically sound methods!**

# Summary

- Simulation is not just a computer programming exercise

- You need to make sure that your program is correct

- It is also important to analyse your results using statistically sound methods based on confidence interval

- Unfortunately, a lot of published research papers in computer networking did not do sound statistical analysis

  - Optional reading: Pawlikowski et al, "On credibility of simulation studies of telecommunication networks", IEEE Communications Magazine, Pages 132-139, January 2002.

# References

- The primary reference is Law and Kelton, "Simulation Modelling and Analysis"
  - Comparing two alternatives, Section 10.1, 10.2 (10.2.1 only)
  - Common random numbers, Section 11.2
- Raj Jain, "The Art of Computer Systems Performance Analysis" has materials on
  - Comparing two alternatives, Sections 13.3, 13.4 (13.4.1 and 13.4.3 only)
- Note that we have only touched on the basic of statistical analysis of simulation data. The above two books (outside the specified sections) will provide you with more in depth discussion on the topic.