

# COMP9444 Neural Networks and Deep Learning

## Term 3, 2020

### Solutions to Exercises 3: Probability

This page was last updated: 09/30/2020 05:13:27

---

#### 1. Bayes' Rule

<https://powcoder.com>

One bag contains 2 red balls and 3 white balls. Another bag contains 3 red balls and 2 green balls. One of these bags is chosen at random, and two balls are drawn randomly from that bag, without replacement. Both of the balls turn out to be red. What is the probability that the first bag is the one that was chosen?

Let  $B$  = first bag is chosen,  $R$  = both balls are red. Then

$$P(R | B) = (2/5) * (1/4) = 1/10$$

$$P(R | \neg B) = (3/5) * (2/4) = 3/10$$

$$P(R) = (1/2) * (1/10) + (1/2) * (3/10) = 1/5$$

$$P(B | R) = P(R|B) * P(B) / P(R) = (1/10) * (1/2) / (1/5) = 1/4$$


#### 2. Entropy and Kullback–Leibler Divergence

Consider these two probability distributions on the same space  $\Omega = \{A, B, C, D\}$

$$p = \langle 1/2, 1/4, 1/8, 1/8 \rangle$$

$$q = \langle 1/4, 1/8, 1/8, 1/2 \rangle$$

a. Construct a Huffman tree for each distribution  $p$  and  $q$



b. Compute the entropy  $H(p)$

$$H(p) = H(q) = \frac{1}{2}(-\log \frac{1}{2}) + \frac{1}{4}(-\log \frac{1}{4}) + \frac{1}{8}(-\log \frac{1}{8}) + \frac{1}{8}(-\log \frac{1}{8})$$

$$= \frac{1}{2}(1) + \frac{1}{4}(2) + \frac{1}{8}(3) + \frac{1}{8}(3) = 1.75$$

Assignment Project Exam Help

c. Compute the KL-Divergence in each direction  $D_{KL}(p \parallel q)$  and  $D_{KL}(q \parallel p)$

Add WeChat powcoder

$$D_{KL}(p \parallel q) = \frac{1}{2}(2-1) + \frac{1}{4}(3-2) + \frac{1}{8}(3-3) + \frac{1}{8}(1-3) = 0.5$$

https://powcoder.com

$$D_{KL}(q \parallel p) = \frac{1}{4}(1-2) + \frac{1}{8}(2-3) + \frac{1}{8}(3-3) + \frac{1}{2}(3-1) = 0.625$$

Add WeChat powcoder

Which one is larger? Why?

$D_{KL}(q \parallel p)$  is larger, mainly because the frequency of D has increased from  $\frac{1}{8}$  to  $\frac{1}{2}$ , so it incurs a cost of  $3-1=2$  additional bits every time it occurs (which is often).