

COMP9444 Neural Networks and Deep Learning

Term 3, 2020

Exercises 7: Reinforcement Learning

This page was last updated: 11/08/2020 06:07:55

Consider an environment with two states $S = \{S_1, S_2\}$ and two actions $A = \{a_1, a_2\}$, where the (deterministic) transitions δ and reward R for each state and action are as follows:

$$\delta(S_1, a_1) = S_1, R(S_1, a_1) = +1$$

$$\delta(S_1, a_2) = S_2, R(S_1, a_2) = -2$$

$$\delta(S_2, a_1) = S_1, R(S_2, a_1) = +7$$

$$\delta(S_2, a_2) = S_2, R(S_2, a_2) = +3$$

1. Draw a picture of this environment, using circles for the states and arrows for the transitions.
2. Assuming a discount factor of $\gamma = 0.1$, determine
 - a. the optimal policy $\pi^*: S \rightarrow A$
 - b. the value function $V^*: S \rightarrow R$
 - c. the "Q" function $Q^*: S \times A \rightarrow R$

Write the Q values in a matrix like this:

Q	a_1	a_2
S_1		
S_2		

Trace through the first few steps of the Q-learning algorithm, with a learning rate of 1 and with all Q values initially set to zero. Explain why it is necessary to force exploration through probabilistic choice of actions, in order to ensure convergence to the true Q values.

3. Now let's consider how the Value function changes as the discount factor γ varies between 0 and 1.
There are four deterministic policies for this environment, which can be written as π_{11} , π_{12} , π_{21} and π_{22} , where $\pi_{ij}(S_1) = a_i$, $\pi_{ij}(S_2) = a_j$
 - a. Calculate the value function $V_{(\gamma)}^\pi: S \rightarrow R$ for each of these four policies (keeping γ as a variable)
 - b. Determine for which range of values of γ each of the policies π_{11} , π_{12} , π_{21} , π_{22} is optimal

Make sure you attempt the questions yourself, before looking at the [Sample Solutions](#).

<https://powcoder.com>

Assignment Project Exam Help
Assignment Project Exam Help
Add WeChat powcoder
<https://powcoder.com>
Add WeChat powcoder