

Assignment Project Exam Help

<https://powcoder.com>

COMP9517: Computer Vision

Add WeChat powcoder

Tracking

Motion Tracking



- Tracking is the problem of generating an inference about the motion of an object given a sequence of images

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder



Applications

- **Motion capture**

- Record motion of people to control cartoon characters in animations
- Modify the motion record to obtain slightly different behaviours

- **Recognition from motion**

- Determine the identity of a moving object
- Assess what the object is doing

- **Surveillance**

- Detect and track objects in a scene for security
- Monitor their activities and warn if anything suspicious happens

- **Targeting**

- Decide which objects to shoot in scene
- Make sure the objects get hit

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Difficulties in Tracking


- **Loss of information** caused by projection of the 3D world on a 2D image
- **Noise** in images
- Complex object **motion**
- **Non-rigid** or articulated nature of objects
- Partial and full object **occlusions**
- Complex object **shapes**
- Scene **illumination** changes
- **Real-time** processing requirements

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example Tracking Problem



Single moving microscopic particle

- Imaged with signal-to-noise ratio (SNR) of 1.5

Human visual motion perception

- Not so accurate and reproducible in quantification
- Good at integrating spatial and temporal information
- Powerful in making associations and predictions

Computer vision challenges

- Integration of spatial and temporal information
- Modeling and incorporation of prior knowledge
- Probabilistic rather than deterministic approach

Bayesian estimation methods...

Motion Assumptions

- When moving objects do not have unique texture or colour, the characteristics of the motion itself must be used to connect detected points into trajectories
- Assumptions about each moving object:
 - Location changes smoothly over time
 - Velocity (speed and direction) changes smoothly over time
 - Can be at only one location in space at any given time
 - Not in same location as another object at the same time

Topics

- **Bayesian inference**

Using *probabilistic models* to perform tracking

- **Kalman filtering**

Using *linear model assumptions* for tracking

- **Particle filtering**

Using *nonlinear models* for tracking

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>
Bayesian Inference

Add WeChat powcoder

Problem Definition

- A moving object has a **state** which evolves over time

Random variable: X_i can contain any quantities of interest

Specific value: x_i (position, velocity, acceleration, shape, intensity, colour, ...)

<https://powcoder.com>

- The state is **measured** at each time point

Random variable: Y_i in computer vision the

Specific value: y_i measurements are typically features computed from the images

- Measurements are combined to estimate the state

Three Main Steps

- **Prediction:** use the measurements $(y_0, y_1, \dots, y_{i-1})$ up to time $i-1$ to predict the state at time i

$$P(X_i | Y_0 = y_0, Y_1 = y_1, \dots, Y_{i-1} = y_{i-1})$$

- **Association:** select the measurements at time i that are related to the object state
- **Correction:** use the incoming measurement y_i to update the state prediction

$$P(X_i | Y_0 = y_0, Y_1 = y_1, \dots, Y_{i-1} = y_{i-1}, Y_i = y_i)$$

Independence Assumptions

- Current state depends only on the immediate past

$$P(X_i | X_0, X_1, \dots, X_{i-1}) = P(X_i | X_{i-1})$$

Assignment Project Exam Help


- Measurements depend only on the current state

<https://powcoder.com>

$$P(Y_i, Y_j, \dots, Y_k | X_i) = P(Y_i | X_i) P(Y_j, \dots, Y_k | X_i)$$

Add WeChat powcoder

These assumptions imply
the tracking problem has
the structure of inference
on a hidden Markov model



Tracking by Bayesian Inference

- Prediction

$$\begin{aligned}
 P(X_i | y_0, y_1, \dots, y_{i-1}) &= \int \boxed{P(X_i, X_{i-1} | y_0, y_1, \dots, y_{i-1})} dX_{i-1} \\
 &= \int P(X_i | X_{i-1}, \cancel{y_0, y_1, \dots, y_{i-1}}) P(X_{i-1} | y_0, y_1, \dots, y_{i-1}) dX_{i-1} \\
 &= \int \underbrace{P(X_i | X_{i-1})}_{\text{dynamics model}} \underbrace{P(X_{i-1} | y_0, y_1, \dots, y_{i-1})}_{\text{posterior of previous time}} dX_{i-1}
 \end{aligned}$$

dynamics
model

posterior of
previous time

$$\begin{aligned}
 P(X_i, X_{i-1} | y_0, y_1, \dots, y_{i-1}) &= \frac{P(X_i, X_{i-1}, y_0, y_1, \dots, y_{i-1})}{P(y_0, y_1, \dots, y_{i-1})} \\
 &= \frac{P(X_i | X_{i-1}, y_0, y_1, \dots, y_{i-1}) P(X_{i-1}, y_0, y_1, \dots, y_{i-1})}{P(y_0, y_1, \dots, y_{i-1})} \\
 &= P(X_i | X_{i-1}, y_0, y_1, \dots, y_{i-1}) \frac{P(X_{i-1}, y_0, y_1, \dots, y_{i-1})}{P(y_0, y_1, \dots, y_{i-1})} \\
 &= P(X_i | X_{i-1}, y_0, y_1, \dots, y_{i-1}) P(X_{i-1} | y_0, y_1, \dots, y_{i-1})
 \end{aligned}$$

Tracking by Bayesian Inference

- Correction

$$\begin{aligned}
 P(X_i | y_0, y_1, \dots, y_i) &= \frac{P(X_i, y_0, y_1, \dots, y_i)}{P(y_0, y_1, \dots, y_i)} \\
 &= \frac{P(y_i | X_i, y_0, y_1, \dots, y_{i-1}) P(X_i | y_0, y_1, \dots, y_{i-1}) P(y_0, y_1, \dots, y_{i-1})}{P(y_0, y_1, \dots, y_i)} \\
 &= P(y_i | X_i) P(X_i | y_0, y_1, \dots, y_{i-1}) \underbrace{\frac{P(y_0, y_1, \dots, y_{i-1})}{P(y_0, y_1, \dots, y_i)}}_{\text{constant}} \\
 &\propto \underbrace{P(y_i | X_i)}_{\text{measurement model}} \underbrace{P(X_i | y_0, y_1, \dots, y_{i-1})}_{\text{prediction of current state}}
 \end{aligned}$$

Tracking by Bayesian Inference

In summary, tracking by Bayesian inference is done by iterative prediction and correction:

Assignment Project Exam Help

- Prediction

$$P(X_i | Y_{0:i-1}) = \int P(X_i | X_{i-1}) P(X_{i-1} | Y_{0:i-1}) dX_{i-1}$$

https://powcoder.com
Add WeChat powcoder

Posterior at time $i - 1$

- Correction

$$P(X_i | Y_{0:i}) \propto P(Y_i | X_i) P(X_i | Y_{0:i-1})$$

Posterior at time i

$$Y_{0:k} = (Y_0 = y_0, Y_1 = y_1, \dots, Y_k = y_k)$$

Tracking by Bayesian Inference

To make tracking by Bayesian inference work in practice you need to design two models:

- Dynamics model $P(X_i | X_{i-1})$
<https://powcoder.com>
- Measurement model $P(Y_i | X_i)$
Add WeChat powcoder

The specific design choices are application dependent

Tracking by Bayesian Inference

Final estimates are computed from the posterior:

- Example 1: expected a posteriori (EAP)


$$\hat{x}_i = \int x_i P(X_i = x_i | Y_{0:i}) dx_i$$

- Example 2: maximum a posteriori (MAP)

$$\hat{x}_i = \arg \max_{x_i} P(X_i = x_i | Y_{0:i})$$


These are the most popular ones but others are possible

Tracking by Bayesian Inference



Bayesian Tracking Example

Estimating the coordinates of a moving particle:




Assignment Project Exam Help

<https://powcoder.com>
Kalman Filtering

Add WeChat powcoder

Probability Density Propagation



Linear / Gaussian Assumption

If we assume the dynamics (state transition) model and the measurement model to be linear, and the noise to be additive Gaussian, then all the probability densities will be Gaussians

Assignment Project Exam Help

$$x \sim N(\mu, \Sigma)$$

- The state is advanced by multiplying with some known matrix and then adding a zero-mean normal random variable

<https://powcoder.com>

Add WeChat powcoder

$$x_i = Ax_{i-1} + q_{i-1}$$


- The measurement is obtained by multiplying the state by some matrix and then adding a zero-mean normal random variable

$$y_i = Hx_i + r_i$$

$$x_i \sim N(Ax_{i-1}, Q)$$

$$y_i \sim N(Hx_i, R)$$

Kalman Filtering




Assignment Project Exam Help

<https://powcoder.com>
Particle Filtering

Add WeChat powcoder

Probability Density Propagation



Non-Linear / Non-Gaussian Case

- Represent the conditional state density by a set of samples (particles) with corresponding weights (importance)

Assignment Project Exam Help

$$P(X_i | Y_{0:i}) \rightarrow \{s_i^{(n)}, \pi_i^{(n)}\}_{n=1}^M$$


<https://powcoder.com>

Add WeChat powcoder



Particle Filtering

- Propagate each sample using the dynamics model and obtain its new weight using the measurement model



Particle Filtering Algorithm

Iterate

From the “old” sample set $\{\mathbf{s}_{k-1}^{(n)}, \pi_{k-1}^{(n)}, c_{k-1}^{(n)}, n = 1, \dots, N\}$ at time-step t_{k-1} , construct a “new” sample set $\{\mathbf{s}_k^{(n)}, \pi_k^{(n)}, c_k^{(n)}, n = 1, \dots, N\}$ for time t_k .

Construct the n^{th} of N new samples as follows:

1. **Select** a sample $\mathbf{s}_k'^{(n)}$ as follows:

- (a) generate a random number $r \in [0, 1]$, uniformly distributed.
- (b) find, by binary subdivision, the smallest j for which $c_{k-1}^{(j)} \geq r$
- (c) set $\mathbf{s}_k'^{(n)} = \mathbf{s}_{k-1}^{(j)}$

2. **Predict** by sampling from

$$p(\mathcal{X}_k | \mathcal{X}_{k-1} = \mathbf{s}_k'^{(n)})$$

to choose each $\mathbf{s}_k^{(n)}$. For instance, in the case that the dynamics are governed by a linear AR process, the new sample value may be generated as: $\mathbf{s}_k^{(n)} = A \mathbf{s}_k'^{(n)} + (I - A) \bar{\mathbf{x}} + B \mathbf{w}_k^{(n)}$ where $\mathbf{w}_k^{(n)}$ is a vector of standard normal random variates, and BB^T is the process noise covariance.

3. **Measure** and weight the new position in terms of the measured features \mathbf{Z}_k :


$$\pi_k^{(n)} = p(\mathbf{Z}_k | \mathcal{X}_k = \mathbf{s}_k^{(n)})$$

then normalise so that $\sum_n \pi_k^{(n)} = 1$ and store together with cumulative probability as $(\mathbf{s}_k^{(n)}, \pi_k^{(n)}, c_k^{(n)})$ where

$$\begin{aligned} c_k^{(0)} &= 0, \\ c_k^{(n)} &= c_k^{(n-1)} + \pi_k^{(n)} \quad \text{for } n = 1, \dots, N. \end{aligned}$$

Example Application

Tracking of active contour representations of objects



Particle filtering is also known variously as sequential Monte Carlo (SMC) filtering, bootstrap filtering, the condensation algorithm...

Example Application

Tracking of object location in the presence of clutter



Walking pedestrian represented by a state vector consisting of a center position and a bounding box:

$$s_i = (x, y, w, h)_i$$

$$s_i^{(n)} \text{ (samples)}$$

$$\hat{s}_i \text{ (estimated)}$$

$$\tilde{s}_i \text{ (truth/annotated)}$$

Example Application

Tracking of object location in the presence of clutter



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

https://www.youtube.com/watch?v=j-duyzShJ_o

References and Acknowledgements

- Chapters 5 and 8 of Szeliski 2010
- Chapter 18 of Forsyth and Ponce 2011
- Chapter 9 of Shapiro and Stockman 2001
- Paper by M. Isard and A. Blake 1998
<https://powcoder.com>
CONDENSATION: Conditional density propagation for visual tracking
Available online via the UNSW Library
- Images drawn from the above references