

Assignment Project Exam Help

COMP9517: Computer Vision

<https://powcoder.com>

Add WeChat powcoder
Feature Representation

Part 2

Feature Types

- Colour features (Part 1)
 - Colour moments
 - Colour histogram
- Texture features (Part 1)
 - Haralick texture features
 - Local binary patterns (LBP)
 - Scale-invariant feature transform (SIFT)
 - Texture feature encoding
- Shape features (Part 2)
 - Basic shape features
 - Shape context
 - Histogram of oriented gradients (HOG)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Shape Features

- **Shape** is an essential feature of material objects that can be used to identify and classify them
- Example: object recognition

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Shape Features

- Human perception of an object or region involves capturing prominent / salient aspects of shape
- Shape features in an image are normally extracted after the image has been segmented into object regions

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Shape Features

- Challenges

- Invariance to rigid transformations


Assignment Project Exam Help

<https://powcoder.com>

- Tolerance to non-rigid deformations


Add WeChat powcoder

- Correspondence unknown



Basic Shape Features

- Simple geometrical shape descriptors




Basic Shape Features

- Convexity versus concavity of an object


An object O is called convex (or concave) if the straight line between any two points in the object is (or is not) contained in the object

$$\forall \mathbf{a}, \mathbf{b} \in O, \quad \forall 0 \leq \alpha \leq 1$$

$$(1 - \alpha)\mathbf{a} + \alpha\mathbf{b} \in O$$



Convex




Concave

- Convex hull of an object

The smallest convex set that contains the object

- Convex deficiency of an object

Set difference between the convex hull and the object



Basic Shape Features

- Simple geometrical shape descriptors



Compactness:


Ratio of the area of an object to the area of a circle with the same perimeter

Circularity:

Ratio of 4π times the area of an object to the second power of its perimeter ($4\pi A/P^2$ equals 1 for a circle)

Basic Shape Features

- Simple geometrical shape descriptors



Elongation:

Ratio between the
length and width
of the object's
bounding box

Eccentricity:

Ratio of the length
of the minor axis
to the length of
the major axis

Assignment Project Exam Help

- <https://powcoder.com>


Add WeChat powcoder



10

Boundary Descriptors


- Local curvature descriptor
 - The curvature of an object is a local shape attribute
 - Convex (versus concave) parts have positive (versus negative) curvature



Boundary Descriptors

- Two interpretations of local curvature

Suppose the boundary is parameterized as $C:[0,1] \rightarrow \mathbf{R}^2 \Rightarrow C(s)=[x(s), y(s)]$



Geometrical interpretation

$$\kappa(s) = \pm \frac{1}{r(s)}$$

Physical interpretation

$$\kappa(s) = \pm \left\| \frac{d\boldsymbol{\tau}}{ds}(s) \right\|$$

Boundary Descriptors

- Global curvature descriptors

- Total bending energy

$$B = \oint_C \kappa^2(s) ds$$

Assignment Project Exam Help

- Amount of physical energy stored in a rod bent to the contour
 - Circular objects have the smallest contour bending energy $B = 2\pi/r$

<https://powcoder.com>
Add WeChat powcoder

- Total absolute curvature

$$K = \oint_C |\kappa(s)| ds$$

- Absolute value of the curvature integrated along the object contour
 - Convex objects have the smallest total absolute curvature $K = 2\pi$


Boundary Descriptors

- Radial distance descriptor
 - Use the centroid of the shape as the reference point and compute the radial distance for all N pixels along its boundary

$$d(n) = \sqrt{(x(n) - \bar{x})^2 + (y(n) - \bar{y})^2}$$

for $n = 0, 1, \dots, N-1$


<https://powcoder.com>
Add WeChat powcoder



- Scale invariance is achieved by normalising $d(n)$ by the maximum distance to obtain the radial distance $r(n)$
- The number of times the signal $r(n)$ crosses its mean can be used as a measure of boundary roughness

Application Example

- Combining feature descriptors to classify objects




Shape Context

- **Shape context** is a point-wise local feature descriptor
 - Pick n points on the contour of a shape
 - For each point p_i , construct a histogram h_i of the relative coordinates of the other $n - 1$ points \Rightarrow this is the shape context of p_i

$$h_i(k) = \frac{1}{n-1} \sum_{\substack{q \neq p_i \\ (q - p_i) \in \text{bin}(k)}} 1$$

Add WeChat powcoder



S. Belongie, J. Malik, J. Puzicha, "Shape matching and object recognition using shape contexts," IEEE Transactions on Pattern Analysis and Machine Intelligence 24(4):509-522. <https://doi.org/10.1109/34.993558>

Application Example

- Shape matching



query 1: 0.086 2: 0.108 3: 0.109



query 1: 0.066 2: 0.073 3: 0.077



query 1: 0.046 2: 0.107 3: 0.114


Shape Context

- Shape matching
 - Step 1: Sample a list of points on shape edges
For example from Canny edge detector (Gaussian filtering, intensity gradient, non-maximum suppression, hysteresis thresholding, edge tracking)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Shape Context

- Shape matching
 - Step 2: Compute the shape context for each point

$$h_i(k) = \frac{\#\{q \neq p_i : (q - p_i) \in \sin(k)\}}{\#\{q \neq p_i : (q - p_i) \in \sin(k)\}}$$

- Step 3: Compute the cost matrix between two shapes P and Q
 The cost between any two points $p \in P$ and $q \in Q$ with corresponding shape contexts g and h is defined as

$$C_S = \frac{1}{2} \sum_{k=1}^K \frac{[g(k) - h(k)]^2}{g(k) + h(k)} \Rightarrow$$



Shape Context

- Shape matching
 - Step 4: Find the one-to-one matching that minimises the total cost between pairs of points on the two shapes

Assignment Project Exam Help

$$H(\pi) = \sum_i C(p_i, q_{\pi(i)})$$

<https://powcoder.com>

- Step 5: Transform or deform one shape to the other based on the previous one-to-one point matching
 - Choose the desired transformation (for example affine)
 - Apply least-squares or RANSAC fitting

Add WeChat powcoder

Shape Context

- Shape matching
 - Step 6: Compute the shape distance

$$D_{sc}(P, Q) = \frac{1}{n} \sum_{p \in P} \min_{q \in Q} C(p, T(q)) + \frac{1}{m} \sum_{q \in Q} \min_{p \in P} C(p, T(q))$$

<https://powcoder.com>

Other costs may also be taken into consideration

- Appearance of the image at the points
- Bending energy of the transformation

Application Example

- Shape matching



query



1: 0.086



2: 0.108



3: 0.109



query



1: 0.066



2: 0.073



3: 0.077



query



1: 0.046



2: 0.107



3: 0.114

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

1) Sample points

2) Compute shape context

3) Compute cost matrix

4) Find point matching

5) Perform transformation

6) Compute distance

Histogram of Oriented Gradients

- HOG describes the distributions of gradient orientations in localized areas and does not require initial segmentation



N. Dalal and B. Triggs, "Histograms of oriented gradients for human detection," Computer Vision and Pattern Recognition 2005. <https://doi.org/10.1109/CVPR.2005.177>


Histogram of Oriented Gradients

- Step 1: Calculate gradient magnitude and orientation at each pixel with a gradient operator => gradient vector

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Histogram of Oriented Gradients

- Step 2: Divide orientations into N bins and assign the gradient magnitude of each pixel to the bin corresponding to its orientation => cell histogram
 - For example 9 bins evenly divided from 0 to 180 degrees

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder




Histogram of Oriented Gradients

- Step 3: Concatenate and block-normalise cell histograms to generate detection-window level HOG descriptor



Histogram of Oriented Gradients

- Detection via sliding window on the image




Histogram of Oriented Gradients


- Detection via sliding window on the image

Assignment Project Exam Help

HOG feature map



Detector response map




<https://powcoder.com>

Add WeChat powcoder

Application Example

- Human detection



<https://www.pyimagesearch.com/2015/11/09/pedestrian-detection-opencv/>

Application Example


- Human detection



<https://www.youtube.com/watch?v=0hMMRIB9DUc>

Application Example

- Deformable part model



P. Felzenszwalb, D. McAllester, D. Ramanan, "A discriminatively trained, multiscale, deformable part model," Computer Vision and Pattern Recognition 2008. <https://doi.org/10.1109/CVPR.2008.4587597>

Summary

- Feature representation is essential in solving almost all types of computer vision problems
- Most commonly used image features:
 - Colour features (Part 1)
 - Colour moments and histogram
 - Texture features (Part 1)
 - Haralick, LBP, SIFT
 - Shape features (Part 2)
 - Basic, shape context, HOG

Summary

- Other techniques described
 - Descriptor matching
 - Feature encoding (Bag-of-Words)
 - k-means clustering
 - Alignment and RANSAC
 - Spatial transformations
 - Shape features
 - Shape matching
 - Sliding window detection

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

References and Acknowledgements

- Szeliski, Chapter 4 (in particular Sections 4.1.1 to 4.1.3 and 4.3.2), Chapter 6 (in particular Sections 6.1.1 to 6.1.4)
- Some content are extracted from the above resource, James Hays slides, and slides from Michael A. Wirth
- L. Liu et al., [From BoW to CNN: two decades of texture representation for texture classification](https://powcoder.com), International Journal of Computer Vision, 2019
- And other resources as indicated by the hyperlinks