

COMS 4771
Assignment Project Exam Help
Perceptron and Kernelization
<https://powcoder.com>

Add WeChat powcoder

Nakul Verma

Last time...


- Generative vs. Discriminative Classifiers
- Nearest Neighbor (NN) classification
- Optimality of k -NN
- Coping with drawbacks of k -NN
- Decision Trees
- The notion of overfitting in machine learning

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

A Closer Look Classification



Linear Decision Boundary



Assume binary classification $y = \{-1, +1\}$
(What happens in multi-class case?)

Learning Linear Decision Boundaries

g = decision boundary

$d=1$ case: $g(x) = w_1 x + w_0 = 0$

Assignment Project Exam Help

general: $g(\vec{x}) = \vec{w} \cdot \vec{x} + w_0 = 0$

<https://powcoder.com>

f = linear classifier

Add WeChat powcoder

$$f(x) := \begin{cases} +1 & \text{if } g(\vec{x}) \geq 0 \\ -1 & \text{if } g(\vec{x}) < 0 \end{cases}$$

$$= \text{sign}(\vec{w} \cdot \vec{x} + w_0)$$

of parameters to learn in \mathbf{R}^d ?

Dealing with w_0

$$g(\vec{x}) = \vec{w} \cdot \vec{x} + w_0$$

$$= \underbrace{\begin{pmatrix} \vec{w} \\ w_0 \end{pmatrix}}_{\vec{w}'} \cdot \underbrace{\begin{pmatrix} \vec{x} \\ 1 \end{pmatrix}}_{\vec{x}'} \quad \text{bias}$$



Assignment Project Exam Help

<https://powcoder.com>


$$g(\vec{x}') = \vec{w}' \cdot \vec{x}' \quad \text{homogeneous}$$

Add WeChat powcoder

"lifting"




The Linear Classifier



A basic computational unit in a neuron

Can Be Combined to Make a Network



Amazing fact:

Can approximate any smooth function!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

An artificial neural network

How to Learn the Weights?

Given labeled training data (bias included): $(\vec{x}_1, y_1), (\vec{x}_2, y_2), \dots, (\vec{x}_n, y_n)$

Want: \vec{w} , which **minimizes** the training error, i.e.

$$\arg \min_{\vec{w}} \frac{1}{n} \sum_{i=1}^n \mathbf{1}[\text{sign}(\vec{w} \cdot \vec{x}_i) \neq y_i]$$
$$= \arg \min_{\vec{w}} \sum_{\substack{x_i \\ \text{s.t. } y_i = +1}} \mathbf{1}[\vec{x}_i \cdot \vec{w} \leq 0] + \sum_{\substack{x_i \\ \text{s.t. } y_i = -1}} \mathbf{1}[\vec{x}_i \cdot \vec{w} \geq 0]$$

Add WeChat powcoder

*How do we **minimize**?*

- Cannot use the standard technique (take derivative and examine the stationary points). Why?

Unfortunately: NP-hard to solve or even approximate!

Finding Weights (Relaxed Assumptions)

Assignment Project Exam Help

Can we approximate the weights if we make reasonable assumptions?


<https://powcoder.com>

What if the training data is linearly separable?

Add WeChat powcoder

Linear Separability

Say there is a **linear** decision boundary which can **perfectly separate** the training data



Finding Weights

Given: labeled training data $S = (\vec{x}_1, y_1), (\vec{x}_2, y_2), \dots, (\vec{x}_n, y_n)$

Want to determine: is there a \vec{w} which satisfies $y_i(\vec{w} \cdot \vec{x}_i) \geq 0$ (for all i)

Assignment Project Exam Help
i.e., is the training data linearly separable?

<https://powcoder.com>

Since there are $d+1$ variables and $|S|$ constraints, it is possible to solve efficiently it via a (constraint) optimization program. (How?)

*Can find it in a much **simpler** way!*

The Perceptron Algorithm

Given: labelled training data $S = (\vec{x}_1, y_1), (\vec{x}_2, y_2), \dots, (\vec{x}_n, y_n)$

Initialize $\vec{w}^{(0)} = 0$


For $t = 1, 2, 3, \dots$

If exists $(\vec{x}, y) \in S$ s.t. $\text{sign}(\vec{w}^{(t-1)} \cdot \vec{x}) \neq y$


$$\vec{w}^{(t)} \leftarrow \begin{cases} \vec{w}^{(t-1)} + \vec{x} & \text{if } y = +1 \\ \vec{w}^{(t-1)} - \vec{x} & \text{if } y = -1 \end{cases}$$

(terminate when no such training sample exists)

Perceptron Algorithm: Geometry



Perceptron Algorithm: Geometry



The Perceptron Algorithm

Input: labelled training data $S = (\vec{x}_1, y_1), (\vec{x}_2, y_2), \dots, (\vec{x}_n, y_n)$

Initialize $\vec{w}^{(0)} = 0$

For $t = 1, 2, 3, \dots$

If exists $(\vec{x}, y) \in S$ s.t. $\text{sign}(\vec{w}^{(t-1)} \cdot \vec{x}) \neq y$

$$\vec{w}^{(t)} \leftarrow \begin{cases} \vec{w}^{(t-1)} + \vec{x} & \text{if } y = +1 \\ \vec{w}^{(t-1)} - \vec{x} & \text{if } y = -1 \end{cases}$$

(terminate when no such training sample exists)

Question: Does the perceptron algorithm terminates? If so, when?

Perceptron Algorithm: Guarantee

Theorem (Perceptron mistake bound):

Assume there is a (unit length) \vec{w}^* that can separate the training sample S with margin γ

Let $R = \max_{\vec{x} \in S} \|\vec{x}\|$

Assignment Project Exam Help

Then, the perceptron algorithm will make at most $T := \left(\frac{R}{\gamma}\right)^2$ mistakes.

Add WeChat powcoder

Thus, the algorithm will terminate in T rounds!

umm... but what about the generalization or the test error?

Proof

Key quantity to analyze:

How far is $\vec{w}^{(t)}$ from \vec{w}^* ?

Suppose the perceptron algorithm makes a mistake in iteration t , then

$$\begin{aligned}\vec{w}^{(t)} \cdot \vec{w}^* &= (\vec{w}^{(t-1)} + y\vec{x}) \cdot \vec{w}^* \\ &\geq \vec{w}^{(t-1)} \cdot \vec{w}^* + y\vec{x} \cdot \vec{w}^*\end{aligned}$$

$$\begin{aligned}\|\vec{w}^{(t)}\|^2 &= \|\vec{w}^{(t-1)} + y\vec{x}\|^2 \\ &= \|\vec{w}^{(t-1)}\|^2 + 2y(\vec{w}^{(t-1)} \cdot \vec{x}) + \|y\vec{x}\|^2 \\ &\leq \|\vec{w}^{(t-1)}\|^2 + R^2\end{aligned}$$

Proof (contd.)

for all iterations t

$$\vec{w}^{(t)} \cdot \vec{w}^* \geq \vec{w}^{(t-1)} \cdot \vec{w}^* + \gamma$$

$$\|\vec{w}^{(t)}\|^2 \leq \|\vec{w}^{(t-1)}\|^2 + R^2$$

Assignment Project Exam Help

<https://powcoder.com>

So, after T rounds

$$T\gamma \leq \vec{w}^{(T)} \cdot \vec{w}^* \leq \|\vec{w}^{(T)}\| \|\vec{w}^*\| \leq R\sqrt{T}$$

Add WeChat powcoder

Therefore:
$$T \leq \left(\frac{R}{\gamma}\right)^2$$



What Good is a Mistake Bound?

- It's an upper bound on the number of mistakes made by an **online algorithm** on an **arbitrary sequence** of examples

i.e. no i.i.d. assumption and not loading all the data at once!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Online algorithms with small mistake bounds can be used to develop classifiers with **good generalization error**!

Other Simple Variants on the Perceptron

Voted perceptron

Average perceptron

Winnow

...

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Linear Classification


Assignment Project Exam Help

<https://powcoder.com>
Linear classification simple,

but... *when is real-world data linearly separable?*
Add WeChat powered by


What about non-linear decision boundaries?

Non linear decision boundaries are common:



Generalizing Linear Classification

Suppose we have the following training data:



d=2 case:

Assignment Project Exam Help

$$g(\vec{x}) = w_1 x_1^2 + w_2 x_2^2 + w_0$$

<https://powcoder.com>

*say, the decision boundary is
some sort of ellipse*

Add WeChat powcoder

e.g. circle of radius r :

$$w_1 = 1$$

$$w_2 = 1$$

$$w_0 = -r^2$$

separable via a circular decision boundary

not linear in \vec{x} !

But g is Linear in *some* Space!

$$g(\vec{x}) = w_1 x_1^2 + w_2 x_2^2 + w_0 \quad \text{non linear in } x_1 \text{ \& } x_2$$

$$= w_1 \chi_1 + w_2 \chi_2 + w_0 \quad \text{linear in } \chi_1 \text{ \& } \chi_2!$$

Assignment Project Exam Help

<https://powcoder.com>


So if we apply a feature transformation on our data:

Add WeChat powcoder

$$\phi(x_1, x_2) \mapsto (x_1^2, x_2^2)$$

Then g becomes linear in ϕ - transformed feature space!

Feature Transformation Geometrically



Feature Transform for Quadratic Boundaries

\mathbf{R}^2 case: (generic quadratic boundary)

$$g(\vec{x}) = w_1 x_1^2 + w_2 x_2^2 + w_3 x_1 x_2 + w_4 x_1 + w_5 x_2 + w_0$$

$$= \sum_{p+q \leq 2} w^{p,q} x_1^p x_2^q$$

feature transformation:

$$\phi(x_1, x_2) \mapsto (x_1^2, x_2^2, x_1 x_2, x_1, x_2, 1)$$

\mathbf{R}^d case: (generic quadratic boundary)

$$g(\vec{x}) = \sum_{i,j=1}^d \sum_{p+q \leq 2} w_{i,j}^{p,q} x_i^p x_j^q$$

This captures all pairwise interactions between variables

feature transformation:

$$\phi(x_1, x_2) \mapsto (x_1^2, x_2^2, \dots, x_d^2, x_1 x_2, \dots, x_{d-1} x_d, x_1, x_2, \dots, x_d, 1)$$

Data is Linearly Separable in some Space!

Theorem:

Given n distinct points $S = \{\vec{x}_1, \vec{x}_2, \dots, \vec{x}_n\}$

there exists a feature transform such that for *any* labelling of S is linearly separable in the transformed space!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

(feature transforms are sometimes called the Kernel transforms)

the proof is almost trivial!

Proof

Given n points, consider the mapping into \mathbf{R}^n :

$$\phi(\vec{x}_i) \mapsto \begin{pmatrix} 0 \\ \vdots \\ 0 \\ 1 \\ 0 \\ \vdots \\ 0 \end{pmatrix} \quad \begin{array}{l} \text{(zero in all coordinates} \\ \text{except in coordinate } i) \end{array}$$

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Then, the decision boundary induced by linear weighting $\vec{w}^* = \begin{pmatrix} y_1 \\ \vdots \\ y_n \end{pmatrix}$ perfectly separates the input data!



Transforming the Data into Kernel Space

Pros:

Any problem becomes **linearly separable**!

Assignment Project Exam Help

Cons:

What about **computation**? Generic kernel transform is typically $\Omega(n)$

<https://powcoder.com>

Add WeChat powcoder

*Some useful kernel transforms map the input space into **infinite dimensional space**!*

What about **model complexity**?

Generalization performance typically degrades with model complexity

The Kernel Trick (to Deal with Computation)

Explicitly working in generic Kernel space $\phi(\vec{x}_i)$ takes time $\Omega(n)$

But the **dot product** between two data points in kernel space can be computed relatively quickly

Assignment Project Exam Help
 $\phi(\vec{x}_i) \cdot \phi(\vec{x}_j)$ can compute fast

Examples:

<https://powcoder.com>

- quadratic kernel transform for data in \mathbf{R}^d

explicit transform $O(d^2)$ **Add WeChat powcoder**

$$\vec{x} \mapsto (x_1^2, \dots, x_d^2, \sqrt{2}x_1x_2, \dots, \sqrt{2}x_{d-1}x_d, \sqrt{2}x_1, \dots, \sqrt{2}x_d, 1)$$

dot products $O(d)$ $(1 + \vec{x}_i \cdot \vec{x}_j)^2$

- RBF (radial basis function) kernel transform for data in \mathbf{R}^d

explicit transform infinite dimension! $\vec{x} \mapsto (\exp(-\|\vec{x} - \alpha\|^2))_{\alpha \in \mathbb{R}^d}$

dot products $O(d)$ $\exp(-\|\vec{x}_i - \vec{x}_j\|^2)$

The Kernel Trick

The trick is to perform classification in such a way that it **only accesses the data** in terms of **dot products** (so it can be done quicker)

Example: the 'kernel Perceptron'

Recall: $\vec{w}^{(t)} \leftarrow \vec{w}^{(t-1)} + y \vec{x}$

Equivalently $\vec{w} = \sum_{k=1}^n \alpha_k y_k \vec{x}_k$ $\alpha_k = \# \text{ of times mistake was made on } x_k$

Thus, classification becomes

$$f(\vec{x}) := \text{sign}(\vec{w} \cdot \vec{x}) = \text{sign}\left(\vec{x} \cdot \sum_{k=1}^n \alpha_k y_k \vec{x}_k\right) = \text{sign}\left(\sum_{k=1}^n \alpha_k y_k (\vec{x}_k \cdot \vec{x})\right)$$

Only accessing data in terms of dot products!

The Kernel Trick: for Perceptron

classification in original space:

$$f(\vec{x}) = \text{sign}\left(\sum_{k=1}^n \alpha_k y_k (\vec{x}_k \cdot \vec{x})\right)$$

If we were working in the transformed Kernel space, it would have been

Assignment Project Exam Help

$$f(\phi(\vec{x})) = \text{sign}\left(\sum_{k=1}^n \alpha_k y_k (\phi(\vec{x}_k) \cdot \phi(\vec{x}))\right)$$

<https://powcoder.com>

Algorithm:

Add WeChat powcoder

Initialize $\vec{\alpha} = 0$

For $t = 1, 2, 3, \dots, T$

If exists $(\vec{x}_i, y_i) \in S$ s.t. $\text{sign}\left(\sum_{k=1}^n \alpha_k y_k (\phi(\vec{x}_k) \cdot \phi(\vec{x}_i))\right) \neq y_i$

$\alpha_i \leftarrow \alpha_i + 1$

*implicitly working in
non-linear kernel space!*

The Kernel Trick: Significance

$$\sum_{k=1}^n \alpha_k y_k$$

Assignment Project Exam Help
dot products are a measure of similarity
<https://powcoder.com>

Add WeChat powcoder
Can be replaced by any user-defined measure of similarity!

*So, we can work in any user-defined non-linear space **implicitly** **without** the potentially heavy computational cost*

What We Learned...

- Decision boundaries for classification
- Linear decision boundary (linear classification)
Assignment Project Exam Help
- The Perceptron algorithm
<https://powcoder.com>
- Mistake bound for the perceptron
Add WeChat powcoder
- Generalizing to non-linear boundaries (via Kernel space)
- Problems become linear in Kernel space
- The Kernel trick to speed up computation

Questions?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Next time...

Support Vector Machines (SVMs) Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder