

C/CPS 506

Assignment Project Exam Help

Comparative Programming Languages

<https://powcoder.com>

Prof. Alex Ufkes

Add WeChat powcoder

Topic 9: Rust intro & typing

Notice!

**Obligatory copyright notice in the age of digital
delivery and online classrooms:**

Assignment Project Exam Help

<https://powcoder.com>

The copyright to this original work is held by Alex Ufkes. Students registered in course CCPS 505 can use this material for the purposes of this course but no other use is permitted, and there can be no sale or transfer or use of the work for any other purpose without explicit permission of Alex Ufkes.

Course Administration



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Getting closer! Rust is our last language.
- Don't forget about the assignments!

Moving on...

Assignment Project Exam Help
...to imperative.
<https://powcoder.com>

Add WeChat powcoder

Rust is an imperative language. However, we'll see many cool features that remind us of the functional languages we've seen.




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Rust History



- Grew out of a personal project by Mozilla employee Graydon Hoare in 2006
- Mozilla began sponsoring the project in 2009
- Officially announced in 2010
- Rust compiler successfully tested in 2011
- Pre-alpha version released in 2012
- Rust 1.0, the first stable release, arrived on May 15, 2015
- Youngest language we've seen so far
- Open source

IEEE Developer's Survey 2018



Most Loved, Dreaded, and Wanted

% using who want
to keep using

Loved

Dreaded



Wanted

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Also #1 in 2017 and 2016!



In Industry?

Mozilla in collaboration with Samsung

- Parallel web browser engine


Dropbox

- Magic Pocket file system, petabyte storage machines

Tor (The Onion Router)

- Experimenting with porting to Rust (from C) for safety features.

Rust Features



Systems Programming Language:


Assignment Project Exam Help
In contrast with application programming languages.

<https://powcoder.com>

Add WeChat powcoder

- System software includes things like operating systems, utility software, device drivers, compilers, linkers, etc.
- System languages tend to feature more direct access to physical hardware of a given machine.

Rust Features



Syntax:


- Similar to C/C++
- Blocks of code delimited by { }
- Familiar control structures supported (`if`, `else`, `while`, `for`, etc.)
- Supports pattern matching! (`match`)
- Need not use `return`, last expression creates return value
- Functions largely composed of expressions

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Rust Features



Memory Safety:

Assignment Project Exam Help

- Rust is designed to be *memory safe*
- Null or dangling pointers are not permitted.

<https://powcoder.com>

Add WeChat powcoder

“Null or dangling pointers are not permitted”

```
#include <stdio.h>
#include <stdlib.h>
```

```
int main(void)
{
```

```
    int *x = NULL;
    *x = 77;
```

```
    int *y = (int*) malloc(4 * sizeof(int));
    y[4] = 7;
```

```
    printf("%d \n", *x);
    printf("%d \n", y[4]);
```

```
    system("pause");
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- In C, we're allowed to try and access any memory we want.
- This code compiles!
- It produces a run-time error when we try and index into pointer x.
- Overrunning array bounds does not necessarily give a run time error!
- Very unsafe use of memory.

“Null or dangling pointers are not permitted”

```
public class Paradigm
{
    public static void main(String[] args)
    {
        int[] nums = {1, 2, 3, 4, 5};

        nums[5] = 17;

        int[] nums2;
    }
}
```


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Java is safer.
- This code *compiles*, but **always** throws an exception when we access outside array bounds.
- C/C++ only errors if going out of bounds accesses memory that your program doesn't have write permission for.
- Java still allows dangling references.
- `nums2` can be created without instantiating its object.

Rust Features



Assignment Project Exam Help


Memory Safety

<https://powcoder.com>

Add WeChat powcoder

- Rust is designed to be *memory safe*
- Null or dangling pointers are not permitted.
- What about linked lists? Null pointers are useful.
- Rust defines an *option* type, which can be used to test if a pointer has *Some* value or *None*
 - What does this remind you of?

Rust Features



Memory Management:


- Rust does not do garbage collection
- ***Resource acquisition is initialization***
- **RAII** - Originated in C++
- Constructor used to acquire and initialize objects
- Resource *deallocation* is done by the destructor.
- No valid reference to object == no object.
- Not so in Java! Up to garbage collector.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Rust Features



Types and Polymorphism:


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powder

- Type system supports mechanism called “traits”
- Directly inspired by Haskell’s type classes
- Supports type inference for variables declared with **let** keyword.
- Compile error if inference fails.
- Keyword **mut** for mutable variables.

Rust Features



Assignment Project Exam Help


Pattern Matching:

- Rust supports pattern matching!
- Pattern matching is considered a sticking point for people learning Rust.
- We already have experience with it

<https://powcoder.com>

Add WeChat powcoder

Rust & Safety




Strongly, statically typed

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powder

- Strong typing means limited implicit type conversions at compile time.
- C is happy to convert between numeric types without issue. Perhaps a compile warning in C++.
- Java raises compile error if there's a loss of precision (double to float for example).




```
int main(void)
{
    int x = 3.14159;
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
op(7): warning C4244: 'initializing' : conversion from 'double' to 'int', possible loss of data
ects\Tester\Debug\Tester.exe
```



```
public class Paradigm
```

```
{
```

```
    public static void main(String[] args)
```

```
    {
```

```
        float x = 3.1415
```

```
    }
```

```
}
```


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

incompatible types: possible lossy conversion
from double to float

Rust & Safety



No “Undefined Behavior”


- Null pointer dereferencing
 - Attempt to dereference address 0

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
int main(void)
{
    printf("%d\n", NULL);
    system("pause");
}
```




D:\Googl

0

Press any

Rust & Safety



No “Undefined Behavior”

- Null pointer dereferencing
 - Attempt to dereference address 0
- Use of variable before it's initialized
 - In C, we get whatever was in memory before that.
- Only globals auto-initialize to 0

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

```
int x;  
int main(void)  
{  
    int y;  
    printf("%d\n%d\n", x, y);  
}
```

```
quincy  
0  
4199232
```

Rust & Safety



No “Undefined Behavior”

- Null pointer dereferencing
 - Attempt to dereference address 0
 - Use of variable before it's initialized
 - In C, we get whatever was in memory before that.
 - Only globals auto-initialize to 0
- Array index out of bounds
 - May or may not cause runtime error (in C), depends who owns memory

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
#include <stdio.h>
#include <stdlib.h>
```

```
int x;
```

```
int main(void)
```

```
{
```

```
    int y[5];
```

```
    y[6000] = 8;
```

```
}
```

Microsoft Visual Studio



Unhandled exception at 0x00361A43 in Tester.exe: 0xC0000005: Access violation writing location 0x00D05B28.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

☐ Break when this exception type is thrown


[Open Exception Settings](#)

Break

Continue

Ignore

Rust & Safety



No “Undefined Behavior”


- Signed integer overflow & optimization

<https://powcoder.com> $X+1 > X$

Add WeChat powcoder

- If overflow is undefined, compiler can just optimize this to simply **true**.
- Dangerous if X can overflow!
- Forcing compiler to consider overflow means we lose certain optimizations.

Rust Non-Goals



- We do not employ any particularly cutting-edge technologies. Old, established techniques are better.
- We do not prize expressiveness, minimalism or elegance above other goals. These are desirable but subordinate goals.
- We do not intend to cover the complete feature-set of C++, or any other language. Rust should provide majority-case features.
- We do not intend to be 100% static, 100% safe, 100% reflective, or too dogmatic in any other sense. Trade-offs exist.
- We do not demand that Rust run on “every possible platform”. It must eventually work without unnecessary compromises on widely-used hardware and software platforms.



Installing Rust

<https://www.rust-lang.org/en-US/index.html>

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Documentation [Getting Started](#) [Community](#) [Contribute](#)

Fork me on GitHub

Rust is a systems programming language that runs blazingly fast, prevents segfaults, and guarantees thread safety.

Install Rust 1.26.0

May 10, 2018

See who's using Rust, and read more about Rust in production.

```
fn main() {  
    let greetings = ["Hello", "Hola", "Bonjour",
```

Run



Installing Rust

Install Rust

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

To install Rust, download and run
`rustup init`
then follow the onscreen instructions.

If you're a Windows Subsystem for Linux user
run the following in your terminal, then follow
the onscreen instructions to install Rust.


```
curl https://sh.rustup.rs -sSf | sh
```

Rust 1.26.0

May 10, 2018

Editing Rust Code

Any text editor will do, but I like VSCode:




Visual Studio Code:

- Supports Rust syntax coloring
- Useful for other languages

Compiling Rust Code

Command Line - **rustc**



The screenshot shows a Windows Command Prompt window with the following text:

```
C:\Users\aufke\Desktop\RustCode>rustc main.rs
C:\Users\aufke\Desktop\RustCode>main
Hello, world!
C:\Users\aufke\Desktop\RustCode>_
```

Annotations on the image include:

- Red text "Assignment Project Exam Help" at the top.
- Red text "[https://powcoder.com](\"https://powcoder.com\")" in the middle.
- Red text "Add WeChat powcoder" at the bottom.
- A green box highlighting the command `rustc main.rs`.
- A blue arrow pointing from the URL to the command `main`.
- A blue arrow pointing from the text "Add WeChat powcoder" to the output "Hello, world!".

<https://www.rustaceans.org/>



Search for a Rustacean:

(by name, irc nick, username for Reddit, GitHub, Discourse, etc.)

Assignment Project Exam Help

<https://powcoder.com>

This website is for finding Rustaceans. Wondering who is behind that GitHub username or IRC nick? Here is where to find out (search at the top of the page).

Add WeChat powcoder

Rustaceans are people who use Rust, contribute to Rust, or are interested in the development of Rust.



Much of the syntax is reminiscent of C/C++

```
fn main() {  
    println!("Hello, world!");  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Like C, C++, Java, Haskell, and many others, `main()` defines the entry point for executing a Rust program.

```
fn main() {  
    println!("Hello, world!");  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

println vs print!

- The ! indicates we're calling a macro.
- A standard function call doesn't include !


Variables

- By default, Rust variables are immutable
- Once initialized, can't change.
- Like `final` or `const` in other languages
- Declare using `let` keyword:

<https://powcoder.com>

Add WeChat powcoder

```
fn main() {  
    let x = 7;  
    println!("value: {}", x);  
}
```



```
Command Prompt  
C:\_RustCode>rustc main.rs  
  
C:\_RustCode>main  
value: 7  
  
C:\_RustCode>_
```

```
fn main() {  
    let x = 7;  
    println!("value: {}", x);  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Curly brace pair in a println string acts
as a C/C++ style placeholder

Variables

```
fn main() {  
    let x = 7;  
    x = 5;  
    println!("value:");  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
Command Prompt  
error[E0394]: cannot assign twice to immutable variable `x`  
--  
2 |     let x = 7;  
  |     ^ first assignment to `x`  
3 |     x = 5;  
  |     ^ cannot assign twice to immutable variable  
error: aborting due to previous error  
  
For more information about this error, try `rustc --explain E0394`  
C:\_RustCode>
```

Mutable Variables

Use `mut` keyword:

```
fn main() {  
    let mut x = 7;  
    x = 5;  
    println!("value: {}", x);  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- We get a warning, and it's sensible.
- We change the value of x before the initial value is ever read.
- Pointless.

```
Command Prompt  
C:\_RustCode>rustc main.rs  
warning: value assigned to `x` is never read  
--> main.rs:2:9  
    let mut x = 7;  
    ^^^^^  
  
= note: #[warn(unused_assignments)] on by default  
  
C:\_RustCode>main  
value: 5  
  
C:\_RustCode>
```


Constant/Global Variables

Rust still has them:

main.rs x

```
1 const BIN: u32 = 2;
2 fn main() {
3     const BASE: u32 = 10;
4     println!("Base: {}", BIN);
5     println!("Base: {}", BASE);
6 }
7
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Use **const** instead of **let**
- Always immutable
- Can be declared in global scope, unlike **let**
- Must indicate data type (u32)
- More on types coming up.

Constant/Global Variables

Can be declared in global scope, unlike `let`

```
main.rs x
1 const BIN: u32 = 2;
2 let x = 2;
3 fn main() {
4     println!("Base: {}", BIN);
5     println!("Base: {}", x);
6 }
7
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
Command Prompt
C:\_RustCode>rustc main.rs
error: expected item, found `let`
--> main.rs:2:1
2 | let x = 2;
  | ^ expected item
error: aborting due to previous error

C:\_RustCode>
```

Shadowing

Variables with the same name?

In Java, variables can have the same name so long as their scope does not overlap:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
int r = 10;
if (x >= 0) {
    double r = Math.sqrt(x);
}
```

BAD

```
if (x >= 0) {
    double r = Math.sqrt(x); }
else {
    float r = 0; }
```

OK

Shadowing

Variables with the same name?

C++ is less strict. Scopes
can overlap, but they
can't be identical:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
int r = 10;
if (x >= 0) {
    double r = sqrt(4.0);
}
```

OK

```
if (x >= 0) {
    double r = sqrt(4.0);
    float r = 0;
}
```

BAD

Shadowing

Variables with the same name?

```
main.rs x
1 fn main() {
2     let x = 3;
3     let x = x + 1;
4     let x = x * 2;
5     println!("x: {}", x);
6 }
7
```

```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
x: 8
C:\_RustCode>
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Shadowing

Variables with the same name?

```
main.rs x
1 fn main() {
2     let x = 3;
3     let x = x + 1;
4     let x = x * 2;
5     println!("x: {}", x);
6 }
7
```

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

- What we're doing here is like re-binding in Haskell or Elixir.
- This doesn't work with mutable variables.
- Think of this mathematically – We're simply saying let x = something else.

Shadowing VS `mut`

Why not just use shadowing? Why do we need `mut`?

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder



The image shows a code editor window with a file named `main.rs` containing the following Rust code:

```
1 fn main() {  
2     let mut x = 3;  
3     x = x + 1;  
4     x = 3.1415;  
5     println!("x: {}",  
6 }
```

Overlaid on the right is a Command Prompt window showing the output of `rustc main.rs`. It displays a type mismatch error:

```
C:\_RustCode>rustc main.rs  
error[E0308]: mismatched types  
--> main.rs:4:9  
4 |         x = 3.1415;  
  |         ^^^^^^ expected integral variable,  
  |         found floating-point variable  
= note: expected type `{integer}`  
       found type `{float}`
```

- Mutable variables are stuck with their type.
- Can't assign a value of a different type.

Shadowing VS `mut`

Why not just use shadowing? Why do we need `mut`?

```
main.rs x
1 fn main() {
2     let x = 3;
3     let x = x + 1;
4     let x = 3.1415;
5     println!("x: {}", x);
6 }
7
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
C:\_RustCode>rustc main.rs
warning: unused variable: `x`
--> main.rs:3:9
3 |     let x = x + 1;
  |         ^ help: consider using `_x` instead
= note: #[warn(unused_variables)] on by default
```

- With shadowing (rebinding) we can use different types.
- Again, we get a warning because we're rebinding before the original binding is ever used.

Shadowing VS `mut`

Why not just use shadowing? Why do we need `mut`?

- With `mut`, we're *mutating* a variable in memory.
- Storing a different value in the same variable.
- The name still refers to the same place, thus the **type must stay the same**.
- With shadowing, we're getting a new variable in memory each time.
- We're changing what a given name is referring to.
- We're not changing the existing value.

Data Types

Two subsets: Scalar and Compound

Reminder: Rust is statically typed. Must know all variable types at compile time.

Scalar types represent a single value:

- Rust has four: integers, floating-point, Booleans, characters.

Compound types group multiple values:

- Two primitive compound types: tuples and arrays.

Scalar Types: Integers

Length	Signed	Unsigned
8-bit	i8	u8
16-bit	i16	u16
32-bit	i32	u32
64-bit	i64	u64
arch	isize	usize

- Signed integers are stored using 2s comp
- Arch will be 32 bits on a 32 bit system, 64 bits on a 64 bit system.
- When not specified, Rust defaults to i32

Specify Type?

Rust has type inference, but we can be explicit:

```
main.rs x
1 fn main() {
2     let x: u8 = 3;
3     let y: i64 = 5;
4     let z: isize = 999;
5     println!("x: {}", x);
6     println!("y: {}", y);
7     println!("z: {}", z);
8 }
9
```

```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
x: 3
y: 5
z: 999
C:\_RustCode>
```

Integer Literals

In addition to just writing the value...

Number literals	Example
Decimal	98_222
Hex	0xff
Octal	0o77
Binary	0b1111_0000
Byte (u8 only)	<u>b'A'</u>

Bytes can be character literals

Notice the...

- This is a handy visual sugar
- Hard to count the zeroes in 1000000000. What number is this?
- Easy to see 1_000_000_000 is one billion.

```
main.rs x
1 fn main() {
2     let x = 1_000_000_000;
3     println!("x: {}", x);
4 }
5
```

Scalar Types: Floating Point

- Two kinds – 32 and 64 bit (float and double, single and double precision)
- Represented using standard IEEE-754

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat poweoder

Default




```
1 fn main() {  
2   let x: f32 = 1.0/3.0;  
3   let y: f64 = 1.0/3.0;  
4   println!("x: {}", x);  
5   println!("y: {}", y);  
6 }
```

Command Prompt

```
C:\_RustCode>rustc main.rs  
  
C:\_RustCode>main  
x: 0.33333334  
y: 0.3333333333333333  
  
C:\_RustCode>
```


Numeric Operations



The image shows a Rust IDE window with a file named `main.rs` and a terminal window. The code in `main.rs` is as follows:

```
1 fn main() {  
2     let r1 = 2 + 3;  
3     let r2 = 3/4;  
4     let r3 = 2 % 3.0;  
5     println!("r1:");  
6     println!("r2:");  
7     println!("r3:");  
8 }  
9
```

A red arrow points to line 4, `let r3 = 2 % 3.0;`. The terminal window shows the command `rustc main.rs` and the following error message:

```
error[E0277]: cannot mod `{integer}` by `{float}`  
  --> main.rs:4:16  
   |  
4  |         let r3 = 2 % 3.0;  
   |                     ^ no implementation for `{integer} % {float}`  
   = help: the trait `std::ops::Rem<float>` is not implemented for `{integer}`
```


Overlaid on the image is a red watermark that reads: "Assignment Project Exam Help", "https://powcoder.com", and "Add WeChat powcoder".

Numeric Operations

```
main.rs x
1 fn main() {
2     let r1 = 2 + 3 * 6;
3     let r2 = 3 / 4;
4     let r3 = 2 % 3;
5     println!("r1: {}", r1);
6     println!("r2: {}", r2);
7     println!("r3: {}", r3);
8 }
9
```

```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
r1: 20
r2: 0
r3: 2
C:\_RustCode>
```

Mixed Expressions?



The image shows a Rust code editor window with a file named `main.rs` and a Windows Command Prompt window. The code in `main.rs` is as follows:

```
1 fn main() {  
2     let r1 = 3/4;  
3     let r2 = 3/4.0;  
4     let r3: f64 = 3/4;  
5     println!("r1: {}", r1);  
6     println!("r2: {}", r2);  
7     println!("r3: {}", r3);  
8 }  
9
```

A red arrow points to line 3, `let r2 = 3/4.0;`. The Command Prompt window shows the output of `rustc main.rs`:

```
C:\RustCode>rustc main.rs  
error[E0277]: cannot divide `{integer}` by `{float}`  
--> main.rs:3:15  
3 |         let r2 = 3/4.0;  
  |                   ^ no implementation for `{integer}`  
    / `{float}`  
= help: the trait `std::ops::Div<{float}>` is not implemented for `{integer}`  
: mismatched types  
:4:19
```

Overlaid on the image is a red watermark that reads: "Assignment Project Exam Help", "https://powcoder.com", and "Add WeChat powcoder".

Rust doesn't mess around when it comes to implicit type conversion.

Mixed Expressions?

```
main.rs x
1 fn main() {
2   let r1: f64 = 3/4;
3   let r2 = 3 as f64;
4   println!("{}", r1);
5   println!("{}", r2);
6 }
7
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
Command Prompt
C:\_RustCode>rustc main.rs
error[E0308]: mismatched types
--> main.rs:2:19
   |
2  |   let r1: f64 = 3/4;
   |                 ^^^ expected f64, found
   |                 integral variable
   |
   = note: expected type `f64`
           found type `{integer}`

error: aborting due to previous error
```

Mixed Expressions?

```
main.rs x
1 fn main() {
2     //let r1: f64 = 3/4;
3     let r2 = 3 as f64/4 as f64;
4     //println!("{}", r1);
5     println!("r2: {}", r2);
6 }
7
```

Assignment Project Exam Help

Cast using: **as** *type*

<https://powcoder.com>

Add WeChat powcoder

- Comments same as Java/C/C++
- Both block and single-line

Command Prompt

```
C:\_RustCode>rustc main.rs
```


```
C:\_RustCode>main
r2: 0.75
```

```
C:\_RustCode>
```

Finally!

Mixed Expressions?

Division may truncate, good reason to avoid implicit conversion...



```
C:\_RustCode>rustc main.rs
error[E0277]: cannot add a float to an integer --> main.rs:2:16
  2 |     let r1 = 3 + 4.0;
    |               ^ no implementation for `{integer} + {float}`
   = help: the trait `std::ops::Add<{float}>` is not implemented for `{integer}`

error: aborting due to previous error

For more information about this error, run `rustc --explain E0277`.
C:\_RustCode>
```

```
main.rs
1 fn main() {
2     let r1 = 3 + 4.0;
3     println!("r1: {}", r1);
4 }
```

Why?!

- Adding `float` to `int` means converting the integer to a floating-point type, then adding.
- CPU doesn't add different types.
- Float and int arithmetic is done using different instructions, in different locations on CPU.
- It's possible to introduce errors in precision!
- An integer in binary is *exactly precise*.
- The same value represented as a floating point may lose significant digits.
- Most languages don't even warn about this – Rust doesn't allow it at all.

```
public class MethodTester
{
    public static void main(String[] args)
    {
        int a = 2111111111;
        System.out.println(a);


        float b = a;
        a = (int) b;

        System.out.println(a);
    }
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Scalar Types: Boolean

`true`, `false`. Easy:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
main.rs x
1 fn main() {
2     let b1 = true;
3     let b2: bool = false;
4     println!("b1: {}", b1);
5     println!("b2: {}", b2);
6 }
7
```

```
C:\_RustCode>rustc main.rs
C:\_RustCode>main
b1: true
b2: false
C:\_RustCode>
```

Scalar Types: Characters

Rust supports Unicode:

```
main.rs x
1 fn main() {
2     let c1 = 'Z';
3     let c2 = '\u{00C5}';
4     println!("c1: {}", c1);
5     println!("c2: {}", c2);
6 }
7
```

Command Prompt

```
C:\_RustCode>rustc main.rs
C:\_RustCode>main
c1: Z
c2: Å
C:\_RustCode>
```

Compound Types: Tuples

```
main.rs
1 fn main() {
2     let vals1 = (8, 3.14, '!');
3     let vals2: (i32, f64, char) = (8, 3.14, '!');
4 }
5
```

Tuples can be heterogeneous, and we need not specify type. Rust can infer it.

Accessing Elements

De-structuring!

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
main.rs x
1 fn main()
2 {
3     let tup = (42, 3.141592, '!');
4     let (x, y, z) = tup;
5
6     println!("{}", x, y, z);
7 }
8
```

Command Prompt

```
C:\_RustCode>rustc main.rs
```

```
C:\_RustCode>main
42, 3.141592, !
```

```
C:\_RustCode>
```

Accessing Elements

Can also access directly:

```
main.rs x
1 fn main()
2 {
3     let tup = (42, 3.141592, '!');
4     println!("{}", tup.0, tup.1, tup.2);
5 }
6
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Can we go out of bounds?

```
Command Prompt

C:\_RustCode>rustc main.rs

C:\_RustCode>main
42, 3.141592, !
```

Accessing Elements

Out of bounds:

```
main.rs x
1 fn main()
2 {
3     let tup = (42, 3.141592, '!');
4     println!("{}", tup.0);
5     println!("{}", tup.1);
6     println!("{}", tup.2);
7     println!("{}", tup.3);
8 }
9
```

```
Command Prompt
C:\_Rustcode>rustc main.rs
error[E0612]: attempted out-of-bounds tuple index `3` on type `({integer}, {float}, char)`
   --> main.rs:7:20
    |
7   |     println!("{}", tup.3);
    |                        ^^^^^
error: aborting due to previous error
```

Compile error in Rust

Accessing Elements

Can we fool it?

```
fn main()
{
    let x = 4;
    let tup = (1, 2, 3);

    println!("{}", tup.x);
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Command Prompt

C:_RustCode>rustc main.rs

error[E0609]: no field `x` on type `({integer}, teger}, {integer})`
--> main.rs:6:24

```
println!("{}", tup.x);
                  ^
```

error: aborting due to previous error

For more information about this error, try `rustc -explain E0609`.

C:_RustCode>

Nope.

Compound Types

Arrays

```
main.rs x
1 fn main()
2 {
3     let nums = [1, 2, 3, 4, 5];
4     println!("{}", nums[0], nums[1], nums[2], nums[3], nums[4]);
5
6 }
7
```

```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
1, 2, 3, 4, 5
C:\_RustCode>
```

Arrays in Rust are: homogeneous, zero-indexed, fixed in size.

Accessing Elements

Out of bounds:

```
main.rs x
1 fn main()
2 {
3     let nums = [1, 2, 3, 4, 5];
4     println!("{}", nums[5]);
5 }
6
```

```
Command Prompt
C:\_RustCode>main
thread 'main' panicked at 'index out of bounds: the len is 5 but the index is 5',
main.rs:4:20
note: run with `RUST_BACKTRACE=1` for a backtrace.

C:\_RustCode>
```

Runtime error, much like Java.
Prevents out of bounds array accesses.

Array of Tuples

Same rules as Haskell:

main.rs x

```
1 fn main()
2 {
3     let nums = [(1, 'a'), (2, 'b'), (3, 'c')];
4
5     println!("{}", {}, nums[0].0, nums[0].1);
6 }
7
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Command Prompt
C:_RustCode>rustc main.rs
C:_RustCode>main
1, a
C:_RustCode>

Array of Tuples

Same rules as Haskell: Tuple types must be the same

```
main.rs x
1 fn main()
2 {
3     let nums = [(1, 'a'), (2, 'b'), (3, 42)];
4
5
6 }
7
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
Command Prompt
C:\_RustCode>rustc main.rs
error[E0308]: mismatched types                --> main.rs:3:41
3 |     let nums = [(1, 'a'), (2, 'b'), (3, 42)];
  |                                     ^^ expected char, found u8
error: aborting due to previous error
```

Types & Literals: Summary

4 Scalar types:

Integer – u8, u16, u32, u64, usize, i8, i16, i32, i64, isize

Floating Point – f32, f64

Boolean – bool (true, false)

Character – Unicode: 'Z', 'a', '&', '\u{00C5}', etc

2 Compound types:

Tuple – heterogeneous

Arrays – homogeneous

Rust supports other data structures such as strings and vectors. These are not base types, but very useful.

Strings

```
main.rs x
1 fn main()
2 {
3     let word1 = "He\nllo";
4     let word2 = "Rust is fun\n";
5
6     println!("{}", word1);
7     println!("{}", word2);
8 }
9
```

```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
He
llo
Rust is fun
C:\_RustCode>
```

String literals and escape characters are as expected

FUNCTIONS

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Functions

We've seen `main()`

```
main.rs x
1 fn main()
2 {
3     like_main_but_not_as_good ();
4 }
5
6 fn like_main_but_not_as_good ()
7 {
8     println!("Hello World!");
9 }
10
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Returns nothing, accepts no arguments.
- Convention for naming functions is snake_case.
- Words separated by underscores.

Functions

```
main.rs x
1 fn main()
2 {
3     like_main_but_not_as_good ();
4 }
5
6 fn like_main_but_not_as_good ()
7 {
8     println!("Hello World!");
9 }
10
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
Hello World!
C:\_RustCode>
```

Unlike C/C++, Rust doesn't care about ordering

Parameters

identifier: **type**

- Parameters separated by commas.
- Indicating type is **mandatory**
- Nothing too unusual here

main.rs x

```
1 fn main()
2 {
3     print_val (5);
4     print_two_vals (5, 3.14);
5 }
6
7 fn print_val (n: i32)
8 {
9     println!("{}", n);
10 }
11
12 fn print_two_vals (n1: i32, n2: f64)
13 {
14     println!("{}", n1, n2);
15 }
```

Command Prompt

```
C:\_RustCode>rustc main.rs
```

```
C:\_RustCode>main
```

```
5
5, 3.14
```

```
C:\_RustCode>
```

Careful Now...

```
main.rs x
1 fn main()
2 {
3     print_val (5);
4     print_two_vals (5, 3);
5 }
6
7 fn print_val (n: i32)
8 {
9     println!("{}", n);
10 }
11
12 fn print_two_vals (n1: i32, n2: f64)
13 {
14     println!("{}", n1, n2);
15 }
16
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
Command Prompt
C:\_RustCode>rustc main.rs
error[E0308]: mismatched types
--> main.rs:4:24
4 |     print_two_vals (5, 3);
  |                        ^ expected f64,
  |                        found integral variable
= note: expected type `f64`
       found type `{integer}`
error: aborting due to previous error

For more information about this error, try
`rustc --explain E0308`.
```

Statements & Expressions

Rust is *primarily* expression based, but still has statements.

Two types of statements:

- Declaration statements return nothing
- Expression statements return empty tuple `()`

```
let x = 6; // This is a declaration statement
```

The above does not return a value. We can't do the following:

```
let y = (let x = 6);
```

Statements & Expressions

Rust is *primarily* expression based, but still has statements.

Two types of statements:

- Declaration statements return nothing
- Expression statements return empty tuple ()

`5 + 2; // This is an expression statement`

The above expression is evaluated, but the result is ignored (not saved).

`5 + 2` is an **expression**. It evaluates to 7.

`y = 5+2;` is an **expression statement**. It returns (), but the result of the nested expression `5+2` is saved to `y`

Statements & Expressions

```
let y = (let x = 6);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
main.rs x
1 fn main()
2 {
3     let x = (let y = 6);
4 }
```

```
Command Prompt
C:\RustCode>rustc main.rs
error: expected expression, found statement (`let`)
--> main.rs:3:14
3     let x = (let y = 6);
                  ^^^ expected expression
= note: variable declaration using `let` is a statement
error: aborting due to previous error
```

Statements & Expressions

```
public static void main(String[] args)
{
    int x, y;
    x = (y = 6);
}
```

OK

Assignment Project Exam Help

<https://powcoder.com>

Not OK... but what does this error mean?

Add WeChat powcoder

main.rs x

```
1 fn main()
2 {
3     let mut x: i32;
4     let mut y: i32;
5     x = (y = 8);
6 }
```

```
C:\_RustCode>rustc main.rs
error[E0308]: mismatched types
--> main.rs:5:9
5 |         x = y = 8;
  |         ^^^^^ expected i32, found ()
= note: expected type `i32`
       found type `()`
```


Statements & Expressions

```
main.rs x
1 fn main()
2 {
3     let mut x: i32;
4     let mut y: i32;
5     x = (y = 8);
6 }
7
```

```
Command Prompt
C:\_RustCode>rustc main.rs
error[E0308]: mismatched types
   --> main.rs:5:9
    |
5   |     x = y = 8;
    |           ^ expected i32, found ()
    = note: expected type `i32`
           found type `()`
error: aborting due to previous error
```

- Variable **y** gets re-assigned.
- The *expression statement* (**y=8**) returns an empty tuple in Rust.
- Can't assign an empty tuple to a variable declared to hold **i32**!

Statements & Expressions

```
fn main()
{
    let mut x = 5;
    let y = x = 3;
}
```

Assignment Project Exam Help

Here:

<https://powcoder.com>


Add WeChat powcoder

- Value of x will be 3
- Value of y will be () empty tuple

Statements & Expressions

`x + 6`

`// This is an expression`



Expression
statement


Assignment Project Exam Help

`// This is an expression statement`
`// containing an expression`

Add WeChat powcoder

Declaration
statement

In fact:



Scope Blocks as Expressions

Creating a new scope block?

We can do this in Java and C/C++, though again it isn't so common:

Assignment Project Exam Help

```
public static void main(String[] args)
{
    int x;
    {
        int y;
        y = 0;
    }
}
```

Add WeChat powcoder

Not a control structure or method, just a block of code with its own scope

Scope Blocks as Expressions

Scope blocks like this are expressions in Rust:

```
main.rs x Lab4.rs
1 fn main()
2 {
3     let x = 5;
4
5     let y = {
6         let z = 3;
7         z + 1
8     };
9
10    println!("{}", x, y);
11 }
12
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

There's a few things going on here:

- We're trying to bind a value to y.
- Thus, the block { } should evaluate to something.
- Notice there's no semicolon after `z + 1`
- `z + 1` is an expression.
- Adding a semi-colon would make it an *expression statement*.
- Thus, the block { } would return ().
- Probably not what we want.

Scope Blocks as Expressions

Scope blocks like this are expressions in Rust:

expression!

Assignment Project Exam Help

```
let y = { let x = 3; x + 1 } ;
```

<https://powcoder.com>

Add WeChat powcoder

The diagram illustrates the concept of a scope block as an expression in Rust. It shows the code `let y = { let x = 3; x + 1 } ;`. A green box highlights the scope block `{ let x = 3; x + 1 }`, with the word *expression!* written above it in green. A blue bracket underneath the entire line of code indicates that the whole thing is a declaration statement. Red text overlays include 'Assignment Project Exam Help', 'https://powcoder.com', and 'Add WeChat powcoder'.

This whole thing is a declaration statement

Scope Blocks as Expressions

Scope blocks like this are expressions in Rust:

```
main.rs x Lab4.rs
1 fn main()
2 {
3     let x = 5;
4
5     let y = {
6         let z = 3;
7         z + 1
8     };
9
10    println!("{}", x, y);
11 }
```

Command Prompt


```
C:\_RustCode>rustc main.rs
C:\_RustCode>main
5 4
C:\_RustCode>
```

Return Value

Think of functions the same way.
The last line should be an expression – no semi-colon.

Assignment Project Exam Help

```
main.rs x
1 fn main()
2 {
3     println!("{}", plus_five(8));
4 }
5
6 fn plus_five (n: i32) -> i32
7 {
8     n + 5
9 }
10
```



<https://powcoder.com>

Add WeChat powcoder


-> type

- Explicitly indicate return type
- Result of expression gets returned

```
Command Prompt
C:\_RustCode>rustc main.rs
C:\_RustCode>main
13
C:\_RustCode>
```


Return Value

Add semicolon? It becomes expression statement, returns (), type mismatch:



```
main.rs x
1 fn main()
2 {
3     println!("{}",
4 }
5
6 fn plus_five (n: i32)
7 {
8     n + 5;
9 }
10
```

```
Command Prompt
C:\_RustCode>rustc main.rs
error[E0308]: mismatched types
--> main.rs:7:1
7 | }
8 |     n + 5;
   - help: consider removing this semicolon
   ^ expected i32, found ()
= note: expected type `i32`
      found type `()`
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

Fantastic Rust Reference:

Assignment Project Exam Help

<https://doc.rust-lang.org/book/second-edition/>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

