

Linked List

Assignment Project Exam Help

<https://powcoder.com>

Juan Zhai

Add WeChat powcoder

juan.zhai@rutgers.edu

Java is Pass by Value

```
public static Node insert(Node front, int data){
    //front stores the address 2000 when main calls insert()
    Node node = new Node(data, front); //suppose node stores the address
2800
    front = node; /*front stores 2800 because this assignment copies the
                    address 2800 stored in node to front*/
    return front; //return front which stores the address 2800
}

public static void set(Node front, int data){
    front.data = data; /*front stores the address 2800, this assignment
                        updates the data field in the address 2800*/
}

public static void main(String[] args){
    Node head = new Node(3, null); //suppose head stores the address 2000
    head = insert(head, 6); /*before assignment, head stores the address
                            2000, after assignment, head stores the address 2800
                            so the list now has 6 and 3*/
    set(head, 5); /*head stores the address 2800, the info stored in 2800
                  is changed to 5, so the list now has 5 and 3*/
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Object-oriented programming

- When we insert/delete nodes from a linked list, we need to return *front* since the address stored in *front* may be updated. By returning *front*, the caller will know where to get the latest linked list.
- What if we want the method to return a boolean value to tell us whether the operation is successfully performed or not?
- We are manipulating the linked list that is pointed to by *front*, is it possible that all the operations share *front* to avoid sending *front* back and forth?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Object-oriented programming

- Object-oriented programming (OOP) is based on the concept of objects.
- Each object contains data (in the form of instance variables, known as *attributes* or *properties*), and operations (in the form of methods).
- A feature of objects is that an object's methods can access and modify the data fields of the object with which they are associated.
- Encapsulate a linked list object with *front* as its data and insertion/deletion operations as its methods.
→ unnecessary to pass *front* as a parameter any more

```
public class Point {
    public int x;
    public int y;
```

```
    public Point(int p, int q) {
        this.x = p;
        this.y = q;
    }
```

```
    public double distanceNonStatic(Point p) {
        return Math.sqrt(this.x * p.x + this.y * p.y);
    }
```

```
    public static double distanceStatic(Point p1, Point p2) {
        return Math.sqrt(p1.x * p2.x + p1.y * p2.y);
    }
```

```
    public static void main(String args) {
        Point p1 = new Point(0, 0);
        Point p2 = new Point(1, 1);
        double dis1 = p1.distanceNonStatic(p2);
        double dis2 = Point.distanceStatic(p1, p2);
        System.out.println(dis1 + " " + dis2);
    }
```

need object to call a non-static method

Use class name to call a static method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```

public Class Node{
    public String data;
    public Node link;
    public Node(int data,
                Node next){
        this.data = data;
        this.link = link;
    }
}

```

```

public Class LinkedList{
    Node front;
    public LinkedList(){
        front = null;
    }
    public void print(){
        Node ptr = front;
        while (ptr != null) {
            System.out.println(ptr.data);
            current = ptr.link;
        }
    }
    public void addFront(int data){
        Node node = new Node(data,
                               null);
        node.link = front;
        head = front;
    }
}

```

Encapsulate data

non-static methods

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```

public static void main(String[]
    args){
    LinkedList list = new
        LinkedList();
    list.addFront("Apple");
    list.addFront("Banana");
    list.addFront("Orange");
    list.print();
}

```

```
public static void main(String[] args){
    Node list = new Node(); //list points to the first node
    list = addFront(list, "Apple");
    list = addFront(list, "Banana");
```

} **static methods:** belong to Class, all objects have the same view, so just use class name to invoke static methods, no need to use objects: className.methodName(), className can be omitted if the method is called within the class.

```
public static void main(String[] args){
    LinkedList list = new LinkedList(); //list is an
    object with the instance variable head which points to
    the first node (encapsulate the data "head")
    list.addFront("Apple");
    list.insertFront("Banana");
```

} **non-static methods:** different objects have different views (different values for different instance variables), need to invoke a method on an object: obj.methodName()

head is an instance variable

1. *Non-static methods have access to head, so no need to pass head as a parameter*
2. *The modifications in the non-static methods are made to head and each object has access to its instance variable (head) , so no need to return head*

Generics

- Define IntNode for integers, define StringNode for strings, is there a general way applicable for all data types?
- Define a class to accept objects of some generic type
- By convention, we use ***T*** and it stands for “template”
- A generic class is said to be a template that can be concretized to contain objects of any particular type when the generic class itself is instantiated

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Generics

```
//T: generic type parameter
public class Node<T>{
    public T info;
    public Node link;
    ...
}

public class LinkedList<T>(){
    Node<T> head;
    ...
    public void addFront(T o) {...}
    public T get(int index) {...}
}

public class BookApp(){
    ...
    LinkedList<Book> list = new LinkedList<Book>();
    //instantiate the generic class
    list.addFront(New Book("Name", "author"))
    Book book = list.get(6);
    //the retrieved item is a Book object
    System.out.println(book.author);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Exceptions

```
public class LinkedList<T>(){
    Node<T> front;
    ...
    public T getFront() throws NoSuchElementException{
        if (front == null) {
            // throw new NoSuchElementException();
            throw new NoSuchElementException("empty ...");
        }
        return front.data;
    }
}
```

throws: declare an exception in method signature, meaning likely to throw

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

throw: throw an exception in method body explicitly. After executing throw statement, the control is given back to its caller (just like return), and the following statements will not be executed.

- Separate normal flow from error situations with exceptions
- When an error occurs, create an exception and throw it to launch an exceptional control flow

- Refer to Sakai code for Linked List with generics and exceptions

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Doubly linked list

- A doubly linked list is a linked list in which each node has previous link that points to the previous node in the linked list


Assignment Project Exam Help



Add WeChat powcoder

The previous link of the first node is null

```
public Class Node{  
    String data;  
    Node next;  
    Node prev;  
}
```



Insert after a specified node

```
public static void insertAfter(Node prevNode, String data) {
    //1. check whether the given previous node is null
    if(prevNode == null)
        throw new NullPointerException("Previous node is NULL.");
    //2. create a new node with the given data
    Node newNode = new Node(data);
    //3. make the new node's next point to the next node of prevNode
    newNode.next = prevNode.next;
    //4. make the previous node's next point to the new node
    prevNode.next = newNode;
    //5. make the new node's prev link point to the previous node
    newNode.prev = prevNode;
    //6. make the new node's next node's prev point to the new node
    if(newNode.next != null)
        newNode.next.prev = newNode;
}
```

Delete a specified node in the middle




Assignment Project Exam Help

```
ptr->next->prev = ptr->prev;
```


```
ptr->prev->next = ptr->next;
```

<https://powcoder.com>

Add WeChat powcoder



Circular Linked List




Assignment Project Exam Help

- A circular linked list is a linked list in which the last node refers back to the first node
- All the nodes are connected to form a circle
- There is no NULL at the end
- By keeping a pointer to the last entry, we have access to the first and last entry both in constant time.
 - Last: rear
 - First: rear.link

Search target


```
public boolean search(String target) {  
    if(rear == null)  
        return false;  
    Node ptr = rear.next;  
    while(ptr != rear){  
        if(ptr.data == target)  
            return true;  
        ptr = ptr.next;  
    }  
    return rear.data == target;  
}
```



- Search from the first node.
- If there is only one node in the list, then rear.next is rear.
No iterations are performed. Comparison is done at last line.

Search target

```
public boolean search(String target) {  
    if(rear == null)  
        return false;  
    Node ptr = rear;  
    do {  
        if(ptr.data == target)  
            return true;  
        ptr = ptr.next;  
    } while(ptr != rear)  
    return false;  
}
```



- Compare the last node and then search from the first node.
- If there is only one node in the list, then rear.next is rear.
One iteration is done to perform the comparison.


Add Front

```
public void AddFront(String data) {  
    Node node = new Node(data, null);  
    if(rear == null){        // no node, an empty list  
        rear = node;  
        rear.next = rear;  
    }  
    else{  
        node.next = rear.next;  
        rear.next = node;  
    }  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Delete Front

```
public int deleteFront() throws NoSuchElementException{
    if(rear == null)        // no node, an empty list
        throw new NoSuchElementException();
    int tmp = rear.next.data;
    if(rear == rear.next)    // only one node
        rear = null;
    else
        rear.next = rear.next.next; // at least two nodes
    return tmp;
}
```

