

CS 320 :
Assignment Project Exam Help
Functions
<https://powcoder.com>

Add WeChat powcoder

Marco Gaboardi


MSC 116

gaboardi@bu.edu

Announcements

- Interpreter part 3 due Sunday
(last programming assignment) **Assignment Project Exam Help**
- Last Theory Assignment due the 10th
(deadline extension) **<https://powcoder.com>**
Add WeChat powcoder

Parsing and semantic analysis



Today plan

- More on Functions

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Terminology




Language for basic stack manipulations with local variables definitions and functions

```
...  
<com> ::= push <const> | add | sub | mul | div  
        | neg | rem | swap | let | end | bind  
        | fun <name> <args> <body> | return | call
```

Add WeChat powcoder

Language for basic stack manipulations with local variables definitions and functions



Language for basic stack manipulations with local variables definitions and functions

Assignment Project Exam Help

<https://powcoder.com>

funEnd

Add WeChat powcoder

Keyword to mark
where a function
declaration ends.

Language for basic stack manipulations with local variables definitions and functions

Assignment Project Exam Help

<https://powcoder.com>

return

Add WeChat powcoder

Keyword to mark when
a function needs to
return a value.

Language for basic stack manipulations with local variables definitions and functions

Assignment Project Exam Help


<https://powcoder.com>

call

Add WeChat powcoder

Keyword to mark when
a function needs to be
called.

Language for basic stack manipulations with local variables definitions and functions



What are the design considerations for functions?

Assignment Project Exam Help

<https://powcoder.com>

We need to think about:

- parameter passing
- parameters returning
- variables: local vs global
- scope of variables
- nesting of subprograms
- referencing environment

Add WeChat powcoder

Parameter Passing

Parameter passing methods are ways in which parameters are transmitted to and from sub programs.


- Semantic Models of Parameter Passing
- Implementation Models for these semantic models

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Semantic Modes of Parameter Passing



How to transfer a value

- We have different ways to provide access to a value to a subprogram
 - Physically move a value
 - An access path is transmitted (e.g. pointer or reference)
- These are orthogonal to the mode of the parameters

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

TopHat Q15-Q18

Add WeChat powcoder


Implementation Models

Techniques used for parameter passing :

- Call by Value (In mode) Assignment Project Exam Help
- Call by Result (Out mode) <https://powcoder.com>
- Call by Value-Result (In-out mode) Add WeChat powcoder
- Call by Reference (In-out mode)

Pass-by-Value (In Mode)

- The **value** of the actual parameter is used to initialize the corresponding formal parameter
- Normally implemented by copying
- Can be implemented by transmitting an access path but then one needs to enforce write protection.




Pass-by-Result (Out Mode)

- When a parameter is passed by result, no value is transmitted to the subprogram;
 - the corresponding formal parameter acts as a local variable;
 - its value is transmitted to caller's actual parameter when control is returned to the caller, by physical move



Pass-by-Value-Result (inout Mode)

- A combination of pass-by-value and pass-by-result
- Actual values are copied in both directions.
- Formal parameters have local storage




Pass-by-Reference (Inout Mode)

- Pass an access path to the value
- Passing process is efficient (no copying and no duplicated storage)
- Slower accesses (compared to pass-by-value) to formal parameters
- Potentials for unwanted side effects (collisions)
- Unwanted **aliases** (access broadened)

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder



Pass-by-Name (Inout Mode)

- By **textual** substitution
- Formal parameters are bound to an access method at the time of the call, but actual binding to a value or address takes place at the time of a reference or assignment



Implementing Parameter-Passing Methods


- In most languages parameter communication takes place through the run-time stack (more in the future)
- **Pass-by-value** parameters have their values copied into stack locations. <https://powcoder.com>
- **Pass-by-reference** are the simplest to implement; only an address is placed in the stack
- In **Pass-by-result** the caller reads from the stack the final value of the parameter before the stack of the callee is disposed

Implementing Parameter-Passing Methods

Function header: `void sub(int a, int b, int c, int d)`

Function call: `sub(w, x, y, z)`

(pass `w` by value, `x` by result, `y` by value-result, `z` by reference)



Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Let assume that “simple” subprograms cannot be nested and that have only static local variables.

How a subprogram is executed? How can we implement the call-return procedure?

Function call

Call Semantics:

- Save the execution status of the caller
- In mode and inout mode parameters must be provided
- Pass the return address to the called subprogram
- Transfer control to the called subprogram

Function return

Return Semantics:

- If pass-by-value-result or out mode parameters are used, move the current values of those parameters to their corresponding actual parameters
- Restore the execution status of the caller
- Transfer control back to the caller


Activation Records for Simple Functions

- We need to store some information to guarantee the correct execution of the subprogram. This constitutes the **activation record** of the subprogram.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Activation Records for Simple Functions

- We need to store some information to guarantee the correct execution of the subprogram. This constitutes the **activation record** of the subprogram.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Variables which are locally defined by the subprogram


Activation Records for Simple Functions

- We need to store some information to guarantee the correct execution of the subprogram. This constitutes the **activation record** of the subprogram.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



The actual
parameters passed
to the subprogram


Activation Records for Simple Functions

- We need to store some information to guarantee the correct execution of the subprogram. This constitutes the **activation record** of the subprogram.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Information we need to store

- An activation record instance is a concrete example of an activation record (the collection of data for a particular subprogram activation)
- The activation record contains the non-code information that we need for the execution of the program.

Implementing Simple Functions: Activation Record

- The activation record format is static
- An activation record instance is dynamically created when a subprogram is called
- An activation record instance is dynamically deallocated when a subprogram returns
- Activation record instances reside on the run-time stack

For each activation record instance we need to maintain an **Environment Pointer (EP)** pointing at the base of the instance and used to deallocating it.

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example: Activation Records stack for Simple Functions


```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

call to sub3()



Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Sub3

Local Variables
Parameters
Return Address

call to sub3()




Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Sub3

Local Variables
Parameters
Return Address

call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Sub3



Local Variables
Parameters
Return Address

call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

Sub2

Sub3



call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Sub2

Sub3

Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Sub2

Sub3

Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

call to sub3()


Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Sub1


Sub2

Sub3

call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

Sub1

Sub2

Sub3

call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder



Sub1

Sub2

Sub3

Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

Sub1

Sub2

Sub3

call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Sub2

Sub3

Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

call to sub3()


Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Sub2

Sub3

Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Local Variables
Parameters
Return Address
Local Variables
Parameters
Return Address

Sub3



call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Sub3

Local Variables
Parameters
Return Address



call to sub3()

Example: Activation Records stack for Simple Functions

```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Sub3

Local Variables
Parameters
Return Address

call to sub3()



Example: Activation Records stack for Simple Functions


```
function sub1 (...) {  
...  
};  
function sub2 (...) {  
...  
Sub1 (...)  
};  
function sub3 (...) {  
...  
Sub2 (...)  
};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

call to sub3()



Assignment Project Exam Help

<https://powcoder.com>

TopHat Q6-Q10

Add WeChat powcoder

Local variables

- Variables whose scope is usually the body of the subprogram in which they are defined
- They can be static or stack-dynamic
- A subprogram can use variables that are heap-dynamic but these usually do not count as local.

Local variables

```
let plus2 = fun x ->  
    let y = 2 in x + y
```

<https://powcoder.com>

Add WeChat powcoder

Here y is a local
variable to the function
plus2

Local variables?

What is the
value of `y` here?

Assignment Project Exam Help

<https://powcoder.com>

```
let y = 2 in  
let plus2 = fun x-> x + y in plus2 (plus2 4)
```

How about `y` here?
Is it local?

And here?

Local variables?

```
input
push x
push 3
bind
  fun addX arg
  push x
  push arg
  add
  return
  funEnd
push x
push 5
bind
push a
push 3
bind
push addX
push a
call
quit
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

What is the
value of x here?

Assignment Project Exam Help

<https://powcoder.com>

Subprograms with stack-dynamic variables

Add WeChat powcoder

Implementing Subprograms with Stack-Dynamic Local Variables: Activation Record

- The activation record format is static, but its size may be dynamic to deal with stack dynamic variables.
- We need a [dynamic link](https://powcoder.com) pointing to the base of the instance of the activation record of the caller – this will help us deallocate the activation record instance when it has dynamic size.
- The collection of dynamic links in the stack at a given time is called the [dynamic chain](#), or [call chain](#)


Function Calls for General Programs

- General semantics of calls to a subprogram
 - In mode and inout mode **parameters** must be provided **Assignment Project Exam Help**
 - **Stack-dynamic allocation of local variables** **https://powcoder.com**
 - **Save the execution status** of the calling program **Add WeChat powcoder**
 - **Transfer of control** to the subprogram and arrange for the return
 - If subprogram nesting is supported, access to nonlocal variables must be arranged through **a static link (we will see this next time).**

Function Returns for General Programs

- General semantics of subprogram returns:
 - Out mode and inout mode parameters must have their values returned
 - Deallocation of stack-dynamic local variables
 - Restore the execution status
 - Return control to the caller

Typical Activation Record for a Language with Stack-Dynamic Local Variables



Example in C

```
void sub(float total, int part)
{
    int list[5];
    float sum;
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Local Variable	sum
Local Variable	list[4]
Local Variable	list[3]
Local Variable	list[2]
Local Variable	list[1]
Local Variable	list[0]
Parameter	part
Parameter	total
Dynamic Link	
Return Address	

Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



main

Local Variable

p


Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




main

Local Variable

p

Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

fun1

main

Local Variable	t
Local Variable	s
Parameter	r
Dynamic Link	
Return to main	
Local Variable	p

Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

fun1

main

Local Variable	t
Local Variable	s
Parameter	r
Dynamic Link	
Return to main	
Local Variable	p


Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x)
{
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder



Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```





Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

fun1

main

Local Variable	t
Local Variable	s
Parameter	r
Dynamic Link	
Return to main	
Local Variable	p


Example

```
void fun1(float r)
{
    int s, t;
    ...
    fun2(s);
    ...
}
void fun2(int x) {
    int y;
    ...
    fun3(y);
    ...
}
void fun3(int q) {
    ...
}
void main() {
    float p;
    ...
    fun1(p);
    ...
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



main

Local Variable

p

Assignment Project Exam Help

<https://powcoder.com>

TopHat Q11-Q12

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Passing functions as arguments

Add WeChat powcoder

Local variables when passing a function?

What is the value of `y` here?

Assignment Project Exam Help

<https://powcoder.com>

```
let y = 2 in  
let plus2 = fun x-> x + y in plus2 (plus2 4)
```

How about `y` here?
Is it local?

And here?

Local variables?

```
input
push x
push 3
bind
  fun addX arg
  push x
  push arg
  add
  return
  funEnd
push x
push 5
bind
push a
push 3
bind
push addX
push a
call
quit
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

What is the
value of x here?

Closures

- A **closure** is a pair consisting of the **function code p** and its **referencing environment m**:

(p, m)
Assignment Project Exam Help

- It is similar to a configuration but where **p** is the code of a function.
- The **referencing environment** is needed to provide values to the variables when the function (subprogram) can be called from an arbitrary place in the program
- Closures are needed if a (function (subprogram) can **access variables in nesting scopes** and it can be called from anywhere
- A static-scope language that does not permit nested subprograms doesn't need closures

Example of closure

```
let y = 2 in  
let plus2 = fun x -> x + y in plus2 (plus2 4)
```

<https://powcoder.com>

What is the closure that
will be created here?

(fun x -> x + y / y=2)

Local variables?

input
push x push 3 bind <div><div>fun addX arg push x push arg add return funEnd</div><div>Assignment Project Exam Help https://powcoder.com Add WeChat powcoder</div></div> push x push 5 bind push a push 3 bind push addX push a call quit

What is the closure that will be created here?

(fun arg -> push x; push arg; add; return / x=3)

Closures vs Scope

```
let y = 2 in  
let plus2 = fun x -> x + 2 in plus2 (plus2 4)
```

<https://powcoder.com>

We said that we need a closure to find the value of y.

Add WeChat powcoder

```
(fun x -> x + y in plus2 (plus2 4) / y=2)
```

What are we assuming
here about the scope
of y?

Tips for interpreter part 3: Language for basic stack manipulations with local variables definitions and functions

- Since in our interpreter we want to pass functions as arguments to other functions, when you encounter a function declaration you should construct a **closure**:

- 1) the **name** of the function
- 2) the **name** of the formal parameter
- 3) the **code** in the function body
- 4) the current **environment**

(Notice that 3 and 4 constitute the function code.)

```
type value = ...  
| CLOSURE of (name * name * (command list) * (name*value)list)
```

Tips for interpreter part 3: Language for basic stack manipulations with local variables definitions and functions

How do we call a function?

```
push fun_name  
push arg  
call
```

1. Check if `fun_name` is bound to a closure.
2. Check if `arg` is a value or a name bound to a value (including closures for functions).
3. If both yes, then we can execute the body of the function – otherwise error.
4. We have to execute it in the environment we have in the closure with an additional binding between the formal parameter and the value of the actual (`arg`).
5. We also need to execute it using a new stack

Tips for interpreter part 3: Language for basic stack manipulations with local variables definitions and functions

Preparing for function evaluation (step 4)

```
push fun_name  
push arg  
call
```

We have to execute the code in the environment we have in the closure with an additional binding between the formal parameter and the value of the actual (arg).

Add WeChat powcoder
We have to use the environment in the closure.

Tips for interpreter part 3: Language for basic stack manipulations with local variables definitions and functions

What to do when the function terminates?



Assignment Project Exam Help

1. Restore the previous environment
<https://powcoder.com>
2. ~~Add WeChat powcoder~~ Restore the previous stack
3. Push on the restored stack the last element on the function stack
4. Resume the execution from after the call instruction

Tips for interpreter part 3: Language for basic stack manipulations with local variables definitions and functions

What to do when the function terminates with a return?

Assignment Project Exam Help

```
...  
...  
return
```

1. Immediately stop the execution
<https://powcoder.com>
2. Restore the previous environment
Add WeChat powcoder
3. Restore the previous stack
4. Push on the restored stack the last element on the function stack
5. Resume the execution from after the call instruction