

Assignment Project Exam Help

Announcements

Reminder: Midterm out on Thursday will be available on Blackboard (must be done by Friday)


90 minutes, must be completed after you start. Closed book.

Have scratch paper ready, some problems ask you to write out steps/show your work that can be shown on the scratch paper. Make sure to identify the problems you are showing your work for. **Upload the scratch paper on the midterm form found on piazza right after you complete your test or it won't be counted!**

- ps4 self-grading form out, due 10/30
- Lab this week – midterm review

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

Probabilistic Generative Models

<https://powcoder.com>

Add WeChat powcoder

CS 542 Machine Learning

Assignment Project Exam Help Today

Add WeChat powcoder

- Probabilistic classification


- Linear Discriminant Analysis

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Probabilistic Classification



- Can model output value directly, but having a probability is often more useful
- **Bayes classifier**: minimizes the probability of misclassification
$$y = \underset{k}{\operatorname{argmax}} p(Y = k | X = x)$$
- Want to model conditional distribution, $p(Y = y | X = x)$, then assign label based on it

Assignment Project Exam Help

Two approaches to classification

Add WeChat powcoder

- **Discriminative**: represent $p(Y|X)$ as function of parameters θ , then learn θ from training data

Assignment Project Exam Help

- **Generative**: use <https://powcoder.com> Bayes Rule to write


Add WeChat powcoder

$$P(Y = k | X = x) = \frac{P(X = x | Y = k)P(Y = k)}{P(X = x)}$$

then learn parameters of **class-conditional density** $p(X|Y)$
and **class prior** $p(Y)$ --- ignore $p(X)$

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

Generative vs Discriminative

<https://powcoder.com>

Add WeChat powcoder

Intuition

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Cookie Robots

- Suppose you own a cookie factory
- Want to detect bad cookies and discard them

Assignment Project Exam Help

Cookie Robots

Add WeChat powcoder

$P(X|Y), P(Y)$



$P(Y|X)$

“The Chef”

- Can make good and bad cookies
- Compares new cookie to those
- Decides if it is good or bad

“The Critic”

- Cannot make cookies
- Has seen lots of good and bad cookies
- Decides if it is good or bad



Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder

Generative vs Discriminative

Add WeChat powcoder

$P(X|Y), P(Y)$

$P(Y|X)$




- **Generative**: model the class-conditional distribution of features, e.g. LDA, Naïve Bayes
- **Discriminative**: model the decision boundary directly, e.g. Logistic Regression, SVM

Can sample from distribution

Cannot sample from distribution

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

Linear Discriminant Analysis Derivation

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Bayes Classifier

Add WeChat powcoder

Find an estimate $P(Y | X)$. Then, given an input x_0 , we predict the output as in a Bayes classifier:

<https://powcoder.com>

$$y_0 = \underset{y}{\operatorname{argmax}} P(Y = y_0 | X = x_0).$$

Assignment Project Exam Help

Generative Classifier
Add WeChat powcoder

Instead of estimating $P(Y / X)$, we will estimate:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Generative Classifier
Add WeChat powcoder

Instead of estimating $P(Y | X)$, we will estimate:

1. $P(X | Y)$: Given the category, what is the distribution of the inputs.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Generative Classifier
Add WeChat powcoder

Instead of estimating $P(Y | X)$, we will estimate:

1. $P(X | Y)$: Given the category, what is the distribution of the inputs.
2. $P(Y)$: How likely are each of the categories.

Add WeChat powcoder

Assignment Project Exam Help

Generative Classifier
Add WeChat powcoder

Instead of estimating $P(Y | X)$, we will estimate:

1. $P(X | Y)$: Given the category, what is the distribution of the inputs.
2. $P(Y)$: How likely are each of the categories.

Then, we use *Bayes rule* to obtain the estimate:

$$P(Y = k | X = x) = \frac{P(X = x | Y = k)P(Y = k)}{P(X = x)}$$

Assignment Project Exam Help

Generative Classifier
Add WeChat powcoder

Instead of estimating $P(Y | X)$, we will estimate:

1. $P(X | Y)$: Given the category, what is the distribution of the inputs.
2. $P(Y)$: How likely are each of the categories.

Then, we use *Bayes rule* to obtain the estimate:

$$P(Y = k | X = x) = \frac{P(X = x | Y = k)P(Y = k)}{\sum_j P(X = x | Y = j)P(Y = j)}$$


Assignment Project Exam Help Linear Discriminant Analysis (LDA)

Add WeChat powcoder

Instead of estimating $P(Y | X)$, we will estimate:

1. We model $P(X = x | Y = k) = f_k(x)$ as a *Multivariate Normal Distribution*:

Assignment Project Exam Help



2. $P(Y = k) = \pi_k$ is estimated by the fraction of training samples of class k .

Assignment Project Exam Help
LDA prior and class-conditional density
Add WeChat powcoder

Suppose that:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA prior and class-conditional density

Add WeChat powcoder

Suppose that:

- ▶ We know $P(Y = k) = \pi_k$ exactly.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA prior and class-conditional density

Add WeChat powcoder

Suppose that:

- ▶ We know $P(Y = k) = \pi_k$ exactly.
- ▶ $P(X = x|Y = k)$ is Multivariate Normal with density:

<https://powcoder.com>

$$f_k(x) = \frac{1}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Add WeChat powcoder

Assignment Project Exam Help

LDA prior and class-conditional density

Add WeChat powcoder

Suppose that:

- ▶ We know $P(Y = k) = \pi_k$ exactly.
- ▶ $P(X = x|Y = k)$ is Multivariate Normal with density:

<https://powcoder.com>

$$f_k(x) = \frac{1}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Add WeChat powcoder

μ_k : Mean of the inputs for category k .

Σ : Covariance matrix (common to all categories).

Assignment Project Exam Help

LDA prior and class-conditional density

Add WeChat powcoder

Suppose that:

- ▶ We know $P(Y = k) = \pi_k$ exactly.
- ▶ $P(X = x|Y = k)$ is Multivariate Normal with density:

<https://powcoder.com>

$$f_k(x) = \frac{1}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$


Add WeChat powcoder

μ_k : Mean of the inputs for category k .

Σ : Covariance matrix (common to all categories).

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

LDA Solution

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

By Bayes rule, the probability of category k , given the input x is:

$$P(Y = k | X = x) = \frac{f_k(x)\pi_k}{P(X = x)}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

By Bayes rule, the probability of category k , given the input x is:

$$P(Y = k | X = x) = \frac{f_k(x)\pi_k}{P(X = x)}$$

Assignment Project Exam Help

The denominator does not depend on the output k , so we can write it as a constant:

<https://powcoder.com>

$$P(Y = k | X = x) = C \times f_k(x)\pi_k$$

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

By Bayes rule, the probability of category k , given the input x is:

$$P(Y = k | X = x) = \frac{f_k(x)\pi_k}{P(X = x)}$$

Assignment Project Exam Help

The denominator does not depend on the output k , so we can write it as a constant:

<https://powcoder.com>

$$P(Y = k | X = x) = C \times f_k(x)\pi_k$$

Add WeChat powcoder

Now, expanding $f_k(x)$:

$$P(Y = k | X = x) = \frac{C\pi_k}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x-\mu_k)^T \Sigma^{-1} (x-\mu_k)}$$

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

$$P(Y = k | X = x) = \frac{C \pi_k}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

$$P(Y = k | X = x) = \frac{C \pi_k}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Now, let us absorb everything that does not depend on k into a constant C' :

$$P(Y = k | X = x) = C' \pi_k e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

$$P(Y = k | X = x) = \frac{C \pi_k}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Now, let us absorb everything that does not depend on k into a constant C' :

$$P(Y = k | X = x) = C' \pi_k e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Add WeChat powcoder

and take the logarithm of both sides:

$$\log P(Y = k | X = x) = \log C' + \log \pi_k - \frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k).$$

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

$$P(Y = k | X = x) = \frac{C \pi_k}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Now, let us absorb everything that does not depend on k into a constant C' :

$$P(Y = k | X = x) = C' \pi_k e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Add WeChat powcoder

and take the logarithm of both sides:

$$\log P(Y = k | X = x) = \log C' + \log \pi_k - \frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k).$$

This is the same for every category, k .

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

$$P(Y = k | X = x) = \frac{C \pi_k}{(2\pi)^{p/2} |\Sigma|^{1/2}} e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Now, let us absorb everything that does not depend on k into a constant C' :

$$P(Y = k | X = x) = C' \pi_k e^{-\frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k)}$$

Add WeChat powcoder

and take the logarithm of both sides:

$$\log P(Y = k | X = x) = \log C' + \log \pi_k - \frac{1}{2}(x - \mu_k)^T \Sigma^{-1} (x - \mu_k).$$

This is the same for every category, k .

So we want to find the maximum of this over k .

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

Goal, maximize the following over k :

$$\log \pi_k - \frac{1}{2}(x - \mu_k)^T \Sigma^{-1}(x - \mu_k).$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

Goal, maximize the following over k :

$$\log \pi_k - \frac{1}{2}(x - \mu_k)^T \Sigma^{-1}(x - \mu_k).$$
$$= \log \pi_k - \frac{1}{2} [x^T \Sigma^{-1} x + \mu_k^T \Sigma^{-1} \mu_k] + x^T \Sigma^{-1} \mu_k$$

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

Goal, maximize the following over k :

$$\begin{aligned} & \log \pi_k - \frac{1}{2}(x - \mu_k)^T \Sigma^{-1}(x - \mu_k). \\ &= \log \pi_k - \frac{1}{2} [x^T \Sigma^{-1} x + \mu_k^T \Sigma^{-1} \mu_k] + x^T \Sigma^{-1} \mu_k \\ &= C// + \log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k \end{aligned}$$

<https://powcoder.com>
Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

Goal, maximize the following over k :

$$\begin{aligned} & \log \pi_k - \frac{1}{2}(x - \mu_k)^T \Sigma^{-1}(x - \mu_k). \\ &= \log \pi_k - \frac{1}{2} [x^T \Sigma^{-1} x + \mu_k^T \Sigma^{-1} \mu_k] + x^T \Sigma^{-1} \mu_k \\ &= C// + \log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

We define the objective:

$$\delta_k(x) = \log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k$$

At an input x , we predict the output with the highest $\delta_k(x)$.

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

What is the decision boundary? It is the set of points in which 2 classes do just as well:

$$\delta_k(x) = \delta_l(x)$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

What is the decision boundary? It is the set of points in which 2 classes do just as well:

$$\delta_k(x) = \delta_l(x)$$

$$\log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k = \log \pi_l - \frac{1}{2} \mu_l^T \Sigma^{-1} \mu_l + x^T \Sigma^{-1} \mu_l$$

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA has linear decision boundaries

Add WeChat powcoder

What is the decision boundary? It is the set of points in which 2 classes do just as well:



$$\delta_k(x) = \delta_l(x)$$

$$\log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k = \log \pi_l - \frac{1}{2} \mu_l^T \Sigma^{-1} \mu_l + x^T \Sigma^{-1} \mu_l$$

<https://powcoder.com>

This is a linear equation in x .

Add WeChat powcoder



Assignment Project Exam Help

Estimating π_k

Add WeChat powcoder

$$\pi_k = \frac{\#\{i : y_i = k\}}{n}$$

Assignment Project Exam Help
In English, the fraction of training samples of class k .

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Estimating the parameters of $f_k(x)$

Add WeChat powcoder

Estimate the center of each class μ_k :

$$\mu_k = \frac{1}{\# \{i; y_i = k\}} \sum_{i; y_i = k} x_i$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Estimating the parameters of $f_k(x)$

Add WeChat powcoder

Estimate the center of each class μ_k :

$$\mu_k = \frac{1}{\# \{i; y_i = k\}} \sum_{i; y_i = k} x_i$$

Assignment Project Exam Help

Estimate the common covariance matrix Σ :

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Estimating the parameters of $f_k(x)$

Add WeChat powcoder

Estimate the center of each class μ_k :

$$\mu_k = \frac{1}{\# \{i; y_i = k\}} \sum_{i; y_i = k} x_i$$

Assignment Project Exam Help

Estimate the common covariance matrix Σ :

<https://powcoder.com>

- One dimension ($p = 1$):

Add WeChat powcoder

$$\sigma^2 = \frac{1}{n - K} \sum_{k=1}^K \sum_{i; y_i = k} (x_i - \mu_k)^2$$

Assignment Project Exam Help

Estimating the parameters of $f_k(x)$

Add WeChat powcoder

Estimate the center of each class μ_k :

$$\mu_k = \frac{1}{\# \{i; y_i = k\}} \sum_{i; y_i = k} x_i$$

Assignment Project Exam Help

Estimate the common covariance matrix Σ :

<https://powcoder.com>

- One dimension ($p = 1$):

Add WeChat powcoder

$$\sigma^2 = \frac{1}{n - K} \sum_{k=1}^K \sum_{i; y_i = k} (x_i - \mu_k)^2$$

- Many dimensions ($p > 1$): Compute the vectors of deviations $(x_1 - \mu_{y_1}), (x_2 - \mu_{y_2}), \dots, (x_n - \mu_{y_n})$ and use an estimate of its covariance matrix, Σ .

Assignment Project Exam Help

LDA prediction

Add WeChat powcoder

For an input x , predict the class with the largest:

$$\delta_k(x) = \log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LDA prediction

Add WeChat powcoder

For an input x , predict the class with the largest:

$$\delta_k(x) = \log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k$$

The decision boundaries are defined by:

Assignment Project Exam Help

$$\log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k = \log \pi_l - \frac{1}{2} \mu_l^T \Sigma^{-1} \mu_l + x^T \Sigma^{-1} \mu_l$$

Add WeChat powcoder

Assignment Project Exam Help

LDA prediction

Add WeChat powcoder

For an input x , predict the class with the largest:



$$\delta_k(x) = \log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k$$

The decision boundaries are defined by:

$$\log \pi_k - \frac{1}{2} \mu_k^T \Sigma^{-1} \mu_k + x^T \Sigma^{-1} \mu_k = \log \pi_l - \frac{1}{2} \mu_l^T \Sigma^{-1} \mu_l + x^T \Sigma^{-1} \mu_l$$

Add WeChat powcoder


Solid lines in.



Assignment Project Exam Help Quadratic discriminant analysis (QDA)

Add WeChat powcoder

The assumption that the inputs of every class have the same covariance Σ can be quite restrictive:



Assignment Project Exam Help

Quadratic discriminant analysis (QDA)

Add WeChat powcoder

In **quadratic discriminant analysis** we estimate a mean μ_k and a covariance matrix Σ_k for each class separately.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Quadratic discriminant analysis (QDA)

Add WeChat powcoder

In **quadratic discriminant analysis** we estimate a mean μ_k and a covariance matrix Σ_k for each class separately.

Assignment Project Exam Help

Given an input, it is easy to derive an objective function:

<https://powcoder.com>

$$\delta_k(x) = \log \pi_k - \frac{1}{2} \mu_k^T \Sigma_k^{-1} \mu_k + x^T \Sigma_k^{-1} \mu_k - \frac{1}{2} x^T \Sigma_k^{-1} x - \frac{1}{2} \log |\Sigma_k|$$

Add WeChat powcoder

Assignment Project Exam Help

Quadratic discriminant analysis (QDA)

Add WeChat powcoder

In **quadratic discriminant analysis** we estimate a mean μ_k and a covariance matrix Σ_k for each class separately.

Assignment Project Exam Help

Given an input, it is easy to derive an objective function:

<https://powcoder.com>

$$\delta_k(x) = \log \pi_k - \frac{1}{2} \mu_k^T \Sigma_k^{-1} \mu_k + x^T \Sigma_k^{-1} \mu_k - \frac{1}{2} x^T \Sigma_k^{-1} x - \frac{1}{2} \log |\Sigma_k|$$

Add WeChat powcoder


This objective is now quadratic in x and so are the decision boundaries.

Assignment Project Exam Help Quadratic discriminant analysis (QDA)

Add WeChat powcoder


- ▶ Bayes boundary (---)
- ▶ LDA (.....)
- ▶ QDA (—).

Assignment Project Exam Help



Assignment Project Exam Help

Add WeChat powcoder



Linear Discriminant Analysis

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

More intuition

Assignment Project Exam Help

Illustration of Decision Boundary

Add WeChat powcoder


$$\log \frac{\pi_k}{\pi_l} - \frac{1}{2}(\mu_k + \mu_l)^T \Sigma^{-1}(\mu_k - \mu_l) + x^T \Sigma^{-1}(\mu_k - \mu_l) = 0$$

class prior log-ratio constant input covariance diff. in class means

<https://powcoder.com>



Add WeChat powcoder

Can re-write as $\theta_0 + x^T \theta = 0$



Assignment Project Exam Help

Effect of Covariance Matrix



- covariance matrix determines the shape of the Gaussian density, so
- in LDA, the Gaussian densities for different classes have the same shape, but are shifted versions of each other (different mean vectors).

Assignment Project Exam Help

Effect of Class Prior

Add WeChat powcoder

- What effect does the prior $p(\text{class})$, or π_k , have?

Assignment Project Exam Help

- Lets look at an example for 2 classes...

<https://powcoder.com>

Add WeChat powcoder


$$\log \frac{\pi_k}{\pi_l} - \frac{1}{2}(\mu_k + \mu_l)^T \Sigma^{-1}(\mu_k - \mu_l) + x^T \Sigma^{-1}(\mu_k - \mu_l) = 0$$

↑
class prior
log-ratio

Assignment Project Exam Help

$$p(C_1|x) \propto p(x|C_1)p(C_1)$$


Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Model class-conditional probability of a 2D feature vector for class 1 as a multivariate Gaussian density.

Assignment Project Exam Help

Add WeChat powcoder

$$p(C_2|x) \propto p(x|C_2)p(C_2)$$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Now consider class 2 with a similar Gaussian conditional density, which has the same covariance but a different mean

Assignment Project Exam Help

$$p(C_1|x) \propto p(x|C_1)p(C_1)$$

$$p(C_2|x) \propto p(x|C_2)p(C_2)$$

Add WeChat powcoder




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

decision
hypersurface




If the priors for each class are the same (i.e. 0.5), then the **decision hypersurface** cuts directly between the two means, with a direction parallel to the elliptical shape of the modes of the Gaussian densities shaped by their (identical) covariance matrices.

Assignment Project Exam Help

$$p(C_1|x) \propto p(x|C_1)p(C_1)$$

$$p(C_2|x) \propto p(x|C_2)p(C_2)$$

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

decision
hypersurface




Now if the priors for each class are unequal, the decision hypersurface cuts between the two means with a direction as before, but now will be located further from the more likely class. This biases the predictor in favor of the more likely class.

Assignment Project Exam Help

Posterior probability $p(C_1|\mathbf{x})$ for two classes C_1, C_2

Add WeChat powcoder




Bishop Figure 4.10 The left-hand plot shows the class-conditional densities for two classes, denoted red and blue. On the right is the corresponding posterior probability $p(C_1|\mathbf{x})$, which is given by a logistic sigmoid of a linear function of \mathbf{x} . The surface in the right-hand plot is coloured using a proportion of red ink given by $p(C_1|\mathbf{x})$ and a proportion of blue ink given by $p(C_2|\mathbf{x}) = 1 - p(C_1|\mathbf{x})$.

More than two classes, unequal

covariances



- more general case of unequal covariances (here shown for four classes)
- QDA
- the decision hypersurface is no longer a hyperplane, i.e. it is **nonlinear**.



Assignment Project Exam Help

Generative vs Discriminative

Add WeChat powcoder



- Generative: model the class-conditional distribution of features
- **Pros:** Can use it to generate new features
- **Cons:** more parameters, e.g. LDA has $O(n^2)$

- Discriminative: model the decision boundary directly, e.g. Logistic Regression
- **Pros:** fewer parameters, e.g. LogReg has $O(n)$
- **Cons:** Cannot generate new features

Assignment Project Exam Help

Do they produce the same classifier?

Add WeChat powcoder

- Generative LDA approach will estimate μ_1, μ_2 , and Σ to maximize joint likelihood $p(x, y)$ and then compute the linear decision boundary, i.e., θ_j and θ_0 are functions of those parameters. In particular, θ_j and θ_0 are not completely independent.

Assignment Project Exam Help

<https://powcoder.com>

- Discriminative approach (logistic regression) will directly estimate θ_j and θ_0 , without assuming any constraints between them, by maximizing conditional likelihood $p(y|x)$
- The two methods will give different decision boundaries, even both are linear.



Add WeChat powcoder

Assignment Project Exam Help

LDA for image classification

Add WeChat powcoder

- Discriminative Decorrelation for Clustering and Classification
Hariharan, Malik and Ramanan, 2012
 - Showed that LDA requires a lot less training than discriminative models for this task
- Assignment Project Exam Help



(a) Image (left) and HOG (right)

Learned LDA model for class "bicycle"

<http://home.bharathh.info/pubs/pdfs/BharathECCV2012.pdf>

Assignment Project Exam Help

Next Class

Add WeChat powcoder

Midterm! (no lecture)

Assignment Project Exam Help

Next Tuesday-

<https://powcoder.com>

Probabilistic Models II: Bayesian Methods

priors over parameters; Bayesian linear regression

Add WeChat powcoder

Reading: Bishop Ch 2.3