

Assignment Project Exam Help

Announcements

Add WeChat powcoder


Reminder: ps2 due Thursday at midnight (Boston)

Assignment Project Exam Help

- Self-Grading form for ps1 out Friday 9/25 (1 week to turn in)
<https://powcoder.com>
Add WeChat powcoder
- Self-Grading form for ps2 out Monday 9/28 (1 week to turn in)
- Lab this week (no more rotations) – Linear/Logistic Regression, Anaconda

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

Unsupervised Learning I
<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Today


Add WeChat powcoder

- Unsupervised learning
 - K-Means clustering
 - Gaussian Mixture clustering
- <https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

Unsupervised Learning I

<https://powcoder.com>


Add WeChat powcoder

Clustering

Assignment Project Exam Help

Add WeChat powcoder

Supervised learning




Training set: $\{(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), (x^{(3)}, y^{(3)}), \dots, (x^{(m)}, y^{(m)})\}$

Assignment Project Exam Help

Add WeChat powcoder

Unsupervised learning



Training set: $\{x^{(1)}, x^{(2)}, x^{(3)}, \dots, x^{(m)}\}$


Clustering

Assignment Project Exam Help

Add WeChat powcoder



Gene analysis



Social network analysis


Assignment Project Exam Help

<https://powcoder.com>



Types of voters


Add WeChat powcoder



Trending news

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

Unsupervised Learning I


<https://powcoder.com>

Add WeChat powcoder

K-means Algorithm


Assignment Project Exam Help

Add WeChat powcoder




Assignment Project Exam Help

Add WeChat powcoder




Assignment Project Exam Help

Add WeChat powcoder




Assignment Project Exam Help

Add WeChat powcoder




Assignment Project Exam Help

Add WeChat powcoder




Assignment Project Exam Help

Add WeChat powcoder




Assignment Project Exam Help

Add WeChat powcoder




Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help


Add WeChat powcoder



Assignment Project Exam Help

Add WeChat powcoder

K-means algorithm



Input:

- K (number of clusters)
- Training set $\{x^{(1)}, x^{(2)}, \dots, x^{(m)}\}$

<https://powcoder.com>


Add WeChat powcoder

$x^{(i)} \in \mathbb{R}^n$ (drop $x_0 = 1$ convention)

Assignment Project Exam Help

Add WeChat powcoder

K-means algorithm



Randomly initialize K cluster centroids $\mu_1, \mu_2, \dots, \mu_K \in \mathbb{R}^n$

Repeat {

for $i = 1$ to m

$c^{(i)} :=$ index (from 1 to K) of cluster centroid
closest to $x^{(i)}$

for $k = 1$ to K

$\mu_k :=$ average (mean) of points assigned to cluster k

}

Assignment Project Exam Help

K-means Cost Function

$c^{(i)}$ = index of cluster $(1, 2, \dots, K)$ to which example $x^{(i)}$ is currently assigned

μ_k = cluster centroid k ($\mu_k \in \mathbb{R}^n$)


$\mu_{c^{(i)}}$ = cluster centroid of cluster to which example $x^{(i)}$ has been assigned

<https://powcoder.com>

Optimization cost: "distortion"

$$J(c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K) = \frac{1}{m} \sum_{i=1}^m \|x^{(i)} - \mu_{c^{(i)}}\|^2$$

$$\min_{\substack{c^{(1)}, \dots, c^{(m)}, \\ \mu_1, \dots, \mu_K}} J(c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K)$$



Assignment Project Exam Help

Random initialization

Add WeChat powcoder

Should have $K < m$


Randomly pick K training examples.

Assignment Project Exam Help

<https://powcoder.com>

Set μ_1, \dots, μ_K equal to these K examples.

Add WeChat powcoder



Assignment Project Exam Help


Local Optima

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help

Avoiding Local Optima with Random Initialization

Add WeChat powcoder

For $i = 1$ to 100 {

Randomly initialize K-means

Run K-means. Get $c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K$.

Compute cost function (distortion)

$J(c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K)$
}


Pick clustering that gave lowest cost $J(c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K)$

Assignment Project Exam Help

How to choose K ?

Add WeChat powcoder


Elbow method:



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Assignment Project Exam Help



How to choose K?

Add WeChat powcoder

Sometimes, you're running K-means to get clusters to use for some later/downstream purpose. Evaluate K-means based on a metric for how well it performs for that later purpose.

Assignment Project Exam Help

E.g.




<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

Unsupervised Learning I


<https://powcoder.com>

Add WeChat powcoder

Mixtures of Gaussians

Mixtures of Gaussians:

Assignment Project Exam Help
Add WeChat powcoder
Intuition



“Soft” cluster membership


Define a distribution over x :

To generate each point x ,

- Choose its cluster component z
- Sample x from the Gaussian distribution for that component

Mixtures of Gaussians:

component membership variable z




- Assume K components, k -th component is a Gaussian with parameters μ_k, Σ_k
- Introduce discrete r.v. $z \in R^K$ that denotes the component that generates the point
- one element of z is equal to 1 and others are 0, i.e. “one-hot”:

$$z_k \in \{0,1\} \text{ and } \sum_k z_k = 1$$

Assignment Project Exam Help

Mixtures of Gaussians:

Add WeChat powcoder




- Suppose $K = 2$ components, k -th component is a Gaussian with parameters μ_k, Σ_k
- To sample i -th data point:
 - Pick component z^i with $p(z_k = 1) = \pi_k$ (parameter)
 - for example, $\pi_k = 0.5$, and we picked $z^1 = [0, 1]^T$
 - Pick data point x^i with probability $N(x; \mu_k, \Sigma_k)$

Mixtures of Gaussians

Add WeChat powcoder

- $z_k \in \{0,1\}$ and $\sum_k z_k = 1$
- K components, k -th component is a Gaussian with parameters μ_k, Σ_k



Assignment Project Exam Help

- define the joint distribution $p(\mathbf{x}, \mathbf{z})$ in terms of a marginal distribution $p(\mathbf{z})$ and a conditional distribution $p(\mathbf{x}|\mathbf{z})$

<https://powcoder.com>

$$p(\mathbf{x}) = \sum_{\mathbf{z}} p(\mathbf{z}) p(\mathbf{x}|\mathbf{z}) = \sum_{k=1}^K \pi_k \mathcal{N}(\mathbf{x}|\mu_k, \Sigma_k)$$

- where

$$p(z_k = 1) = \pi_k \quad 0 \leq \pi_k \leq 1 \quad \sum_{k=1}^K \pi_k = 1$$

$$p(\mathbf{x}|\mathbf{z}) = \prod_{k=1}^K \mathcal{N}(\mathbf{x}|\mu_k, \Sigma_k)^{z_k}$$

Substitute and simplify

Assignment Project Exam Help Maximum Likelihood Solution for Add WeChat powcoder Mixture of Gaussians

- This distribution is known as a Mixture of Gaussians

$$p(\mathbf{x}) = \sum_{k=1}^K \pi_k \mathcal{N}(\mathbf{x} | \mu_k, \Sigma_k)$$

<https://powcoder.com>

- We can estimate parameters using Maximum Likelihood, i.e. maximize

Add WeChat powcoder

$$\ln p(\mathbf{X} | \boldsymbol{\pi}, \boldsymbol{\mu}, \boldsymbol{\Sigma}) =$$

$$\ln p(x^1, x^2, \dots, x^N | \pi_1, \dots, \pi_K, \mu_1, \dots, \mu_K, \Sigma_1, \dots, \Sigma_K)$$

- This algorithm is called Expectation Maximization (EM)
- Very similar to soft version of K-Means!

Assignment Project Exam Help

Expectation Maximization

Add WeChat powcoder

- We can estimate parameters using Maximum Likelihood, i.e. minimize neg. log likelihood

$$-\ln p(\mathbf{X}|\boldsymbol{\pi}, \boldsymbol{\mu}, \boldsymbol{\Sigma}) = -\sum_{n=1}^N \ln \left\{ \sum_{k=1}^K \pi_k \mathcal{N}(\mathbf{x}_n | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k) \right\}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Problem: don't know values of “hidden” (or “latent”) variable z , we don't observe it
- Solution: treat z^i as parameters and use **coordinate descent**

Assignment Project Exam Help

Coordinate Descent


Add WeChat powcoder

gradient descent:

- Minimize w.r.t all parameters at each step

coordinate descent:

- fix some coordinates, minimize w.r.t. the rest
- alternate




Assignment Project Exam Help

$$f(x) = \frac{1}{2}x^T \begin{pmatrix} 1 & 0.5 \\ 0.5 & 1 \end{pmatrix} x - \begin{pmatrix} 1.5 & 1.5 \end{pmatrix} x, \quad x_0 = \begin{pmatrix} 0 & 0 \end{pmatrix}^T$$

<https://powcoder.com>


Add WeChat powcoder



Credit: Martin Takac

Assignment Project Exam Help

Expectation Maximization



Coordinate descent for
Mixtures of Gaussians:

Alternate

- fix π, μ, Σ , update z^i
- fix z^i , update π, μ, Σ

Assignment Project Exam Help

Expectation Maximization Algorithm

Add WeChat powcoder

- A general technique for finding maximum likelihood estimators in **latent variable** models
- Initialize and iterate until convergence.

Assignment Project Exam Help

E-Step: estimate posterior probability of the latent variables $p(z_k|x)$, holding parameters fixed

<https://powcoder.com>

M-Step: maximize likelihood w.r.t parameters (here μ_k, Σ_k, π_k) using latent probabilities from E-step

Add WeChat powcoder

Assignment Project Exam Help

EM for Gaussian Mixtures Example

Add WeChat powcoder





Figure 9.8 Illustration of the EM algorithm using the Old Faithful set as used for the illustration of the K -means algorithm in Figure 9.1. See the text for details.

Assignment Project Exam Help

EM for Gaussian Mixtures

Add WeChat powcoder

1. Initialize the means μ_k , covariances Σ_k and mixing coefficients π_k , and evaluate the initial value of the log likelihood.
2. **E step.** Evaluate the responsibilities using the current parameter values


$$\gamma(z_k) \equiv p(z_k = 1 | \mathbf{x}_n) = \frac{\pi_k \mathcal{N}(\mathbf{x}_n | \mu_k, \Sigma_k)}{\sum_{j=1}^K \pi_j \mathcal{N}(\mathbf{x}_n | \mu_j, \Sigma_j)} \quad (9.23)$$

3. **M step.** Re-estimate the parameters using the current responsibilities

$$\mu_k^{\text{new}} = \frac{1}{N_k} \sum_{n=1}^N \gamma(z_{nk}) \mathbf{x}_n \quad N_k = \sum_{n=1}^N \gamma(z_{nk}) \quad (9.24)$$

$$\Sigma_k^{\text{new}} = \frac{1}{N_k} \sum_{n=1}^N \gamma(z_{nk}) (\mathbf{x}_n - \mu_k^{\text{new}}) (\mathbf{x}_n - \mu_k^{\text{new}})^T \quad (9.25)$$

$$\pi_k^{\text{new}} = \frac{N_k}{N} \quad (9.26)$$

see Bishop Ch. 9.2

Assignment Project Exam Help

Gaussian Mixtures

Add WeChat powcoder

Data: $X = \{x_n\}$


Parameters: π_k, μ_k, Σ_k

$$-\sum_{n=1}^N \ln \left\{ \sum_{k=1}^K \pi_k \mathcal{M}(x_n | \mu_k, \Sigma_k) \right\}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



How many possible solutions for K clusters? K^N

Is the cost function convex? no

Assignment Project Exam Help

Summary

Add WeChat powcoder

- Unsupervised learning

Assignment Project Exam Help

- Discrete latent variables:

- K-Means clustering
- Gaussian Mixture clustering

<https://powcoder.com>

Add WeChat powcoder

- Next time: Continuous latent variables
 - Principal components analysis

Assignment Project Exam Help

Next Class

Add WeChat powcoder

Unsupervised Learning I: PCA:

dimensionality reduction, PCA

Assignment Project Exam Help

<https://powcoder.com>

Reading: Bishop 12.1

Add WeChat powcoder