

Python Network Programming

David M. Beazley

<http://www.dabeaz.com>

Assignment Project Exam Help

Edition: Thu Jun 17 19:49:58 2010

<https://powcoder.com>

Add WeChat powcoder

Copyright (C) 2010

David M Beazley

All Rights Reserved

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Python Network Programming : Table of Contents

1. Network Fundamentals	4
2. Client Programming	32
3. Internet Data Handling	49
4. Web Programming Basics	65
5. Advanced Networks	93

Edition: Thu Jun 17 19:49:58 2010

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Slide Title Index

0. Introduction

Introduction	0-1
Support Files	0-2
Python Networking	0-3
This Course	0-4
Standard Library	0-5
Prerequisites	0-6

1. Network Fundamentals

Network Fundamentals	1-1
The Problem	1-2
Two Main Issues	1-3
Network Addressing	1-4
Standard Ports	1-5
Using netcat	1-6
Connections	1-7
Client/Server Concept	1-8
Request/Response Cycle	1-9
Using Telnet	1-10
Data Transport	1-11
Sockets	1-12
Socket Basics	1-13
Socket Types	1-14
Using a Socket	1-15
TCP Client	1-16
Exercise 1.1	1-17
Server Implementation	1-18
TCP Server	1-19
Exercise 1.2	1-27
Advanced Sockets	1-28
Partial Reads/Writes	1-29
Sending All Data	1-31
End of Data	1-32
Data Reassembly	1-33
Timeouts	1-34
Non-blocking Sockets	1-35
Socket Options	1-36
Sockets as Files	1-37
Exercise 1.3	1-39
Odds and Ends	1-40
UDP : Datagrams	1-41
UDP Server	1-42
UDP Client	1-43
Unix Domain Sockets	1-44
Raw Sockets	1-45
Sockets and Concurrency	1-46

Threaded Server	1-50
Forking Server (Unix)	1-51
Asynchronous Server	1-52
Utility Functions	1-53
Omissions	1-54
Discussion	1-55

2. Client Programming

Client Programming	2-1
Overview	2-2
urllib Module	2-3
urllib protocols	2-5
HTML Forms	2-6
Web Services	2-8
Parameter Encoding	2-9
Sending Parameters	2-10
Response Data	2-12
Response Headers	2-13
Response Status	2-14
Exercise 2.1	2-15
urllib Limitations	2-16
urllib2 Module	2-17
urllib2 Example	2-18
urllib2 Requests	2-19
Requests with Data	2-20
Request Headers	2-21
urllib2 Error Handling	2-22
urllib2 Openers	2-23
urllib2 build_opener()	2-24
Example : Login Cookies	2-25
Discussion	2-26
Exercise 2.2	2-27
Limitations	2-28
ftplib	2-29
Upload to a FTP Server	2-30
httpplib	2-31
smtplib	2-32
Exercise 2.3	2-33

3. Internet Data Handling

Internet Data Handling	3-1
Overview	3-2
CSV Files	3-3
Parsing HTML	3-4
Running a Parser	3-6
HTML Example	3-7
XML Parsing with SAX	3-9
Brief XML Refresher	3-10
SAX Parsing	3-11

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Exercise 3.1	3-13	WSGI Example	4-37
XML and ElementTree	3-14	WSGI Applications	4-38
etree Parsing Basics	3-15	WSGI Environment	4-39
Obtaining Elements	3-17	Processing WSGI Inputs	4-41
Iterating over Elements	3-18	WSGI Responses	4-42
Element Attributes	3-19	WSGI Content	4-44
Search Wildcards	3-20	WSGI Content Encoding	4-45
cElementTree	3-22	WSGI Deployment	4-46
Tree Modification	3-23	WSGI and CGI	4-48
Tree Output	3-24	Exercise 4.5	4-49
Iterative Parsing	3-25	Customized HTTP	4-50
Exercise 3.2	3-28	Exercise 4.6	4-53
JSON	3-29	Web Frameworks	4-54
Sample JSON File	3-30	Commentary	4-56
Processing JSON Data	3-31		
Exercise 3.3	3-32		

5. Advanced Networking

4. Web Programming

Web Programming Basics	4-1	Advanced Networking	5-1
Introduction	4-2	Overview	5-2
Overview	4-3	Problem with Sockets	5-3
Disclaimer	4-4	SocketServer	5-4
HTTP Explained	4-5	SocketServer Example	5-5
HTTP Client Requests	4-6	Execution Model	5-11
HTTP Responses	4-7	Exercise 5.1	5-12
HTTP Protocol	4-8	Big Picture	5-13
Content Encoding	4-9	Concurrent Servers	5-14
Payload Packaging	4-10	Server Mixin Classes	5-15
Exercise 4.1	4-11	Server Subclassing	5-16
Role of Python	4-12	Exercise 5.2	5-17
Typical Python Tasks	4-13	Distributed Computing	5-18
Content Generation	4-14	Discussion	5-19
Example : Page Templates	4-15	XML-RPC	5-20
Commentary	4-17	Simple XML-RPC	5-21
Exercise 4.2	4-18	XML-RPC Commentary	5-23
HTTP Servers	4-19	XML-RPC and Binary	5-24
A Simple Web Server	4-20	Exercise 5.3	5-25
Exercise 4.3	4-21	Serializing Python Objects	5-26
A Web Server with CGI	4-22	pickle Module	5-27
CGI Scripting	4-23	Pickling to Strings	5-28
CGI Example	4-24	Example	5-29
CGI Mechanics	4-27	Miscellaneous Comments	5-31
Classic CGI Interface	4-28	Exercise 5.4	5-32
CGI Query Variables	4-29	multiprocessing	5-33
cgi Module	4-30	Connections	5-34
CGI Responses	4-31	Connection Use	5-35
Note on Status Codes	4-32	Example	5-36
CGI Commentary	4-33	Commentary	5-38
Exercise 4.4	4-34	What about...	5-40
WSGI	4-35	Network Wrap-up	5-41
WSGI Interface	4-36	Exercise 5.5	5-42

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Section 0

Introduction

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder Support Files

- Course exercises:

<http://www.dabeaz.com/python/pythonnetwork.zip>

- This zip file should be downloaded and extracted someplace on your machine
- All of your work will take place in the the "PythonNetwork" folder

Python Networking

- Network programming is a major use of Python
- Python standard library has wide support for network protocols, data encoding/decoding, and other things you need to make it work
- Writing network programs in Python tends to be substantially easier than in C/C++

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 3

<https://powcoder.com>

Add WeChat powcoder This Course

- This course focuses on the essential details of network programming that all Python programmers should probably know
 - Low-level programming with sockets
 - High-level client modules
 - How to deal with common data encodings
 - Simple web programming (HTTP)
 - Simple distributed computing

Copyright (C) 2010, <http://www.dabeaz.com>

I- 4

Standard Library

- We will only cover modules supported by the Python standard library
- These come with Python by default
- Keep in mind, much more functionality can be found in third-party modules
- Will give links to notable third-party libraries as appropriate

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 5

<https://powcoder.com>

Add WeChat powcoder Prerequisites

- You should already know Python basics
- However, you don't need to be an expert on all of its advanced features (in fact, none of the code to be written is highly sophisticated)
- You should have some prior knowledge of systems programming and network concepts

Copyright (C) 2010, <http://www.dabeaz.com>

I- 6

Section I


Network Fundamentals

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
The Problem

- Communication between computers



- It's just sending/receiving bits

Two Main Issues

- Addressing
 - Specifying a remote computer and service
- Data transport
 - Moving bits back and forth

Assignment Project Exam Help


Copyright (C) 2010, <http://www.dabeaz.com>

I- 3

<https://powcoder.com>

Add WeChat powcoder Network Addressing

- Machines have a hostname and IP address
- Programs/services have port numbers



Copyright (C) 2010, <http://www.dabeaz.com>

I- 4

Standard Ports

- Ports for common services are preassigned

21	FTP
22	SSH
23	Telnet
25	SMTP (Mail)
80	HTTP (Web)
110	POP3 (Mail)
119	NNTP (News)
443	HTTPS (web)

- Other port numbers may just be randomly assigned to programs by the operating system

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 5

<https://powcoder.com>

Add WeChat powcoder
Using netstat

- Use 'netstat' to view active network connections

```
shell % netstat -a
Active Internet connections (servers and established)
Proto Recv-Q Send-Q Local Address           Foreign Address
tcp        0      0 *:imaps                  *:*
tcp        0      0 *:pop3s                  *:*
tcp        0      0 localhost:mysql          *:*
tcp        0      0 *:pop3                   *:*
tcp        0      0 *:imap2                  *:*
tcp        0      0 *:8880                   *:*
tcp        0      0 *:www                    *:*
tcp        0      0 192.168.119.139:domain  *:*
tcp        0      0 localhost:domain         *:*
tcp        0      0 *:ssh                    *:*
...
```

- Note: Must execute from the command shell on both Unix and Windows

Copyright (C) 2010, <http://www.dabeaz.com>

I- 6

Connections

- Each endpoint of a network connection is always represented by a host and port #
- In Python you write it out as a tuple (host,port)

```
("www.python.org", 80)  
("205.172.13.4", 443)
```

- In almost all of the network programs you'll write, you use this convention to specify a network address

Assignment Project Exam Help


Copyright (C) 2010, <http://www.dabeaz.com>

I- 7

<https://powcoder.com>

Add WeChat powcoder Client/Server Concept

- Each endpoint is a running program
- Servers wait for incoming connections and provide a service (e.g., web, mail, etc.)
- Clients make connections to servers



Copyright (C) 2010, <http://www.dabeaz.com>

I- 8

Request/Response Cycle

- Most network programs use a request/response model based on messages
- Client sends a request message (e.g., HTTP)

```
GET /index.html HTTP/1.0
```

- Server sends back a response message

```
HTTP/1.0 200 OK
Content-type: text/html
Content-length: 48823
```

```
<HTML>
```

```
...
```

- The exact format depends on the application

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder Using Telnet

- As a debugging aid, telnet can be used to directly communicate with many services

```
telnet hostname portnum
```

- Example:

```
shell % telnet www.python.org 80
Trying 82.94.237.218...
Connected to www.python.org.
Escape character is '^]'.
type this and press → GET /index.html HTTP/1.0
return a few times

HTTP/1.1 200 OK
Date: Mon, 31 Mar 2008 13:34:03 GMT
Server: Apache/2.2.3 (Debian) DAV/2 SVN/1.4.2
mod_ssl/2.2.3 OpenSSL/0.9.8c
...
```

Data Transport

- There are two basic types of communication
- Streams (TCP): Computers establish a connection with each other and read/write data in a continuous stream of bytes---like a file. This is the most common.
- Datagrams (UDP): Computers send discrete packets (or messages) to each other. Each packet contains a collection of bytes, but each packet is separate and self-contained.

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 11

<https://powcoder.com>

Add WeChat powcoder Sockets

- Programming abstraction for network code
- Socket: A communication endpoint



- Supported by socket library module
- Allows connections to be made and data to be transmitted in either direction

Copyright (C) 2010, <http://www.dabeaz.com>

I- 12

Socket Basics

- To create a socket

```
import socket  
s = socket.socket(addr_family, type)
```

- Address families

```
socket.AF_INET      Internet protocol (IPv4)  
socket.AF_INET6     Internet protocol (IPv6)
```

- Socket types

```
socket.SOCK_STREAM  Connection based stream (TCP)  
socket.SOCK_DGRAM   Datagrams (UDP)
```

- Example:

```
from socket import *  
s = socket(AF_INET, SOCK_STREAM)
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 13

<https://powcoder.com>

Add WeChat powcoder

Socket Types

- Almost all code will use one of following

```
from socket import *  
  
s = socket(AF_INET, SOCK_STREAM)  
s = socket(AF_INET, SOCK_DGRAM)
```

- Most common case: TCP connection

```
s = socket(AF_INET, SOCK_STREAM)
```

Copyright (C) 2010, <http://www.dabeaz.com>

I- 14

Using a Socket

- Creating a socket is only the first step

```
s = socket(AF_INET, SOCK_STREAM)
```

- Further use depends on application
- Server
 - Listen for incoming connections
- Client
 - Make an outgoing connection

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 15

<https://powcoder.com>

Add WeChat powcoder TCP Client

- How to make an outgoing connection

```
from socket import *  
s = socket(AF_INET, SOCK_STREAM)  
s.connect(("www.python.org", 80)) # Connect  
s.send("GET /index.html HTTP/1.0\n\n") # Send request  
data = s.recv(10000) # Get response  
s.close()
```

- `s.connect(addr)` makes a connection

```
s.connect(("www.python.org", 80))
```
- Once connected, use `send()`, `recv()` to transmit and receive data
- `close()` shuts down the connection

Copyright (C) 2010, <http://www.dabeaz.com>

I- 16

Exercise I.I

Time : 10 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 17

<https://powcoder.com>

Add WeChat powcoder Server Implementation

- Network servers are a bit more tricky
- Must listen for incoming connections on a well-known port number
- Typically run forever in a server-loop
- May have to service multiple clients

Copyright (C) 2010, <http://www.dabeaz.com>

I- 18

TCP Server

- A simple server

```
from socket import *
s = socket(AF_INET, SOCK_STREAM)
s.bind(("", 9000))
s.listen(5)
while True:
    c, a = s.accept()
    print "Received connection from", a
    c.send("Hello %s\n" % a[0])
    c.close()
```

- Send a message back to a client

```
% telnet localhost 9000
Connected to localhost.
Escape character is '^]'.
Hello 127.0.0.1
Connection closed by foreign host.
```

Server message

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

TCP Server

- Address binding

```
from socket import *
s = socket(AF_INET, SOCK_STREAM)
s.bind(("", 9000))
s.listen(5)
while True:
    c, a = s.accept()
    print "Received connection from", a
    c.send("Hello %s\n" % a[0])
    c.close()
```

binds the socket to
a specific address

- Addressing

```
s.bind(("", 9000))
s.bind("localhost", 9000)
s.bind("192.168.2.1", 9000)
s.bind("104.21.4.2", 9000)
```

binds to localhost

If system has multiple
IP addresses, can bind
to a specific address

TCP Server

- Start listening for connections

```
from socket import *
s = socket(AF_INET, SOCK_STREAM)
s.bind(("", 9000))
s.listen(5) ← Tells operating system to
                 start listening for
                 connections on the socket
while True:
    c, a = s.accept()
    print "Received connection from", a
    c.send("Hello %s\n" % a[0])
    c.close()
```

- `s.listen(backlog)`
- backlog is # of pending connections to allow
- Note: not related to max number of clients

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

TCP Server

- Accepting a new connection

```
from socket import *
s = socket(AF_INET, SOCK_STREAM)
s.bind(("", 9000))
s.listen(5)
while True:
    c, a = s.accept() ← Accept a new client connection
    print "Received connection from", a
    c.send("Hello %s\n" % a[0])
    c.close()
```

- `s.accept()` blocks until connection received
- Server sleeps if nothing is happening

TCP Server

- Client socket and address

```
from socket import *
s = socket(AF_INET,SOCK_STREAM)
s.bind(("",9000))
s.listen(5)
while True:
    c,a = s.accept()
    print "Received connection from", a
    c.send("Hello %s\n" % a[0])
    c.close()
```

Accept returns a pair (client_socket,addr)

<socket._socketobject object at 0x3be30>

This is a new socket that's used for data

("104.23.11.4",27743)

This is the network/port address of the client that connected

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 23

<https://powcoder.com>

Add WeChat powcoder

TCP Server

- Sending data

```
from socket import *
s = socket(AF_INET,SOCK_STREAM)
s.bind(("",9000))
s.listen(5)
while True:
    c,a = s.accept()
    print "Received connection from", a
    c.send("Hello %s\n" % a[0])
    c.close()
```

Send data to client

Note: Use the client socket for transmitting data. The server socket is only used for accepting new connections.

Copyright (C) 2010, <http://www.dabeaz.com>

I- 24

TCP Server

- Closing the connection

```
from socket import *
s = socket(AF_INET, SOCK_STREAM)
s.bind(("", 9000))
s.listen(5)
while True:
    c, a = s.accept()
    print "Received connection from", a
    c.send("Hello %s\n" % a[0])
    c.close() ← Close client connection
```

- Note: Server can keep client connection alive as long as it wants
- Can repeatedly receive/send data

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

TCP Server

- Waiting for the next connection

```
from socket import *
s = socket(AF_INET, SOCK_STREAM)
s.bind(("", 9000))
s.listen(5)
while True:
    c, a = s.accept() ← Wait for next connection
    print "Received connection from", a
    c.send("Hello %s\n" % a[0])
    c.close()
```

- Original server socket is reused to listen for more connections
- Server runs forever in a loop like this

Exercise 1.2

Time : 20 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I - 27

<https://powcoder.com>

Add WeChat powcoder Advanced Sockets

- Socket programming is often a mess
- Huge number of options
- Many corner cases
- Many failure modes/reliability issues
- Will briefly cover a few critical issues

Copyright (C) 2010, <http://www.dabeaz.com>

I - 28

Partial Reads/Writes

- Be aware that reading/writing to a socket may involve partial data transfer
- `send()` returns actual bytes sent
- `recv()` length is only a maximum limit

```
>>> len(data)
1000000
>>> s.send(data)
37722
```

Sent partial data

```
>>> data = s.recv(10000)
>>> len(data)
6420
```

Received less than max

Assignment Project Exam Help

<https://powcoder.com>

Partial Reads/Writes

- Be aware that for TCP, the data stream is continuous---no concept of records, etc.

```
# Client
...
s.send(data)
s.send(moredata)
...
```

```
# Server
...
data = s.recv(maxsize)
...
```

This `recv()` may return data from both of the sends combined or less data than even the first send

- A lot depends on OS buffers, network bandwidth, congestion, etc.

Sending All Data

- To wait until all data is sent, use `sendall()`
`s.sendall(data)`
- Blocks until all data is transmitted
- For most normal applications, this is what you should use
- Exception :You don't use this if networking is mixed in with other kinds of processing (e.g., screen updates, multitasking, etc.)

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 31

<https://powcoder.com>

Add WeChat powcoder End of Data

- How to tell if there is no more data?
- `recv()` will return empty string

```
>>> s.recv(1000)
''
>>>
```
- This means that the other end of the connection has been closed (no more sends)

Copyright (C) 2010, <http://www.dabeaz.com>

I- 32

Data Reassembly

- Receivers often need to reassemble messages from a series of small chunks
- Here is a programming template for that

```
fragments = []                # List of chunks
while not done:
    chunk = s.recv(maxsize)   # Get a chunk
    if not chunk:
        break                 # EOF. No more data
    fragments.append(chunk)

# Reassemble the message
message = "".join(fragments)
```

- Don't use string concat (+=). It's slow.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Timeouts

- Most socket operations block indefinitely
- Can set an optional timeout

```
s = socket(AF_INET, SOCK_STREAM)
...
s.settimeout(5.0)    # Timeout of 5 seconds
...
```

- Will get a timeout exception

```
>>> s.recv(1000)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
socket.timeout: timed out
>>>
```

- Disabling timeouts

```
s.settimeout(None)
```

Non-blocking Sockets

- Instead of timeouts, can set non-blocking

```
>>> s.setblocking(False)
```

- Future send(),recv() operations will raise an exception if the operation would have blocked

```
>>> s.setblocking(False)
>>> s.recv(1000) ← No data available
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
socket.error: (35, 'Resource temporarily unavailable')
>>> s.recv(1000) ← Data arrived
'Hello World\n'
>>>
```

- Sometimes used for polling

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder Socket Options

- Sockets have a large number of parameters
- Can be set using s.setsockopt()
- Example: Reusing the port number

```
>>> s.bind("",9000)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "<string>", line 1, in bind
socket.error: (48, 'Address already in use')
>>> s.setsockopt(socket.SOL_SOCKET,
...               socket.SO_REUSEADDR, 1)
>>> s.bind("",9000)
>>>
```

- Consult reference for more options

Sockets as Files

- Sometimes it is easier to work with sockets represented as a "file" object

```
f = s.makefile()
```

- This will wrap a socket with a file-like API

```
f.read()  
f.readline()  
f.write()  
f.writelines()  
for line in f:  
    ...  
f.close()
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I- 37

<https://powcoder.com>

Add WeChat powcoder
Sockets as Files

- Commentary : From personal experience, putting a file-like layer over a socket rarely works as well in practice as it sounds in theory.
- Tricky resource management (must manage both the socket and file independently)
- It's easy to write programs that mysteriously "freeze up" or don't operate quite like you would expect.

Copyright (C) 2010, <http://www.dabeaz.com>

I- 38

Exercise 1.3

Time : 15 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I - 39

<https://powcoder.com>


Add WeChat powcoder
Odds and Ends

- Other supported socket types
 - Datagram (UDP) sockets
 - Unix domain sockets
 - Raw sockets/Packets
- Sockets and concurrency
- Useful utility functions

Copyright (C) 2010, <http://www.dabeaz.com>

I - 40

UDP : Datagrams



- Data sent in discrete packets (Datagrams)
- No concept of a "connection"
- No reliability, no ordering of data
- Datagrams may be lost, arrive in any order
- Higher performance (used in games, etc.)

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I - 41

<https://powcoder.com>

Add WeChat powcoder UDP Server

- A simple datagram server

```
from socket import *  
s = socket(AF_INET, SOCK_DGRAM) ← Create datagram socket  
  
s.bind(("", 10000)) ← Bind to a specific port  
  
while True:  
    data, addr = s.recvfrom(maxsize) ← Wait for a message  
  
    resp = "Get off my lawn!"  
    s.sendto(resp, addr) ← Send response (optional)
```


- No "connection" is established
- It just sends and receives packets

Copyright (C) 2010, <http://www.dabeaz.com>

I - 42

UDP Client

- Sending a datagram to a server



- Key concept: No "connection"
- You just send a data packet

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I - 43

<https://powcoder.com>

Add WeChat powcoder Unix Domain Sockets

- Available on Unix based systems. Sometimes used for fast IPC or pipes between processes
- Creation:

```
s = socket(AF_UNIX, SOCK_STREAM)  
s = socket(AF_UNIX, SOCK_DGRAM)
```

- Address is just a "filename"

```
s.bind("/tmp/foo")          # Server binding  
s.connect("/tmp/foo")       # Client connection
```

- Rest of the programming interface is the same

Copyright (C) 2010, <http://www.dabeaz.com>

I - 44

Raw Sockets

- If you have root/admin access, can gain direct access to raw network packets
- Depends on the system
- Example: Linux packet sniffing

```
s = socket(AF_PACKET, SOCK_DGRAM)
s.bind(("eth0", 0x0800)) # Sniff IP packets

while True:
    msg, addr = s.recvfrom(4096) # get a packet
    ...
```

Assignment Project Exam Help


Copyright (C) 2010, <http://www.dabeaz.com>

I - 45

<https://powcoder.com>

Add WeChat powcoder Sockets and Concurrency

- Servers usually handle multiple clients




Copyright (C) 2010, <http://www.dabeaz.com>

I - 46

Sockets and Concurrency

- Each client gets its own socket on server



Assignment Project Exam Help


Copyright (C) 2010, <http://www.dabeaz.com>

I - 47

<https://powcoder.com>

Add WeChat powcoder Sockets and Concurrency

- New connections make a new socket



Copyright (C) 2010, <http://www.dabeaz.com>

I - 48

Sockets and Concurrency

- To manage multiple clients,
 - Server must always be ready to accept new connections
 - Must allow each client to operate independently (each may be performing different tasks on the server)
- Will briefly outline the common solutions

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I - 49

<https://powcoder.com>

Add WeChat powcoder Threaded Server

- Each client is handled by a separate thread

```
import threading
from socket import *

def handle_client(c):
    ... whatever ...
    c.close()
    return

s = socket(AF_INET, SOCK_STREAM)
s.bind(("", 9000))
s.listen(5)
while True:
    c, a = s.accept()
    t = threading.Thread(target=handle_client,
                        args=(c,))
```

Copyright (C) 2010, <http://www.dabeaz.com>

I - 50

Forking Server (Unix)

- Each client is handled by a subprocess

```
import os
from socket import *
s = socket(AF_INET, SOCK_STREAM)
s.bind(('', 9000))
s.listen(5)
while True:
    c, a = s.accept()
    if os.fork() == 0:
        # Child process.  Manage client
        ...
        c.close()
        os._exit(0)
    else:
        # Parent process. Clean up and go
        # back to wait for more connections
        c.close()
```

- Note: Omitting some critical details

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder Asynchronous Server

- Server handles all clients in an event loop

```
import select
from socket import *
s = socket(AF_INET, SOCK_STREAM)
...
clients = [] # List of all active client sockets
while True:
    # Look for activity on any of my sockets
    input, output, err = select.select(s+clients,
                                       clients, clients)

    # Process all sockets with input
    for i in input:
        ...

    # Process all sockets ready for output
    for o in output:
        ...
```

- Frameworks such as Twisted build upon this

Utility Functions

- Get the hostname of the local machine

```
>>> socket.gethostname()  
'foo.bar.com'  
>>>
```

- Get the IP address of a remote machine

```
>>> socket.gethostbyname("www.python.org")  
'82.94.237.218'  
>>>
```

- Get name information on a remote IP

```
>>> socket.gethostbyaddr("82.94.237.218")  
( 'dinsdale.python.org', [], ['82.94.237.218'] )  
>>>
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I - 53

<https://powcoder.com>

Add WeChat powcoder Omissions

- socket module has hundreds of obscure socket control options, flags, etc.
- Many more utility functions
- IPv6 (Supported, but new and hairy)
- Other socket types (SOCK_RAW, etc.)
- More on concurrent programming (covered in advanced course)

Copyright (C) 2010, <http://www.dabeaz.com>

I - 54

Discussion

- It is often unnecessary to directly use sockets
- Other library modules simplify use
- However, those modules assume some knowledge of the basic concepts (addresses, ports, TCP, UDP, etc.)
- Will see more in the next few sections...

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

I - 55

<https://powcoder.com>

Add WeChat powcoder

Section 2

Client Programming

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
Overview

- Python has library modules for interacting with a variety of standard internet services
- HTTP, FTP, SMTP, NNTP, XML-RPC, etc.
- In this section we're going to look at how some of these library modules work
- Main focus is on the web (HTTP)

urllib Module

- A high level module that allows clients to connect a variety of internet services
 - HTTP
 - HTTPS
 - FTP
 - Local files
- Works with typical URLs on the web...

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 3

<https://powcoder.com>

Add WeChat powcoder

urllib Module

- Open a web page: `urlopen()`

```
>>> import urllib
>>> u = urllib.urlopen("http://www.python.org/index.html")
>>> data = u.read()
>>> print data
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML ...
...
>>>
```
- `urlopen()` returns a file-like object
- Read from it to get downloaded data

Copyright (C) 2010, <http://www.dabeaz.com>

2- 4

urllib protocols

- Supported protocols

```
u = urllib.urlopen("http://www.foo.com")
u = urllib.urlopen("https://www.foo.com/private")
u = urllib.urlopen("ftp://ftp.foo.com/README")
u = urllib.urlopen("file:///Users/beazley/blah.txt")
```

- Note: HTTPS only supported if Python configured with support for OpenSSL

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 5

<https://powcoder.com>

Add WeChat powcoder

HTML Forms

- One use of urllib is to automate forms

Your name:

Your email:

- Example HTML source for the form

```
<FORM ACTION="/subscribe" METHOD="POST">
Your name: <INPUT type="text" name="name" size="30"><br>
Your email: <INPUT type="text" name="email" size="30"><br>
<INPUT type="submit" name="submit-button" value="Subscribe">
```

Copyright (C) 2010, <http://www.dabeaz.com>

2- 6

HTML Forms

- Within the form, you will find an action and named parameters for the form fields

```
<FORM ACTION="/subscribe" METHOD="POST">  
Your name: <INPUT type="text" name="name" size="30"><br>  
Your email: <INPUT type="text" name="email" size="30"><br>  
<INPUT type="submit" name="submit-button" value="Subscribe">
```

- Action (a URL)

`http://somedomain.com/subscribe`

- Parameters:

`name`
`email`

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 7

<https://powcoder.com>

Add WeChat powcoder Web Services

- Another use of urllib is to access web services
 - Downloading maps
 - Stock quotes
 - Email messages
- Most of these are controlled and accessed in the same manner as a form
- There is a particular request and expected set of parameters for different operations

Copyright (C) 2010, <http://www.dabeaz.com>

2- 8

Parameter Encoding

- `urlencode()`
- Takes a dictionary of fields and creates a URL-encoded string of parameters

```
fields = {  
    'name' : 'Dave',  
    'email' : 'dave@dabeaz.com'  
}  
  
parms = urllib.urlencode(fields)
```

- Sample result

```
>>> parms  
'name=Dave&email=dave%40dabeaz.com'  
>>>
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 9

<https://powcoder.com>

Add WeChat powcoder Sending Parameters

- Case I : GET Requests

```
<FORM ACTION="/subscribe" METHOD="GET">  
Your name: <INPUT type="text" name="name" size="30"><br>  
Your email: <INPUT type="text" name="email" size="30"><br>  
<INPUT type="submit" name="submit-button" value="Subscribe">
```

- Example code:

```
fields = { ... }  
parms = urllib.urlencode(fields)  
u = urllib.urlopen("http://somedomain.com/subscribe?" + parms)
```

You create a long URL by concatenating
the request with the parameters

<http://somedomain.com/subscribe?name=Dave&email=dave%40dabeaz.com>

Copyright (C) 2010, <http://www.dabeaz.com>

2- 10

Sending Parameters

- Case 2 : POST Requests

```
<FORM ACTION="/subscribe" METHOD="POST">  
Your name: <INPUT type="text" name="name" size="30"><br>  
Your email: <INPUT type="text" name="email" size="30"><br>  
<INPUT type="submit" name="submit-button" value="Subscribe">
```

- Example code:

```
fields = { ... }  
parms = urllib.urlencode(fields)  
u = urllib.urlopen("http://somedomain.com/subscribe", parms)
```

Parameters get uploaded separately
as part of the request body

POST /subscribe HTTP/1.0

name=Dave&email=dave@dabeaz.com

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 11

<https://powcoder.com>

Add WeChat powcoder Response Data

- To read response data, treat the result of `urlopen()` as a file object

```
>>> u = urllib.urlopen("http://www.python.org")  
>>> data = u.read()  
>>>
```

- Be aware that the response data consists of the raw bytes transmitted
- If there is any kind of extra encoding (e.g., Unicode), you will need to decode the data with extra processing steps.

Copyright (C) 2010, <http://www.dabeaz.com>

2- 12

Response Headers

- HTTP headers are retrieved using .info()

```
>>> u = urllib.urlopen("http://www.python.org")
>>> headers = u.info()
>>> headers
<httplib.HTTPMessage instance at 0x1118828>
>>> headers.keys()
['content-length', 'accept-ranges', 'server',
 'last-modified', 'connection', 'etag', 'date',
 'content-type']
>>> headers['content-length']
'13597'
>>> headers['content-type']
'text/html'
>>>
```

- A dictionary-like object

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 13

<https://powcoder.com>

Add WeChat powcoder Response Status

- urlopen() ignores HTTP status codes (i.e., errors are silently ignored)
- Can manually check the response code

```
u = urllib.urlopen("http://www.python.org/java")
if u.code == 200:
    # success
    ...
elif u.code == 404:
    # Not found!
    ...
elif u.code == 403:
    # Forbidden
    ...
```

- Unfortunately a little clumsy (fixed shortly)

Copyright (C) 2010, <http://www.dabeaz.com>

2- 14

Exercise 2.1

Time : 15 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 15

<https://powcoder.com>

Add WeChat powcoder
urllib Limitations

- urllib only works with simple cases
- Does not support cookies
- Does not support authentication
- Does not report HTTP errors gracefully
- Only supports GET/POST requests

Copyright (C) 2010, <http://www.dabeaz.com>

2- 16

urllib2 Module

- urllib2 - The sequel to urllib
- Builds upon and expands urllib
- Can interact with servers that require cookies, passwords, and other details
- Better error handling (uses exceptions)
- Is the preferred library for modern code

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 17

<https://powcoder.com>

Add WeChat powcoder urllib2 Example

- urllib2 provides urlopen() as before

```
>>> import urllib2
>>> u = urllib2.urlopen("http://www.python.org/index.html")
>>> data = u.read()
>>>
```

- However, the module expands functionality in two primary areas
 - Requests
 - Openers

Copyright (C) 2010, <http://www.dabeaz.com>

2- 18

urllib2 Requests

- Requests are now objects

```
>>> r = urllib2.Request("http://www.python.org")
>>> u = urllib2.urlopen(r)
>>> data = u.read()
```

- Requests can have additional attributes added
- User data (for POST requests)
- Customized HTTP headers

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 19

<https://powcoder.com>

Add WeChat powcoder Requests with Data

- Create a POST request with user data

```
data = {
    'name' : 'dave',
    'email' : 'dave@dabeaz.com'
}

r = urllib2.Request("http://somedomain.com/subscribe",
                    urllib.urlencode(data))
u = urllib2.urlopen(r)
response = u.read()
```

- Note :You still use `urllib.urlencode()` from the older `urllib` library

Copyright (C) 2010, <http://www.dabeaz.com>

2- 20

Request Headers

- Adding/Modifying client HTTP headers

```
headers = {  
    'User-Agent' : 'Mozilla/4.0 (compatible; MSIE 7.0;  
Windows NT 5.1; .NET CLR 2.0.50727)'  
}  
  
r = urllib2.Request("http://somedomain.com/",  
                    headers=headers)  
u = urllib2.urlopen(r)  
response = u.read()
```

- This can be used if you need to emulate a specific client (e.g., Internet Explorer, etc.)

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 21

<https://powcoder.com>

Add WeChat powcoder urllib2 Error Handling

- HTTP Errors are reported as exceptions

```
>>> u = urllib2.urlopen("http://www.python.org/perl")  
Traceback...  
urllib2.HTTPError: HTTP Error 404: Not Found  
>>>
```

- Catching an error

```
try:  
    u = urllib2.urlopen(url)  
except urllib2.HTTPError,e:  
    code = e.code          # HTTP error code
```

- Note: urllib2 automatically tries to handle redirection and certain HTTP responses

Copyright (C) 2010, <http://www.dabeaz.com>

2- 22

urllib2 Openers

- The function `urlopen()` is an "opener"
- It knows how to open a connection, interact with the server, and return a response.
- It only has a few basic features---it does not know how to deal with cookies and passwords
- However, you can make your own opener objects with these features enabled

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 23

<https://powcoder.com>

Add WeChat powcoder urllib2 build_opener()

- `build_opener()` makes an custom opener

```
# Make a URL opener with cookie support
opener = urllib2.build_opener(
    urllib2.HTTPCookieProcessor()
)
u = opener.open("http://www.python.org/index.html")
```

- Can add a set of new features from this list

```
CacheFTPHandler
HTTPBasicAuthHandler
HTTPCookieProcessor
HTTPODigestAuthHandler
ProxyHandler
ProxyBasicAuthHandler
ProxyDigestAuthHandler
```

Copyright (C) 2010, <http://www.dabeaz.com>

2- 24

Example : Login Cookies

```
fields = {
    'txtUsername' : 'dave',
    'txtPassword' : '12345',
    'submit_login' : 'Log In'
}
opener = urllib2.build_opener(
    urllib2.HTTPCookieProcessor()
)
request = urllib2.Request(
    "http://somedomain.com/login.asp",
    urllib.urlencode(fields))

# Login
u = opener.open(request)
resp = u.read()

# Get a page, but use cookies returned by initial login
u = opener.open("http://somedomain.com/private.asp")
resp = u.read()
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 25

<https://powcoder.com>

Add WeChat powcoder Discussion

- urllib2 module has a huge number of options
- Different configurations
- File formats, policies, authentication, etc.
- Will have to consult reference for everything

Copyright (C) 2010, <http://www.dabeaz.com>

2- 26

Exercise 2.2

Time : 15 Minutes

Password: guido456

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 27

<https://powcoder.com>

Add WeChat powcoder Limitations

- urllib and urllib2 are useful for fetching files
- However, neither module provides support for more advanced operations
- Examples:
 - Uploading to an FTP server
 - File-upload via HTTP Post
 - Other HTTP methods (e.g., HEAD, PUT)

Copyright (C) 2010, <http://www.dabeaz.com>

2- 28

ftplib

- A module for interacting with FTP servers
- Example : Capture a directory listing

```
>>> import ftplib
>>> f = ftplib.FTP("ftp.gnu.org", "anonymous",
...               "dave@dabeaz.com")
>>> files = []
>>> f.retrlines("LIST", files.append)
'226 Directory send OK.'
>>> len(files)
15
>>> files[0]
'-rw-r--r--      1 0      0      1765 Feb 20 16:47 README'
>>>
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 29

<https://powcoder.com>

Add WeChat powcoder Upload to a FTP Server

```
host      = "ftp.foo.com"
username  = "dave"
password  = "1235"
filename  = "somefile.dat"

import ftplib
ftp_serv  = ftplib.FTP(host, username, password)

# Open the file you want to send
f = open(filename, "rb")

# Send it to the FTP server
resp = ftp_serv.storbinary("STOR "+filename, f)

# Close the connection
ftp_serv.close()
```

Copyright (C) 2010, <http://www.dabeaz.com>

2- 30

httplib

- A module for implementing the client side of an HTTP connection

```
import httplib
c = httplib.HTTPConnection("www.python.org",80)
c.putrequest("HEAD", "/tut/tut.html")
c.putheader("Someheader", "Somevalue")
c.endheaders()

r = c.getresponse()
data = r.read()
c.close()
```

- Low-level control over HTTP headers, methods, data transmission, etc.

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 31

<https://powcoder.com>

Add WeChat powcoder smtplib

- A module for sending email messages

```
import smtplib
serv = smtplib.SMTP()
serv.connect()

msg = """\
From: dave@dabeaz.com
To: bob@yahoo.com
Subject: Get off my lawn!

Blah blah blah"""

serv.sendmail("dave@dabeaz.com", ['bob@yahoo.com'], msg)
```

- Useful if you want to have a program send you a notification, send email to customers, etc.

Copyright (C) 2010, <http://www.dabeaz.com>

2- 32

Exercise 2.3

Time : 15 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

2- 33

<https://powcoder.com>

Add WeChat powcoder

Section 3

Internet Data Handling

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
Overview

- If you write network clients, you will have to worry about a variety of common file formats
- CSV, HTML, XML, JSON, etc.
- In this section, we briefly look at library support for working with such data

CSV Files

- Comma Separated Values

```
Elwood,Blues,"1060 W Addison,Chicago 60637",110  
McGurn,Jack,"4902 N Broadway,Chicago 60640",200
```

- Parsing with the CSV module

```
import csv  
f = open("schmods.csv","r")  
for row in csv.reader(f):  
    # Do something with items in row  
    ...
```

- Understands quoting, various subtle details

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 3

<https://powcoder.com>

Add WeChat powcoder
Parsing HTML

- Suppose you want to parse HTML (maybe obtained via `urlopen`)
- Use the `HTMLParser` module
- A library that processes HTML using an "event-driven" programming style

Copyright (C) 2010, <http://www.dabeaz.com>

3- 4

Parsing HTML

- Define a class that inherits from HTMLParser and define a set of methods that respond to different document features

```
from HTMLParser import HTMLParser
class MyParser(HTMLParser):
    def handle_starttag(self, tag, attrs):
        ...
    def handle_data(self, data):
        ...
    def handle_endtag(self, tag):
        ...
```

starttag data endtag

↓ ↓ ↓

<tag attr="value" attr="value">data</tag>

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 5

<https://powcoder.com>

Add WeChat powcoder Running a Parser

- To run the parser, you create a parser object and feed it some data

```
# Fetch a web page
import urllib
u = urllib.urlopen("http://www.example.com")
data = u.read()

# Run it through the parser
p = MyParser()
p.feed(data)
```

- The parser will scan through the data and trigger the various handler methods

Copyright (C) 2010, <http://www.dabeaz.com>

3- 6

HTML Example

- An example: Gather all links

```
from HTMLParser import HTMLParser
class GatherLinks(HTMLParser):
    def __init__(self):
        HTMLParser.__init__(self)
        self.links = []
    def handle_starttag(self, tag, attrs):
        if tag == 'a':
            for name, value in attrs:
                if name == 'href':
                    self.links.append(value)
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 7

<https://powcoder.com>

Add WeChat powcoder

HTML Example

- Running the parser

```
>>> parser = GatherLinks()
>>> import urllib
>>> data = urllib.urlopen("http://www.python.org").read()
>>> parser.feed(data)
>>> for x in parser.links:
...     print x
/search/
/about
/news/
/doc/
/download/
...
>>>
```

Copyright (C) 2010, <http://www.dabeaz.com>

3- 8

XML Parsing with SAX

- The event-driven style used by HTMLParser is sometimes used to parse XML
- Basis of the SAX parsing interface
- An approach sometimes seen when dealing with large XML documents since it allows for incremental processing

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 9

<https://powcoder.com>

Add WeChat powcoder Brief XML Refresher

- XML documents use structured markup

```
<contact>
  <name>Elwood Blues</name>
  <address>1060 W Addison</address>
  <city>Chicago</city>
  <zip>60616</zip>
</contact>
```

- Documents made up of elements

```
<name>Elwood Blues</name>
```
- Elements have starting/ending tags
- May contain text and other elements

Copyright (C) 2010, <http://www.dabeaz.com>

3- 10

SAX Parsing

- Define a special handler class

```
import xml.sax

class MyHandler(xml.sax.ContentHandler):
    def startDocument(self):
        print "Document start"
    def startElement(self, name, attrs):
        print "Start:", name
    def characters(self, text):
        print "Characters:", text
    def endElement(self, name):
        print "End:", name
```

- In the class, you define methods that capture elements and other parts of the document

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 11

<https://powcoder.com>

Add WeChat powcoder
SAX Parsing

- To parse a document, you create an instance of the handler and give it to the parser

```
# Create the handler object
hand = MyHandler()

# Parse a document using the handler
xml.sax.parse("data.xml", hand)
```

- This reads the file and calls handler methods as different document elements are encountered (start tags, text, end tags, etc.)

Copyright (C) 2010, <http://www.dabeaz.com>

3- 12

Exercise 3.1

Time : 15 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 13

<https://powcoder.com>

Add WeChat powcoder XML and ElementTree

- xml.etree.ElementTree module is one of the easiest ways to parse XML
- Lets look at the highlights

Copyright (C) 2010, <http://www.dabeaz.com>

3- 14

etree Parsing Basics

- Parsing a document

```
from xml.etree.ElementTree import parse
doc = parse("recipe.xml")
```

- This builds a complete parse tree of the entire document
- To extract data, you will perform various kinds of queries on the document object

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 15

<https://powcoder.com>

Add WeChat powcoder etree Parsing Basics

- A mini-reference for extracting data
- Finding one or more elements

```
elem = doc.find("title")
for elem in doc.findall("ingredients/item"):
    statements
```

- Element attributes and properties

```
elem.tag           # Element name
elem.text          # Element text
elem.get(aname [,default]) # Element attributes
```

Copyright (C) 2010, <http://www.dabeaz.com>

3- 16

Obtaining Elements

```
<?xml version="1.0" encoding="iso-8859-1"?>
```

```
<recipe>
```

```
  <title>Famous Guacamole</title>
```

```
  <description>
```

```
    A southwest favorite!
```

```
  </description>
```

```
  <ingredients>
```

```
    <item num="2">Large avocados, chopped</item>
```

```
    <item num="1">Tomato, chopped</item>
```

```
    <item num="1/2" units="C">White onion, chopped</item>
```

```
    <item num="1" units="tbl">Fresh squeezed lemon juice</item>
```

```
    <item num="1">Jalapeno pepper, diced</item>
```

```
    <item num="1" units="tbl">Fresh cilantro, minced</item>
```

```
    <item num="3" units="tsp">Sea Salt</item>
```

```
    <item num="6" units="bottles">Ice-cold beer</item>
```

```
  </ingredients>
```

```
  <directions>
```

```
    Combine all ingredients and hand whisk to desired consistency.
```

```
    Serve and enjoy with ice-cold beers.
```

```
  </directions>
```

```
</recipe>
```

```
doc = parse("recipe.xml")
```

```
desc_elem = doc.find("description")
```

```
desc_text = desc_elem.text
```

or

```
doc = parse("recipe.xml")
```

```
desc_text = doc.findtext("description")
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 17

<https://powcoder.com>

Add WeChat powcoder Iterating over Elements

```
<?xml version="1.0" encoding="iso-8859-1"?>
```

```
<recipe>
```

```
  <title>Famous Guacamole</title>
```

```
  <description>
```

```
    A southwest favorite!
```

```
  </description>
```

```
  <ingredients>
```

```
    <item num="2">Large avocados, chopped</item>
```

```
    <item num="1">Tomato, chopped</item>
```

```
    <item num="1/2" units="C">White onion, chopped</item>
```

```
    <item num="1" units="tbl">Fresh squeezed lemon juice</item>
```

```
    <item num="1">Jalapeno pepper, diced</item>
```

```
    <item num="1" units="tbl">Fresh cilantro, minced</item>
```

```
    <item num="3" units="tsp">Sea Salt</item>
```

```
    <item num="6" units="bottles">Ice-cold beer</item>
```

```
  </ingredients>
```

```
  <directions>
```

```
    Combine all ingredients and hand whisk to desired consistency.
```

```
    Serve and enjoy with ice-cold beers.
```

```
  </directions>
```

```
</recipe>
```

```
doc = parse("recipe.xml")
```

```
for item in doc.findall("ingredients/item"):
```

```
    statements
```

Copyright (C) 2010, <http://www.dabeaz.com>

3- 18

Element Attributes

```
<?xml version="1.0" encoding="iso-8859-1"?>
<recipe>
  <title>Famous Guacamole</title>
  <description>
    A southwest favorite!
  </description>
  <ingredients>
    <item num="1" units="tbl">Fresh cilantro, minced</item>
    <item num="3" units="tsp">Sea Salt</item>
    <item num="6" units="bottles">Ice-cold beer</item>
  </ingredients>
  <directions>
    Combine all ingredients and hand whisk to desired consistency.
    Serve and enjoy with ice-cold beers.
  </directions>
</recipe>
```

```
for item in doc.findall("ingredients/item"):
    num = item.get("num")
    units = item.get("units")
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 19

<https://powcoder.com>

Add WeChat powcoder Search Wildcards

- Specifying a wildcard for an element name

```
items = doc.findall("*/item")
items = doc.findall("ingredients/*")
```

- The * wildcard only matches a single element
- Use multiple wildcards for nesting

```
<?xml version="1.0"?>
<top>
  <a>
    <b>
      <c>text</c>
    </b>
  </a>
</top>
```

```
c = doc.findall("*/*/c")
c = doc.findall("a/*/c")
c = doc.findall("*/b/c")
```

Copyright (C) 2010, <http://www.dabeaz.com>

3- 20

Search Wildcards

- Wildcard for multiple nesting levels (//)

```
items = doc.findall("//item")
```

- More examples

```
<?xml version="1.0"?>
<top>
  <a>
    <b>
      <c>text</c>
    </b>
  </a>
</top>
```

```
c = doc.findall("//c")
c = doc.findall("a//c")
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 21

<https://powcoder.com>

Add WeChat powcoder cElementTree

- There is a C implementation of the library that is significantly faster

```
import xml.etree.cElementTree
doc = xml.etree.cElementTree.parse("data.xml")
```

- For all practical purposes, you should use this version of the library given a choice
- Note :The C version lacks a few advanced customization features, but you probably won't need them

Copyright (C) 2010, <http://www.dabeaz.com>

3- 22

Tree Modification

- ElementTree allows modifications to be made to the document structure

- To add a new child to a parent node

```
node.append(child)
```

- To insert a new child at a selected position

```
node.insert(index, child)
```

- To remove a child from a parent node

```
node.remove(child)
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 23

<https://powcoder.com>

Add WeChat powcoder Tree Output

- If you modify a document, it can be rewritten
- There is a method to write XML

```
doc = xml.etree.ElementTree.parse("input.xml")
# Make modifications to doc
...
# Write modified document back to a file
f = open("output.xml", "w")
doc.write(f)
```

- Individual elements can be turned into strings

```
s = xml.etree.ElementTree.tostring(node)
```

Copyright (C) 2010, <http://www.dabeaz.com>

3- 24

Iterative Parsing

- An alternative parsing interface

```
from xml.etree.ElementTree import iterparse
parse = iterparse("file.xml", ('start','end'))

for event, elem in parse:
    if event == 'start':
        # Encountered an start <tag ...>
        ...
    elif event == 'end':
        # Encountered an end </tag>
        ...
```

- This sweeps over an entire XML document
- Result is a sequence of start/end events and element objects being processed

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 25

<https://powcoder.com>

Add WeChat powcoder Iterative Parsing

- If you combine iterative parsing and tree modification together, you can process large XML documents with almost no memory overhead
- Programming interface is significantly easier to use than a similar approach using SAX
- General idea : Simply throw away the elements no longer needed during parsing

Copyright (C) 2010, <http://www.dabeaz.com>

3- 26

Iterative Parsing

- Programming pattern

```
from xml.etree.ElementTree import iterparse
parser = iterparse("file.xml",('start','end'))

for event,elem in parser:
    if event == 'start':
        if elem.tag == 'parenttag':
            parent = elem
    if event == 'end':
        if elem.tag == 'tagname':
            # process element with tag 'tagname'
            ...
            # Discard the element when done
            parent.remove(elem)
```

- The last step is the critical part

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 27

<https://powcoder.com>

Add WeChat powcoder
Exercise 3.2

Time : 15 Minutes

Copyright (C) 2010, <http://www.dabeaz.com>

3- 28

JSON

- Javascript Object Notation
- A data encoding commonly used on the web when interacting with Javascript
- Sometime preferred over XML because it's less verbose and faster to parse
- Syntax is almost identical to a Python dict

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 29

<https://powcoder.com>

Add WeChat powcoder Sample JSON File

```
{
  "recipe" : {
    "title" : "Famous Guacomole",
    "description" : "A southwest favorite!",
    "ingredients" : [
      {"num": "2", "item": "Large avocados, chopped"},
      {"num": "1/2", "units": "C", "item": "White onion, chopped"},
      {"num": "1", "units": "tbl", "item": "Fresh squeezed lemon juice"},
      {"num": "1", "item": "Jalapeno pepper, diced"},
      {"num": "1", "units": "tbl", "item": "Fresh cilantro, minced"},
      {"num": "3", "units": "tsp", "item": "Sea Salt"},
      {"num": "6", "units": "bottles", "item": "Ice-cold beer"}
    ],
    "directions" : "Combine all ingredients and hand whisk to desired consistency. Serve and enjoy with ice-cold beers."
  }
}
```

Copyright (C) 2010, <http://www.dabeaz.com>

3- 30

Processing JSON Data

- Parsing a JSON document

```
import json
doc = json.load(open("recipe.json"))
```

- Result is a collection of nested dict/lists

```
ingredients = doc['recipe']['ingredients']
for item in ingredients:
    # Process item
    ...
```

- Dumping a dictionary as JSON

```
f = open("file.json", "w")
json.dump(doc, f)
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

3- 31

<https://powcoder.com>

Add WeChat powcoder
Exercise 3.3

Time : 15 Minutes

Copyright (C) 2010, <http://www.dabeaz.com>

3- 32

Section 4

Web Programming Basics

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
Introduction

- The web is (obviously) so pervasive, knowing how to write simple web-based applications is basic knowledge that all programmers should know about
- In this section, we cover the absolute basics of how to make a Python program accessible through the web

Overview

- Some basics of Python web programming
- HTTP Protocol
- CGI scripting
- WSGI (Web Services Gateway Interface)
- Custom HTTP servers

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 3

<https://powcoder.com>

Add WeChat powcoder Disclaimer


- Web programming is a huge topic that could span an entire multi-day class
- It might mean different things
 - Building an entire website
 - Implementing a web service
- Our focus is on some basic mechanisms found in the Python standard library that all Python programmers should know about

Copyright (C) 2010, <http://www.dabeaz.com>

4- 4

HTTP Explained

- HTTP is the underlying protocol of the web
- Consists of requests and responses



Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 5

<https://powcoder.com>

Add WeChat powcoder HTTP Client Requests

- Client (Browser) sends a request

```
GET /index.html HTTP/1.1
Host: www.python.org
User-Agent: Mozilla/5.0 (Macintosh; U; Intel Mac OS X; en-US; rv:1.9.2.1) Gecko/20100101 Firefox/3.6.10
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/css;q=0.8,image/png,*/*;q=0.5
Accept-Language: en-us,en;q=0.5
Accept-Encoding: gzip,deflate
Accept-Charset: ISO-8859-1,utf-8;q=0.7,*;q=0.7
Keep-Alive: 300
Connection: keep-alive
<blank line>
```

- Request line followed by headers that provide additional information about the client

Copyright (C) 2010, <http://www.dabeaz.com>

4- 6

HTTP Responses

- Server sends back a response

HTTP/1.1 200 OK

Date: Thu, 26 Apr 2007 19:54:01 GMT

Server: Apache/2.0.54 (Debian GNU/Linux) DAV/2 SVN/1.1.4 mod

Last-Modified: Thu, 26 Apr 2007 18:40:24 GMT

Accept-Ranges: bytes

Content-Length: 14315

Connection: close

Content-Type: text/html

<HTML>

...

- Response line followed by headers that further describe the response contents

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 7

<https://powcoder.com>

Add WeChat powcoder HTTP Protocol

- There are a small number of request types

GET

POST

HEAD

PUT

- There are standardized response codes

200 OK

403 Forbidden

404 Not Found

501 Not implemented

...

- But, this isn't an exhaustive tutorial

Copyright (C) 2010, <http://www.dabeaz.com>

4- 8

Content Encoding

- Content is described by these header fields:

```
Content-type:  
Content-length:
```

- Example:

```
Content-type: image/jpeg  
Content-length: 12422
```

- Of these, Content-type is the most critical
- Length is optional, but it's polite to include it if it can be determined in advance

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 9

<https://powcoder.com>

Add WeChat powcoder Payload Packaging

- Responses must follow this formatting

Headers	
...	
Content-type: image/jpeg	
Content-length: 12422	
...	
\r\n	(Blank Line)
Content	
(12422 bytes)	

Copyright (C) 2010, <http://www.dabeaz.com>

4- 10

Exercise 4.1

Time : 10 Minutes

Assignment Project Exam Help


Copyright (C) 2010, <http://www.dabeaz.com>

4- 11

<https://powcoder.com>

Add WeChat powcoder Role of Python

- Most web-related Python programming pertains to the operation of the server



- Python scripts used on the server to create, manage, or deliver content back to clients

Copyright (C) 2010, <http://www.dabeaz.com>

4- 12

Typical Python Tasks

- Static content generation. One-time generation of static web pages to be served by a standard web server such as Apache.
- Dynamic content generation. Python scripts that produce output in response to requests (e.g., form processing, CGI scripting).

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 13

<https://powcoder.com>

Add WeChat powcoder Content Generation

- It is often overlooked, but Python is a useful tool for simply creating static web pages
- Example :Taking various pages of content, adding elements, and applying a common format across all of them.
- Web server simply delivers all of the generated content as normal files

Copyright (C) 2010, <http://www.dabeaz.com>


4- 14

Example : Page Templates

- Create a page "template" file

Note the special \$variable → **\$content**

```
<html>
  <body>
    <table width=700>
      <tr><td>
        Your Logo : Navigation Links
      <hr>
      </td></tr>
      <tr><td>
        $content
      <hr>
      <em>Copyright (C) 2008</em>
      </td></tr>
    </table>
  </body>
</html>
```



Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 15

<https://powcoder.com>

Add WeChat powcoder Example : Page Templates

- Use template strings to render pages

```
from string import Template

# Read the template string
pagetemplate = Template(open("template.html").read())

# Go make content
page = make_content()

# Render the template to a file
f = open(outfile, "w")
f.write(pagetemplate.substitute(content=page))
```

- Key idea : If you want to change the appearance, you just change the template

Copyright (C) 2010, <http://www.dabeaz.com>

4- 16

Commentary

- Using page templates to generate static content is extremely common
- For simple things, just use the standard library modules (e.g., `string.Template`)
- For more advanced applications, there are numerous third-party template packages

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 17

<https://powcoder.com>

Add WeChat powcoder
Exercise 4.2

Time : 10 Minutes

Copyright (C) 2010, <http://www.dabeaz.com>

4- 18

HTTP Servers

- Python comes with libraries that implement simple self-contained web servers
- Very useful for testing or special situations where you want web service, but don't want to install something larger (e.g., Apache)
- Not high performance, sometimes "good enough" is just that

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 19

<https://powcoder.com>

Add WeChat powcoder A Simple Web Server

- Serve files from a directory

```
from BaseHTTPServer import HTTPServer
from SimpleHTTPServer import SimpleHTTPRequestHandler
import os
os.chdir("/home/docs/html")
serv = HTTPServer(("", 8080), SimpleHTTPRequestHandler)
serv.serve_forever()
```

- This creates a minimal web server
- Connect with a browser and try it out

Copyright (C) 2010, <http://www.dabeaz.com>

4- 20

Exercise 4.3

Time : 10 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 21

<https://powcoder.com>

Add WeChat powcoder A Web Server with CGI

- Serve files and allow CGI scripts

```
from BaseHTTPServer import HTTPServer
from CGIHTTPServer import CGIHTTPRequestHandler
import os
os.chdir("/home/docs/html")
serv = HTTPServer(("", 8080), CGIHTTPRequestHandler)
serv.serve_forever()
```

- Executes scripts in `"/cgi-bin"` and `"/htbin"` directories in order to create dynamic content

Copyright (C) 2010, <http://www.dabeaz.com>

4- 22

CGI Scripting

- Common Gateway Interface
- A common protocol used by existing web servers to run server-side scripts, plugins
- Example: Running Python, Perl, Ruby scripts under Apache, etc.
- Classically associated with form processing, but that's far from the only application

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 23

<https://powcoder.com>

Add WeChat powcoder CGI Example

- A web-page might have a form on it

Your name:

Your email:

- Here is the underlying HTML code

```
<FORM ACTION="/cgi-bin/subscribe.py" METHOD="POST">  
Your name: <INPUT type="text" name="name" size="30"><br>  
Your email: <INPUT type="text" name="email" size="30"><br>  
<INPUT type="submit" name="submit-button" value="Subscribe">
```

Specifies a CGI program on the server

Copyright (C) 2010, <http://www.dabeaz.com>

4- 24

CGI Example

- Forms have submitted fields or parameters

```
<FORM ACTION="/cgi-bin/subscribe.py" METHOD="POST">
Your name: <INPUT type="text" name="name" size="30"><br>
Your email: <INPUT type="text" name="email" size="30"><br>
<INPUT type="submit" name="submit-button" value="Subscribe">
```

- A request will include both the URL (cgi-bin/subscribe.py) along with the field values

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 25

<https://powcoder.com>

Add WeChat powcoder

CGI Example

- Request encoding looks like this:

Request → POST /cgi-bin/subscribe.py HTTP/1.1
User-Agent: Mozilla/5.0 (Macintosh; U; Intel Mac OS
Accept: text/xml,application/xml,application/xhtml
Accept-Language: en-us,en;q=0.5
...

Query String → name=David+Beazley&email=dave%40dabeaz.com&submit-button=Subscribe HTTP/1.1


- Request tells the server what to run
- Query string contains encoded form fields

Copyright (C) 2010, <http://www.dabeaz.com>

4- 26

CGI Mechanics

- CGI was originally implemented as a scheme for launching processing scripts as a subprocess to a web server



- Script will decode the request and carry out some kind of action

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 27

<https://powcoder.com>

Add WeChat powcoder Classic CGI Interface

- Server populates environment variables with information about the request

```
import os
os.environ['SCRIPT_NAME']
os.environ['REMOTE_ADDR']
os.environ['QUERY_STRING']
os.environ['REQUEST_METHOD']
os.environ['CONTENT_TYPE']
os.environ['CONTENT_LENGTH']
os.environ['HTTP_COOKIE']
...
```

- stdin/stdout provide I/O link to server

```
sys.stdin      # Read to get data sent by client
sys.stdout     # Write to create the response
```

Copyright (C) 2010, <http://www.dabeaz.com>

4- 28

CGI Query Variables

- For GET requests, an env. variable is used

```
query = os.environ['QUERY_STRING']
```

- For POST requests, you read from stdin

```
if os.environ['REQUEST_METHOD'] == 'POST':  
    size = int(os.environ['CONTENT_LENGTH'])  
    query = sys.stdin.read(size)
```

- This yields the raw query string

```
name=David+Beazley&email=dave  
%40dabeaz.com&submit-button=Subscribe
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 29

<https://powcoder.com>

Add WeChat powcoder cgi Module

- A utility library for decoding requests
- Major feature: Getting the passed parameters

```
#!/usr/bin/env python  
# subscribe.py  
import cgi  
form = cgi.FieldStorage() ← Parse parameters  
  
# Get various field values  
name = form.getvalue('name')  
email = form.getvalue('email')
```

- All CGI scripts start like this
- FieldStorage parses the incoming request into a dictionary-like object for extracting inputs

Copyright (C) 2010, <http://www.dabeaz.com>

4- 30

CGI Responses

- CGI scripts respond by simply printing response headers and the raw content

```
name = form.getvalue('name')
email = form.getvalue('email')
... do some kind of processing ...

# Output a response
print "Status: 200 OK"
print "Content-type: text/html"
print
print "<html><head><title>Success!</title></head><body>"
print "Hello %s, your email is %s" % (name,email)
print "</body>"
```

- Normally you print HTML, but any kind of data can be returned (for web services, you might return XML, JSON, etc)

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 31

<https://powcoder.com>

Add WeChat powcoder Note on Status Codes

- In CGI, the server status code is set by including a special "Status:" header field

```
import cgi
form = cgi.FieldStorage()
name = form.getvalue('name')
email = form.getvalue('email')
...
→ print "Status: 200 OK"
print "Content-type: text/html"
print
print "<html><head><title>Success!</title></head><body>"
print "Hello %s, your email is %s" % (name,email)
print "</body>"
```

- This is a special server directive that sets the response status

Copyright (C) 2010, <http://www.dabeaz.com>

4- 32

CGI Commentary

- There are many more minor details (consult a reference on CGI programming)
- The basic idea is simple
 - Server runs a script
 - Script receives inputs from environment variables and stdin
 - Script produces output on stdout
- It's old-school, but sometimes it's all you get

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 33

<https://powcoder.com>

Add WeChat powcoder
Exercise 4.4

Time : 25 Minutes

Copyright (C) 2010, <http://www.dabeaz.com>

4- 34

WSGI

- Web Services Gateway Interface (WSGI)
- This is a standardized interface for creating Python web services
- Allows one to create code that can run under a wide variety of web servers and frameworks as long as they also support WSGI (and most do)
- So, what is WSGI?

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 35

<https://powcoder.com>

Add WeChat powcoder WSGI Interface

- WSGI is an application programming interface loosely based on CGI programming
- In CGI, there are just two basic features
 - Getting values of inputs (env variables)
 - Producing output by printing
- WSGI takes this concept and repackages it into a more modular form

Copyright (C) 2010, <http://www.dabeaz.com>

4- 36

WSGI Example

- With WSGI, you write an "application"
- An application is just a function (or callable)

```
def hello_app(environ, start_response):  
    status = "200 OK"  
    response_headers = [ ('Content-type','text/plain')]  
    response = []  
  
    start_response(status,response_headers)  
    response.append("Hello World\n")  
    response.append("You requested :"+environ['PATH_INFO'])  
    return response
```

- This function encapsulates the handling of some request that will be received

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder WSGI Applications

- Applications always receive just two inputs

```
def hello_app(environ, start_response):  
    status = "200 OK"  
    response_headers = [ ('Content-type','text/plain')]  
    response = []  
  
    start_response(status,response_headers)  
    response.append("Hello World\n")  
    response.append("You requested :"+environ['PATH_INFO'])  
    return response
```

- environ - A dictionary of input parameters
- start_response - A callable (e.g., function)

WSGI Environment

- The environment contains CGI variables

```
def hello_app(environ, start_response):  
    status = "200 OK"  
    response_headers = [ ('Content-type','text/plain')]  
  
    environ['REQUEST_METHOD']  
    environ['SCRIPT_NAME']  
    environ['PATH_INFO']  
    environ['QUERY_STRING']  
    environ['CONTENT_TYPE']  
    environ['CONTENT_LENGTH']  
    environ['SERVER_NAME']  
    ...
```

['PATH_INFO']

- The meaning and values are exactly the same as in traditional CGI programs

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder WSGI Environment

- Environment also contains some WSGI variables

```
def hello_app(environ, start_response):  
    status = "200 OK"  
    response_headers = [ ('Content-type','text/plain')]  
  
    environ['wsgi.input']  
    environ['wsgi.errors']  
    environ['wsgi.url_scheme']  
    environ['wsgi.multithread']  
    environ['wsgi.multiprocess']  
    ...
```

['PATH_INFO']

- wsgi.input - A file-like object for reading data
- wsgi.errors - File-like object for error output

Processing WSGI Inputs

- Parsing of query strings is similar to CGI

```
import cgi
def sample_app(environ, start_response):
    fields = cgi.FieldStorage(environ['wsgi.input'],
                              environ=environ)
    # fields now has the CGI query variables
    ...
```

- You use FieldStorage() as before, but give it extra parameters telling it where to get data

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 41

<https://powcoder.com>

Add WeChat powcoder WSGI Responses

- The second argument is a function that is called to initiate a response

```
def hello_app(environ, start_response):
    status = "200 OK"
    response_headers = [ ('Content-type', 'text/plain')]
    response = []

    start_response(status, response_headers)
    response.append("Hello World\n")
    response.append("You requested : "+environ['PATH_INFO'])
    return response
```



- You pass it two parameters
 - A status string (e.g., "200 OK")
 - A list of (header, value) HTTP header pairs

Copyright (C) 2010, <http://www.dabeaz.com>

4- 42

WSGI Responses

- `start_response()` is a hook back to the server
- Gives the server information for formulating the response (status, headers, etc.)
- Prepares the server for receiving content data

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 43

<https://powcoder.com>

Add WeChat powcoder WSGI Content

- Content is returned as a sequence of byte strings

```
def hello_app(environ, start_response):
    status = "200 OK"
    response_headers = [ ('Content-type', 'text/plain')]
    response = []

    start_response(status, response_headers)
    response.append("Hello World\n")
    response.append("You requested :"+environ['PATH_INFO'])
    return response
```

- Note: This differs from CGI programming where you produce output using `print`.

Copyright (C) 2010, <http://www.dabeaz.com>

4- 44

WSGI Content Encoding

- WSGI applications must always produce bytes
- If working with Unicode, it must be encoded

```
def hello_app(environ, start_response):  
    status = "200 OK"  
    response_headers = [ ('Content-type', 'text/html') ]  
  
    start_response(status, response_headers)  
    return [u"That's a spicy Jalape\u00f1o".encode('utf-8')]
```

- This is a little tricky--if you're not anticipating Unicode, everything can break if a Unicode string is returned (be aware that certain modules such as database modules may do this)

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 45

<https://powcoder.com>

Add WeChat powcoder WSGI Deployment

- The main point of WSGI is to simplify deployment of web applications
- You will notice that the interface depends on no third party libraries, no objects, or even any standard library modules
- That is intentional. WSGI apps are supposed to be small self-contained units that plug into other environments

Copyright (C) 2010, <http://www.dabeaz.com>

4- 46

WSGI Deployment

- Running a simple stand-alone WSGI server

```
from wsgiref import simple_server
httpd = simple_server.make_server("", 8080, hello_app)
httpd.serve_forever()
```

- This runs an HTTP server for testing
- You probably wouldn't deploy anything using this, but if you're developing code on your own machine, it can be useful

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 47

<https://powcoder.com>

Add WeChat powcoder WSGI and CGI

- WSGI applications can run on top of standard CGI scripting (which is useful if you're interfacing with traditional web servers).

```
#!/usr/bin/env python
# hello.py

def hello_app(environ, start_response):
    ...

import wsgiref.handlers
wsgiref.handlers.CGIHandler().run(hello_app)
```

Copyright (C) 2010, <http://www.dabeaz.com>

4- 48

Exercise 4.5

Time : 20 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 49

<https://powcoder.com>

Add WeChat powcoder Customized HTTP

- Can implement customized HTTP servers
- Use BaseHTTPServer module
- Define a customized HTTP handler object
- Requires some knowledge of the underlying HTTP protocol

Copyright (C) 2010, <http://www.dabeaz.com>

4- 50

Customized HTTP

- Example: A Hello World Server

```
from BaseHTTPServer import BaseHTTPRequestHandler,HTTPServer

class HelloHandler(BaseHTTPRequestHandler):
    def do_GET(self):
        if self.path == '/hello':
            self.send_response(200,"OK")
            self.send_header('Content-type','text/plain')
            self.end_headers()
            self.wfile.write("""<HTML>
<HEAD><TITLE>Hello</TITLE></HEAD>
<BODY>Hello World!</BODY></HTML>""")

serv = HTTPServer(("",8080),HelloHandler)
serv.serve_forever()
```

- Defined a method for "GET" requests

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 51

<https://powcoder.com>


Add WeChat powcoder Customized HTTP

- A more complex server

```
from BaseHTTPServer import BaseHTTPRequestHandler,HTTPServer

class MyHandler(BaseHTTPRequestHandler):
    def do_GET(self):
    ...
    def do_POST(self):
    ...
    def do_HEAD(self):
    ...
    def do_PUT(self):
    ...

serv = HTTPServer(("",8080),MyHandler)
serv.serve_forever()
```



Redefine the behavior of the server by defining code for all of the standard HTTP request types

- Can customize everything (requires work)

Copyright (C) 2010, <http://www.dabeaz.com>

4- 52

Exercise 4.6

Time : 15 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 53

<https://powcoder.com>

Add WeChat powcoder Web Frameworks

- Python has a huge number of web frameworks
 - Zope
 - Django
 - Turbogears
 - Pylons
 - CherryPy
 - Google App Engine
- Frankly, there are too many to list here..

Copyright (C) 2010, <http://www.dabeaz.com>

4- 54

Web Frameworks

- Web frameworks build upon previous concepts
- Provide additional support for
 - Form processing
 - Cookies/sessions
 - Database integration
 - Content management
- Usually require their own training course

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

4- 55

<https://powcoder.com>

Add WeChat powcoder Commentary

- If you're building small self-contained components or middleware for use on the web, you're probably better off with WSGI
- The programming interface is minimal
- The components you create will be self-contained if you're careful with your design
- Since WSGI is an official part of Python, virtually all web frameworks will support it

Copyright (C) 2010, <http://www.dabeaz.com>

4- 56

Section 5

Advanced Networking

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
Overview

- An assortment of advanced networking topics
- The Python network programming stack
- Concurrent servers
- Distributed computing
- Multiprocessing

Problem with Sockets

- In part I, we looked at low-level programming with sockets
- Although it is possible to write applications based on that interface, most of Python's network libraries use a higher level interface
- For servers, there's the SocketServer module

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 3

<https://powcoder.com>

Add WeChat powcoder
SocketServer

- A module for writing custom servers
- Supports TCP and UDP networking
- The module aims to simplify some of the low-level details of working with sockets and put to all of that functionality in one place

Copyright (C) 2010, <http://www.dabeaz.com>

5- 4

SocketServer Example

- To use SocketServer, you define handler objects using classes
- Example: A time server

```
import SocketServer
import time

class TimeHandler(SocketServer.BaseRequestHandler):
    def handle(self):
        self.request.sendall(time.ctime()+"\n")

serv = SocketServer.TCPServer(("",8000),TimeHandler)
serv.serve_forever()
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 5

<https://powcoder.com>

Add WeChat powcoder SocketServer Example


- Handler Class

```
import SocketServer
import time

class TimeHandler(SocketServer.BaseRequestHandler):
    def handle(self):
        self.request.sendall(time.ctime()+"\n")

serv = SocketServer.TCPServer(("",8000),TimeHandler)
serv.serve_forever()
```

Server is implemented
by a handler class



Copyright (C) 2010, <http://www.dabeaz.com>


5- 6

SocketServer Example

- Handler Class

```
import SocketServer
import time
```

Must inherit from
BaseRequestHandler



```
class TimeHandler(SocketServer.BaseRequestHandler):
    def handle(self):
        self.request.sendall(time.ctime())

serv = SocketServer.TCPServer(("", 8000), TimeHandler)
serv.serve_forever()
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 7

<https://powcoder.com>


Add WeChat powcoder SocketServer Example

- handle() method

```
import SocketServer
import time
```

```
class TimeHandler(SocketServer.BaseRequestHandler):
    def handle(self):
        self.request.sendall(time.ctime())
```

Define handle()
to implement the
server action



```
serv = SocketServer.TCPServer(("", 8000), TimeHandler)
serv.serve_forever()
```

Copyright (C) 2010, <http://www.dabeaz.com>

5- 8

SocketServer Example

- Client socket connection

```
import SocketServer
import time

class TimeHandler(SocketServer.BaseRequestHandler):
    def handle(self):
        self.request.sendall(time.ctime())

serv = SocketServer.TCPServer(('', 8000), TimeHandler)
serv.serve_forever()
```

Socket object
for client connection

- This is a bare socket object

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 9

<https://powcoder.com>

Add WeChat powcoder SocketServer Example

- Creating and running the server

```
import SocketServer
import time

class TimeHandler(SocketServer.BaseRequestHandler):
    def handle(self):
        self.request.sendall(time.ctime())

serv = SocketServer.TCPServer(('', 8000), TimeHandler)
serv.serve_forever()
```

Creates a server and
connects a handler

Runs the server
forever

Copyright (C) 2010, <http://www.dabeaz.com>

5- 10

Execution Model

- Server runs in a loop waiting for requests
- On each connection, the server creates a new instantiation of the handler class
- The handle() method is invoked to handle the logic of communicating with the client
- When handle() returns, the connection is closed and the handler instance is destroyed

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 11

<https://powcoder.com>

Add WeChat powcoder
Exercise 5.1

Time : 15 Minutes

Copyright (C) 2010, <http://www.dabeaz.com>

5- 12

Big Picture

- A major goal of SocketServer is to simplify the task of plugging different server handler objects into different kinds of server implementations
- For example, servers with different implementations of concurrency, extra security features, etc.

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 13

<https://powcoder.com>

Add WeChat powcoder Concurrent Servers

- SocketServer supports different kinds of concurrency implementations

```
TCPServer          - Synchronous TCP server (one client)
ForkingTCPServer   - Forking server (multiple clients)
ThreadingTCPServer - Threaded server (multiple clients)
```

- Just pick the server that you want and plug the handler object into it

```
serv = SocketServer.ForkingTCPServer(("", 8000), TimeHandler)
serv.serve_forever()

serv = SocketServer.ThreadingTCPServer(("", 8000), TimeHandler)
serv.serve_forever()
```

Copyright (C) 2010, <http://www.dabeaz.com>

5- 14

Server Mixin Classes

- SocketServer defines these mixin classes

```
ForkingMixIn
ThreadingMixIn
```

- These can be used to add concurrency to other server objects (via multiple inheritance)

```
from BaseHTTPServer import HTTPServer
from SimpleHTTPServer import SimpleHTTPRequestHandler
from SocketServer import ThreadingMixIn
```

```
class ThreadedHTTPServer(ThreadingMixIn, HTTPServer):
    pass
```

```
serv = ThreadedHTTPServer(("",8080),
                           SimpleHTTPRequestHandler)
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 15

<https://powcoder.com>

Add WeChat powcoder Server Subclassing

- SocketServer objects are also subclassed to provide additional customization
- Example: Security/Firewalls

```
class RestrictedTCPServer(TCPServer):
    # Restrict connections to loopback interface
    def verify_request(self, request, addr):
        host, port = addr
        if host != '127.0.0.1':
            return False
        else:
            return True

serv = RestrictedTCPServer(("",8080),TimeHandler)
serv.serve_forever()
```

Copyright (C) 2010, <http://www.dabeaz.com>

5- 16

Exercise 5.2

Time : 15 Minutes

Assignment Project Exam Help


Copyright (C) 2010, <http://www.dabeaz.com>

5- 17

<https://powcoder.com>

Add WeChat powcoder Distributed Computing

- It is relatively simple to build Python applications that span multiple machines or operate on clusters



Copyright (C) 2010, <http://www.dabeaz.com>

5- 18

Discussion

- Keep in mind: Python is a "slow" interpreted programming language
- So, we're not necessarily talking about high performance computing in Python (e.g., number crunching, etc.)
- However, Python can serve as a very useful distributed scripting environment for controlling things on different systems

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 19

<https://powcoder.com>

Add WeChat powcoder
XML-RPC

- Remote Procedure Call
- Uses HTTP as a transport protocol
- Parameters/Results encoded in XML
- Supported by languages other than Python

Copyright (C) 2010, <http://www.dabeaz.com>

5- 20

Simple XML-RPC

- How to create a stand-alone server

```
from SimpleXMLRPCServer import SimpleXMLRPCServer

def add(x,y):
    return x+y

s = SimpleXMLRPCServer(("",8080))
s.register_function(add)
s.serve_forever()
```

- How to test it (xmlrpclib)

```
>>> import xmlrpclib
>>> s = xmlrpclib.ServerProxy("http://localhost:8080")
>>> s.add(3,5)
8
>>> s.add("Hello","World")
"HelloWorld"
```

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 21

<https://powcoder.com>

Add WeChat powcoder Simple XML-RPC

- Adding multiple functions

```
from SimpleXMLRPCServer import SimpleXMLRPCServer

s = SimpleXMLRPCServer(("",8080))
s.register_function(add)
s.register_function(foo)
s.register_function(bar)
s.serve_forever()
```

- Registering an instance (exposes all methods)

```
from SimpleXMLRPCServer import SimpleXMLRPCServer

s = SimpleXMLRPCServer(("",8080))
obj = SomeObject()
s.register_instance(obj)
s.serve_forever()
```

Copyright (C) 2010, <http://www.dabeaz.com>

5- 22

XML-RPC Commentary

- XML-RPC is extremely easy to use
- Almost too easy--you might get the perception that it's extremely limited or fragile
- I have encountered a lot of major projects that are using XML-RPC for distributed control
- Users seem to love it (I concur)

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 23

<https://powcoder.com>

Add WeChat powcoder XML-RPC and Binary

- One wart of caution...
- XML-RPC assumes all strings are UTF-8 encoded Unicode
- Consequence: You can't shove a string of raw binary data through an XML-RPC call
- For binary: must base64 encode/decode
- base64 module can be used for this

Copyright (C) 2010, <http://www.dabeaz.com>

5- 24

Exercise 5.3

Time : 15 Minutes

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 25

<https://powcoder.com>

Add WeChat powcoder Serializing Python Objects

- In distributed applications, you may want to pass various kinds of Python objects around (e.g., lists, dicts, sets, instances, etc.)
- Libraries such as XML-RPC support simple data types, but not anything more complex
- However, serializing arbitrary Python objects into byte-strings is quite simple

Copyright (C) 2010, <http://www.dabeaz.com>

5- 26

pickle Module

- A module for serializing objects
- Serializing an object onto a "file"

```
import pickle
...
pickle.dump(someobj, f)
```

- Unserializing an object from a file

```
someobj = pickle.load(f)
```

- Here, a file might be a file, a pipe, a wrapper around a socket, etc.

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 27

<https://powcoder.com>

Add WeChat powcoder Pickling to Strings

- Pickle can also turn objects into byte strings

```
import pickle
# Convert to a string
s = pickle.dumps(someobj, protocol)
...
# Load from a string
someobj = pickle.loads(s)
```

- This can be used if you need to embed a Python object into some other messaging protocol or data encoding

Copyright (C) 2010, <http://www.dabeaz.com>

5- 28

Example

- Using pickle with XML-RPC

```
# addserv.py
import pickle

def add(px,py):
    x = pickle.loads(px)
    y = pickle.loads(py)
    return pickle.dumps(x+y)

from SimpleXMLRPCServer import SimpleXMLRPCServer
serv = SimpleXMLRPCServer(("",15000))
serv.register_function(add)
serv.serve_forever()
```

- Notice: All input arguments and return values are encoded/decoded with pickle

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 29

<https://powcoder.com>

Add WeChat powcoder

Example

- Passing Python objects from the client

```
>>> import pickle
>>> import xmlrpclib
>>> serv = xmlrpclib.ServerProxy("http://localhost:15000")
>>> a = [1,2,3]
>>> b = [4,5]
>>> r = serv.add(pickle.dumps(a),pickle.dumps(b))
>>> c = pickle.loads(r)
>>> c
[1, 2, 3, 4, 5]
>>>
```

- Again, all input and return values are processed through pickle

Copyright (C) 2010, <http://www.dabeaz.com>

5- 30

Miscellaneous Comments

- Pickle is really only useful if used in a Python-only environment
- Would not use if you need to communicate to other programming languages
- There are also security concerns
- Never use pickle with untrusted clients (malformed pickles can be used to execute arbitrary system commands)

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 31

<https://powcoder.com>

Add WeChat powcoder
Exercise 5.4

Time : 15 Minutes

Copyright (C) 2010, <http://www.dabeaz.com>

5- 32

multiprocessing

- Python 2.6/3.0 include a new library module (multiprocessing) that can be used for different forms of distributed computation
- It is a substantial module that also addresses interprocess communication, parallel computing, worker pools, etc.
- Will only show a few network features here

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 33

<https://powcoder.com>

Add WeChat powcoder Connections

- Creating a dedicated connection between two Python interpreter processes
- Listener (server) process

```
from multiprocessing.connection import Listener
serv = Listener(("", 16000), authkey="12345")
c = serv.accept()
```

- Client process

```
from multiprocessing.connection import Client
c = Client(("servername", 16000), authkey="12345")
```


- On surface, looks similar to a TCP connection

Copyright (C) 2010, <http://www.dabeaz.com>

5- 34

Connection Use

- Connections allow bidirectional message passing of arbitrary Python objects



- Underneath the covers, everything routes through the pickle module
- Similar to a network connection except that you just pass objects through it

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 35

<https://powcoder.com>

Add WeChat powcoder Example

- Example server using multiprocessing

```
# addserv.py

def add(x,y):
    return x+y

from multiprocessing.connection import Listener
serv = Listener("",16000),authkey="12345")
c = serv.accept()
while True:
    x,y = c.recv()          # Receive a pair
    c.send(add(x,y))        # Send result of add(x,y)
```

- Note: Omitting a variety of error checking/exception handling

Copyright (C) 2010, <http://www.dabeaz.com>

5- 36

Example

- Client connection with multiprocessing

```
>>> from multiprocessing.connection import Client
>>> client = Client(("",16000),authkey="12345")
>>> a = [1,2,3]
>>> b = [4,5]
>>> client.send((a,b))
>>> c = client.recv()
>>> c
[1, 2, 3, 4, 5]
>>>
```

- Even though pickle is being used underneath the covers, you don't see it here

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 37

<https://powcoder.com>

Add WeChat powcoder Commentary

- Multiprocessing module already does the work related to pickling, error handling, etc.
- Can use it as the foundation for something more advanced
- There are many more features of multiprocessing not shown here (e.g., features related to distributed objects, parallel processing, etc.)

Copyright (C) 2010, <http://www.dabeaz.com>

5- 38

Commentary

- Multiprocessing is a good choice if you're working strictly in a Python environment
- It will be faster than XML-RPC
- It has some security features (authkey)
- More flexible support for passing Python objects around

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 39

<https://powcoder.com>

Add WeChat powcoder
What about...

- CORBA? SOAP? Others?
- There are third party libraries for this
- Honestly, most Python programmers aren't into big heavyweight distributed object systems like this (too much trauma)
- However, if you're into distributed objects, you should probably look at the Pyro project (<http://pyro.sourceforge.net>)

Copyright (C) 2010, <http://www.dabeaz.com>

5- 40

Network Wrap-up

- Have covered the basics of network support that's bundled with Python (standard lib)
- Possible directions from here...
 - Concurrent programming techniques (often needed for server implementation)
 - Parallel computing (scientific computing)
 - Web frameworks

Assignment Project Exam Help

Copyright (C) 2010, <http://www.dabeaz.com>

5- 41

<https://powcoder.com>

Add WeChat powcoder
Exercise 5.5

Time : 15 Minutes

Copyright (C) 2010, <http://www.dabeaz.com>

5- 42

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Python Network Programming Index

A

accept() method, of sockets, 1-19, 1-22
Address binding, TCP server, 1-20
Addressing, network, 1-4
Asynchronous network server, 1-52

B

BaseRequestHandler, SocketServer module, 5-5
bind() method, of sockets, 1-19, 1-20, 1-42
Browser, emulating in HTTP requests, 2-21
build_opener() function, urllib2 module, 2-24

C

cElementTree module, 3-22
cgi module, 4-30
CGI scripting, 4-23, 4-24, 4-25, 4-26, 4-27
CGI scripting, and WSGI, 4-28
CGI scripting, creating a response, 4-31, 4-32
CGI scripting, environment variables, 4-28
CGI scripting, I/O model, 4-28
CGI scripting, parsing query variables, 4-30
CGI scripting, query string, 4-26
CGI scripting, query variables, 4-29
CherryPy, 4-54
Client objects, multiprocessing module, 5-34
Client/Server programming, 1-8
close() method, of sockets, 1-16, 1-25
Concurrency, and socket programming, 1-46
connect() method, of sockets, 1-16
Connections, network, 1-7
Content encoding, HTTP responses, 4-9
Cookie handling and HTTP requests, 2-25
Cookies, and urllib2 module, 2-17
CORBA, 5-40
Creating custom openers for HTTP requests, 2-24
csv module, 3-3

D

Datagram, 1-43
Distributed computing, 5-18, 5-19

Django, 4-54
dump() function, pickle module, 5-27
dumps() function, pickle module, 5-28

E

ElementTree module, modifying document structure, 3-23
ElementTree module, performance, 3-22
ElementTree module, xml.etree package, 3-14
ElementTree, attributes, 3-19
ElementTree, incremental XML parsing, 3-25
ElementTree, wildcards, 3-20
ElementTree, writing XML, 3-24
End of file, of sockets, 1-32
environ variable, os module, 4-28
Error handling, HTTP requests, 2-22

F

FieldStorage object, cgi module, 4-30
File upload, via urllib, 2-28
Files, reading from a socket, 1-37
Forking server, 1-51
ForkingMixIn class, SocketServer module, 5-15
ForkingTCPServer, SocketServer module, 5-14
ForkingUDPServer, SocketServer module, 5-14
Form data, posting in an HTTP request, 2-10, 2-11, 2-20
FTP server, interacting with, 2-29
FTP, uploading files to a server, 2-30
ftplib module, 2-29

G

gethostbyaddr() function, socket module, 1-53
gethostbyname() function, socket module, 1-53
gethostname() function, socket module, 1-53
Google AppEngine, 4-54

H

Hostname, 1-4
Hostname, obtaining, 1-53
HTML, parsing of, 3-4, 3-7
HTMLParser module, 3-5, 3-7

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

HTTP cookies, 2-25
HTTP protocol, 4-5
HTTP request, with cookie handling, 2-25
HTTP status code, obtaining with urllib, 2-14
HTTP, client-side protocol, 2-31
HTTP, methods, 4-8
HTTP, request structure, 4-6
HTTP, response codes, 4-8
HTTP, response content encoding, 4-9
HTTP, response structure, 4-7, 4-10, 4-12
httplib module, 2-31

I

Interprocess communication, 1-44
IP address, 1-4
IPC, 1-44
IPv4 socket, 1-13
IPv6 socket, 1-13

J

JSON, 3-29
json module, 3-31

L

Limitations, of urllib module, 2-28
listen() method, of sockets, 1-19, 1-21
Listener objects, multiprocessing module, 5-34
load() function, pickle module, 5-27
loads() function, pickle module, 5-28

M

makefile() method, of sockets, 1-37
multiprocessing module, 5-33

N

netstat, 1-6
Network addresses, 1-4, 1-7
Network programming, client-server concept, 1-8
Network programming, standard port assignments, 1-5

O

Objects, serialization of, 5-26
Opener objects, urllib2 module, 2-23
OpenSSL, 2-5

P

Parsing HTML, 3-7
Parsing, JSON, 3-29
Parsing, of HTML, 3-5
pickle module, 5-27
POST method, of HTTP requests, 2-6, 2-7
Posting form data, HTTP requests, 2-10, 2-11, 2-20
Pylons, 4-54

Q

Query string, and CGI scripting, 4-26

R

Raw Sockets, 1-45
recv() method, of sockets, 1-16
recvfrom() method, of sockets, 1-42, 1-43
Request objects, urllib2 module, 2-19
Request-response cycle, network programming, 1-9
RFC-2822 headers, 4-6

S

sax module, xml package, 3-11
select module, 1-52
select() function, select module, 1-52
send() method, of sockets, 1-16, 1-24
sendall() method, of sockets, 1-31
Sending email, 2-32
sendto() method, of sockets, 1-42, 1-43
Serialization, of Python objects, 5-26
serve_forever() method, SocketServer, 5-5
setsockopt() method, of sockets, 1-36
settimeout() method, of sockets, 1-34
SimpleXMLRPCServer module, 5-21

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- simple_server module, wsgiref package, 4-46, 4-47
- smtplib module, 2-32
- SOAP, 5-40
- socket module, 1-13
- socket() function, socket module, 1-13
- Socket, using for server or client, 1-15
- Socket, wrapping with a file object, 1-37
- Sockets, 1-12, 1-13
- Sockets, and concurrency, 1-46
- Sockets, asynchronous server, 1-52
- Sockets, end of file indication, 1-32
- Sockets, forking server example, 1-51
- Sockets, partial reads and writes, 1-29
- Sockets, setting a timeout, 1-34
- Sockets, setting options, 1-36
- Sockets, threaded server, 1-50
- SocketServer module, 5-4
- SocketServer, subclassing, 5-16
- Standard port assignments, 1-5

- UDPServer, SocketServer module, 5-14
- Unix domain sockets, 1-44
- Uploading files, to an FTP server, 2-30
- URL, parameter encoding, 2-6, 2-7
- urlencode() function, urllib module, 2-9
- urllib module, 2-3
- urllib module, limitations, 2-28
- urllib2 module, 2-17
- urllib2 module, error handling, 2-22
- urllib2 module, Request objects, 2-19
- urlopen() function, obtaining response headers, 2-13
- urlopen() function, obtaining status code, 2-14
- urlopen() function, reading responses, 2-12
- urlopen() function, urllib module, 2-4
- urlopen() function, urllib2 module, 2-18
- urlopen(), posting form data, 2-10, 2-11, 2-20
- urlopen(), supported protocols, 2-5
- User-agent, setting in HTTP requests, 2-21

Assignment Project Exam Help

T

- TCP, 1-13, 1-14
- TCP, accepting new connections, 1-22
- TCP, address binding, 1-20
- TCP, client example, 1-16
- TCP, communication with client, 1-21
- TCP, example with SocketServer module, 5-5
- TCP, listening for connections, 1-21
- TCP, server example, 1-19
- TCPServer, SocketServer module, 5-10
- Telnet, using with network applications, 1-10
- Threaded network server, 1-50
- ThreadingMixIn class, SocketServer module, 5-15
- ThreadingTCPServer, SocketServer module, 5-14
- ThreadingUDPServer, SocketServer module, 5-14
- Threads, and network servers, 1-50
- Timeout, on sockets, 1-34
- Turbogears, 4-54
- Twisted framework, 1-52

U

- UDP, 1-13, 1-41
- UDP, client example, 1-43
- UDP, server example, 1-42

- viewing open network connections, 1-6

W

- Web frameworks, 4-51, 4-55
- Web programming, and WSGI, 4-35, 4-36
- Web programming, CGI scripting, 4-23, 4-24, 4-25, 4-26, 4-27
- Web services, 2-8
- Webdav, 2-28
- WSGI, 4-36
- WSGI (Web Services Gateway Interface), 4-35
- WSGI, and CGI environment variables, 4-39
- WSGI, and wsgi.* variables, 4-40
- WSGI, application inputs, 4-38
- WSGI, applications, 4-37
- WSGI, parsing query string, 4-41
- WSGI, producing content, 4-44
- WSGI, response encoding, 4-45
- WSGI, responses, 4-42
- WSGI, running a stand-alone server, 4-46, 4-47
- WSGI, running applications within a CGI script, 4-48
- WWW, see HTTP, 4-5

<https://powcoder.com>

Add WeChat powcoder

X

- XML, element attributes, 3-19
- XML, element wildcards, 3-20
- XML, ElementTree interface, 3-15, 3-16
- XML, ElementTree module, 3-14
- XML, finding all matching elements, 3-18
- XML, finding matching elements, 3-17
- XML, incremental parsing of, 3-25
- XML, modifying documentation structure with ElementTree, 3-23
- XML, parsing with SAX, 3-9
- XML, writing to files, 3-24
- XML-RPC, 5-20

Z

- Zope, 4-54

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder