

Announcements

Reminder: ps3 due tonight 10/8 at midnight (Boston)

- ps4 out today, due 10/15 (1 week)
- ps3 self-grading form out Monday, due 10/19
- Grades for ps1 & ps2 are being posted to blackboard (by Monday)
- Midterm 10/22 – have to finish test once began, should have blank paper that you will submit work/steps for a solution



Neural Networks IV

Recurrent Networks

Today: Outline

- **Recurrent networks:** forward pass, backward pass
- **NN training strategies:** loss functions, dropout, etc.

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder


Network architectures

Feed-forward

Fully connected




Convolutional



Recurrent

time →



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Neural Networks IV

Recurrent Architectures

Recurrent Networks for Sequences of Data

- Sequences in our world:

- Audio
- Text
- Video
- Weather
- Stock market

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- Sequential data is why we build RNN architectures.
- RNNs are tools for making predictions about sequences.

Limitations of Feed-Fwd Networks

- Limitations of feed-forward networks

Assignment Project Exam Help

- **Fixed length**

Inputs and outputs are of fixed lengths

<https://powcoder.com>

Add WeChat powcoder

- **Independence**

Data (example: images) are independent of one another

Advantages of RNN Models

- What feed-forward networks cannot do

Assignment Project Exam Help

- **Variable length**

“We would like to accommodate temporal sequences of various lengths.”


<https://powcoder.com>

Add WeChat powcoder

- **Temporal dependence**

“To predict where a pedestrian is at the next point in time, this depends on where he/she were in the previous time step.”


Vanilla Neural Network (NN)



• NN
Assignment Project Exam Help
<https://powcoder.com>
 x_t : input/event
 h_t : output/prediction
Add WeChat powcoder
 A : chunk of NN

Every input is treated independently.

Recurrent Neural Network (RNN)



- RNN

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The loop allows information to be passed from one time step to the next.

Now we are modeling the dynamics.


Recurrent Neural Network (RNN)

- A recurrent neural network can be thought of as multiple copies of the same network, each passing a message to a successor.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Recurrent Neural Network (RNN)

- A recurrent neural network can be thought of as multiple copies of the same network, each passing a message to a successor.


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




RNN Architectures



Recurrent Neural Network

The state consists of a single “hidden” vector \mathbf{h} :



Assignment Project Exam Help

$$h_t = f_W(h_{t-1}, x_t)$$

<https://powcoder.com>


$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$

$$y_t = W_{hy}h_t$$

parameters

Recurrent Neural Network

The state consists of a single “hidden” vector \mathbf{h} :



Assignment Project Exam Help

$$h_t = f_W(h_{t-1}, x_t)$$


<https://powcoder.com>

$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$

$$y_t = W_{hy}h_t$$

$$g(x) = 2\sigma(2x) - 1$$

activation function
(elementwise)





Neural Networks IV

Example: Character RNN

Character-level language model example


Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Character-level language model example


Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Character-level language model example

Vocabulary:
[h,e,l,o]


Example training
sequence:
“hello”

$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Character-level language model example

Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

[min-char-rnn.py](#) gist: 112 lines of Python


```
1 """
2 Minimal character-level Vanilla RNN model. Written by Andrej Karpathy (@karpathy)
3 BSD license
4 """
5 import numpy as np
6
7 # data I/O
8 data = open('input.txt', 'r').read() # should be simple plain text file
9 chars = list(set(data))
10 data_size, vocab_size = len(data), len(chars)
11 print 'data has %d characters, %d unique.' % (data_size, vocab_size)
12 char_to_ix = { ch:i for i,ch in enumerate(chars) }
13 ix_to_char = { ix:ch for i, ch in enumerate(chars) }
14
15 # hyperparameters
16 hidden_size = 100 # size of hidden layer of neurons
17 seq_length = 25 # number of steps to unroll the RNN for
18 learning_rate = 1e-1
19
20 # model parameters
21 wxh = np.random.randn(hidden_size, vocab_size)*0.01 # input to hidden
22 whh = np.random.randn(hidden_size, hidden_size)*0.01 # hidden to hidden
23 why = np.random.randn(hidden_size, vocab_size)*0.01 # hidden to output
24 bh = np.zeros((hidden_size, 1)) # hidden bias
25 by = np.zeros((vocab_size, 1)) # output bias
26
27 def lossFun(inputs, targets, hprev):
28     """
29     inputs, targets are both list of integers
30     hprev is Hx1 array of initial hidden state
31     returns the loss, gradients on model parameters, and last hidden state
32     """
33     xs, hs, ys, ps = {}, {}, {}, {}
34     hs[-1] = np.copy(hprev)
35     loss = 0
36     # forward pass
37     for t in xrange(len(inputs)):
38         xs[t] = np.zeros((vocab_size,1)) # encode in 1-hot representation
39         xs[t][inputs[t]] = 1
40         hs[t] = np.tanh(np.dot(wxh, xs[t]) + np.dot(whh, hs[t-1]) + bh) # hidden state
41         ys[t] = np.dot(why, hs[t]) + by # unnormalized log probabilities for next chars
42         ps[t] = np.exp(ys[t]) / np.sum(np.exp(ys[t])) # probabilities for next chars
43         loss += -np.log(ps[t][targets[t],0]) # softmax (cross-entropy loss)
44     # backward pass: compute gradients going backwards
45     dwhx, dwhh, dwhy = np.zeros_like(wxh), np.zeros_like(whh), np.zeros_like(why)
46     dbh, dbx = np.zeros_like(bh), np.zeros_like(by)
47     dhnext = np.zeros_like(hs[0])
48     for t in reversed(xrange(len(inputs))):
49         dy = np.copy(ps[t])
50         dy[targets[t]] -= 1 # backprop into y
51         dwhy += np.dot(dy, hs[t].T)
52         dbx += dy
53         dh = np.dot(why.T, dy) + dhnext # backprop into h
54         ddraw = (1 - hs[t]**2) * dh # backprop through tanh nonlinearity
55         dbh += ddraw
56         dwhx += np.dot(ddraw, xs[t].T)
57         dwhh += np.dot(ddraw, hs[t-1].T)
58         dhnext = np.dot(whh.T, ddraw)
59     for dparam in [dwhx, dwhh, dwhy, dbh, dbx]:
60         np.clip(dparam, -5, 5, out=dparam) # clip to mitigate exploding gradients
61     return loss, dwhx, dwhh, dwhy, dbh, dbx, hs[len(inputs)-1]
62
63 def sample(h, seed_ix, n):
64     """
65     sample a sequence of integers from the model
66     h is memory state, seed_ix is seed letter for first time step
67     """
68     x = np.zeros((vocab_size, 1))
69     x[seed_ix] = 1
70     ixes = []
71     for t in xrange(n):
72         h = np.tanh(np.dot(wxh, x) + np.dot(whh, h) + bh)
73         y = np.dot(why, h) + by
74         p = np.exp(y) / np.sum(np.exp(y))
75         ix = np.random.choice(range(vocab_size), p=p.ravel())
76         x = np.zeros((vocab_size, 1))
77         x[ix] = 1
78         ixes.append(ix)
79     return ixes
80
81 n, p = 0, 0
82 mwhx, mwhh, mwhy = np.zeros_like(wxh), np.zeros_like(whh), np.zeros_like(why)
83 mdbh, mdbx = np.zeros_like(bh), np.zeros_like(by) # memory variables for Adagrad
84 smooth_loss = 0 # smoothed loss over time
85 while True:
86     # prepare inputs (we're sweeping from left to right in steps seq_length long)
87     if p+seq_length+1 >= len(data) or n == 0:
88         hprev = np.zeros((hidden_size,1)) # reset RNN memory
89         p = 0 # go from start of data
90         inputs = [char_to_ix[ch] for ch in data[p:p+seq_length]]
91         targets = [ix_to_char[ix] for ix in data[p+1:p+seq_length+1]]
92     # sample from the model now and then
93     if n % 100 == 0:
94         sample_ix = sample(hprev, inputs[0], 200)
95         txt = ''.join(ix_to_char[ix] for ix in sample_ix)
96         print '----\n %s \n----' % (txt, )
97     # for every seq_length characters, report the loss and fetch gradient
98     loss, dwhx, dwhh, dwhy, dbh, dbx, hprev = lossFun(inputs, targets, hprev)
99     smooth_loss = smooth_loss * 0.999 + loss * 0.001
100     if n % 100 == 0: print 'iter %d, loss: %f' % (n, smooth_loss) # print progress
101
102     # perform parameter update with Adagrad
103     for param, dparam, mem in zip([wxh, whh, why, bh, by],
104                                   [dwhx, dwhh, dwhy, dbh, dbx],
105                                   [mwhx, mwhh, mwhy, mdbh, mdbx]):
106         mem += dparam * dparam
107         param += -learning_rate * dparam / np.sqrt(mem + 1e-8) # adagrad update
108     p += seq_length # move data pointer
109     n += 1 # iteration counter
```

[illegible]

Assignment Project Exam Help

Epson AcuLaser C4100 High performance colour lasers for all your
 100 provides businesses with a high performance colour and monochrome printing
 this producing high quality monochrome printing. The C4100 is a compact, high performance
 operate. So now there's no reason to be slow. The C4100 is a compact, high performance
 Where to Buy Support Epson Acutech is a leading provider of high performance
 is the perfect professional printing solution for your business. The C4100 is a compact, high performance
 rate from 60 up to 40W in size. The Epson AcuLaser C4100 is a compact, high performance
 exclusive AcuLaser Color Technologies, more. Where to Buy Support -

WeChat vopwcode



Sonnet 116 – Let me not ...

by William Shakespeare

Let me not to the marriage of true minds
Admit impediments. Love is not love
Which alters when it alteration finds,
Or bends with the remover to remove:
O no! it is an ever-fixed mark
That looks on tempests and is never shaken;
It is the star to every wandering bark,
Whose worth's unknown, although his height be taken.
Love's not Time's fool, though rosy lips and cheeks
Within his bending sickle's compass come;
Love alters not with his brief hours and weeks,
But bears it out even to the edge of doom.
If this be error and upon me proved,
I never writ, nor no man ever loved.

at first:

tyntd-iafhatawiao hr demot lytdws e ,tfti, astai f ogoh eoase rrranbyne 'nhtnee e
plia tk lrgd t o idoe ns, smtt h ne etie h, hregtrs nigtike, aoaenns lng

train more

"Tmont thithey" fomesscerliund
Keushey. Thom here
sheulke, anmerenith ol sivh I lalterthend Bleipile shuw y fil on aseterlome
coaniogenn. "Se linn thund hon at Me linn otion in ther tize."

train more

Aftair fall unsuch that the hall for Prince Velzonski's that me of
her hearly, and behs to so arwage fiving were to it beloge, pavu say falling misfort
how, and Gogition is so overel al and of ar.

train more

"Why do what that day," replied Natasha, and wishing to himself the fact the
princess, Princess Mary was easier, fed in had oftene him.
Pierre aking his soul came to the packs and drove up his father-in-law women.

PANDARUS:

Alas, I think he shall be come approached and the day
When little strain would be attain'd into being never fed,
And who is but a chain and subjects of his death,
I should not sleep.

Second Senator:

They are away this miseries, produced upon my soul,
Breaking and strongly should be buried, when I perish
The earth and thoughts of many states.

DUKE VINCENTIO:

Well, your wit is in the care of side and that

Second Lord:

They would be ruled after this chamber, and
my fair nudes begun out of the fact, to be conveyed
Whose noble souls I'll have the heart of the wars.

Clown:

Come, sir, I will make did behold your worship.

VIOLA:

I'll drink it.

VIOLA:

Why, Salisbury must find his flesh and thought
That which I am not apt, not a man and in fire,
To show the reining of the raven and the wars
To grace my hand reproach within, and not a fair are hand,
That Caesar and my goodly father's world;
When I was heaven of presence and our fleets,
We spare with hours, but cut thy council I am great,
Murdered and by thy master's ready there
My power to give thee but so much as hell:
Some service in the noble bondman here,
Would show him to her wine.

KING LEAR:

O, if you were a feeble sight, the courtesy of your law,
Your sight and several breath, will wear the gods
With his heads, and my hands are wonder'd at the deeds,
So drop upon your lordship's head, and your opinion
Shall be against your honour.



Neural Networks IV

Learning in RNNs

Forward pass

- Forward pass through time


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Recurrent Neural Network (RNN)

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Aside: Forward pass

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Recurrent Neural Network (RNN)

- Error or cost is computed for each prediction.

Aside: Forward pass



$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Backprop Through Time

- Backpropagation through time


$$\frac{\partial E}{\partial W} = \sum_{t=1}^T \frac{\partial E_t}{\partial W}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Aside: Forward pass



BP TT

- Backpropagation through time


Assignment Project Exam Help

$$\frac{\partial E}{\partial W} = \sum_{t=1}^T \boxed{\frac{\partial E_t}{\partial W}}$$


<https://powcoder.com>
Add WeChat powcoder

$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Aside: Forward pass




BP TT



$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$


BP TT



$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \boxed{\frac{\partial h_t}{\partial h_k}} \frac{\partial h_k}{\partial W}$$

Add WeChat powcoder

BP TT




$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \boxed{\frac{\partial h_t}{\partial h_k}} \frac{\partial h_k}{\partial W}$$

Add WeChat powcoder

$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}}$$

BP TT



$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Add WeChat powcoder

$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}}$$

For example @ $t = 2$,

$$\frac{\partial h_2}{\partial h_0} = \prod_{i=1}^2 \frac{\partial h_i}{\partial h_{i-1}} = \frac{\partial h_1}{\partial h_0} \frac{\partial h_2}{\partial h_1}$$

Vanishing (and Exploding) Gradients

$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}}$$

Aside: Forward pass

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Vanishing (and Exploding) Gradients

$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Assignment Project Exam Help


$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}} = \prod_{i=k+1}^t W^T \text{diag}[\phi'(h_{i-1})]$$

Add WeChat powcoder

Aside: Forward pass

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Vanishing (and Exploding) Gradients

$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Assignment Project Exam Help

$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}} = \prod_{i=k+1}^t W^T \text{diag}[\phi'(h_{i-1})]$$


Add WeChat powcoder

$$\left\| \frac{\partial h_i}{\partial h_{i-1}} \right\|$$

Aside: Forward pass

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Vanishing (and Exploding) Gradients

$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Assignment Project Exam Help

$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}} = \prod_{i=k+1}^t W^T \text{diag}[\phi'(h_{i-1})]$$


Add WeChat powcoder

$$\left\| \frac{\partial h_i}{\partial h_{i-1}} \right\| \leq \|W^T\| \|\text{diag}[\phi'(h_{i-1})]\|$$

Aside: Forward pass

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Vanishing (and Exploding) Gradients

$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Assignment Project Exam Help

$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}} = \prod_{i=k+1}^t W^T \text{diag}[\phi'(h_{i-1})]$$


Add WeChat powcoder

$$\left\| \frac{\partial h_i}{\partial h_{i-1}} \right\| \leq \|W^T\| \|\text{diag}[\phi'(h_{i-1})]\| \leq \gamma_W \gamma_\phi$$

Aside: Forward pass

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Vanishing (and Exploding) Gradients

$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Assignment Project Exam Help

$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}} = \prod_{i=k+1}^t W^T \text{diag}[\phi'(h_{i-1})]$$

Add WeChat powcoder


$$\left\| \frac{\partial h_i}{\partial h_{i-1}} \right\| \leq \|W^T\| \|\text{diag}[\phi'(h_{i-1})]\| \leq \gamma_W \gamma_\phi$$

$$\prod_{i=k+1}^t \left\| \frac{\partial h_i}{\partial h_{i-1}} \right\| \leq (\gamma_W \gamma_\phi)^{t-k}$$

Aside: Forward pass

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Vanishing (and Exploding) Gradients

$$\frac{\partial E_t}{\partial W} = \sum_{k=1}^t \frac{\partial E_t}{\partial y_t} \frac{\partial y_t}{\partial h_t} \frac{\partial h_t}{\partial h_k} \frac{\partial h_k}{\partial W}$$

Assignment Project Exam Help

$$\frac{\partial h_t}{\partial h_k} = \prod_{i=k+1}^t \frac{\partial h_i}{\partial h_{i-1}} = \prod_{i=k+1}^t W^T \text{diag}[\phi'(h_{i-1})]$$

Add WeChat powcoder


$$\left\| \frac{\partial h_i}{\partial h_{i-1}} \right\| \leq \|W^T\| \|\text{diag}[\phi'(h_{i-1})]\| \leq \gamma_W \gamma_\phi$$

$$\prod_{i=k+1}^t \left\| \frac{\partial h_i}{\partial h_{i-1}} \right\| \leq \underbrace{(\gamma_W \gamma_\phi)}_{\substack{<1 \text{ vanishing} \\ >1 \text{ exploding}}}^{t-k}$$

Aside: Forward pass

$$h_t = W\phi(h_{t-1}) + W_x x_t$$

$$y_t = W_y \phi(h_t)$$



Vanishing (and Exploding) Gradients

- Exploding Gradients

- Easy to detect

- Clip the gradient at a threshold

<https://powcoder.com>

- Vanishing Gradients

- More difficult to detect

- Architectures designed to combat the problem of vanishing gradients. Example: LSTMs by *Schmidhuber et al.*



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Neural Networks IV

Training strategies

Universality

- Why study neural networks in general?
 - Neural network can approximate any continuous function, even with a single hidden layer!
 - <http://neuralnetworksanddeeplearning.com/chap4.html>

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Why Study Deep Networks?





Figure 6.6: Empirical results showing that deeper networks generalize better when used to transcribe multi-digit numbers from photographs of addresses. Data from Goodfellow *et al.* (2014d). The test set accuracy consistently increases with increasing depth. See figure 6.7 for a control experiment demonstrating that other increases to the model size do not yield the same effect.

Efficiency of convnets



But... Watch Out for Vanishing Gradients

- Consider a simple network, and perform backpropagation



- For simplicity, just a single neuron
- Sigmoid at every layer, $z_j = w_j a_{j-1} + b_j$, $a_j = \sigma(z_j)$
- Cost function C

- Gradient $\partial C / \partial b_1$ is a product of terms:

$$\partial C / \partial b_1 = \sigma'(z_1) w_2 \sigma'(z_2) w_3 \sigma'(z_3) w_4 \sigma'(z_4) (\partial C / \partial a_4)$$

Vanishing Gradients

- Gradient of sigmoid is in $(0, 1/4)$
- Weights are also typically initialized in $(0, 1)$
- Products of small numbers \rightarrow small gradients
- Backprop does not change weights in earlier layers by much!
 - This is an issue with backprop, not with the model itself

RNNs: vanishing and exploding gradients

- Exploding: easy to fix, clip the gradient at a threshold
- Vanishing: More difficult to detect
- Architectures designed to combat the problem of vanishing gradients. Example: LSTMs by *Schmidhuber et al.*

Rectified Linear Units (RELU)

- Alternative non-linearity:

$$g(x) = \max(0, x)$$

- Gradient of this function?
 - Note: need subgradient descent here.
- https://cs224d.stanford.edu/notebooks/vanishing_grad_example.html
- Increasing the number of layers can result in requiring exponentially fewer hidden units per layer (see “Understanding Deep Neural Networks with Rectified Linear Units”)
- Biological considerations
 - On some inputs, biological neurons have no activation
 - On some inputs, neurons have activation proportional to input

Other Activation Functions

- Leaky ReLU: $g(x) = \max(0, x) + \alpha \min(0, x)$ ($\alpha \approx .01$)
- Tanh: $g(x) = 2\sigma(2x) - 1$
- Radial Basis Functions: $g(x) = \exp(-(w - x)^2 / \sigma^2)$
- Softplus: $g(x) = \log(1 + e^x)$
- Hard Tanh: $g(x) = \max(-1, \min(1, x))$
- Maxout: $g(x) = \max_{j \in \mathbb{G}} x_j$
-

Architecture Design and Training Issues

- How many layers? How many hidden units per layer? How to connect layers together? How to optimize?
 - Cost functions
 - L2/L1 regularization
 - Data Set Augmentation
 - Early Stopping
 - Dropout
 - Minibatch Training
 - Momentum
 - Initialization
 - Batch Normalization

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Next Class

Computing cluster/Tensorflow Intro (next Thursday):

Intro to SCC and Tensorflow; please have laptops ready to follow along with the lecture. Expected to last 2 hours

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder