


Announcements

Reminder: pset5 self-grading form and pset6 out, due Today 11/19 11:59pm Boston Time
Assignment Project Exam Help

- Class challenge out Today (will discuss in class)
<https://powcoder.com>
Add WeChat powcoder



Semi-Supervised Learning

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Supervised Learning

Feature Space \mathcal{X}

Label Space \mathcal{Y}

Goal: Construct a predictor $f : \mathcal{X} \rightarrow \mathcal{Y}$ to minimize


$$R(f) \equiv \mathbb{E}_{XY} [\text{loss}(Y, f(X))]$$

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Optimal predictor (Bayes Rule) depends on unknown P_{XY} , so instead
learn a good prediction rule from training data $\{(X_i, Y_i)\}_{i=1}^n \stackrel{\text{iid}}{\sim} P_{XY}(\text{unknown})$



Labeled

Labeled and Unlabeled data



“Crystal” “Needle” “Empty”

Assignment Project Exam Help

0 1 2 3 4 5 6 7 8
8 9 0 1 2 3 4 5 6 7

<https://powcoder.com>

“0” “1” “2” ...

Add WeChat powcoder

Human expert/
Special equipment/
Experiment

“Sports”
“News”
“Science”
...

Unlabeled data, X_i

Labeled data, Y_i

Cheap and abundant !

Expensive and scarce !

Free-of-cost labels?

Luis von Ahn: Games with a purpose (ReCaptcha)

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Email address

Password

STELLA UDON

Type the two words:


reCAPTCHA™ stop spam. read books.

Log In

Word challenging to OCR
(Optical Character Recognition)

You provide a free label!

Semi-Supervised learning



Assignment Project Exam Help

<https://powcoder.com>

Supervised learning (SL)

Labeled data $\{X_i, Y_i\}_{i=1}^n$

Add WeChat powcoder



“Crystal”

X_i

Y_i

Semi-Supervised learning (SSL)

Labeled data $\{X_i, Y_i\}_{i=1}^n$ **and** Unlabeled data $\{X_i\}_{i=1}^m$

$m \gg n$

Goal: Learn a better prediction rule than based on labeled data alone.

Semi-Supervised learning in Humans

Cognitive science

Computational model of how humans learn from labeled and unlabeled data.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- concept learning in children: x =animal, y =concept (e.g., dog)
- Daddy points to a brown animal and says "dog!"
- Children also observe animals by themselves

Can unlabeled data help?

- Positive labeled data
- Negative labeled data
- Unlabeled data

Assignment Project Exam Help

Supervised Decision Boundary

<https://powcoder.com>

Semi-Supervised Decision Boundary

Add WeChat powcoder



Assume each class is a coherent group (e.g. Gaussian)

Then unlabeled data can help identify the boundary more accurately.


Can unlabeled data help?

Unlabeled Images

0 1 2 3 4 5 6 7 8 9
8 9 0 1 2 3 4 5 6 7
6 7 8 9 0 1 2 3 4 5


Labels “0” “1” “2” ...

Assignment Project Exam Help



This embedding can be done by manifold learning algorithms, e.g. tSNE

“Similar” data points have “similar” labels



Assignment Project Exam Help
Algorithms

<https://powcoder.com>

Add WeChat powcoder
Semi-Supervised Learning

Slides credit: Jerry Zhu, Aarti Singh

Some SSL Algorithms

- Self-Training
- Generative methods, mixture models
- Graph-based methods
- Co-Training
- Semi-supervised SVM
- Many others

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Notation

- instance \mathbf{x} , label y
- learner $f : \mathcal{X} \mapsto \mathcal{Y}$
- labeled data $(X_l, Y_l) = \{(\mathbf{x}_{1:l}, y_{1:l})\}$
- unlabeled data $X_u = \{\mathbf{x}_{l+1:l+u}\}$, available during training. Usually $l \ll u$. Let $n = l + u$
- test data $\{(\mathbf{x}_{n+1...}, y_{n+1...})\}$, not available during training

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Self-training

Our first SSL algorithm:

Input: labeled data $\{(\mathbf{x}_i, y_i)\}_{i=1}^l$, unlabeled data $\{\mathbf{x}_j\}_{j=l+1}^{l+u}$.

1. Initially, let $L = \{(\mathbf{x}_i, y_i)\}_{i=1}^l$ and $U = \{\mathbf{x}_j\}_{j=l+1}^{l+u}$.
2. Repeat:
 - 3. Train f from L using supervised learning.
 - 4. Apply f to the unlabeled instances in U .
 - 5. Remove a subset S from U ; add $\{(\mathbf{x}, f(\mathbf{x})) | \mathbf{x} \in S\}$ to L .

Self-training is a *wrapper* method

- the choice of learner for f in step 3 is left completely open
- good for many real world tasks like natural language processing
- but mistake by f can reinforce itself


Self-training Example

Propagating 1-NN


Input: labeled data $\{(\mathbf{x}_i, y_i)\}_{i=1}^l$, unlabeled data $\{\mathbf{x}_j\}_{j=l+1}^{l+u}$, distance function $d()$.

1. Initially, let $L = \{(\mathbf{x}_i, y_i)\}_{i=1}^l$ and $U = \{\mathbf{x}_j\}_{j=l+1}^{l+u}$.
2. Repeat until U is empty:
 3. Select $\mathbf{x} = \operatorname{argmin}_{\mathbf{x} \in U} \min_{\mathbf{x}' \in L} d(\mathbf{x}, \mathbf{x}')$.
 4. Set $f(\mathbf{x})$ to the label of \mathbf{x} 's nearest instance in L .
Break ties randomly.
 5. Remove \mathbf{x} from U ; add $(\mathbf{x}, f(\mathbf{x}))$ to L .


Propagating 1-Nearest-Neighbor: now it works




(a) Iteration 1



(b) Iteration 25



(c) Iteration 74



(d) Final labeling of all instances



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Propagating 1-Nearest-Neighbor: now it doesn't



But with a single outlier...



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Related: Cluster and Label

Input: $(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_l, y_l), \mathbf{x}_{l+1}, \dots, \mathbf{x}_{l+u}$,
a clustering algorithm \mathcal{A} , a supervised learning algorithm \mathcal{L}

1. Cluster $\mathbf{x}_1, \dots, \mathbf{x}_{l+u}$ using \mathcal{A} .
2. For each cluster, let S be the labeled instances in it:
3. Learn a supervised predictor from S : $f_S = \mathcal{L}(S)$.
4. Apply f_S to all unlabeled instances in this cluster.

Output: labels on unlabeled data y_{l+1}, \dots, y_{l+u} .

But again: **SSL sensitive to assumptions**—in this case, that the clusters coincide with decision boundaries. If this assumption is incorrect, the results can be poor.


Co-training

Assumptions

- feature split $x = [x^{(1)}; x^{(2)}]$ exists
- $x^{(1)}$ or $x^{(2)}$ alone is sufficient to learn a good classifier

<https://powcoder.com>

Add WeChat powcoder



Co-training Algorithm

Co-training (Blum & Mitchell, 1998) (Mitchell, 1999) assumes that

- (i) features can be split into two sets;
- (ii) each sub-feature set is sufficient to train a good classifier.

Assignment Project Exam Help

- Initially two separate classifiers are trained with the labeled data, on the two sub-feature sets respectively.
<https://powcoder.com>
- Each classifier then classifies the unlabeled data, and 'teaches' the other classifier with the few unlabeled examples (and the predicted labels) they feel most confident.
Add WeChat powcoder
- Each classifier is retrained with the additional training examples given by the other classifier, and the process repeats.

Co-training Algorithm

Blum & Mitchell'98

Input: labeled data $\{(\mathbf{x}_i, y_i)\}_{i=1}^l$, unlabeled data $\{\mathbf{x}_j\}_{j=l+1}^{l+u}$
each instance has two views $\mathbf{x}_i = [\mathbf{x}_i^{(1)}, \mathbf{x}_i^{(2)}]$,
and a learning speed k .

1. let $L_1 = L_2 = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_l, y_l)\}$.
2. Repeat until unlabeled data is used up:
3. Train view-1 $f^{(1)}$ from L_1 , view-2 $f^{(2)}$ from L_2 .
4. Classify unlabeled data with $f^{(1)}$ and $f^{(2)}$ separately.
5. Add $f^{(1)}$'s top k most-confident predictions $(\mathbf{x}, f^{(1)}(\mathbf{x}))$ to L_2 .
 Add $f^{(2)}$'s top k most-confident predictions $(\mathbf{x}, f^{(2)}(\mathbf{x}))$ to L_1 .
 Remove these from the unlabeled data.

Semi-Supervised Learning

- Generative methods
- Graph-based methods
- Co-Training
- Semi-Supervised SVMs
- Many other methods

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SSL algorithms can use unlabeled data to help improve prediction accuracy if data satisfies appropriate assumptions

Next Class

Practical Advice for Applying ML

Machine learning system design; feature engineering; feature pre-processing, learning with large datasets; SGD and mini-batch GD

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder