

Assignment Project Exam Help

Amortized Analysis and Hashing

<https://powcoder.com>

Add WeChat powcoder

Ted Pyne

Table of Contents

- Amortized Analysis
- Hashing

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Amortized Analysis

- Normal: Require our data structure to be fast on every operation
- Amortized: Require our data structure to be fast “in total”

Assignment Project Exam Help

<https://powcoder.com>

Track runtime using potential function

Cost of operation = real work + change in potential function

Add WeChat powcoder

If potential function has positive delta, “saving” for future operations

NB: Potential function is **not real** - not tracked by algorithm, only used for analysis

Faster Heaps via Amortized Analysis

1. Before: bin-heap with $O(\log n)$ insert, $O(n)$ makeheap, $O(\log n)$ deletemin.
2. Goal: heap with $O(1)$ insert and $O(\log n)$ *amortized* deletemin.

Assignment Project Exam Help

<https://powcoder.com>

Idea: Build up “credit” from prior lazy inserts to pay for our extra deletemin work.

Add WeChat powcoder

Data Structure

Maintain integer array A , heap-of-heaps H .

Elements of H are of form $[k, n]$ where:

1. h is a heap of integers
2. k is smallest element of h

Invariant: Potential function ϕ is always equal to $|A|$.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Insert Operation

insert(k):

A.append(k) **Assignment Project Exam Help**

Increment p

<https://powcoder.com>

Add WeChat powcoder

Deletemin Operation

deletemin():

h = makeheap(A)

insert(H, [peek(h), h])

h' = deletemin(H)

elt = deletemin(h')

insert(H, [peek(h), h])

Set **p** to 0

return elt

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Runtime Analysis

insert(): appends to list, increments p

Total cost $1 + \Delta p = 1 + 1 = O(1)$

<https://powcoder.com>

deletemin(): turns A into heap, does 6 other heap operations, sets p to 0

Total cost $|A| + 6 \log n + \Delta p = |A| - |A| + 6 \log n = O(\log n)$

Hashing

Hash function: map from $[u]$ to $[m]$ where $u \gg m$.

We have a family H of hash functions and choose h from H at random.

Requirement: for all x, y in $[u]$:

<https://powcoder.com>

$$\Pr_h[h(x) = h(y)] = 1 / m.$$

Add WeChat powcoder

Families of Hash Functions

\mathcal{H} is **all functions** on $[u]$ to $[m]$, so we pick a truly random function h .

Is this a valid family of hash functions?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Question

Does there exist a hash family with **one** element?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Second Attempt

Truly random functions are expensive to generate.

A cheaper family: for all i in $[1, m]$, define the function:

$$h_i(x) = (x + i) \bmod m$$

Is this a valid hash family?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Exercise 1

Consider the sequence of operations:

insert(2), insert(3), insert(1), deleteMin(), insert(5), insert(0), deleteMin(), insert(6)

What does the data structure look like after each operation?

<https://powcoder.com>

Add WeChat powcoder

Exercise 2

Suppose we want to implement a dynamically sized array. Let the current number of elements be k , and let m be the size of the current array.

Assignment Project Exam Help

As additional `appendLast()` and `removeLast()` operations occur:

<https://powcoder.com>

1. If $k = m$, allocate a new array of size $2m$ and move all elements over.
2. If $k = m / 4$, allocate a new array of size $m / 2$ and move all elements over.

Add WeChat powcoder

Assuming moving a single element takes $O(1)$ time, show this data structure has $O(1)$ *amortized* runtime for `appendLast()` and `removeLast()` operations.

Exercise 3

Our “linear shift” hash family failed. Let’s try something else.

Assume $u = \{0,1\}^s$ and $v = \{0,1\}^k$ with $+$ and $*$ defined bitwise. Then let \mathbf{M} be the set of all matrices with entries in $\{0,1\}$ with k rows and s columns. For all A in \mathbf{M} , define:

<https://powcoder.com>

Add WeChat $h_A(x) = Ax$ powcoder

Show $\{h_A : A \text{ in } \mathbf{M}\}$ is a hash family.