

# CS157A: Introduction to Database Management Systems

Assignment Project Exam Help

<https://powcoder.com>

Chapter 6:  
The Database Language SQL-Part II

Add WeChat powcoder

Suneuy Kim

# Join Variants

- CROSS JOIN → Cartesian product
- (INNER) JOIN ON → Theta Join
- NATURAL JOIN → Natural Join
- LEFT|RIGHT|FULL OUTER JOIN ON  
: augment the result of a join by the dangling  
tuples

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# MySQL Join Variants

- In MySQL, Join, Cross Join, Inner Join are the same, working as theta join.

Assignment Project Exam Help

```
select uName, title, age  
from User INNER JOIN Loan ON User.uID = Loan.uID  
and age < 20;
```

<https://powcoder.com>  
Add WeChat powcoder

- Replacing INNER JOIN with Cross Join or Join will not change the result.

# MySQL: Inner Join, Cross Join, and Join (Alternative Syntaxes)

`using(a1, a2, ...)` Clause

- This is similar to `on`, but the name of the join attribute(s) must be the same in each table.
- The join attribute(s) only appears *once* in the result set.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
select uName, title
from User INNER JOIN Loan using(uID);
```

# Outer Join

- Dangling tuple

A tuple that fails to join with any tuple of the other relation.

Assignment Project Exam Help

<https://powcoder.com>

- Outer join augments the result of join by the dangling tuples, padded with NULL.

Add WeChat powcoder

# Outer Join

- LEFT|RIGHT|FULL OUTER JOIN pads dangling tuples from LEFT, RIGHT, or BOTH.
- Theta Join  
R LEFT|RIGHT|FULL OUTER JOIN S ON  
<condition>
- Natural Join  
R NATURAL LEFT|RIGHT|FULL OUTER JOIN S

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

R

a	b
10	20
50	5

S

c	d
7	40
10	5
30	8

R LEFT | RIGHT | FULL  
OUTER JOIN S ON b > c

Assignment Project Exam Help

LEFT

a	b	c	d
10	20	7	40
10	20	10	5
50	5	N	N

RIGHT

a	b	c	d
10	20	7	40
10	20	10	5
N	N	30	8

a	b	c	d
10	20	7	40
10	20	10	5
50	5	N	N
N	N	30	8

## Rewriting left outer join

```
select uName, User.uID, title, overdue  
from User, Loan  
where User.uID = Loan.uID
```

Assignment Project Exam Help

<https://powcoder.com>

union all

Add WeChat powcoder

```
select uName, uID, NULL, NULL
```

```
from User
```

```
where uID not in (select uID from Loan);
```



# right outer join

```
select uID, uName, title, overdue  
from User right outer join Loan using (uID);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# full outer join

```
select uID, uName, title, overdue  
from User full outer join Loan using (uID);
```

Assignment Project Exam Help

<https://powcoder.com>

[Q] MySQL does not support full outer join. Can  
you rewrite full outer join without using join ?

Add WeChat powcoder

## full outer join without using join

```
select uName, User.uID, title, overdue  
from User, Loan  
where User.uID = Loan.uID
```

```
union all
```

```
select uName, uID, NULL, NULL  
from User
```

```
where uID not in (select uID from Loan)
```

```
union all
```

```
select NULL, uID, title, overdue  
from Loan
```

```
where uID not in (select uID from User);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Commutativity :  $(A \text{ op } B) = (B \text{ op } A)$
- Associativity:  $(A \text{ op } B) \text{ op } C = A \text{ op } (B \text{ op } C)$

Left | Right outer joins are not commutative.

Full outer join is commutative.

Left | Right | Full outer joins are not associative.

It is important to think of the order of ( ).

# Example: Violation of Associativity

```
DROP DATABASE IF EXISTS JOINTEST;
```

```
CREATE DATABASE JOINTEST;
```

```
USE JOINTEST;
```

```
CREATE TABLE A (id int, M int);
```

```
CREATE TABLE B (id int, N int);
```

```
CREATE TABLE C (id int, val text);
```

```
INSERT INTO A VALUES (1, 1);
```

```
INSERT INTO A VALUES (2, 2);
```

```
INSERT INTO A VALUES (3, 3);
```

```
INSERT INTO B VALUES (1, 1);
```

```
INSERT INTO B VALUES (2, 3);
```

```
INSERT INTO B VALUES (4, 5);
```

```
INSERT INTO C VALUES (1, 'X');
```

```
INSERT INTO C VALUES (3, 'Y');
```

```
INSERT INTO C VALUES (5, 'Z');
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Example: Violation of Associativity

```
SELECT * FROM (A LEFT OUTER JOIN B ON A.M = B.id)
LEFT OUTER JOIN C ON B.id IS NULL;
```

	id	M	id	N	id	val
▶	1	1	1	1	NULL	NULL
	2	2	2	3	NULL	NULL
	3	3	NULL	NULL	1	X
	3	3	NULL	NULL	3	Y
	3	3	NULL	NULL	5	Z

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
SELECT * FROM A LEFT OUTER JOIN (B LEFT OUTER
JOIN C ON B.id IS NULL) ON A.M = B.id;
```

	id	M	id	N	id	val
▶	1	1	1	1	NULL	NULL
	2	2	2	3	NULL	NULL
	3	3	NULL	NULL	NULL	NULL

# On or Where?

```
select uName, age  
from User join Loan on User.uID=Loan.uID  
where loaned > 3 and title = 'Bambi';
```

Assignment Project Exam Help  
<https://powcoder.com>

Add WeChat powcoder

```
select uName, age  
from User join Loan on User.uID=Loan.uID and  
loaned > 3 and title = 'Bambi';
```

# On or Where?

- With an **Inner Join**, the clauses are *effectively* equivalent.
- With an **Outer Join**, they are not the same.

select \* from User **left outer join** Loan **on**  
User.uID = Loan.uID **where** Loan.overdue = true ;  
vs.

select \* from User **left outer join** Loan  
**on** User.uID = Loan.uID and Loan.overdue = true;



```
select User.uID, uName, Loan.uID, title, overdue
from User left join Loan on User.uID = Loan.uID
where Loan.overdue = true;
```

## Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

	uID	uName	uID	title	overdue
▶	1001	Jason S. Wright	1001	Bambi	1
	1001	Jason S. Wright	1001	Bambi	1
	1006	Juanita J. Palmer	1006	Lion King	1
	1007	Otherone with no age	1007	Bambi	1
	1012	Margaret F. Delmonte	1012	Database Systems	1

select User.uID, uName,  
Loan.uID, title, overdue  
from User **left join** Loan  
**on** User.uID = Loan.uID  
and Loan.overdue = 1;

	uID	uName	uID	title	overdue
▶	1001	Jason S. Wright	1001	Bambi	1
	1001	Jason S. Wright	1001	Bambi	1
	1002	Kim	NULL	NULL	NULL
	1003	Jane Koffman	NULL	NULL	NULL
	1004	Katherine H. Lang	NULL	NULL	NULL
	1005	Smith	NULL	NULL	NULL
	1006	Juanita J. Palmer	1006	Lion King	1
	1007	Someone with no age	1007	Bambi	1
	1008	Ethel W. Williams	NULL	NULL	NULL
	1009	Someone with no age	NULL	NULL	NULL
	1010	Candis C. Whitehead	NULL	NULL	NULL
	1011	Kim	NULL	NULL	NULL
	1012	Margaret F. Demonte	1012	Databas...	1
	1013	Susan M. McKeel	NULL	NULL	NULL
	1014	Kim	NULL	NULL	NULL
	1015	Shirley A. Dehaven	NULL	NULL	NULL
	1016	Smith	NULL	NULL	NULL
	1017	Chad G. Turner	NULL	NULL	NULL
	1018	Suzanne J. Champine	NULL	NULL	NULL
	1019	Harry King	NULL	NULL	NULL

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Join using and on together

```
select U1.uID, U1.uName, U1.age, U2.uID,  
U2.uName, U2.age
```

```
from User U1 join User U2 using (age)
```

```
where U1.uID < U2.uID;
```

Assignment Project Example Help

<https://powcoder.com>

Add WeChat powcoder

```
select U1.uID, U1.uName, U1.age, U2.uID,  
U2.uName, U2.age
```

```
from User U1 join User U2 on U1.age = U2.age
```

```
where U1.uID < U2.uID;
```

# Changing three way join to binary join

```
select *  
from Loan join User join Book  
on Loan.uID = User.uID and Loan.title = Book.title ;
```

Assignment Project Exam Help

<https://powcoder.com>



```
select *  
from (Loan join User on Loan.uID = User.uID)  
join Book on Loan.title = Book.title;
```

Add WeChat powcoder

# Natural Join

// Suppose uID is the only common attribute in  
// User and Loan

select distinct uName, title  
from User **natural join** Loan;  
→ <https://powcoder.com>

select distinct uName, title  
from User **join** Loan  
**on** User.uID = Loan.uID;

Note: select \* will return relations with a different schema.

# MySQL doesn't support except (or minus) and intersect

A

x	y
1	a
2	b
3	c
4	d

B

x	y
1	a
3	c

<https://powcoder.com>  
[Add WeChat powcoder](#)

```
DROP TABLE IF EXISTS A;  
CREATE TABLE A (x INT, y VARCHAR(5));  
INSERT INTO A(x,y) VALUES (1, 'a');  
INSERT INTO A(x,y) VALUES (2, 'b');  
INSERT INTO A(x,y) VALUES (3, 'c');  
INSERT INTO A(x,y) VALUES (4, 'd');  
DROP TABLE IF EXISTS B;  
CREATE TABLE B (x INT, y VARCHAR(5));  
INSERT INTO B(x,y) VALUES (1, 'a');  
INSERT INTO B(x,y) VALUES (3, 'c');
```

# Difference in MySQL

A

x	y
1	a
2	b
3	c
4	d

B

x	y
1	a
3	c

```
SELECT * FROM A
WHERE (x, y) NOT IN (SELECT *
FROM B);
```

Assignment Project Exam Help

```
SELECT * FROM A
```

<https://powcoder.com>

```
WHERE NOT EXISTS
(SELECT * FROM B WHERE B.x =
A.x AND B.y = A.y);
```

Add WeChat powcoder

A - B

x	y
2	b
4	d

```
SELECT DISTINCT A.x AS x, A.y AS y
FROM A LEFT OUTER JOIN B USING (x,
y) WHERE B.x IS NULL;
```

# Intersection in MySQL

A

x	y
1	a
2	b
3	c
4	d

B

x	y
1	a
3	c

```
SELECT * FROM A WHERE (x,y)
IN (SELECT * FROM B);
```

Assignment Project Exam Help

```
SELECT * FROM A WHERE EXISTS
(SELECT * FROM B
WHERE B.x=A.x AND B.y =A.y);
```

<https://powcoder.com>

Add WeChat powcoder

$A \cap B$

x	y
1	a
3	c

```
SELECT DISTINCT A.x AS x, A.y AS y
FROM A INNER JOIN B USING (x,y);
```



# Aggregation

- min, max, sum, avg, count

select A1, A2, ..., An ← aggregation appears here.

from R1, R2, ..., Rn

where ← apply to the single tuple at a time

group by

having ← filter the group

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
select avg(age)
from User;
```

```
select min(age)
from User, Loan
where User.uID = Loan.uID and title = 'Bambi';
```

Assignment Project Exam Help  
<https://powcoder.com>  
Add WeChat powcoder

```
select count(*)
from User, Loan
where User.uID = Loan.uID and title = 'Bambi';
```

```
select avg(distinct age)
from User, Loan
where User.uID = Loan.uID and title = 'Bambi' ;
```

VS **Assignment Project Exam Help**

**<https://powcoder.com>**

```
select avg(age)
```

**Add WeChat powcoder**

```
from User
```

```
where uID in
```

```
(select uID from Loan where title = 'Bambi');
```

# Eliminating Duplicates in an Aggregation

```
select count(distinct uID)
from Loan
where title = 'Bambi';
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# group by

- We may follow a SELECT-FROM-WHERE expression by GROUP BY and a list of grouping attributes.
- The relation that results from the FROM-WHERE is grouped according to the values of all those attributes, and any aggregation in SELECT is applied only within each group.

# group by

When there is an aggregation in SELECT clause, there are only two types of terms the SELECT clause can have:

1. Aggregations - these terms are evaluated for each group
2. Grouping attributes can be unaggregated.

# Example: group by

```
select title, count(*)
```

```
from Loan
```

```
group by title;
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# group by

```
select title, min(age), max(age)
```

```
from User, Loan
```

```
where User.uID = Loan.uID
```

```
group by title;
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# group by

[Q] To find the Largest span of ages of users who borrowed the same book

Assignment Project Exam Help

select max(mx-mn)

<https://powcoder.com>

from

(select title, min(age) as mn, max(age) as mx

from User, Loan

where User.uID = Loan.uID

group by title) ST;

# group by

[Q] To find the number of **different** books a user loaned

Assignment Project Exam Help

<https://powcoder.com>

select User.uID, uName, count(**distinct** title)

Add WeChat powcoder

from User, Loan

where User.uID = Loan.uID

group by User.uID;

# Does it work ?

```
select User.uID, uName, count(distinct title), title  
from User, Loan  
where User.uID = Loan.uID  
group by User.uID
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

In MySQL, run this query with

1. set sql\_mode=only\_full\_group\_by

and

2. set sql\_mode=""

# Quiz

Number of books loaned by each user. If a user did not loan any book, show 0 for the number of loaned books.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
select User.uID, uName, count(distinct title)
from User, Loan
where User.uID = Loan.uID
group by User.uID
union
select User.uID, uName, 0
from User
where uID not in (select uID from Loan);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# HAVING Clauses

- HAVING <condition> may follow a GROUP BY clause.
- If so, the condition applies to each group, and groups not satisfying the condition are eliminated.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Requirements on HAVING Conditions

1. An **aggregation in a HAVING** clause applies **only to the group** being tested.

Assignment Project Exam Help

<https://powcoder.com>

select loaned, count(\*)

from User

Add WeChat powcoder

group by loaned

having count(\*) >2

→ Tests if the current group has more than 2 counts

# Requirements on HAVING Conditions

2. Any attributes of relations in the FROM clause may be aggregated in the HAVING clause, but only grouping attributes may appear un-aggregated in the HAVING clause.

<https://powcoder.com>

Add WeChat powcoder

```
select loaned, count(*), avg(age)
from User
group by loaned
having avg(age) > 40 and count(*) >=3 ;
```



# Example: Violation

select loaned, count(\*), age

from User

group by loaned

having age > 40 and count(\*) >=3 ;

an error.

# Having

[Q] To find books loaned at least three times

select title

from Loan

group by title

having count(\*) >=3;

Assignment Project Exam Help

<https://powcoder.com>

[Q] To find a book loaned by at least three different users.

select title

from Loan

group by title

having count(distinct uID) >= 3;

Add WeChat powcoder

# Without using group by and having

To find books with fewer than 3 borrowers

```
select title
from Loan
group by title
having count(*) < 3;
```

```
select distinct title
from Loan L1
where
  (select count(*)
   from Loan L2
   where L2.title = L1.title) < 3;
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

[Q] To find books whose loaner's maximum age is below the average age of users

select title

from User, Loan

where User.userID = Loan.userID

group by title

having max(age) < (select avg(age) from User);

# Null values and Aggregation

- NULL is ignored in any aggregation except for count(\*)

select sum(age) from User: null is ignored

count(\*) counts all tuples including null

count(age) counts non-null ages.

count(distinct age) counts non-null unique ages.

- NULL is treated as an ordinary when forming groups.  
e.g.) select age, count(\*) from user group by age;
- Any aggregation, except count, over an empty bag of values returns NULL. The count of an empty bag is 0.

# Example: Null values and Aggregation

1. select count(\*)  
from User  
where age is not null;

2. select count(distinct age)  
from User  
where age is not null;

3. select count(distinct age)  
from User

4. select distinct age  
from User

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Notes:

2 and 3 return the same result.

4 returns distinct ages including null.

# Data Modification

- `insert into R values (V1, V2, ..., Vn)`
- `insert into R select statement`
- `delete from R where condition`
- `update R`  
    `set attribute = expression`  
    `where condition`
- `update R`  
    `set A1 = expr1, A2 = expr2, ..., An = exprn`  
    `where condition`

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Insert

- To insert a single tuple:

INSERT INTO R (A1, ..., An)

VALUES (v1, ..., vn);

- We may add to the relation name a list of attributes. Two reasons to do so:
  1. We forget the standard order of attributes for the relation.
  2. We don't have values for all attributes, and we want the system to fill in missing components with NULL or a default value.



# Insert

```
insert into Book(title,author,copies)
values('This Book', 'That Author', 40);
```

=

```
insert into Book values
('This Book', 'That Author', 40);
```

```
insert into Book(title,author) values
('This Book', 'That Author');
```

**Add WeChat powcoder**

→ The system will initialize the value of copies to null.

```
Error: insert into Book(title,author,copies)
      values('This Book', 'That Author');
```

```
Error: insert into Book
      values ('This Book', 'That Author');
```

# on update

```
CREATE TABLE USER
```

```
(uID INT AUTO_INCREMENT,
```

```
uNAME VARCHAR(30),
```

```
age INT,
```

```
loaned INT,
```

```
updatedAt timestamp on update current_timestamp,
```

```
PRIMARY KEY (uID)
```

```
);
```

When a row is updated, the field (updatedAt in this example) will get the current timestamp.

# on update

```
insert into user (uname, age, loaned, updateon)  
values('John Smith', 23, 4, now());
```

Inserts a row with the updateon value set to the current timestamp.

1032		John Smith		23		4		2020-09-27 08:43:44
------	--	------------	--	----	--	---	--	---------------------

```
update user set age = 99 where uid = 1032;
```

The updateon value of the row will set to the current timestamp of updating.

1032		John Smith		99		4		2020-09-27 08:46:42
------	--	------------	--	----	--	---	--	---------------------

# AUTO\_INCREMENT

```
CREATE TABLE USER
```

```
(uID INT AUTO_INCREMENT,
```

```
uNAME VARCHAR(30),
```

```
age INT,
```

```
loaned INT,
```

```
updatedAt timestamp on update current_timestamp,
```

```
PRIMARY KEY (uID)
```

```
);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# AUTO\_INCREMENT

- The value of an auto increment attribute is incremented sequentially whenever a new row is added into the database.
- By default, the starting value for AUTO\_INCREMENT is 1, and it will increment by 1 for each new record
- To let AUTO\_INCREMENT sequence start with another value , use, for example, ALTER TABLE USER AUTO\_INCREMENT = 1001;
- The auto increment is commonly used to generate primary keys.
- The defined data type on the auto increment should be large enough to accommodate many records. (e.g. TINYINT limits the number of records that can be added to the table to 255.)
- When a row is deleted from a table, its auto incremented id is not re-used. MySQL continues generating new numbers sequentially.
- The LAST\_INSERT\_ID() function returns the first automatically generated integer successfully inserted for an AUTO\_INCREMENT column.

# Insert

- When you insert any other value into an AUTO\_INCREMENT column, the column is set to that value and the sequence is reset so that the next automatically generated value follows sequentially from the largest column value.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

e.g.

```
insert into user (uid, uname, age, loaned,  
updatedon) values (1500, 'John Smith',  
23, 4, now());
```

# Inserting Many Tuples

- We may insert the entire result of a query into a relation, using the form:

```
INSERT INTO <relation>  
( <subquery> );
```

Assignment Project Exam Help  
<https://powcoder.com>

```
insert into Loan  
(select uID, 'Let's Read!', '0000-00-00', false  
from User where uID not in  
      (select uID from Loan)  
);
```

Add WeChat powcoder

[Q] To have users, who loaned Bambi and not being overdue, loan 'Lion King '.

insert Loan

(select uid, 'Lion King', UTC\_DATE(), false

from USER

where uid in

(select uid from Loan where title='Bambi'  
and overdue = false));

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Delete

- To delete tuples satisfying a condition from some relation:

**Assignment Project Exam Help**  
**DELETE FROM <relation>**  
**WHERE <condition>;**  
**<https://powcoder.com>**  
**Add WeChat powcoder**

# Delete

[Q] To delete a user who borrowed the same books

delete from User  
where uID in  
(select uID  
from Loan  
group by uID  
having count(title) <> count(distinct title)) ;

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Delete – Error

```
delete
from Loan
where uID in
(
  select uID
  from Loan
  group by uID
  having count(title) <> count(distinct title)
) ;
```

**Assignment Project Exam Help**  
<https://powcoder.com>  
**Add WeChat powcoder**

Note: You can't specify the target relation Loan for update in From clause.

# Update

- To change certain attributes in certain tuples of a relation:

[Assignment Project Exam Help](https://powcoder.com)  
UPDATE <relation>  
<https://powcoder.com>  
SET <list of attribute assignments>  
[Add WeChat powcoder](https://powcoder.com)  
WHERE <condition on tuples>;

# Update

[Q] To find a user with age < 15, and turn their overdue to false.

Assignment Project Exam Help

update Loan <https://powcoder.com>

set overdue = false [Add WeChat powcoder](https://powcoder.com)

where overdue = true and uID in (select uID  
from user where age < 15);

update **Loan**

set overdue=false

where overdue = true and uID in (select uID from  
user where age =(select max(age)from user natural  
join **Loan** where title = 'Bambi'));

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Error: Can't specify the target  
loan for update in FROM clause

```
DROP VIEW IF EXISTS OldestBambiUser;
```

```
CREATE VIEW OldestBambiUser AS
```

```
  select distinct uID
```

```
  from user natural join Loan
```

```
  where title = 'Bambi' and age =
```

```
    (select max(age)
```

```
      from user natural join loan
```

```
      where title = 'Bambi');
```

```
update Loan
```

```
set overdue = false
```

```
where overdue = true and uID in
```

```
  (select * from OldestBambiUser);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder