

CS-205 Week3: Arithmetic

- Theory
 - Introduce Prolog's built-in abilities for performing **arithmetic**
 - Apply these to simple list processing problems, using **accumulators**
 - Look at **tail-recursive** predicates and explain why they are more efficient than predicates that are not tail-recursive
- Exercises
 - Exercises of LPN: 5.1, 5.2, 5.3
 - Practical work

Arithmetic in Prolog

- Prolog provides a number of basic arithmetic tools
- Integer and real numbers

Assignment Project Exam Help

<https://powcoder.com>

Arithmetic

$$2 + 3 = 5$$

$$3 \times 4 = 12$$

$$5 - 3 = 2$$

$$3 - 5 = -2$$

$$4 : 2 = 2$$

1 is the remainder when 7 is
divided by 2

Add WeChat powcoder

Prolog

?- 5 is 2+3.

?- 12 is 3*4.

?- 2 is 5-3.

?- -2 is 3-5.

?- 2 is 4/2.

?- 1 is mod(7,2).

Example queries

?- 10 is 5+5.

yes

Assignment Project Exam Help

?- 4 is 2+3.

no

<https://powcoder.com>

Add WeChat powcoder

?- X is 3 * 4.

X=12

yes

?- R is mod(7,2).

R=1

yes

Defining predicates with arithmetic

addThreeAndDouble(X, Y):-

Y is (X+3) * 2.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Defining predicates with arithmetic

addThreeAndDouble(X, Y):-

Y is (X+3) * 2.

Assignment Project Exam Help

<https://powcoder.com>

?- addThreeAndDouble(1, X).

Add WeChat powcoder

X=8

yes

?- addThreeAndDouble(2, X).

X=10

yes

A closer look

- It is important to know that $+$, $-$, $/$ and $*$ do not carry out any arithmetic
- Expressions such as $3+2$, $4-7$, $5/5$ are ordinary Prolog terms
 - Functor: $+$, $-$, $/$, $*$
 - Arity: 2
 - Arguments: integers

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A closer look

?- $X = 3 + 2$.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A closer look

?- $X = 3 + 2.$

$X = 3 + 2$

yes

?-

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A closer look

?- $X = 3 + 2$.

$X = 3 + 2$

yes

Assignment Project Exam Help

<https://powcoder.com>

?- $3 + 2 = X$.

Add WeChat powcoder

A closer look

?- $X = 3 + 2$.

$X = 3 + 2$

yes

Assignment Project Exam Help

<https://powcoder.com>

?- $3 + 2 = X$.

$X = 3 + 2$

Add WeChat powcoder

yes

?-

The is/2 predicate

- To force Prolog to actually evaluate arithmetic expressions, we have to use
Assignment Project Exam Help

is <https://powcoder.com>

Add WeChat powcoder
just as we did in the other examples

- This is an instruction for Prolog to carry out calculations
- Because this is not an ordinary Prolog predicate, there are some restrictions

The is/2 predicate

?- X is 3 + 2.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The is/2 predicate

?- X is 3 + 2.

X = 5

yes

?-

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The is/2 predicate

?- X is 3 + 2.

X = 5

yes

Assignment Project Exam Help

<https://powcoder.com>

?- 3 + 2 is X.

Add WeChat powcoder

The is/2 predicate

?- X is 3 + 2.

X = 5

yes

Assignment Project Exam Help

<https://powcoder.com>

?- 3 + 2 is X.

ERROR: is/2: Arguments are not sufficiently instantiated

?-

The is/2 predicate

?- X is 3 + 2.

X = 5

yes

Assignment Project Exam Help

<https://powcoder.com>

?- 3 + 2 is X.

ERROR: is/2: Arguments are not sufficiently instantiated

?- Result is 2+2+2+2+2.

The is/2 predicate

?- X is 3 + 2.

X = 5

yes

Assignment Project Exam Help

<https://powcoder.com>

?- 3 + 2 is X.

ERROR: is/2: Arguments are not sufficiently instantiated

?- Result is 2+2+2+2+2.

Result = 10

yes

?-

Restrictions on use of is/2

- We are free to use variables on the right hand side of the **is** predicate
- But when Prolog actually carries out the evaluation, the variables must be instantiated with a variable-free Prolog term
- This Prolog term must be an arithmetic expression

Notation

- Two final remarks on arithmetic expressions
 - $3+2$, $4/2$, $4-5$ are just ordinary Prolog terms in a user-friendly notation:
 $3+2$ is really $+(3, 2)$ and so on.
 - Also the **is** predicate is a two-place Prolog predicate

Notation

- Two final remarks on arithmetic expressions
 - $3+2$, $4/2$, $4-5$ are just ordinary Prolog terms in a user-friendly notation:
 $3+2$ is really $+(3,2)$ and so on.
 - Also the **is** predicate is a two-place Prolog predicate

```
?- is(X,+(3,2)).  
X = 5  
yes
```

Arithmetic and Lists

- How long is a list?
 - The empty list has length: zero;
 - A non-empty list has length: one plus length of its tail.

Length of a list in Prolog

```
len([],0).
```

```
len([_|L],N):-
```

```
    len(L,X),
```

```
    N is X + 1.
```

Assignment Project Exam Help

<https://powcoder.com>

?-

Add WeChat powcoder

Length of a list in Prolog

```
len([],0).
```

```
len([_|L],N):-
```

```
    len(L,X),
```

```
    N is X + 1.
```

Assignment Project Exam Help

<https://powcoder.com>

```
?- len([a,b,c,d,e,[a,x],[]],X).
```

Add WeChat powcoder

Length of a list in Prolog

```
len([],0).
```

```
len([_|L],N):-
```

```
    len(L,X),
```

```
    N is X + 1.
```

Assignment Project Exam Help

<https://powcoder.com>

```
?- len([a,b,c,d,e,[a,x],[]],X).
```

```
X=7
```

```
yes
```

```
?-
```

Add WeChat powcoder

Accumulators

- This is quite a good program
 - Easy to understand
 - Relatively efficient
- But there is another method of finding the length of a list
 - Introduce the idea of accumulators
 - Accumulators are variables that hold intermediate results

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Defining acclen/3

- The predicate acclen/3 has three arguments
 - The list whose length we want to find
 - The length of the list, an integer
 - An accumulator, keeping track of the intermediate values for the length

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Defining acclen/3

- The accumulator of acclen/3
 - Initial value of the accumulator is 0
 - Add 1 to accumulator each time we can recursively take the head of a list
 - When we reach the empty list, the accumulator contains the length of the list

Length of a list in Prolog

```
acclen([],Acc,Length):-  
    Length = Acc.
```

Assignment Project Exam Help

```
acclen([_|L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,
```

```
    acclen(L,NewAcc,Length).
```

<https://powcoder.com>

Add WeChat powcoder

?-

Length of a list in Prolog

```
acclen([],Acc,Length):-  
    Length = Acc.
```

add 1 to the accumulator
each time we take off a
head from the list

```
acclen([_|L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

?-

Length of a list in Prolog

```
acclen([],Acc,Length):-  
    Length = Acc.
```

When we reach the empty list,
the accumulator contains the
length of the list

```
acclen([_|L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

?-

Length of a list in Prolog

```
acclen([],Acc,Acc).
```

```
acclen([_|L],OldAcc,Length):-
```

```
    NewAcc is OldAcc + 1,
```

```
    acclen(L,NewAcc,Length).
```

?-

Length of a list in Prolog

```
acclen([],Acc,Acc).
```

```
acclen([_|L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

```
?-acclen([a,b,c],0,Len).
```

```
Len=3
```

```
yes
```

```
?-
```


Search tree for acclen/3

?- acclen([a,b,c],0,Len).

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
acclen([ ],Acc,Acc).
```

```
acclen([_|L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Search tree for acclen/3

?- acclen([a,b,c],0,Len).

/

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
acclen([ ],Acc,Acc).
```

```
acclen([_ | L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Search tree for acclen/3

?- acclen([a,b,c],0,Len).

/

no

?- acclen([b,c],1,Len).

/

\

```
acclen([ ],Acc,Acc).
```

```
acclen([_ | L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Search tree for acclen/3

?- acclen([a,b,c],0,Len).

/

no

?- acclen([b,c],1,Len).

/

no

?- acclen([c],2,Len).

/

\

```
acclen([ ],Acc,Acc).
```

```
acclen([_ | L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Search tree for acclen/3

?- acclen([a,b,c],0,Len).

/

no

?- acclen([b,c],1,Len).

/

no

?- acclen([c],2,Len).

/

no

?- acclen([],3,Len).

/

\

acclen([],Acc,Acc).

acclen([_|L],OldAcc,Length):-
NewAcc is OldAcc + 1,
acclen(L,NewAcc,Length).

Search tree for acclen/3

?- acclen([a,b,c],0,Len).

/

no

?- acclen([b,c],1,Len).

/

no

?- acclen([c],2,Len).

/

no

?- acclen([],3,Len).

/

Len=3

\

no

```
acclen([ ],Acc,Acc).
```

```
acclen([_ | L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Adding a wrapper predicate

```
acclen([ ],Acc,Acc).
```

```
acclen([ _|L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

```
length(List,Length):-
```

```
    acclen(List,0,Length).
```

```
?-length([a,b,c], X).
```

```
X=3
```

```
yes
```

Tail recursion

- Why is `acclen/3` better than `len/2` ?
 - `acclen/3` is tail-recursive, and `len/2` is not
- Difference:
 - In tail recursive predicates the results is fully calculated once we reach the base clause
 - In recursive predicates that are not tail recursive, there are still goals on the stack when we reach the base clause

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Comparison

Not tail-recursive

```
len([],0).  
len(_|L,NewLength):-  
    len(L,Length),  
    NewLength is Length + 1.
```

Tail-recursive

```
acclen([],Acc,Acc).  
acclen(_|L,OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Search tree for len/2

?- len([a,b,c], Len).

```
len([],0).  
len(_|L,NewLength):-  
    len(L,Length),  
    NewLength is Length + 1.
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Search tree for len/2

?- len([a,b,c], Len).

/ \
no ?- len([b,c], Len1).
 Len is Len1 + 1.

len([],0).

len([_|L],NewLength):-

len(L,Length),

NewLength is Length + 1.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Search tree for len/2

?- len([a,b,c], Len).

/ \

no ?- len([b,c], Len1),
Len is Len1 + 1.

/

no ?- len([c], Len2),
Len1 is Len2+1,
Len is Len1+1.

len([],0).

len(_|L,NewLength):-

len(L,Length),

NewLength is Length + 1.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Search tree for len/2

?- len([a,b,c], Len).

/ \
no ?- len([b,c], Len1),
Len is Len1 + 1.

/ \
no ?- len([c], Len2),
Len1 is Len2+1,
Len is Len1+1.

/ \
no ?- len([], Len3),
Len2 is Len3+1,
Len1 is Len2+1,
Len is Len1 + 1.

len([],0).

len([_|L],NewLength):-
len(L,Length),
NewLength is Length + 1.

Search tree for len/2

?- len([a,b,c], Len).

/ \

no ?- len([b,c], Len1),

Len is Len1 + 1.

/ \

no ?- len([c], Len2),

Len1 is Len2 + 1,

Len is Len1 + 1.

/ \

no ?- len([], Len3),

Len2 is Len3 + 1,

Len1 is Len2 + 1,

Len is Len1 + 1.

/ \

Len3=0, Len2=1,

Len1=2, Len=3

len([],0).

len([_|L],NewLength):-

len(L,Length),

NewLength is Length + 1.

Search tree for acclen/3

?- acclen([a,b,c],0,Len).

/

no

?- acclen([b,c],1,Len).

/

no

?- acclen([c],2,Len).

/

no

?- acclen([],3,Len).

/

Len=3

\

no

```
acclen([ ],Acc,Acc).
```

```
acclen([_ | L],OldAcc,Length):-  
    NewAcc is OldAcc + 1,  
    acclen(L,NewAcc,Length).
```

Exercises

- Exercise 5.1
- Exercise 5.2
- Exercise 5.3

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Comparing Integers

- Some Prolog arithmetic predicates actually do carry out arithmetic by themselves
- These are the operators that compare integers

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Comparing Integers

Arithmetic

$x < y$

$x \leq y$

$x = y$

$x \neq y$

$x \geq y$

$x > y$

Prolog

$X < Y$

$X \leq Y$

$X =:= Y$

$X \backslash= Y$

$X \geq Y$

$X > Y$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Comparison Operators

- Have the obvious meaning
- Force both left and right hand argument to be evaluated

Assignment Project Exam Help

<https://powcoder.com>

?- 2 < 4+1.

yes

?- 4+3 > 5+5.

no

Add WeChat powcoder

Comparison Operators

- Have the obvious meaning
- Force both left and right hand argument to be evaluated

Assignment Project Exam Help

<https://powcoder.com>

?- 4 = 4.

yes

?- 2+2 = 4.

no

?- 2+2 =:= 4.

yes

Add WeChat powcoder

Comparing numbers

- We are going to define a predicate that takes two arguments, and is true when:
 - The first argument is a list of integers
 - The second argument is the highest integer in the list
- Basic idea
 - We will use an accumulator
 - The accumulator keeps track of the highest value encountered so far
 - If we find a higher value, the accumulator will be updated

Definition of accMax/3

```
accMax([H|T],A,Max):-
```

```
    H > A,
```

```
    accMax(T,H,Max).
```

```
accMax([H|T],A,Max):-
```

```
    H =< A,
```

```
    accMax(T,A,Max).
```

```
accMax([],A,A).
```

```
?- accMax([1,0,5,4],0,Max).
```

```
Max=5
```

```
yes
```

Adding a wrapper max/2

```
accMax([H|T],A,Max):-
```

```
    H > A,
```

```
    accMax(T,H,Max).
```

```
accMax([H|T],A,Max):-
```

```
    H =< A,
```

```
    accMax(T,A,Max).
```

```
accMax([],A,A).
```

```
max([H|T],Max):-
```

```
    accMax(T,H,Max).
```

```
?- max([1,0,5,4], Max).
```

```
Max=5
```

```
yes
```

```
?- max([-3, -1, -5, -4], Max).
```

```
Max= -1
```

```
yes
```

```
?-
```

Summary of this lecture

- In this lecture we showed how Prolog does **arithmetic**
- We demonstrated the difference between **tail-recursive** predicates and predicates that are not tail-recursive
- We introduced the programming technique of using **accumulators**
- We also introduced the idea of using **wrapper** predicates

Next lecture

- Yes, more lists!
 - Defining the `append/3`, a predicate that concatenates two lists
 - Discuss the idea of reversing a list, first naively using `append/3`, then with a more efficient way using accumulators