

CS 314 Principles of Programming Languages

Lecture 18: Parallelism and Dependence Analysis

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Prof. Zheng Zhang



Rutgers University

November 9, 2018

Class Information

- Project 2 is released.
- Homework 7 will be released this weekend.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Programming with Concurrency

- A PROCESS or THREAD is a potentially-active execution context
- Classic *von Neumann* model of computing has single thread of control, however parallel programs have more than one
- A process or thread can be thought of as
An abstraction of a physical PROCESSOR
- Processes/Threads can come from
 - ▶ Multiple CPUs
 - ▶ Kernel-level multiplexing of single physical machine
 - ▶ Language or library level multiplexing of kernel-level abstraction
- They can run
 - ▶ In true **parallel**
 - ▶ Unpredictably interleaved
 - ▶ Run-until-block

Dependence and Parallelization

Dependence analysis is fundamental to parallelization analysis

Dependence relation: all *task-to-task* execution orderings that must be preserved if the meaning of the program is to remain the same.

The dependence relation can be modeled as a directed graph such that if $A \rightarrow B$, the result of task A is required for the processing of task B

Assignment Project Exam Help


Example:

<https://powcoder.com>
Add WeChat powcoder

$S_1: \pi = 3.14$

$S_2: R = 5$

$S_3: \text{Area} = \pi * R^2$




Statement-level dependence graph

Dependence Graph

- Directed acyclic graph (DAG)
- A node represents a task
- A directed edge represents precedence constraint


DAG example 1:



Dependence Graph

- Directed acyclic graph (DAG)
- A node represents a task
- A directed edge represents precedence constraint

DAG example 2:



Scheduling a DAG

T_p : time to perform computation with p processors

- T_1 : **work** (total # operations)
- T_∞ : **critical path** or **span**


$$T_p \geq \frac{T_1}{p}, \quad T_p \geq T_\infty$$

Assuming a task
takes 1 unit time

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Scheduling a DAG

T_p : time to perform computation with p processors

- T_1 : **work** (total # operations)
- T_∞ : **critical path** or **span**


$$T_p \geq \frac{T_1}{p}, \quad T_p \geq T_\infty$$

Assuming a task
takes 1 unit time

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



$T_1 = ?$

Scheduling a DAG

T_p : time to perform computation with p processors

- T_1 : **work** (total # operations)
- T_∞ : **critical path** or **span**


$$T_p \geq \frac{T_1}{p}, \quad T_p \geq T_\infty$$

Assuming a task
takes 1 unit time

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



$T_\infty = ?$

Scheduling a DAG

T_p : time to perform computation with p processors

- T_1 : **work** (total # operations)
- T_∞ : **critical path** or **span**


$$T_p \geq \frac{T_1}{p}, \quad T_p \geq T_\infty$$

Assuming a task
takes 1 unit time

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



$T_\infty = ?$


Computing Critical Path

Compute the earliest start time of each node

- Keep a value called $S(n)$ associated with each node n
- For each node n

$S(n)$ is the maximum of $\{ S(p) + 1 \}$, for all $p \in \text{pred}(n)$

Assuming a task
takes 1 unit time




Computing Critical Path

Compute the earliest start time of each node

- Keep a value called $S(n)$ associated with each node n
- For each node n

$S(n)$ is the maximum of $\{ S(p) + 1 \}$, for all $p \in \text{pred}(n)$

Assuming a task takes 1 unit time




Computing Critical Path

Compute the earliest start time of each node

- Keep a value called $S(n)$ associated with each node n
- For each node n

$S(n)$ is the maximum of $\{ S(p) + 1 \}$, for all $p \in \text{pred}(n)$

Assuming a task takes 1 unit time




Computing Critical Path

Compute the earliest start time of each node

- Keep a value called $S(n)$ associated with each node n
- For each node n

$S(n)$ is the maximum of $\{ S(p) + 1 \}$, for all $p \in \text{pred}(n)$

Assuming a task takes 1 unit time




Computing Critical Path

Compute the earliest start time of each node

- Keep a value called $S(n)$ associated with each node n
- For each node n

$S(n)$ is the maximum of $\{ S(p) + 1 \}$, for all $p \in \text{pred}(n)$

Assuming a task takes 1 unit time




Computing Critical Path

Compute the earliest start time of each node

- Keep a value called $S(n)$ associated with each node n
- For each node n

$S(n)$ is the maximum of $\{ S(p) + 1 \}$, for all $p \in \text{pred}(n)$

Assuming a task takes 1 unit time



List Scheduling


Based on if the dependence constraints have been resolved

- Schedule the nodes that are ready at every time tick
- A completed operation at the end of one time step can lead to more ready operations at next time tick

Four threads T1, T2, T3, T4

	1	2	3	4	5
T1	start	a	b	f	end
T2		c	e	i	
T3		d	g		
T4			h		

Assuming a task takes 1 unit time



Automatic Parallelization

We will use **loop analysis** as an example to describe automatic dependence analysis and parallelization.

Assumptions:

1. We only have scalar and subscripted variables (no pointers and no control dependence) for loop dependence analysis.
2. We focus on *affine loops*. both loop bounds and memory references are affine functions of loop induction variables.

<https://powcoder.com>

Add WeChat powcoder

A function $f(x_1, x_2, \dots, x_n)$ is **affine** if it is in such a form:

$$\mathbf{f} = c_0 + c_1 * \mathbf{x}_1 + c_2 * \mathbf{x}_2 + \dots + c_n * \mathbf{x}_n, \text{ where } c_i \text{ are all constants}$$

Affine Loops

Three spaces

- Iteration space
 - The set of dynamic execution instances
 - i.e. the set of value vectors taken by loop indices
 - A k -dimensional space for a k -level loop nest
- Data space
 - The set of array elements accessed
 - An n -dimensional space for an n -dimensional array
- Processor space
 - The set of processors in the system
 - In analysis, we may pretend there are unbounded # of virtual processors


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Three Spaces

- Iteration space, data space, and processor space



Assuming one task is one loop iteration,
what is the maximum parallelism?

Maximum parallelism: T_1 / T_∞

Dependence Definition

Bernstein's Condition: — There is a data dependence from statement (instance) S_1 to statement S_2 (instance) if

- Both statements (instances) access the same memory locations
- One of them is a write
- There is a run-time execution path from S_1 to S_2

Assignment Project Exam Help

```
float Z[100]; https://powcoder.com
```

```
for (i=0; i<10; i++)
```

```
    Z[i+10] = Z[i];
```

No dependence across any
two loop iterations!

Data Dependence Classifications

“S₂ depends on S₁” — (S₁ δ S₂)

True (flow) dependence

occurs when S₁ writes a memory location that S₂ later reads (RAW).

Anti dependence

occurs when S₁ reads a memory location that S₂ later writes (WAR).

Assignment Project Exam Help

<https://powcoder.com>

Output dependence

Add WeChat powcoder

occurs when S₁ writes a memory location that S₂ later writes (WAW).

Input dependence

occurs when S₁ reads a memory location that S₂ later reads (RAR).

Simple Dependence Testing

- **Examples:**

```
for (i = 1; i <= 100; i++) {  
  S1: A[i] = ...  
  S2: ...= A[i - 1]  
}
```

```
float Z[100];  
for (i = 0; i < 12; i++) {  
  S: Z[ i+10 ] = Z[i];  
}
```

Assignment Project Exam Help

<https://powcoder.com>

1. Is there dependence?
2. If so, what type of dependence?
3. From which statement (instance) to which statement (instance)?

Dependence Testing

Single Induction Variable (SIV) Test

- Single loop nest with constant lower (LB) and upper (UB) bound, and step 1.

```
for i = LB, UB, 1
```

```
...
```

```
endfor
```

Assignment Project Exam Help

- Two array references as affine function of loop induction variable

```
for i = LB, UB, 1
```

```
R1:  X(a*i + c1) = ...  \\ write
```

```
R2:  ... = X(a*i + c2) ...  \\ read
```

```
endfor
```

Add WeChat powcoder

Question: Is there a true dependence between R1 and R2?

Dependence Testing

```
for i = LB, UB, 1
R1:  X(a*i + c1) = ...    \\ write
R2:  ... = X(a*i + c2) ... \\ read
endfor
```

There is a dependence between R1 and R2 **iff**

$$\exists i, i': LB \leq i \leq UB \text{ and } (a*i + c_1) = (a*i' + c_2)$$

where i and i' represent two iterations in the iteration space. This means that in both iterations, the same element of array X is accessed.

So let's just solve the equation:

$$(a * i + c_1) = (a * i' + c_2) \quad \Rightarrow \quad (c_1 - c_2)/a = i' - i = \Delta d$$

There is a dependence iff

- Δd is an integer value
- $UB - LB \geq \Delta d \geq 0$

Simple Dependence Testing

- **Examples:**

```
for (i = 1; i <= 100; i++) {  
  S1: A[i] = ...  
  S2: ...= A[i - 1]  
}
```

```
float Z[100];  
for (i = 0; i < 12; i++) {  
  S: Z[ i+10 ] = Z[i];  
}
```

Assignment Project Exam Help

<https://powcoder.com>

1. Is there dependence?
2. If so, what type of dependence?
3. From which statement (instance) to which statement (instance)?


Simple Dependence Testing

- Examples:

```
for (i = 1; i <= 100; i++) {  
  S1: A[i] = ...  
  S2: ...= A[i - 1]  
}
```

```
float Z[100];  
for (i = 0; i < 12; i++) {  
  S: Z[i+10] = Z[i];  
}
```

Assignment Project Exam Help



True Dependence
(read after write):


Wt: A[i] in S1 →
Rd: A[i'-1] in S2

$$i' = i + 1$$

$$\Delta d = 1$$

<https://powcoder.com>

Add WeChat powcoder



True Dependence
(read after write):

Wt: Z[i+10] in S →
Rd: Z[i'] in S

$$i' = i + 10$$

$$\Delta d = 10$$

Simple Dependence Testing

- **More Examples:**

```
for (i = 1; i <= 100; i++) {  
    R1: X(i) = ...  
    R2: ... = X(i + 2)  
}
```

```
for (i = 3; i <= 15, i++) {  
    S1: X(2 * i) = ...  
    S2: ... = X(2 * i - 1)  
}
```

Assignment Project Exam Help

<https://powcoder.com>

1. Is there dependence?
2. If so, what type of dependence?
3. From which statement (instance) to which statement (instance)?


Simple Dependence Testing

- **More Examples:**

```
for (i = 1; i <= 100; i++) {  
  R1: X[i] = ...  
  R2: ... = X[i + 2]  
}
```

```
for (i = 3; i <= 15, i++) {  
  S1: X[2 * i] = ...  
  S2: ... = X[2 * i - 1]  
}
```


Assignment Project Exam Help



Anti Dependence
(write after read):
Rd: X[i+2] in R2 →
Wt: X[i'] in R1

<https://powcoder.com>

Add WeChat powcoder



No dependence!

Next Class

Reading:

- ALSU, Chapter 11.1 - 11.3

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder