

Assignment Project Exam Help

Logic Programming

<https://powcoder.com>

March 17, 2021
Add WeChat powcoder

Introduction to Logic Programming

Assignment Project Exam Help

Truly Declarative Paradigm

- User declares **what facts** are true.
- User states some queries.
- System determines **how to use the facts** that are true to answer the queries.

Primary difference between imperative programming and logic programming

- Imperative: explicitly instruct the system how certain computation should be performed.
- Logic: instruct the system what can be used to perform some computation.

Add WeChat powcoder

Prolog

Facts

```
isamother(mary).           %% Horn Clause with no Antecedent
childof(tom, mary).       %% Horn Clause with no Antecedent
```

Rules

```
% Rule: Horn Clause with antecedent
loves(mary, tom) :-
    isamother(mary), childof(tom, mary)
```

Query

```
% Query: Horn Clause with no consequent
?- loves(mary, tom).
```

```
?- loves(X, tom).
```

```
mary
```

```
?- loves(mary, Y).
```

```
tom
```

```
?- loves(mary, jane).
```

```
false
```

What is Logic Programming

Assignment Project Exam Help

There are many (overlapping) perspectives on logic programming:

- ▶ A very high level programming language
- ▶ An interpretation of *declarative specifications*
- ▶ Non-procedural programming
- ▶ Algorithms minus control
- ▶ Computations as *deduction*
- ▶ Theorem proving

<https://powcoder.com>

Add WeChat powcoder

A Very High Level Language

- ▶ A good programming language should not encumber the programmer with non-essential details.
- ▶ The development of programming languages has been toward freeing the programmer of more and more of the details
 - ▶ ASSEMBLY LANGUAGE: symbolic encoding of data and instructions.
 - ▶ FORTRAN: allocation of variables to memory locations, register saving, etc.
 - ▶ ML: explicit variable type declarations
 - ▶ JAVA: Platform specifics
- ▶ Logic Programming Languages are a class of languages which attempt to free us from having to worry about many aspects of explicit control.

Assignment Project Exam Help

- ▶ Logical statement: For all X and Y, X is the father of Y if X is a parent of Y and the gender of X is male.
- ▶ Prolog code:

```
father(X,Y) :-  
    parent(X,Y), gender(X,male)
```
- ▶ Interpret it in two slightly different ways:
 - ▶ declaratively - which must be true if a father relationship holds.
 - ▶ procedurally: what to do to establish that a father relationship holds.

Add WeChat powcoder

Non-procedural Programming

Assignment Project Exam Help

- ▶ A non - procedural language one in which one specifies WHAT needs to be computed but not HOW it is to be done.
- ▶ it specifies a state with constraints, objects and relations:
 - ▶ the set of objects involved in the computation
 - ▶ the relationships which hold between them
 - ▶ the constraints which must hold for the problem to be solved
- ▶ the language interpreter or compiler will decide HOW to satisfy the constraints.

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ Nikolas Wirth (architect of Pascal) used the following slogan as the title of a book: $\text{Algorithms} + \text{Data Structures} = \text{Programs}$
- ▶ Bob Kowalski offers a similar one to express the central theme of logic programming: $\text{Algorithms} = \text{Logic} + \text{Control}$
- ▶ We can view the LOGIC component as: a specification of the essential logical constraints of a particular problem
- ▶ CONTROL component as: advice to an evaluation machine (e.g. an interpreter or compiler) on how to go about satisfying the constraints)

<https://powcoder.com>

Add WeChat powcoder

Computation as Deduction

- ▶ Computation is related to logical proofs and is not restricted to functional (Church) or imperative (Turing/Von Neumann) computation models.

- ▶ inductive reasoning: particular cases to general cases - inductive reasonable and proof

- ▶ deductive reasoning:

All men are mortal. (First premise)

Socrates is a man. (Second premise)

Therefore, Socrates is mortal. (Conclusion)

- ▶ It uses the language of logic to express data and programs, e.g.,
Forall X and Y, X is the father of Y if X is a parent of Y and the gender of X is male.
- ▶ Current logic programming languages use first order logic (FOL)
- ▶ Propositions, e.g., A is father of B, predicates, e.g., parent (X Y), and quantifier symbols such as \exists and \forall on objects (more in discrete maths books).

Assignment Project Exam Help

- ▶ Logic programming uses the notion of an automatic theorem prover as an interpreter.
- ▶ The theorem prover derives a desired solution from an initial set of axioms.
- ▶ Note that the proof must be a "constructive" one so that more than a true/false answer can be obtained, e.g., the answer to exists x such that $x = \sqrt{16}$ should be $x = 4$ or $x = -4$ rather than true

<https://powcoder.com>

Add WeChat powcoder

A Short History

Assignment Project Exam Help

1965 Efficient theorem provers - Resolution (Alan Robinson)

1965 Theorem Proving for problem solving (Cordell Green)

1969 PLANNER, theorem proving as programming (Carl Hewett)

1970 Micro - Planner, an implementation (Sussman, Charniak and Winograd)

1970 Prolog, an implementation (Alain Colmerauer)

1972 Book: Logic for Problem Solving. (Kowalski)

1977 DEC - 10 Prolog, an efficient interpreter/compiler (Warren and Pereira)

1982 Japan's 5th Generation Computer Project

1985 Datalog and deductive databases

1995 Prolog interpreter embedded in NT

<https://powcoder.com>

Add WeChat powcoder

PROLOG is the FORTRAN of Logic Programming

Assignment Project Exam Help

- ▶ Prolog is the only widely used logic programming language.
- ▶ As a Logic Programming language, it has a number of advantages: simple, small, fast, easy to write good compilers for it.
- ▶ Disadvantages:
 - ▶ It has a fixed control strategy.
 - ▶ It has a strong procedural aspect
 - ▶ limited support parallelism or concurrency or multi-threading.
- ▶ Datalog is a subset of Prolog, fully declarative.

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ Step 1: presenting knowledge: predicate logic
 - ▶ fact: proposition that's unconditional true
 - ▶ rule: proposition that's conditional true; dependent on other propositions
 - ▶ a fact or a rule is a statement or clause in Prolog.
- ▶ Step 2: "execute a program": make inference from a database of facts and rules

<https://powcoder.com>
Add WeChat powcoder

To Understand Computing with Logic

Assignment Project Exam Help

We need to understand Logic.

Logic

- Declarative Statements describing the state of the world.
 - Declarative Statements are either true or false
- Rules of Reasoning use existing declarative statements to conclude new declarative statements.

Basic Constituents of Logic

Assignment Project Exam Help

- ① Individuals in the world (constants).
- ② Relations over these individuals (properties or predicates): E.g., Edges between nodes.
 - Relations have arity (number of individuals involved in the relation)
- ③ Quantifiers and variables used to describe all or some individuals

<https://powcoder.com>
Add WeChat powcoder

Facts and Rules.

E.g. n is a node, n has an edge to n' .

Another Example

Assignment Project Exam Help

Declarative Statements: Facts and Rules
<https://powcoder.com>

- 1 Every mother loves her children.
- 2 Mary is a mother and Tom is Mary's child.

Queries

Does Mary love Tom?
Add WeChat powcoder

Another Example

Assignment Project Exam Help

- Constants: *mary*, *tom*, ...
- Predicates: *isamother*/1, *childof*/2, *loves*/2

<https://powcoder.com>

Declarative Statements: Facts and Rules

Facts Mary is a mother *isamother*(*mary*)

Facts Tom is Mary's child. *childof*(*tom*, *mary*)

Rule Every mother loves her children:

$\forall X:\forall Y. (\text{loves}(X, Y) \leftarrow (\text{isamother}(X) \wedge \text{childof}(Y, X)))$

Queries:

Does Mary love Tom?

true [?] *loves*(*mary*, *tom*) *true*

Horn Clause

Assignment Project Exam Help

Alfred Horn

A Horn Clause

<https://powcoder.com>

$$c \quad h_1 \wedge h_2 \wedge \dots \wedge h_n$$

where c is the consequent and the conjunction of h_i s is the antecedent.

Add WeChat powcoder

Horn Clause

Assignment Project Exam Help

Alfred Horn

A Horn Clause:

<https://powcoder.com>

$$c \quad h_1 \wedge h_2 \wedge \dots \wedge h_n$$

where c is the consequent and the conjunction of h_i 's is the antecedent.

[Add WeChat powcoder](https://powcoder.com)

If all h_i 's are true then c is true

Horn Clause: $c \bigwedge_i h_i$

Assignment Project Exam Help

A Horn clause

$$c \leftarrow h_1 \wedge h_2 \wedge \dots \wedge h_n$$

is written in prolog as

`c :- h1, h2, ..., hn`

Horn Clause	Prolog
Consequent c	goal
Antecedent $\bigwedge_i h_i$	subgoals

Horn Clause with no Antecedent

Fact

Horn Clause with Antecedent

Rule

Horn Clause with no Consequent

Query

Add WeChat powcoder

<https://powcoder.com>

Logic program is a collection of Horn Clauses

- How do we write

as a Horn Clause Statement

$c \leftarrow h_1 \vee h_2$
 $c \leftarrow h_1$
 $c \leftarrow h_2$

<https://powcoder.com>

Add WeChat powcoder

```
edge(a, b).  
edge(b, c).  
edge(c, a).  
reach(X, Y) :- edge(X, Y).  
reach(X, Y) :- edge(X, Z), reach(Z, Y).
```

?-reach(a, X)

b, c

Prolog

Facts

```
isamother(mary).    %% Horn Clause with no Antecedent
childof(tom, mary). %% Horn Clause with no Antecedent
childof(jerry, mary). %% Horn Clause with no Antecedent
```

Rules

```
%% Rule: Horn Clause with antecedent and with variables
%% X and Y are universally quantified
loves(X, Y) :-
    isamother(X), childof(Y, X).
```

```
%% X is universally quantified
%% Y, Z are existentially quantified
hassibling(X) :-
    childof(X, Y), childof(Z, Y).
```


Query

```
%% Query: Horn Clause with no consequent
?- loves(mary, X). %% X is existentially quantified
?- hassibling(jerry).
```

Queries with variables

Assignment Project Exam Help

Queries:

`?- loves(mary, X).`means: does there exist an X such that $\text{loves}(\text{mary}, X)$ is true.

Queries with free variables will generate a binding for free variables

Queries with variables


```
isamother(mary).
childof(jane, mary).
childof(tom, mary).
```

```
loves(X, Y) :- isamother(X), childof(Y, X).
```

What is the result of ?- loves(mary, X).

Computes all possible way to satisfy $\exists X.\text{loves}(\text{mary}, X)$.

loves(mary, X)



Syntax of Logic Programs

Assignment Project Exam Help

Terms

<https://powcoder.com>
constants, variables, functors (uninterpreted functions with terms as arguments)

Formulas

[Add WeChat powcoder](https://powcoder.com)
predicates with terms as arguments, boolean combination of predicates and universal/existentially quantified variables followed by predicates.

Syntax of Logic Programs

Assignment Project Exam Help

```

Clause -> Predicate.                <-- fact
        | Predicate :- PredicateSeq. <-- rule
PredicateSeq -> Predicate
               | Predicate, PredicateSeq

```

```

Predicate -> PredName(TermSeq)
TermSeq   -> Term
           | Term, TermSeq

```

```

Term      -> FunctorName(TermSeq) | Constant | Variable

```


Example

Assignment Project Exam Help

```
odd(succ(0)). %% fact using a Functor
odd(succ(succ(Z))) :- odd(Z). %% rule using a Functor
```

```
?- odd(X). %% Query
```

<https://powcoder.com>



Assignment Project Exam Help

- ▶ Install on mac: brew install swi-prolog
- ▶ Install on different machines: <https://www.swi-prolog.org/build/>
- ▶ edit your program in any editor and save it as test.pl
- ▶ run the program using: swi-prolog test.pl
- ▶ stop running the program: halt.
- ▶ frequently used command link

<https://powcoder.com>

Add WeChat powcoder

Demo: case sensitive

Executing Logic Programs

Assignment Project Exam Help

Unification/Most General Unifiers

Variable bindings

<https://powcoder.com>

Backward Chaining/Goal-directed Reasoning

Reducing one proof obligation (goal) into simpler ones (subgoals).

Add WeChat powcoder

Backtracking

Search for proofs (answers).

Unification

Assignment Project Exam Help

Given two atomic formula (predicates), they can be unified if and only if they can be made syntactically identical by replacing the variables in them by some terms.

- Unify `childof(jane, X)` and `childof(jane, mary)`?
yes by replacing `X` by `mary`
- Unify `childof(jane, X)` and `childof(jane, Y)`?
yes by replacing `X` and `Y` by the same individual
- Unify `childof(jane, X)` and `childof(Y, mary)`?
yes by replacing `X` by `mary`, and `Y` by `jane`
- Unify `childof(jane, X)` and `childof(tom, Y)`? No.

Substitution

Assignment Project Exam Help

Substitution maps variables to terms.

Instantiation is the application of substitution to all variables in a prolog formula or term.

- Unify `childof(jane, X)` and `childof(Y, mary)`?
yes by $[X \mapsto \text{mary}, Y \mapsto \text{jane}]$
- Unify $\neg(f(X) \rightarrow X)$ and $p(Y \rightarrow a)$?
yes by $[X \mapsto a, Y \mapsto f(a)]$

Add WeChat powcoder

Recall, term can be constant, variable, functor.

Most General Unifier

Assignment Project Exam Help

MGU results from a substitution that bounds free variables as little as possible

<https://powcoder.com>

- Unify $p(X, f(Y))$ and $p(g(Z), W)$
 - $[X \mapsto g(a), Y \mapsto b, W \mapsto f(b)]$
 - $[X \mapsto g(Z), W \mapsto f(Y)]$ **MGU**
- Unify $(W \mapsto g(Z), Z) \text{ and } f(X, Y \mapsto h(X))$
MGU

Add WeChat powcoder

Soln: $[W \mapsto X, Y \mapsto g(Z), Z \mapsto h(x)]$ MGU

Or, $[W \mapsto X, Y \mapsto g(h(x)), Z \mapsto h(x)]$ MGU

Unification and Computing with Logic

Assignment Project Exam Help

Given a query (prove/disprove a predicate holds)

- Search the facts and rules to find whether the query unifies with any consequent
- If the search fails, return false (query result)
- If the search is successful, then
 - if the unification occurs with the consequent of a fact, return the substitution of the variables (if any)
 - if the unification occurs with the consequent of a rule, instantiate the variables (if any) and prove the subgoals

Example: Recap

Facts, Rules

```
isamother(mary).
childof(tom, mary)
```

```
loves(mary, tom)
```

```
loves(X, Y) :-
```

```
isamother(mary) childof(tom, mary)
```

```
isamother(X),
```

```
childof(Y, X).
```

true

true

Queries

Query unifies with the rule
MGU: $[X \mapsto \text{mary}, Y \mapsto \text{tom}]$.

```
?- loves(mary, tom).
```

```
Yes
```


Backtracking: Example Recap

```
isanother(mary).
childof(jane, mary).
childof(tom, mary).
```

```
loves(X, Y) :- isanother(X), childof(Y, X).
```

What is the result of ?- loves(mary, X)

Computes all possible way to satisfy $\exists X.\text{loves}(\text{mary}, X)$.



More Language Features

Assignment Project Exam Help

<https://powcoder.com>

- Lists
- Numbers
- if-then-else

Add WeChat powcoder

Lists

A list is ordered sequence of terms enclosed in `[...]`

- `[a, b, c]`: list containing three elements/atoms `a`, `b` and `c`
- `[]`: empty list
- `[a, [b, c], [[d, e]], []]`: list can contain elements of different types
- `[a|[b, c]]`: same as `[a, b, c]`, `a` is called the head of the list and `[b, c]` is the tail of the list

?- `[1, 2, 3] = [X|Xs]`.

`X = 1`

`Xs = [2, 3]`

?- `[1, 2, 3] = [X|[Y|Rest]]`.

`X = 1`

`Y = 2`

`Rest = [3]`

Example

Append one list to another

- appending an empty list L_1 to list L_2 results in L_2
- appending a non-empty list L_1 to list L_2 results in L if the head of L_1 and L are the same and the tail of L is obtained by appending the tail of L_1 to list L_2

If \mathcal{L} represents the set of lists, then signature of append is

$\mathcal{L} \times \mathcal{L} \times \mathcal{L} \subseteq \text{append}$

`append([], L, L).`

```
append([X|Xs], L, [X|Ys]) :-
    append(Xs, L, Ys).
```

Example

Assignment Project Exam Help

Reverse a list (again!)

```
reverse([], []).
```

```
reverse([X|Xs], L) :- reverse(Xs, Ys, append(Ys, [X], L)).
```

Length of a list

```
length([], 0).
```

```
length([X|Xs], N) :- length(Xs, M), N is M + 1.
```

How about?

```
length([], 0).
```

```
length([X|Xs], N) :- M is N - 1, length(Xs, M).
```

Unification vs Computation

Assignment Project Exam Help

- $X = 3$: X is unified to 3 (assignment w/o computation)
- $X = 3 + 1$: X is unified to $3 + 1$ (not 4)
- X is $3 + 1$: X is assigned to 4

?- X is $Y + 1$.

Uninstantiated argument of evaluable function +/2

?- X is 3, $X = 3$.

$X = 3$

?- $X = 3$, Y is $X + 1$

$X = 3$

$Y = 4$

?- X is 3, X is $X + 1$.

no

<https://powcoder.com>

Add WeChat powcoder

if-then-else

Assignment Project Exam Help

```
?- Z = 3, (Z == 3 -> X = 1, Y = 2; X = 2, Y = 1).
```

```
Z = 3
```

```
X = 1
```

```
Y = 2
```

```
mypred(Z, X, Y) :-
```

```
    (Z == 3
```

```
    -> X = 1,
```

```
    Y = 2
```

```
    ; X = 2,
```

```
    Y = 1
```

```
).
```

```
mypred(Z, X, Y) :-
```

```
    Z == 3, X = 1, Y = 2.
```

```
mypred(Z, X, Y) :-
```

```
    Z \= 3, X = 2, Y = 1.
```

<https://powcoder.com>

Add WeChat powcoder

Example: search on graphs

Assignment Project Exam Help

```
edge(a, b).  
edge(b, c).  
edge(c, a).
```

<https://powcoder.com>

```
reach(X, Y) :-  
    edge(X, Y).  
reach(X, Y) :-
```

Add WeChat powcoder

```
    ?- reach(a, c)
```

Example: write a parser with Prolog

Assignment Project Exam Help

```
sentence → noun-phrase verb-phrase .  
noun-phrase → article noun  
article → a | the  
noun → girl | dog  
verb-phrase → verb noun-phrase  
verb → see | pet
```

<https://powcoder.com>

4. (30 pt) Consider the simple grammar above. Write a Prolog program that parses sentences (represented as lists of words) using the grammar.

Add WeChat powcoder

Example: write a parser with Prolog

Assignment Project Exam Help

```
1 sentence([]).
2 sentence([A,B|Tail]):- noun-phrase(A,B),checkVerbPhrase(Tail).
3 checkVerbPhrase([A,B,C|Tail]):- verb-phrase(A,B,C),checkPeriod(Tail).
4 checkPeriod([Head|Tail]):- end(Head), isNull(Tail), sentence(Tail).
5
6
7 noun-phrase(A,B):- article(A),noun(B).
8 verb-phrase(A,B,C):- verb(A),noun-phrase(B,C).
9 isEnd(A):-end(A).
10 isNull([]).
11
12
13 article().
14 article(the).
15 noun(girl).
16 noun(dog).
17 verb(pets).
18 verb(sees).
19 end(' ').
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ numbers: max
- ▶ list: append, reverse
- ▶ constraint problems
- ▶ language parsing
- ▶ graph search problems

<https://powcoder.com>

Add WeChat powcoder