

# CS373 Data Mining and Machine Learning

## Lecture 1

Assignment Project Exam Help

<https://powcoder.com>

Jean Honorio  
Add WeChat powcoder  
Purdue University

*(originally prepared by Tommi Jaakkola, MIT CSAIL)*

# Course topics

- Supervised learning
  - linear and non-linear classifiers, kernels
  - rating, ranking, collaborative filtering
  - model selection, complexity, generalization
  - conditional Random fields, structured prediction

Assignment Project Exam Help

<https://powcoder.com>

- Unsupervised learning, modeling
  - mixture models, topic models
  - Hidden Markov Models
  - Bayesian networks
  - Markov Random Fields, factor graphs


Add WeChat powcoder

# Machine learning

- Learning from examples



+ |



- |



+ |



- |

training set

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Machine learning

- Learning from examples



+ |



- |



+ |



- |

training set

Assignment Project Exam Help


The training set of labeled examples  
<https://powcoder.com>  
specifies the learning task only  
Add WeChat powcoder  
implicitly

# Machine learning

- Learning from examples



+ |



- |



+ |



- |

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



?

Our goal is to accurately label new websites that were not part of the training set

training set

# Machine learning

- Learning from examples



+ |



+ |



- |

training set

predicted new website

label

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

classifier = mapping

from websites to labels



# “Examples”

- We will have to first represent the examples (websites) in a manner that can be easily mapped to labels

news article

White House  
officials consulted  
with the Justice  
Department in  
preparing a list of  
U.S. attorneys who  
would be removed.

(NYT 03/13/07)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# “Examples”


- We will have to first represent the examples (websites) in a manner that can be easily mapped to labels

news article

White House  
officials consulted  
with the Justice  
Department in  
preparing a list of  
U.S. attorneys who  
would be removed.

(NYT 03/13/07)

bag of  
words



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# “Examples”


- We will have to first represent the examples (websites) in a manner that can be easily mapped to labels

news article

White House  
officials consulted  
with the Justice  
Department in  
preparing a list of  
U.S. attorneys who  
would be removed.

(NYT 03/13/07)

bag of  
words



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# “Examples”


- We will have to first represent the examples (websites) in a manner that can be easily mapped to labels

news article

White House  
officials consulted  
with the Justice  
Department in  
preparing a list of  
U.S. attorneys who  
would be removed.

(NYT 03/13/07)

bag of  
words



counts


0	politics
1	Justice
0	government
0	president
1	House
...	...

$x$

a vector whose coordinates (features)  
specify how many times (or whether)  
particular words appeared in the article

# The learning task

- The training set is now a set of labeled points



- Our goal is to find a “good” classifier  $f : \mathcal{X} \rightarrow \{-1, 1\}$  based on the training set  $D = \{(\underline{x}_i, y_i)_{i=1, \dots, n}\}$  so that  $f(\underline{x})$  correctly labels any new websites  $\underline{x}$


# The learning task

- The training set is now a set of labeled points

## Part I:

### Model selection

what type of classifiers  
should we consider?



- Our goal is to find a “good” classifier  $f : \mathcal{X} \rightarrow \{-1, 1\}$  based on the training set  $D = \{(\underline{x}_i, y_i)_{i=1, \dots, n}\}$  so that  $f(\underline{x})$  correctly labels any new websites  $\underline{x}$


# The learning task

- The training set is now a set of labeled points

**Part 1:**

**Model selection**

what type of classifiers  
should we consider?




**Part 2:**

**Estimation**

how to select the best  
classifier in the set?

- Our goal is to find a “good” classifier  $f : \mathcal{X} \rightarrow \{-1, 1\}$  based on the training set  $D = \{(\underline{x}_i, y_i)_{i=1, \dots, n}\}$  so that  $f(\underline{x})$  correctly labels any new websites  $\underline{x}$

# Part I: allowing all classifiers?




Add WeChat powcoder

- We can easily construct a “silly classifier” that perfectly classifies any distinct set of training points

$$f(\underline{x}) = \begin{cases} y_i, & \text{if } \underline{x} = \underline{x}_i \text{ for some } i \\ -1, & \text{otherwise} \end{cases}$$

- But it doesn’t “generalize” (it doesn’t classify new points very well)

# Part I: allowing few classifiers?



Add WeChat powcoder

- We could instead consider very few alternatives such as

$$f(\underline{x}) = 1, \quad \text{for all } \underline{x} \in \mathcal{X}, \quad \text{or}$$

$$f(\underline{x}) = -1, \quad \text{for all } \underline{x} \in \mathcal{X},$$

- But neither one classifies even training points very well


# Part I: linear classifiers

- A linear classifier (through origin) with parameters  $\underline{\theta}$  divides the space into positive and negative halves

$$\begin{aligned} f(\underline{x}; \underline{\theta}) &= \text{sign}(\underline{\theta} \cdot \underline{x}) = \text{sign}(\theta_1 x_1 + \dots + \theta_d x_d) \\ &= \begin{cases} +1, & \text{if } \underline{\theta} \cdot \underline{x} > 0 \\ -1, & \text{if } \underline{\theta} \cdot \underline{x} \leq 0 \end{cases} \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder






# Part I: linear classifiers

- A linear classifier (through origin) with parameters  $\underline{\theta}$  divides the space into positive and negative halves

$$\begin{aligned} f(\underline{x}; \underline{\theta}) &= \text{sign}(\underline{\theta} \cdot \underline{x}) = \text{sign}(\theta_1 x_1 + \dots + \theta_d x_d) \\ &= \begin{cases} +1, & \text{if } \underline{\theta} \cdot \underline{x} > 0 \\ -1, & \text{if } \underline{\theta} \cdot \underline{x} \leq 0 \end{cases} \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder




# Part I: linear classifiers

- A linear classifier (through origin) with parameters  $\underline{\theta}$  divides the space into positive and negative halves

$$\begin{aligned} f(\underline{x}; \underline{\theta}) &= \text{sign}(\underline{\theta} \cdot \underline{x}) = \text{sign}(\theta_1 x_1 + \dots + \theta_d x_d) \\ &= \begin{cases} +1, & \text{if } \underline{\theta} \cdot \underline{x} > 0 \\ -1, & \text{if } \underline{\theta} \cdot \underline{x} \leq 0 \end{cases} \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder



Recall:  
 $\cos(\text{angle}) = \text{dot product of two unit vectors}$   
 $\cos(90) = 0$


# Part I: linear classifiers

- A linear classifier (through origin) with parameters  $\underline{\theta}$  divides the space into positive and negative halves

$$\begin{aligned} f(\underline{x}; \underline{\theta}) &= \text{sign}(\underline{\theta} \cdot \underline{x}) = \text{sign}(\theta_1 x_1 + \dots + \theta_d x_d) \\ &= \begin{cases} +1, & \text{if } \underline{\theta} \cdot \underline{x} > 0 \\ -1, & \text{if } \underline{\theta} \cdot \underline{x} \leq 0 \end{cases} \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder



## Part 2: estimation

- We can use the training error as a surrogate criterion for finding the best linear classifier through origin

$$\hat{R}_n(\underline{\theta}) = \frac{1}{n} \sum_{i=1}^n \text{Loss}(y_i, f(\underline{x}_i; \underline{\theta}))$$

where  $\text{Loss}(y, y') = \begin{cases} 1, & \text{if } y \neq y' \\ 0, & \text{o.w.} \end{cases}$

Add WeChat powcoder

- Other choices are possible (and often preferable)

# Perceptron algorithm

- The perceptron algorithm considers each training point in turn, adjusting the parameters to correct any mistakes

Initialize:  $\underline{\theta} = 0$

Repeat until convergence:

<https://powcoder.com>  
Add WeChat powcoder  
for  $t = 1, \dots, n$   
if  $y_t(\underline{\theta} \cdot \underline{x}_t) \leq 0$  (mistake)  
 $\underline{\theta} \leftarrow \underline{\theta} + y_t \underline{x}_t$

- The algorithm will converge (no mistakes) if the training points are *linearly separable*, otherwise it won't converge

# Perceptron algorithm: motivation

- If we make a mistake on the  $t^{\text{th}}$  training point, then

$$y_t(\underline{\theta} \cdot \underline{x}_t) \leq 0$$

- After the update, we have

$$\theta' = \theta + y_t x_t$$

<https://powcoder.com>

Add WeChat powcoder

# Perceptron algorithm: motivation

- If we make a mistake on the  $t^{\text{th}}$  training point, then

$$y_t(\underline{\theta} \cdot \underline{x}_t) \leq 0$$

- After the update, we have

$$\theta' = \theta + y_t x_t$$

$$y_t(\underline{\theta}' \cdot \underline{x}_t) = y_t([\underline{\theta} + y_t \underline{x}_t] \cdot \underline{x}_t)$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Perceptron algorithm: motivation

- If we make a mistake on the  $t^{\text{th}}$  training point, then

$$y_t(\underline{\theta} \cdot \underline{x}_t) \leq 0$$

- After the update, we have

$$\theta' = \theta + y_t x_t$$

$$\begin{aligned} y_t(\underline{\theta}' \cdot \underline{x}_t) &= y_t([\underline{\theta} + y_t \underline{x}_t] \cdot \underline{x}_t) \\ &= y_t(\underline{\theta} \cdot \underline{x}_t + y_t \underline{x}_t \cdot \underline{x}_t) \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm: motivation

- If we make a mistake on the  $t^{\text{th}}$  training point, then

$$y_t(\underline{\theta} \cdot \underline{x}_t) \leq 0$$

- After the update, we have

$$\underline{\theta}' = \underline{\theta} + y_t \underline{x}_t$$

Assignment Project Exam Help

$$y_t(\underline{\theta}' \cdot \underline{x}_t) = y_t([\underline{\theta} + y_t \underline{x}_t] \cdot \underline{x}_t)$$

<https://powcoder.com>

Add WeChat powcoder

$$= y_t(\underline{\theta} \cdot \underline{x}_t + y_t \underline{x}_t \cdot \underline{x}_t)$$

$$= y_t(\underline{\theta} \cdot \underline{x}_t) + y_t^2 \underline{x}_t \cdot \underline{x}_t$$

# Perceptron algorithm: motivation

- If we make a mistake on the  $t^{\text{th}}$  training point, then

$$y_t(\underline{\theta} \cdot \underline{x}_t) \leq 0$$

- After the update, we have

$$\underline{\theta}' = \underline{\theta} + y_t \underline{x}_t$$

$$\begin{aligned} y_t(\underline{\theta}' \cdot \underline{x}_t) &= y_t([\underline{\theta} + y_t \underline{x}_t] \cdot \underline{x}_t) \\ &= y_t(\underline{\theta} \cdot \underline{x}_t + y_t \underline{x}_t \cdot \underline{x}_t) \\ &= y_t(\underline{\theta} \cdot \underline{x}_t) + y_t^2 \underline{x}_t \cdot \underline{x}_t \\ &= y_t(\underline{\theta} \cdot \underline{x}_t) + \|\underline{x}_t\|^2 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Perceptron algorithm: motivation

- If we make a mistake on the  $t^{\text{th}}$  training point, then

$$y_t(\underline{\theta} \cdot \underline{x}_t) \leq 0$$

- After the update, we have

$$\underline{\theta}' = \underline{\theta} + y_t \underline{x}_t$$

Assignment Project Exam Help

$$y_t(\underline{\theta}' \cdot \underline{x}_t) = y_t([\underline{\theta} + y_t \underline{x}_t] \cdot \underline{x}_t)$$

<https://powcoder.com>

Add WeChat powcoder

$$= y_t(\underline{\theta} \cdot \underline{x}_t + y_t \underline{x}_t \cdot \underline{x}_t)$$

$$= y_t(\underline{\theta} \cdot \underline{x}_t) + y_t^2 \underline{x}_t \cdot \underline{x}_t$$

$$= y_t(\underline{\theta} \cdot \underline{x}_t) + \|\underline{x}_t\|^2$$

- So that  $y_t(\underline{\theta}' \cdot \underline{x}_t)$  increases based on the update

# Perceptron algorithm


- Iterative updates based on mistakes

$$\theta_0 = 0$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm

- Iterative updates based on mistakes


$$\underline{\theta}_0 = 0$$

$$\underline{\theta}_1 = \underline{\theta}_0 + 1 \underline{x}_1$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm

- Iterative updates based on mistakes


$$\underline{\theta}_0 = 0$$

$$\underline{\theta}_1 = \underline{\theta}_0 + 1 \underline{x}_1$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm

- Iterative updates based on mistakes


$$\underline{\theta}_0 = 0$$

$$\underline{\theta}_1 = \underline{\theta}_0 + 1 \underline{x}_1$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm

- Iterative updates based on mistakes


$$\underline{\theta}_0 = 0$$

$$\underline{\theta}_1 = \underline{\theta}_0 + 1 \underline{x}_1$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





# Perceptron algorithm

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 2)

- Iterative updates based on mistakes


$$\underline{\theta}_0 = 0$$

$$\underline{\theta}_1 = \underline{\theta}_0 + 1 \underline{x}_1$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 2)

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 2)

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 2)

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder





# Perceptron algorithm (take 2)

- Iterative updates based on mistakes


$$\underline{\theta}_0 = 0$$

$$\underline{\theta}_1 = \underline{\theta}_0 + 1 \underline{x}_1$$

$$\underline{\theta}_2 = \underline{\theta}_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 3)

- Iterative updates based on mistakes


$$\underline{\theta}_0 = 0$$

$$\underline{\theta}_1 = \underline{\theta}_0 + 1 \underline{x}_1$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 3)

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 3)

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 3)

- Iterative updates based on mistakes


$$\underline{\theta}_0 = 0$$

$$\underline{\theta}_1 = \underline{\theta}_0 + 1 \underline{x}_1$$

$$\underline{\theta}_2 = \underline{\theta}_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder



# Perceptron algorithm (take 3)

- Iterative updates based on mistakes


$$\theta_0 = 0$$

$$\theta_1 = \theta_0 + 1 \underline{x}_1$$

$$\theta_2 = \theta_1 + (-1) \underline{x}_2$$

<https://powcoder.com>

Add WeChat powcoder




# “Margin”

- We can get a handle on convergence by assuming that there exists a target classifier with good properties
- One such property is margin, i.e., how close the separating boundary is to the points

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




# “Margin”

- We can get a handle on convergence by assuming that there exists a target classifier with good properties
- One such property is margin, i.e., how close the separating boundary is to the points

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder






# “Margin”

- We can get a handle on convergence by assuming that there exists a target classifier with good properties
- One such property is margin, i.e., how close the separating boundary is to the points

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Recall:

$\cos(\text{angle}) = \text{dot product of two unit vectors}$   
dotted distance = radius \*  $\cos(\text{angle})$


# “Margin”

- We can get a handle on convergence by assuming that there exists a target classifier with good properties
- One such property is margin, i.e., how close the separating boundary is to the points

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Perceptron convergence theorem

- If there exists  $\underline{\theta}^*$  such that

$$y_i(\underline{\theta}^* \cdot \underline{x}_i) \geq \gamma, \quad i = 1, \dots, n$$

and  $\|\underline{x}_i\| \leq R$  then the perceptron algorithm makes at most

Assignment Project Exam Help

$$\frac{\|\underline{\theta}^*\|^2 R^2}{\gamma^2}$$

Add WeChat powcoder

mistakes (on the training set).

- Note that the result does NOT depend on  $\dim(\underline{\theta})$ ,  $n$