

## Structured Query Language

CS430/630  
Lecture 4

Slides based on "Database Management Systems" 3rd ed, Ramakrishnan and Gehrke

## Relational Query Language: SQL

- ▶ Supports simple, yet powerful querying of data.
  - ▶ Precise semantics for relational queries.
  - ▶ DML (Data Manipulation Language)
  - ▶ DDL (Data Definition Language)
- ▶ SQL developed by IBM (system R) in the 1970s
- ▶ Standards:
  - ▶ SQL-86
  - ▶ SQL-89 (minor revision)
  - ▶ SQL-92 (major revision)
  - ▶ SQL-99 (major extensions, triggers, recursive queries)
  - ▶ SQL 2003 (XML), 2006, 2008, 2011

▶ 2

## SQL Data Types

- ▶ Character strings
  - ▶ **CHAR(n), VARCHAR(n)**: fixed and variable-length strings
- ▶ Bits
  - ▶ **BOOLEAN** – values **TRUE, FALSE, UNKNOWN**
  - ▶ **BIT(n)**
- ▶ Numerical:
  - ▶ **INTEGER (INT)**
  - ▶ Floating point: **FLOAT** (or **REAL**), **DOUBLE PRECISION**
  - ▶ Fixed precision: **DECIMAL(n, p)**
    - ▶ 1234.56 is of type **DECIMAL(6,2)**, precision 6, scale 2
- ▶ **DATE** and **TIME**

▶ 3

## Creating Relations in SQL

```
CREATE TABLE Students
(sid CHAR(20),
 name CHAR(20),
 login CHAR(10),
 age INTEGER,
 gpa REAL);
```

DDL

```
CREATE TABLE Enrolled
(sid CHAR(20),
 cid CHAR(20),
 grade CHAR(2));
```

DDL

▶ 4

## Destroying and Altering Relations

```
DROP TABLE Students;
```

DDL

- ▶ Deletes relation *Students*, including schema information and all the tuples

```
ALTER TABLE Students
ADD firstYear INTEGER;
```

DDL

- ▶ Add new column to schema
- ▶ Every tuple is extended with **NULL** value in added field
- ▶ Default value may be specified instead of **NULL**

▶ 5

## Structure of SQL SELECT Query

SELECT	[DISTINCT] target-list
FROM	relation-list
WHERE	qualification

- ▶ **relation-list** = list of relation names
  - ▶ possibly with a **range-variable** after each name
- ▶ **target-list** = list of attributes of relations in **relation-list**
- ▶ **qualification** = conditions **Attr op const** or **Attr1 op Attr2**
  - ▶ **op** is one of **<, >, =, >=, <=, <>**, or string operators
  - ▶ Expressions connected using **AND, OR** and **NOT**
- ▶ **DISTINCT** = optional, eliminates duplicates
  - ▶ By default duplicates are **NOT** eliminated!

▶

## Conceptual Evaluation Strategy

- **Semantics of SQL query**
  1. Compute the cross-product of *relation-list*
  2. Discard resulting tuples if they fail *qualifications*
  3. Delete attributes that are not in *target-list*
  4. If **DISTINCT** is specified, eliminate duplicate rows
- **This strategy is least efficient way to compute a query!**
  - Optimizer finds efficient strategies to compute *the same result*

## Example Schema

Sailors				Boats		
sid	sname	rating	age	bid	name	color
22	dustin	7	45.0	101	interlake	red
31	lubber	8	55.5	103	clipper	green
58	rusty	10	35.0			

  

Reserves		
sid	bid	day
22	101	10/10/96
58	103	11/12/96

## Conceptual Evaluation Example

```
SELECT S.sname
FROM Sailors S, Reserves R
WHERE S.sid=R.sid AND R.bid=103
```

(sid)	sname	rating	age	(sid)	bid	day
22	dustin	7	45.0	22	101	10/10/96
22	dustin	7	45.0	58	103	11/12/96
31	lubber	8	55.5	22	101	10/10/96
31	lubber	8	55.5	58	103	11/12/96
58	rusty	10	35.0	22	101	10/10/96
58	rusty	10	35.0	58	103	11/12/96

## A Note on Range Variables

- Really needed only if the same relation appears twice in the **FROM** clause (SELECT ... FROM Sailors S1, Sailors S2)

```
SELECT S.sname
FROM Sailors S, Reserves R
WHERE S.sid = R.sid AND R.bid=103
```

*It is good style, however, to use range variables always!*

Instead of ...

```
SELECT sname
FROM Sailors S, Reserves R
WHERE S.sid = Reserves.sid AND bid=103
```

## Duplicate Tuples and DISTINCT

```
SELECT S.sname
FROM Sailors S, Reserves R
WHERE S.sid=R.sid
```

- Would adding **DISTINCT** to this query make a difference?
- What is the effect of replacing *S.sname* by *S.sid* in the **SELECT** clause?
- Would adding **DISTINCT** to this variant of the query make a difference?

## Expressions and Strings

- “Find rating and number of years to retirement for sailors whose names begin with ‘d’, end with ‘n’ and contain at least three characters”

```
SELECT S.rating, 60 - S.age AS Yr_to_retire
FROM Sailors S
WHERE S.sname LIKE 'd_%n'
```

- **AS** allows to (re)name fields in result.
- **LIKE** is used for string matching
  - \_ stands for any one character
  - % stands for 0 or more arbitrary characters

## Expressions and Strings - Example

```
SELECT S.rating, 60 - S.age AS Yr_to_retire
FROM Sailors S
WHERE S.sname LIKE 'd_%n'
```

*Sailors*

sid	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

rating	Yr_to_retire
7	15

## Set Operations

- ▶ **UNION**
  - ▶ compute the union of any two *union-compatible* sets of tuples
- ▶ **INTERSECT**
  - ▶ compute the intersection of any two *union-compatible* sets of tuples
- ▶ **EXCEPT or MINUS**
  - ▶ Set difference of any two *union-compatible* sets of tuples
- ▶ Duplicates eliminated by default!
  - ▶ UNION ALL, INTERSECT ALL, EXCEPT ALL retain duplicates
  - ▶ Contrast with non-set SQL operations

## Adding and Deleting Tuples

- ▶ Insert single tuple

```
INSERT INTO Students (sid, name, login, age, gpa)
VALUES ('53688', 'Smith', 'smith@ee', 18, 3.2);
```

- ▶ Delete all tuples satisfying condition

```
DELETE
FROM Students S
WHERE S.name = 'Smith';
```

▶ 15

## Data Modifications: Inserts

```
INSERT INTO Table (attr1, attr2, ...)
VALUES (val1, val2, ...);
```

- ▶ Values and attribute domains must match
- ▶ Attributes not specified will be assigned value NULL
- ▶ Variation: insert tuples returned by SELECT

```
INSERT INTO Table (attr1, attr2, ...)
SELECT col1, col2, ...
FROM ...
[WHERE ...]
[OR ...]
[HAVING ...];
```

▶

## Data Modifications: Updates

- ▶ No new tuples created
- ▶ Attribute values of existing tuples modified
 

```
UPDATE Table
SET attr1=expression1, attr2=expression2 [...]
```
- ▶ Values and attribute domains must match
- ▶ It is possible to use subqueries:

```
UPDATE Table
SET attr1= (SELECT value1
            FROM ...
            WHERE ...)
WHERE condition;
```

▶

## Integrity Constraints (ICs)

- ▶ **IC:** condition that must hold for *any* instance of the database; e.g., *domain constraints*
  - ▶ Specified when schema is defined.
  - ▶ Checked when relations are modified.
- ▶ A *legal* instance satisfies all specified ICs
  - ▶ It is the DBMS's role to enforce IC
- ▶ ICs we study
  - ▶ Primary key constraints
  - ▶ Foreign key constraints
  - ▶ Referential integrity

▶ 18

## Primary and Candidate Keys in SQL

- ▶ **Primary keys** specified by keyword **PRIMARY KEY**
- ▶ **Candidate keys** specified by keyword **UNIQUE**
- ▶ Distinctions between the two:
  - ▶ Any attribute in the primary key is **NOT** allowed to have **NULL** values
  - ▶ Primary key attributes may have special roles in the DBMS internals (although from the logical point of view is same as unique)
- ▶ Declaration
  - ▶ In-line with the respective attribute
    - ▶ Only if one-attribute key!
  - ▶ Or as separate constraint line

▶ 19

## Keys in SQL - Examples

### Schema and Instance

Students			Courses		
sid	sname	age	cid	cname	room
53666	Smith	20	114	Calculus	M123
53650	Jones	25	115	Databases	M234
53681	Adams	22			

  

Enrolled		
sid	cid	grade
53666	114	A
53650	115	B
53666	115	B

▶

## Keys in SQL - Examples

"For a given student and course, there is a single grade."

```
CREATE TABLE Enrolled
(sid CHAR(20),
 cid CHAR(20),
 grade CHAR(2),
 PRIMARY KEY (sid,cid))
```

"Students can take only one course, and receive a single grade for that course; further, no two students in a course receive the same grade."

```
CREATE TABLE Enrolled
(sid CHAR(20) PRIMARY KEY,
 cid CHAR(20),
 grade CHAR(2),
 UNIQUE (cid,grade))
```

▶

## Foreign Keys, Referential Integrity

- ▶ **Foreign key**
  - ▶ Set of fields in relation A that refer to a tuple in relation B
  - ▶ Must correspond to primary key of relation B (or UNIQUE)
  - ▶ Not necessary for field names in A and B to be the same!!!  
`FOREIGN KEY (attr1) REFERENCES B (attr2)`
- ▶ E.g. *sid* in Enrolled is a foreign key referring to Students:
  - ▶ Enrolled(*sid*: string, *cid*: string, *grade*: string)
- ▶ Referential integrity is achieved by enforcing all foreign keys  
no "dangling references"

▶ 22

## Foreign Keys in SQL

- ▶ Only students listed in the Students relation should be allowed to enroll for courses

```
CREATE TABLE Enrolled
(sid CHAR(20), cid CHAR(20), grade CHAR(2),
 PRIMARY KEY (sid,cid),
 FOREIGN KEY (sid) REFERENCES Students)
```

Enrolled			Students		
sid	cid	grade	sid	sname	age
53666	114	A	53666	Smith	20
53650	115	B	53650	Jones	25
53666	115	B	53681	Adams	22

▶ 23