

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
Security and Authorization

CS430/630
Lecture 18

Definitions

- ▶ **Security policy**

- ▶ specifies who is authorized to do what

- ▶ **Security mechanism**

- ▶ allows to **enforce** a chosen security policy

<https://powcoder.com>

- ▶ **Terminology**

- ▶ Users = **Subjects** or **Principals**

- ▶ Data = **Objects**

- ▶ **Two important functions needed to achieve security**

- ▶ **Authentication (AuthN)**

- ▶ **Authorization (AuthZ)**



Authentication

- ▶ Establishing the **identity** of the user, or **who** the user is
- ▶ Subjects (users) present authentication **credentials**
 - ▶ Username/Password combination – “what user knows”
 - ▶ Digital certificates (cryptographic tokens) – “what user has”
 - ▶ Biometrics – “what user is”
- ▶ Some credential types stronger than others
 - ▶ For high-security applications, **multi-factor** authentication
 - ▶ E.g., password + fingerprint

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>



Authorization

- ▶ Once we know who the user is, what can s/he access?
 - ▶ What objects (data) the subjects is allowed access to?
 - ▶ What kind of operations is the subject allowed to perform?
 - ▶ Read-only, modify, append
 - ▶ Authorization also referred to as access control
- ▶ Two main categories of access control
 - ▶ **Discretionary:** object owner decides authorization policy for its objects (Unix system)
 - ▶ **Mandatory:** system-wide rules that dictate who gets to access what (multi-level security, Bell-LaPadula)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Discretionary Access Control

- ▶ Based on the concept of access rights or **privileges**
 - ▶ Privileges for objects (tables and views)
 - ▶ Mechanisms for granting and revoking privileges

Assignment Project Exam Help

- ▶ Object creator automatically gets all privileges on it
 - ▶ DBMS keeps track of who subsequently gains and loses privileges
 - ▶ DBMS ensures that only requests from users who have the necessary privileges (at the time the request is issued) are allowed

<https://powcoder.com>

Add WeChat powcoder



GRANT Command

GRANT privilege_list ON object TO user_list [WITH GRANT OPTION]

- ▶ The following **privileges** can be specified:
 - ▶ **SELECT**
 - ▶ can read all columns
 - ▶ including those added later via ALTER TABLE command
 - ▶ **INSERT(col-name)**
 - ▶ can insert tuples with non-null or non-default values in this column
 - ▶ INSERT means same right with respect to all columns
 - ▶ **DELETE**
 - ▶ can delete tuples
 - ▶ **REFERENCES (col-name)**
 - ▶ can define foreign keys (in other tables) that refer to this column

GRANT Command (contd)

- ▶ If a privilege is granted with **GRANT OPTION**, the grantee can pass privilege on to other users
 - ▶ Special **ALL PRIVILEGES** privilege
- ▶ Only owner can execute **CREATE, ALTER, and DROP**

<https://powcoder.com>

Add WeChat powcoder



Examples

GRANT INSERT, SELECT ON Sailors TO Horatio

- ▶ Horatio can query Sailors or insert tuples into it

GRANT DELETE ON Sailors TO Yuppy WITH GRANT OPTION

- ▶ Yuppy can delete tuples, and also authorize others to do so

GRANT INSERT (*rating*) ON Sailors TO Dustin

- ▶ Dustin can insert (only) the *rating* field of Sailors tuples



REVOKE Command

```
REVOKE [GRANT OPTION FOR] privilege_list ON object  
FROM user_list [CASCADE | RESTRICT]
```

- ▶ **REVOKE** Assignment Project Exam Help
 - ▶ Revokes privileges
- ▶ **CASCADE**: when a privilege is revoked from X, it is also revoked from all users who got it solely from X
 - ▶ Privilege is said to be **ABANDONED**
 - ▶ A graph with the granting relationship is maintained
- ▶ **RESTRICT**: if revoke causes some privilege to be abandoned, it is **NOT** executed




Authorization Graph

- ▶ Keeps track of active authorization on objects
 - ▶ Each authorization ID (user) corresponds to a node
 - ▶ Granting a privilege adds **labeled** edge to graph
 - ▶ Removing privilege deletes one or more edges from graph
 - ▶ Special “**System**” node that originates all privileges
 - ▶ Note: it is possible to have multiple edges between same pair of nodes (with same direction)!
- ▶ How to determine if access is allowed for an ID?
 - ▶ There must be a **path** from System to that ID formed of privileges equal (or stronger) than the one required




Authorization Graph



Joe: CREATE TABLET ...

ALLPRIV,
Yes





Assignment Project Exam Help


<https://powcoder.com>




Add WeChat powcoder




Authorization Graph




Authorization Graph




Authorization Graph



Authorization Graph



Authorization Graph




Cal: GRANT SELECT ON T TO Bob WITH GRANT OPTION

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




SELECT, Yes




SELECT,
Yes

SELECT,
Yes


SELECT,
Yes




SELECT, Yes



Authorization Graph



Authorization Graph



Art, Bob can still access T!


No “temporal order” memorized

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

ALLPRIV,
Yes



SELECT,
Yes




SELECT, Yes


SELECT,
Yes



SELECT,
Yes



Another Example




Joe: GRANT INSERT(name) to Art

ALLPRIV,
Yes


Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



INSERT(name), No



Another Example




Joe: GRANT INSERT to Art

ALLPRIV,
Yes


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




INSERT(name), No



INSERT, No



Another Example




Joe: REVOKE INSERT FROM Art

ALLPRIV,
Yes


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




INSERT(name), No



INSERT, No



Another Example




Joe: REVOKE INSERT FROM Art

ALLPRIV,
Yes


Assignment: Project Exam Help
sub-privileges NOT revoked

Contrast this with granting
<https://powcoder.com>
same privilege twice!

Add WeChat powcoder



INSERT(name), No



Security at the Level of a Field!

- ▶ Can create a view that only returns one field of one tuple
 - ▶ Then grant access to that view accordingly
- ▶ Allows for arbitrary granularity of control, but:
 - ▶ Tedious to specify and maintain policies
 - ▶ Performance is unacceptable
 - ▶ Too many view creations and look-ups
- ▶ Another solution
 - ▶ Attach labels to subjects and objects
 - ▶ Create rules of access based on labels

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Mandatory Access Control

- ▶ Based on system-wide policies that cannot be changed by individual users (even if they own objects)
 - ▶ Each **DB object** is assigned a **security class**
 - ▶ Each **subject** (user or user program) is assigned a **clearance** for a security class
 - ▶ Rules based on security classes and clearances govern who can read/write which objects
- ▶ Many commercial systems do not support mandatory access control
 - ▶ Some specialized versions do
 - ▶ e.g., those used in military applications

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Bell-LaPadula Model

- ▶ Security classes:

- ▶ Top secret (TS)
- ▶ Secret (S)
- ▶ Confidential (C)
- ▶ Unclassified (U):
- ▶ $TS > S > C > U$

Assignment Project Exam Help

<https://powcoder.com>

- ▶ Each object (O) and subject (S) is assigned a class

- ▶ S can read O only if $class(S) \geq class(O)$ (Simple Security Property or No Read Up)
- ▶ S can write O only if $class(S) \leq class(O)$ (*-Property or No Write Down)



Intuition

- ▶ Idea is to ensure that information can never flow from a higher to a lower security level
- ▶ The mandatory access control rules are applied in addition to any discretionary controls that are in effect

<https://powcoder.com>

Add WeChat powcoder

