SQL Aggregates **Practice Queries**

CS430/630 Lecture 9

Slides based on "Database Management Systems" 3rd ed, Ramakrishnan and Gehrke

Example 1

Students ($\underline{\text{sid:integer}}$, sname:string, age:integer) Enrolled (sid:integer, cid:integer, grade:integer)
Courses(cid:integer, cname:string, credits:integer)

"Find the average age of students taking some course with 3 credits"

Simple solution, but if same student takes multiple 3-credit courses, it may not be what we expect

SELECT AVG (S.age) FROM Students S, Enrolled E, Courses C WHERE S.sid = E.sid AND E.cid = C.cid AND C.credits = 3

CEkar plex 3

Students (sid:integer, s Enrolled (sid:integer, cid:integer, grade:integer)
Courses(cid:integer, cname:string, credits:integer)

"Find the average age of students taking some course with 3 credits" $\frac{1}{1}$

SELECT AVG (S1.age) FROM Students S1 WHERE S1.sid IN (SELECT S.sid

FROM Students S, Enrolled E, Courses C

WHERE S.sid = E.sid AND Ecid C.cid

Students (<u>sid:integer</u>, sname:string, age:integer) Enrolled ($\underline{\text{sid:integer}}$, $\underline{\text{cid:integer}}$, grade:integer) Courses (cid:integer, cname:string, credits:integer) the average age of enrolled students for each course with at least 10 enrolled

Fin the average age of enrolled students udents. Els the course (amed) a well." SELECT C.cname, AVG(S.age) FROM Students S, Enrolled E, Courses C WHERE S.sid = E.sid AND E.cid = C.cid GROUP BY C.cid, C.cname

HAVING COUNT(*)>=10

Example 3

Students (sid:integer, sname:string, age:integer) Enrolled (sid:integer, cid:integer, grade:integer)
Courses(cid:integer, cname:string, credits:integer)

"Find the average age over enrolled students that are 25 or younger for each course with at least 10 enrolled students (of any age)'

SELECT C.cname, AVG(S.age) FROM Students S, Enrolled E, Courses C WHERE S.sid = E.sid AND E.cid = C.cid AND S.age <= 25 GROUP BY C.cid. C.cname HAVING 10 <= (SELECT COUNT(*) FROM Enrolled E1 WHERE E1.cid = C.cid)

Example 4

Students (sid:integer, sname:string, age:integer) Enrolled (sid:integer, cid:integer, grade:integer) Courses(cid:integer, cname:string, credits:integer)

"Find the average age of enrolled students for each course satisfying following two conditions: (1) course has at least 10 enrolled students and (2) average enrolled student age higher than 20"

SELECT C.cname, AVG(S.age) FROM Students S, Enrolled E, Courses C WHERE S.sid = E.sid AND E.cid = C.cid GROUP BY C.cid, C.cname HAVING AVG(S.age) > 20 AND COUNT(*) >= 10

Example 5

Students (<u>sid:integer</u>, sname:string, age:integer)
Enrolled (<u>sid:integer</u>, <u>cid:integer</u>, grade:integer)
Courses(<u>cid:integer</u>, cname:string, credits:integer)

"Find the average age of enrolled students for each course satisfying following two conditions: (1) course has at least 10 enrolled students and (2) at least one enrolled student has age higher than 20"

SELECT C.cname, AVG(S.age)
FROM Students S, Enrolled E, Courses C
WHERE S.sid = E.sid AND E.cid = C.cid
GROUP BY C.cid, C.cname
HAVING ANY(S.age) > 20 AND COUNT(*) >= 10

Þ

Example 6

Students (sid:integer, sname:string, age:integer)
Enrolled (sid:integer, cid:integer, grade:integer)
Courses(cid:integer, cname:string, credits:integer)

"Find the courses that have the highest average age computed among students 25 or younger (i.e., highest among all courses) and also have at least 10 students of any age enrolled. Output the course name and the above-mentioned average age value."

SELECT Temp.cname, Temp.avg_age
FROM (SELECT C.cname, AVG(S.age) AS avg_age
FROM Students S, Enrolled E, Courses C
WHERE S.sid = E.sid AND E.cid = C.cid AND S.age <= 25
GROUP BY C.cid, C.cname
HAVING 10 <= (SELECT COUNT(*)
FROM Enrolled E1
WHERE E1.cid = C.cid)) Temp

WHERE Temp.avg_age = (SELECT MAX(Temp. avg_age) FROM Temp)

•

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder