

JavaScript is disabled on your browser.

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

jminusminus

Class JPostDecrementOp

- [java.lang.Object](#)
- [jminusminus.AST](#)
- [jminusminus.JStatement](#)
- [jminusminus.JExpression](#)
- [jminusminus.JUnaryExpression](#)
- [jminusminus.JPostDecrementOp](#)

.

Add WeChat powcoder

```
class JPostDecrementOp  
extends JUnaryExpression
```

The AST node for an expr--.

- **Field Summary**
- **Fields inherited from class [jminusminus.JUnaryExpression](#)**
[arg](#)
- **Fields inherited from class [jminusminus.JExpression](#)**
[isStatementExpression](#), [type](#)
- **Fields inherited from class [jminusminus.JAST](#)**
[compilationUnit](#), [line](#)
- **Constructor Summary**

Constructors

Constructor and Description

```
JPostDecrementOp(int line, JExpression arg)
```

Construct an AST node for an expr-- expression given its line number, and the operand.

- **Method Summary**

Methods

**Modifier and
Type**

Method and Description

JExpression	analyze (Context context) Analyze the operand as a lhs (since there is a side effect), check types and determine the type of the result.
void	codegen (CLEmitter output) In generating code for a post-decrement operation, we treat simple variable (JVariable) operands specially since the JVM has an increment instruction.

- **Methods inherited from class jminusminus.JUnaryExpression**

writeToStdOut

- **Methods inherited from class jminusminus.JExpression**

codegen, isStatementExpression, type

- **Methods inherited from class jminusminus.JAST**

line, partialCodegen

- **Methods inherited from class java.lang.Object**

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

- **Constructor Detail**

- **JPostDecrementOp**

publicJPostDecrementOp(intline,
JExpressionarg)

Construct an AST node for an expr-- expression given its line number, and the operand.

Parameters:

line - line in which the expression occurs in the source file.
arg - the operand.

- **Method Detail**

- **analyze**

publicJExpressionanalyze(Contextcontext)

Analyze the operand as a lhs (since there is a side effect), check types and determine the type of the result.

Specified by:

analyze in class JExpression

Parameters:

context - context in which names are resolved.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Returns:

the analyzed (and possibly rewritten) AST subtree.

- **codegen**

```
public void codegen(CLEmitter output)
```

In generating code for a post-decrement operation, we treat simple variable (JVariable) operands specially since the JVM has an increment instruction. Otherwise, we rely on the JLhs code generation support for generating the proper code. Notice that we distinguish between expressions that are statement expressions and those that are not; we insure the proper value (before the decrement) is left atop the stack in the latter case.

Specified by:

`codegen` in class `JAST`

Parameters:

`output` - the code emitter (basically an abstraction for producing the .class file).

- **Prev Class**
- **Next Class**

- Frames
- No Frames

- All Classes

- Summary:
- Nested |
- Field |
- Constr |
- Method

- Detail:
- Field |
- Constr |
- Method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder