

JavaScript is disabled on your browser.

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

jminusminus

Class JThis

- [java.lang.Object](#)
- [jminusminus.AST](#)
- [jminusminus.JStatement](#)
- [jminusminus.JExpression](#)
- [jminusminus.JThis](#)

.

Assignment Project Exam Help
<https://powcoder.com>

Add WeChat powcoder

```
class JThis
extends JExpression
```

The AST for a "this" expression. It serves as a target of some field selection or message.

- **Field Summary**
- **Fields inherited from class jminusminus.JExpression**
[isStatementExpression](#), [type](#)
- **Fields inherited from class jminusminus.JAST**
[compilationUnit](#), [line](#)
- **Constructor Summary**

Constructors

Constructor and Description

```
JThis(int line)
```

Construct an AST node for a "this" expression given its line number.

- **Method Summary**

Methods	
Modifier and Type	Method and Description
<code>JExpression</code>	<code>analyze</code> (<code>Context</code> context) Analysis involves simply determining the type in which we are, since that determines the type of this target.
<code>void</code>	<code>codegen</code> (<code>CLEmitter</code> output) Simply generate code to load "this" onto the stack.
<code>void</code>	<code>writeToStdOut</code> (<code>PrettyPrinter</code> p) inheritDoc

- **Methods inherited from class `jminusminus.JExpression`**

`codegen`, `isStatementExpression`, `type`

- **Methods inherited from class `jminusminus.JAST`**

`line`, `partialCodegen`

- **Methods inherited from class `java.lang.Object`**

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

- **Constructor Detail**

- **`JThis`**

`public JThis(int line)`

Construct an AST node for a "this" expression given its line number.

Parameters:

Line - line in which the expression occurs in the source file.

- **Method Detail**

- **`analyze`**

`public JExpression analyze(Context context)`

Analysis involves simply determining the type in which we are, since that determines the type of this target.

Specified by:

`analyze` in class `JExpression`

Parameters:

context - context in which names are resolved.

Returns:

the analyzed (and possibly rewritten) AST subtree.

- **`codegen`**

`public void codegen(CLEmitter output)`

Simply generate code to load "this" onto the stack.

Specified by:

`codegen` in class `JAST`

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Parameters:

output - the code emitter (basically an abstraction for producing the .class file).

- **writeToStdOut**

```
public void writeToStdOut(PrettyPrinter p)
```

```
inheritDoc
```

Specified by:

`writeToStdOut` in class `JAST`

Parameters:

p - for pretty printing with indentation.

- **Prev Class**
- **Next Class**

- Frames
- No Frames

- All Classes

- Summary:
- Nested |
- Field |
- Constr |
- Method

- Detail:
- Field |
- Constr |
- Method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder