

JavaScript is disabled on your browser.

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

jminusminus

Class NHIRPutField

- [java.lang.Object](#)
 - [jminusminus.NHIRInstruction](#)
 - [jminusminus.NHIRPutField](#)

.

<https://powcoder.com>

```
class NHIRPutField  
extends NHIRInstruction
```

Add WeChat powcoder

HIR instruction representing JVM (put) field instructions.

- **Field Summary**

Fields	
Modifier and Type	Field and Description
String	name Name of the field being accessed.
int	opcode Opcode of the JVM instruction.
String	target Target for the field.
int	value HIR id of the value of the field.

- **Fields inherited from class jminusminus.NHIRInstruction**
`block, hirMnemonic, id, lir, lType, sType`

- **Constructor Summary**

Constructors
Constructor and Description

```
NHIRPutField(NBasicBlock block, int id, int opcode,
String target, String name, String sType, String lType,
int value)
Construct an NHIRPutField instruction.
```

- **Method Summary**

Methods	
Modifier and Type	Method and Description
NLIRInstruction	toLir() Convert and return a low-level representation (LIR) of this HIR instruction.
String	toString() Return a string representation of this instruction.

- **Methods inherited from class jminusminus.NHIRInstruction**

`equals, id`

- **Methods inherited from class java.lang.Object**

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait`

- **Field Detail**

- **opcode**

`public int opcode`

Opcode of the JVM instruction.

- **target**

`public String target`

Target for the field.

- **name**

`public String name`

Name of the field being accessed.

- **value**

`public int value`

HIR id of the value of the field.

- **Constructor Detail**

- **NHIRPutField**

`public NHIRPutField(NBasicBlock block,`

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
intid,  
intopcode,  
Stringtarget,  
Stringname,  
StringsType,  
StringlType,  
intvalue)
```

Construct an NHIRPutField instruction.

Parameters:

block - enclosing block.
id - identifier of the instruction.
opcode - JVM opcode for the instruction.
target - target for the field.
name - name of the field.
sType - type (short name) of the field.
lType - type (long name) of the field.
value - HIR id of the value of the field.

- **Method Detail**

- **toLir**

```
publicNLIRInstructiontoLir()
```

Description copied from class: **NHIRInstruction**

Convert and return a low-level representation (LIR) of this HIR instruction. Also adds the returned LIR instruction to the list of LIR instructions for the block containing this instruction, along with any other intermediate LIR instructions needed.

Overrides:

toLir in class **NHIRInstruction**

Returns:

LIR instruction corresponding to this HIR instruction.

- **toString**

```
publicStringtoString()
```

Description copied from class: **NHIRInstruction**

Return a string representation of this instruction.

Overrides:

toString in class **NHIRInstruction**

Returns:

string representation of this instruction.

- Overview
- Package
- **Class**
- Tree
- Deprecated
- Index
- Help

- **Prev Class**
- **Next Class**

- Frames
- No Frames

- All Classes

- Summary:
- Nested |
- Field |
- Constr |
- Method

- Detail:
- Field |
- Constr |
- Method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder