

JavaScript is disabled on your browser.

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

jminusminus

Class NHIRNewArray

- [java.lang.Object](#)
 - [jminusminus.NHIRInstruction](#)
 - [jminusminus.NHIRNewArray](#)

.

<https://powcoder.com>

```
class NHIRNewArray  
extends NHIRInstruction
```

Add WeChat powcoder

HIR instruction representing JVM array creation instructions.

• Field Summary

Fields	
Modifier and Type	Field and Description
int	dim Dimension of the array.
int	opcode Opcode of the JVM instruction.

- **Fields inherited from class [jminusminus.NHIRInstruction](#)**
[block](#), [hirMnemonic](#), [id](#), [lir](#), [lType](#), [sType](#)

• Constructor Summary

Constructors
Constructor and Description

```
NHIRNewArray(NBasicBlock block, int id, int opcode, int dim,
String sType, String lType)
```

Construct an NHIRNewArray instruction.

- **Method Summary**

Methods

Modifier and Type

Method and Description

```
NLIRInstruction toLir()
Convert and return a low-level representation (LIR) of this
HIR instruction.
```

```
String toString()
Return a string representation of this instruction.
```

- **Methods inherited from class jminusminus.NHIRInstruction**
equals, id

- **Methods inherited from class java.lang.Object**
clone, equals, finalize, getClass, hashCode, notify,
notifyAll, wait, wait, wait

Assignment Project Exam Help

- **Field Detail**

- **opcode**
public int opcode

Opcode of the JVM instruction.

- **dim**
public int dim

Dimension of the array.

- **Constructor Detail**

- **NHIRNewArray**
public NHIRNewArray(NBasicBlock block,
int id,
int opcode,
int dim,
String sType,
String lType)

Construct an NHIRNewArray instruction.

Parameters:

block - enclosing block.
id - identifier of the instruction.
opcode - JVM opcode for the instruction.
dim - dimension of the array.
sType - type (short name) of the array.
lType - type (long name) of the array.

<https://powcoder.com>

Add WeChat powcoder

- **Method Detail**

- **toLir**

```
publicNLIRInstructiontoLir()
```

Description copied from class: `NHIRInstruction`

Convert and return a low-level representation (LIR) of this HIR instruction. Also adds the returned LIR instruction to the list of LIR instructions for the block containing this instruction, along with any other intermediate LIR instructions needed.

Overrides:

`toLir` in class `NHIRInstruction`

Returns:

LIR instruction corresponding to this HIR instruction.

- **toString**

```
publicStringtoString()
```

Description copied from class: `NHIRInstruction`

Return a string representation of this instruction.

Overrides:

`toString` in class `NHIRInstruction`

Returns:

string representation of this instruction.

Assignment Project Exam Help

- **Prev Class**

- **Next Class**

- **Frames**

- **No Frames**

- **All Classes**

- **Summary:**

- **Nested |**

- **Field |**

- **Constr |**

- **Method**

- **Detail:**

- **Field |**

- **Constr |**

- **Method**

<https://powcoder.com>

Add WeChat powcoder