

JavaScript is disabled on your browser.

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

jminusminus

Class NLIRGetField

- [java.lang.Object](#)
 - [jminusminus.NLIRInstruction](#)
 - [jminusminus.NLIRGetField](#)

.

<https://powcoder.com>

```
class NLIRGetField  
extends NLIRInstruction
```

Add WeChat powcoder

LIR instruction representing JVM (get) field instructions.

• Field Summary

Fields	
Modifier and Type	Field and Description
String	name Name of the field being accessed.
int	opcode Opcode of the JVM instruction.
String	target Target for the field.

- **Fields inherited from class [jminusminus.NLIRInstruction](#)**
[block](#), [id](#), [lirMnemonic](#), [reads](#), [write](#)

• Constructor Summary

Constructors

Constructor and Description

```
NLIRGetField(NBasicBlock block, int id, int opcode,  
String target, String name, String sType, String lType)  
Construct an NLIRGetField instruction.
```

- **Method Summary**

Methods

**Modifier and
Type**

Method and Description

void	toSpim (PrintWriter out) Translate this LIR instruction into SPIM and write it out to the specified output stream.
String	toString () Return a string representation of this instruction.

- **Methods inherited from class jminusminus.NLIRInstruction**

allocatePhysicalRegisters

- **Methods inherited from class java.lang.Object**

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

- **Field Detail**

- **opcode**

public int opcode

Opcode of the JVM instruction.

- **target**

public String target

Target for the field.

- **name**

public String name

Name of the field being accessed.

- **Constructor Detail**

- **NLIRGetField**

```
public NLIRGetField(NBasicBlock block,  
                    int id,  
                    int opcode,  
                    String target,  
                    String name,  
                    String sType,  
                    String lType)
```

Construct an NLIRGetField instruction.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Parameters:

block - enclosing block.
id - identifier of the instruction.
opcode - JVM opcode for the return instruction.
target - target for the field.
name - name of the field.
sType - type (short name) of the field.
lType - type (long name) of the field.

- **Method Detail**

- **toSpim**

```
public void toSpim(PrintWriter out)
```

Description copied from class: `NLIRInstruction`

Translate this LIR instruction into SPIM and write it out to the specified output stream.

Overrides:

`toSpim` in class `NLIRInstruction`

Parameters:

out - output stream for SPIM code.

- **toString**

```
public String toString()
```

Description copied from class: `NLIRInstruction`

Return a string representation of this instruction.

Overrides:

`toString` in class `NLIRInstruction`

Returns:

string representation of this instruction.

- **Prev Class**
- **Next Class**

- Frames
- No Frames

- All Classes

- Summary:
- Nested |
- Field |
- Constr |
- Method

- Detail:
- Field |
- Constr |
- Method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder