

- Prev
- Next
- Frames
- No Frames
- All Classes

Serialized Form

- **Package `jminusminus`**

- Class `jminusminus.ParseException` extends `Exception` implements `Serializable`

- **Serialized Fields**

- **`specialConstructor`**

`boolean specialConstructor`

This variable determines which constructor was used to create this object and thereby affects the semantics of the "getMessage" method (see below).

- **`currentToken`**

`Token currentToken`

This is the last token that has been consumed successfully. If this object has been created due to a parse error, the token following this token will (therefore) be the first error token.

- **`expectedTokenSequences`**

`int[][] expectedTokenSequences`

Each entry in this array is an array of integers. Each array of integers represents a sequence of tokens (by their ordinal values) that is expected at this point of the parse.

- **`tokenImage`**

`String[] tokenImage`

This is a reference to the "tokenImage" array of the generated parser within which the parse error occurred. This array is defined in the generated ...Constants interface.

- **`eol`**

`String eol`

The end of line string for this machine.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Class **jminusminus.TokenMgrError** extends **Error** implements **Serializable**

- **Serialized Fields**

- **errorCode**

`int errorCode`

Indicates the reason why the exception is thrown. It will have one of the above 4 values.

- [Prev](#)
- [Next](#)
- [Frames](#)
- [No Frames](#)
- [All Classes](#)
- [Help](#)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder