

JavaScript is disabled on your browser.

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

jminusminus

Class CLFieldInstruction

- [java.lang.Object](#)
 - [jminusminus.CLIInstruction](#)
 - [jminusminus.CLFieldInstruction](#)

.

<https://powcoder.com>

```
class CLFieldInstruction
extends CLIInstruction
```

Add WeChat powcoder

Representation for FIELD instructions.

- **Field Summary**
- **Fields inherited from class jminusminus.CLIInstruction**
`instructionInfo`, `localVariableIndex`, `mnemonic`, `opcode`,
`operandCount`, `pc`, `stackUnits`
- **Constructor Summary**

Constructors

Constructor and Description

```
CLFieldInstruction(int opcode, int pc, int index,
int stackUnits)
```

Construct a CLFieldInstruction object.

- **Method Summary**

Methods

Modifier and Type

Method and Description

```
ArrayList<Integer> toBytes()  
Return the bytecode for this  
instruction.
```

- **Methods inherited from class `jminusminus.CLIInstruction`**

`byteAt`, `isValid`, `localVariableIndex`, `mnemonic`, `opcode`,
`operandCount`, `pc`, `stackUnits`

- **Methods inherited from class `java.lang.Object`**

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`,
`notifyAll`, `toString`, `wait`, `wait`, `wait`

- **Constructor Detail**

- **CLFieldInstruction**

```
public CLFieldInstruction(int opcode,  
                          int pc,  
                          int index,  
                          int stackUnits)
```

Construct a CLFieldInstruction object.

Parameters:

`opcode` - the opcode for this instruction.

`pc` - index of this instruction within the code array of a method.

`index` - index into the constant pool, the item at which contains the
name and descriptor of the field.

`stackUnits` - words produced, words consumed from the operand
stack by this instruction.

- **Method Detail**

- **toBytes**

```
public ArrayList<Integer> toBytes()
```

Description copied from class: `CLIInstruction`

Return the bytecode for this instruction.

Specified by:

`toBytes` in class `CLIInstruction`

Returns:

bytecode.

- Overview
- Package
- **Class**
- Tree
- Deprecated
- Index
- Help

- **Prev Class**
- **Next Class**

- Frames
- No Frames

- All Classes

- Summary:
- Nested |
- Field |
- Constr |
- Method

- Detail:
- Field |
- Constr |
- Method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder