

JavaScript is disabled on your browser.

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

jminusminus

Class CLRuntimeVisibleAnnotationsAttribute

- [java.lang.Object](#)
 - [jminusminus.CLObjectInfo](#)
 - [jminusminus.CLAttributeInfo](#)
 - [jminusminus.CLRuntimeVisibleAnnotationsAttribute](#)

.

<https://powcoder.com>

```
class CLRuntimeVisibleAnnotationsAttribute  
extends CLAttributeInfo
```

Add WeChat powcoder

Representation of RuntimeVisibleAnnotations_attribute structure (JVM Spec Section 4.8.15).

• Field Summary

Fields	
Modifier and Type	Field and Description
<code>ArrayList<CLAnnotation></code>	annotations RuntimeVisibleAnnotations_attribute.annotations item.
<code>int</code>	numAnnotations RuntimeVisibleAnnotations_attribute.num_annotations item.

- **Fields inherited from class [jminusminus.CLAttributeInfo](#)**
`attributeLength`, `attributeNameIndex`

• Constructor Summary

Constructors	
	Constructor and Description

```
CLRuntimeVisibleAnnotationsAttribute(int attributeNameIndex,
long attributeLength, int numAnnotations,
ArrayList<CLAnnotation> annotations)
Construct a CLRuntimeVisibleAnnotationsAttribute object.
```

- **Method Summary**

Methods	
Modifier and Type	Method and Description
void	write (CLOutputStream out) Write the contents of this attribute to the specified output stream.
void	writeToStdOut (PrettyPrinter p) Write the contents of this attribute to STDOUT in a format similar to that of javap.

- **Methods inherited from class [java.lang.Object](#)**

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Assignment Project Exam Help

- **Field Detail**

<https://powcoder.com>

- **numAnnotations**

public int numAnnotations

RuntimeVisibleAnnotations_attribute.num_annotations item.

- **annotations**

public [ArrayList](#)<[CLAnnotation](#)> annotations

RuntimeVisibleAnnotations_attribute.annotations item.

- **Constructor Detail**

- **CLRuntimeVisibleAnnotationsAttribute**

```
public CLRuntimeVisibleAnnotationsAttribute(int attributeNameIndex,
long attributeLength,
int numAnnotations,
```

```
ArrayList<CLAnnotation> annotations)
```

Construct a CLRuntimeVisibleAnnotationsAttribute object.

Parameters:

attributeNameIndex -

RuntimeVisibleAnnotations_attribute.attribute_name_index item.

attributeLength -

RuntimeVisibleAnnotations_attribute.attribute_length item.

numAnnotations -

RuntimeVisibleAnnotations_attribute.num_annotations item.

annotations - RuntimeVisibleAnnotations_attribute.annotations

Add WeChat powcoder

item.

- **Method Detail**

- **write**

```
public void write(CLOutputStream out)
    throws IOException
```

Description copied from class: `CLAttributeInfo`

Write the contents of this attribute to the specified output stream.

Overrides:

`write` in class `CLAttributeInfo`

Parameters:

out - output stream.

Throws:

`IOException` - if an error occurs while writing.

- **writeToStdOut**

```
public void writeToStdOut(PrettyPrinter p)
```

Description copied from class: `CLAttributeInfo`

Write the contents of this attribute to STDOUT in a format similar to that of javap.

Overrides:

`writeToStdOut` in class `CLAttributeInfo`

Parameters:

p - for pretty printing with indentation.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)