

JavaScript is disabled on your browser.

- [Prev Class](#)
- [Next Class](#)

- [Frames](#)
- [No Frames](#)

- [All Classes](#)

- [Summary:](#)
- [Nested |](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

- [Detail:](#)
- [Field |](#)
- [Constr |](#)
- [Method](#)

jminusminus

Class CLAnnotationDefaultAttribute

- [java.lang.Object](#)
 - [jminusminus.CLAttributeInfo](#)
 - [jminusminus.CLAnnotationDefaultAttribute](#)

.

<https://powcoder.com>

```
class CLAnnotationDefaultAttribute  
extends CLAttributeInfo
```

Add WeChat powcoder

Representation of AnnotationDefault_attribute structure (JVM Spec Section 4.8.2).

- **Field Summary**

| Modifier and Type | Fields |
|----------------------|-----------------------|
| | Field and Description |

| | |
|----------------|---|
| CLElementValue | defaultValue |
| | AnnotationDefault_attribute.defaultValue item. |

- **Fields inherited from class jminusminus.CLAttributeInfo**
[attributeLength](#), [attributeNameIndex](#)

- **Constructor Summary**

| Constructors |
|-----------------------------|
| Constructor and Description |

```
CLAnnotationDefaultAttribute(int attributeNameIndex,  
long attributeLength, CLElementValue defaultValue)
```

Construct a CLAnnotationDefaultAttribute object.

- **Method Summary**

| Methods | |
|-------------------|---|
| Modifier and Type | Method and Description |
| void | write (CLOutputStream out) Write the contents of this attribute to the specified output stream. |
| void | writeToStdOut (PrettyPrinter p) Write the contents of this attribute to STDOUT in a format similar to that of javap. |

- **Methods inherited from class [java.lang.Object](#)**

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

- **Field Detail**

- **defaultValue**

[public \[CLOutputStream\]\(#\) defaultValue](#)

[AnnotationDefault_attribute.defaultValue](#) item.

- **Constructor Detail**

- **CLAnnotationDefaultAttribute**

[public \[CLAnnotationDefaultAttribute\]\(#\)\(\[int\]\(#\) attributeNameIndex, \[long\]\(#\) attributeLength, \[CLOutputStream\]\(#\) defaultValue\)](#)

Construct a CLAnnotationDefaultAttribute object.

Parameters:

[attributeNameIndex](#) -

[AnnotationDefault_attribute.attribute_name_index](#) item.

[attributeLength](#) - [AnnotationDefault_attribute.attribute_length](#) item.

[defaultValue](#) - [AnnotationDefault_attribute.defaultValue](#) item.

- **Method Detail**

- **write**

[public void write\(\[CLOutputStream\]\(#\) out\)](#)
throws [IOException](#)

Description copied from class: [CLAttributeInfo](#)

Write the contents of this attribute to the specified output stream.

Overrides:

[write](#) in class [CLAttributeInfo](#)

Parameters:

[out](#) - output stream.

Throws:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

`IOException` - if an error occurs while writing.

- **writeToStdOut**

```
public void writeToStdOut(PrettyPrinter p)
```

Description copied from class: `CLAttributeInfo`

Write the contents of this attribute to STDOUT in a format similar to that of javap.

Overrides:

`writeToStdOut` in class `CLAttributeInfo`

Parameters:

p - for pretty printing with indentation.

- **Prev Class**
- **Next Class**

- Frames
- No Frames

- All Classes

- Summary:
- Nested |
- Field |
- Constr |
- Method

- Detail:
- Field |
- Constr |
- Method

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder