

Assignment Project Exam Help

Communication Patterns

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Client-Server Architecture

A Generic Server


<https://powcoder.com>

Concurrency Patterns

Add WeChat powcoder

Client-Server Architecture

- ▶ Common asynchronous communication pattern
- ▶ For example: a web server handles requests for web pages from clients (web browsers)



Example: Factorial Server

```
1 -module(mserver).
2 -export([start/0,compute_factorial/2]).
3 -import(fact,[fact/1]).
4
5 loop(Count) ->
6   receive
7     {get_count, From, Ref} ->
8       From ! {result, Ref, Count},
9       loop(Count);
10    {factorial, From, Ref, N} ->
11      Result = fact(N),
12      From ! {result, Ref, Result},
13      loop(Count+1);
14    stop -> true
15  end.
16
17 % starting server with initial state 0
18
19 start() -> spawn(fun() -> loop(0) end).
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Note how the server state is a parameter of loop

Example: Factorial Server

Client

```
1 compute_factorial(Pid, N) ->  
2   Ref = make_ref(0),  
3   Pid ! {factorial, self(), Ref, N},  
4   receive  
5     {result, Ref, Result} ->  
6     Result  
7   end.
```

Test

```
1 > c(mserver).  
2 {ok,mserver}.  
3 > P=mserver:start().  
4 <0.40.0>  
5 > mserver:compute_factorial(P,10).  
6 3628800
```

Example: Factorial Server

Assignment Project Exam Help

What if the server crashes or stops?

```
1 > P ! stop
2 > mserver:compute_factorial(P,10).
3 ...no response...
```

<https://powcoder.com>

- ▶ Why do we get no response?
- ▶ Can you modify the code so that we receive a `timeout`?

Add WeChat powcoder

Registered Processes – Recap

- ▶ As seen in class, Erlang has a method for publishing a process identifier

- ▶ Any other process can communicate with it

- ▶ BIF `register`

```
1 % starting server with initial state 0
2 start() ->
3     Pid = spawn(fun() -> loop(0) end),
4     register(server, Pid).
```

- ▶ Unregister with `unregister(name)`

- ▶ Registration lookup `whereis(name)`

Registered Processes – Recap

The atom server can be used instead of a concrete process ID

```
1 > mserver2:start().
2 true
3 > mserver2:compute_factorial(server,10).
4 3628800
5 > server:stop.
6 stop
7 > mserver2:compute_factorial(server,10).
8 ** exception error: bad argument
9     in function mserver2:compute_factorial/2 (mserver2.erl, line
10 > mserver2:start().
11 true
12 > mserver2:compute_factorial(server,10).
13 3628800
```


Assignment Project Exam Help

- ▶ Message passing abstractions extend easily for distributed environments

- ▶ Erlang nodes

- ▶ An instance of an Erlang runtime system

- ▶ Nodes can easily communicate with each other

- ▶ Creating a node

```
erl -name 'nodeS@127.0.0.1' -setcookie lecture
```

- ▶ The cookie provides security (not everyone can connect)

- ▶ The name reflects the node's IP address

Add WeChat powcoder

Assignment Project Exam Help

- ▶ Creating two nodes (for simplicity on the same machine)

```
1 erl -name 'nodeS@127.0.0.1' -setcookie lecture
2 erl -name 'nodeC@127.0.0.1' -setcookie lecture
```

- ▶ Connecting nodes

<https://powcoder.com>

```
1 (nodeC@127.0.0.1)> net_adm:ping('nodeS@127.0.0.1').
2 pong
3 (nodeC@127.0.0.1)> nodes().
4 ['nodeS@127.0.0.1']
```

Add WeChat powcoder

Distributed Factorial Server – Running Your Code

Send the compiled version of your code to the connected nodes

```
1 (nodeC@127.0.0.1)> nl(fact).  
2 abcast  
3 (nodeC@127.0.0.1)> nl(mserver2).  
4 abcast
```

The server gets started on the nodeS node

```
1 (nodeS@127.0.0.1)> mserver2:start().  
2 true
```

The client communicates with the server

```
(nodeC@127.0.0.1)> mserver2:compute_factorial({server,  
3628800 nodeS@127.0.0.1'}, 10).
```

- ▶ Use of `{registered_name, node@IP}` instead of the pid or only the registered name
- ▶ Code has not been changed for running in a distributed setting!

Assignment Project Exam Help

Client Server Architecture
A Generic Server

<https://powcoder.com>

Concurrency Patterns

Add WeChat powcoder

Assignment Project Exam Help

- ▶ The code for a generic server takes care of the communication, faults, and upgrades
- ▶ <https://powcoder.com> Programmers then only focus on writing the engine (i.e. what the server does)
- ▶ No communication primitives are required in the engine

Add WeChat powcoder

A Generic Server

The code must expose the following features:

- ▶ Correct
 - ▶ It implements a proper server/client request/reply interaction
- ▶ Parametrized
 - ▶ It is parametric on the engine
- ▶ Robust
 - ▶ It does not crash if the engine goes wrong
- ▶ Upgradable
 - ▶ It allows to upgrade the engine of the server without shutting it down

A Generic Server

```
1 loop(State, F) ->  
2   receive  
3     {update, From, Ref, NewF} ->  
4       From ! {ok, Ref},  
5       loop(State, NewF) ;  
6  
7     {request, From, Ref, Data} ->  
8       R, NS = F(State, Data),  
9       From ! {result, Ref, R},  
10      loop(NS, F);  
11  
12   stop -> true  
13 end.
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

How can the server go wrong when evaluating $F(\text{State}, \text{Data})$?

Exceptions – The evaluation of expressions can fail

► Arithmetic error

```
1 > 1/0.  
2 ** exception error: bad argument in an arithmetic expression  
3    in operator  '/'/2  
4    called as 1 / 0
```

► Bad pattern matching

```
1 [] = [1].  
2 ** exception error: no match of right hand side value [1]
```

► Undefined functions

```
1 net_adm:ping(1,2).  
2 ** exception error: undefined function net_adm:ping/2
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Exceptions

```
1 > catch(1/0).
2 {'EXIT',{badarith,[{erl_eval, '/', [1,0]},
3                  {erl_eval, do_apply, 5},
4                  {erl_eval, expr, 5},
5                  {shell, exprs, 7},
6                  {shell, eval_exprs, 7},
7                  {shell, eval_loop, 3}]}}
8 > catch([_] = [_]).
9 {'EXIT',{badmatch,[_]},{[erl_eval, expr, 5]}}}
10 > catch(net_adm:ping(1,2)).
11 {'EXIT',{undef,[{net_adm, ping, [1,2]},
12                {erl_eval, do_apply, 5},
13                {erl_eval, expr, 5},
14                {shell, exprs, 7},
15                {shell, eval_exprs, 7},
16                {shell, eval_loop, 3}]}}}
17 >
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Exceptions

```
1 loop(State, F) ->
2   receive
3     {update, From, Ref, NewF} ->
4     From ! {ok, Ref},
5     loop(State, NewF);
6
7     {request, From, Ref, Data} ->
8     ,,, case catch(F(State, Data)) of
9         {EXIT, Reason} ->
10        From ! {exit, Ref, Reason},
11        loop(State, F);
12        {R, NewState} ->
13        From ! {result, Ref, R},
14        loop(NewState, F);
15        _ ->
16        end
17
18   stop -> true
19 end.
```

- It propagates the exception from the server to the client

Exceptions

```
1 loop(State, F) ->
2   receive
3     {update, From, Ref, NewF} ->
4     From ! {ok, Ref},
5     loop(State, NewF);
6
7     {request, From, Ref, Data} ->
8     case catch(F(State, Data)) of
9     , _ of
10    , _ of
11    , _ of
12      {R, NewState} ->
13        From!{result, Ref, R},
14        loop(NewState, F)
15      end
16
17    stop -> true
18 end.
```

- It propagates the exception from the server to the client

Exceptions

```
1 loop(State, F) ->
2   receive
3     {update, From, Ref, NewF} ->
4     From ! {ok, Ref},
5     loop(State, NewF);
6
7     {request, From, Ref, Data} ->
8     case catch(F(State, Data)) of
9       {'EXIT', Reason} ->
10        From ! {exit, Ref, Reason},
11        loop(State, F);
12      {R, NewState} ->
13        From ! {result, Ref, R},
14        loop(NewState, F);
15      _ ->
16        From ! {error, Ref},
17        loop(State, F);
18 end.
```

- It propagates the exception from the server to the client

Assignment Project Exam Help

```
1 start(Name, State, F) ->  
2   Pid = spawn(fun() -> loop(State, F) end),  
3   register(Name, Pid),  
4   Pid.
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

```
1 request(Pid, Data) ->
2     Ref = make_ref(),
3     Pid!{request, self(), Ref, Data}
4     receive
5         {result, Ref, Result} ->
6             Result;
7         {exit, Ref, Reason} ->
8             exit(Reason)
9     end
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ Upgrading the server's engine

```
1 update(Pid, Fun) ->  
2   Ref = make_ref(),  
3   Pid!{update, self(), Ref, Fun},  
4   receive  
5     {ok, Ref} ->  
6       ok  
7   end.
```

<https://powcoder.com>

Add WeChat powcoder

Factorial Server Revisited

```
1 -module(factServer).  
2 -export([start/0, compute_factorial/1]).  
3 -import(fact, [fac/1]).  
4  
5 engine(Count, {factorial, N}) ->  
6     Result = math_examples:factorial(N),  
7     {Result, Count+1} ;  
8  
9 engine(Count, {get_count}) ->  
10    {Count, Count}.  
11  
12 start() ->  
13     genserver:start(server, 0, fun engine/2).  
14  
15 compute_factorial(N) ->  
16     genserver:request(server, {factorial, N}).
```

- Observe that there are no message passing primitives!

Assignment Project Exam Help

```
1 4> factServer:start().
```

```
2 <0.6910>
```

```
3 5> factServer.compute_factorial(23).
```

```
4 25852016738884976640000
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Revisiting the following using message passing:

- ▶ A semaphore (already seen last class)
- ▶ Barrier synchronisation
- ▶ Resource allocation
- ▶ Readers and writers


<https://powcoder.com>

Add WeChat powcoder

Barrier Synchronization Revisited

- ▶ N processes must wait for the slowest before continuing with the next activity
- ▶ Widely used in parallel programming

Assignment Project Exam Help



Add WeChat powcoder

Barrier Synchronization Revisited

Assignment Project Exam Help

```
1 start(N) ->
2   Pid = spawn(fun() -> coordinator(N,N,[]) end),
3   register(coordinator, Pid).
4
5 coordinator(N,0,Ps) ->
6   [{From, {ack, Ref}} || {From, Res} <- Ps ],
7   coordinator(N,N,[ ]).
8
9 coordinator(N,M,Ps) ->
10  receive
11    {reach, From, Ref} ->
12      coordinator(N,M+1, [{From, left} || Ps ])
13  end.
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Using the barrier

```
1 reach_wait(Server) ->  
2   Ref = make_ref(),  
3   Server !- reach, self(), Ref,  
4   receive  
5     {ack, Ref} -> true  
6   end.
```

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ A controller controls access to copies of some resources (of the same kind)
- ▶ Clients requiring multiple resources should not ask for resources one at a time
- ▶ Clients make requests to take or return any number of the resources
 - ▶ A request should only succeed if there are sufficiently many resources available
 - ▶ Otherwise the request must block

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

```
1 > c(ralloc).  
2 {ok, ralloc}  
3 > ralloc:start([1,1,1,1]).  
4 true  
5 > ralloc:request(3).  
6 [1,1,1]  
7 > ralloc:release([1]).  
8 ok  
9 > ralloc:request(2).  
10 [1,1]  
11 > ralloc:request(10).
```

<https://powcoder.com>

Add WeChat powcoder

In the last line, the process blocks

Resource Allocation

```
1 loop(Resources) ->
2   Available = length(Resources),
3   receive
4     {req, From, Ref, Number} when Number <= Available ->
5     {res, Ref, lists:sublist(Resources, Number)},
6     loop(lists:sublist(Resources, Number+1, Available));
7
8     {ret, List} -> loop(lists:append(Resources, List))
9   end.
10
11 % continues...
```

- Function `lists:sublist` returns a slice of a list; Examples

```
1 > lists:sublist([1,2,3,4], 2).
2 [1,2]
3 > lists:sublist([1,2,3,4], 2, 2).
4 [2,3]
5 > lists:sublist([1,2,3,4], 2, 5).
6 [2,3,4]
7 > lists:sublist([1,2,3,4], 5, 2).
8 []
```

Resource Allocation

```
1 start(Init) ->
2   Pid = spawn(fun() -> loop(Init) end),
3   register(rserver, Pid).
4
5
6 request(N) ->
7   Ref = make_ref(),
8   rserver ! {req, self(), Ref, N},
9   receive
10    {res, Ref, List} -> List
11  end.
12
13 release(List) ->
14   rserver ! {ret, List},
15   ok
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

- ▶ Two kinds of processes share access to a “database”
- ▶ Readers examine the contents
 - ▶ Multiple readers allowed concurrently
- ▶ Writers examine and modify data
 - ▶ A writer must have mutex
- ▶ Readers and writers in a few lines

<https://powcoder.com>

Add WeChat powcoder

Readers and Writers Revisited

```
1 loop(Rs, Ws) ->
2   receive
3   {start_read, From, Ref} when Ws == 0 ->
4     From ! {ok_to_read, Ref},
5     loop(Rs+1, Ws) ;
6
7   {start_write, From, Ref} when Ws == 0 and Rs == 0 ->
8     From ! {ok_to_write, Ref},
9     loop(Rs, Ws+1) ;
10
11   end_read -> loop(Rs-1, Ws) ;
12
13   end_write -> loop(Rs, Ws-1) ;
14 end.
```

Is it a fair solution?

Readers and Writers Revisited

```
1 loop(Rs, Ws) ->
2   receive
3   {start_read, From, Ref} when Ws == 0 ->
4     From ! {ok_to_read, Ref},
5     loop(Rs+1, Ws) ;
6
7   {start_write, From, Ref} when Ws == 0 and Rs == 0 ->
8     From ! {ok_to_write, Ref},
9     loop(Rs, Ws+1) ;
10
11   end_read -> loop(Rs-1, Ws) ;
12
13   end_write -> loop(Rs, Ws-1) ;
14 end.
```

Is it a fair solution? Unfair for writers

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
1 loop() ->
2 receive
3     {start_read, From, Ref} ->
4         From ! {ok_to_read, Ref},
5         loop_read(1),
6         loop();
7
8     {start_write, From, Ref} ->
9         From ! {ok_to_write, Ref},
10        receive
11            end_write -> loop()
12        end
13 end.
```

Fair Readers and Writers

```
1 loop_read(0) -> ok ;
2 loop_read(Rs) ->
3     receive
4         {start_read, From, Ref} ->
5             From ! {ok_to_read, Ref},
6             loop_read(Rs+1) ;
7
8         end_read -> loop_read(Rs-1) ;
9
10        {start_write, From, Ref} ->
11            receive end_read -> ok end
12            || _ <- lists:seq(1,Rs) ],
13            From ! {ok_to_write, Ref},
14            receive
15                end_write -> ok
16            end
17        end.
```

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

- ▶ At top-level `loop` relies on the fairness property of Erlang (i.e. the oldest message that matches any guard is processed)
- ▶ Function `loop_read` implements fairness
- ▶ Line `[receive end_read ->ok end || _ <- lists:seq(1,Rs)]` performs as many receive as the number `Rs`

Fair Readers and Writers

- A FSM that describes its behavior



- Format of events:

<received event>, <condition> / <triggered event>