Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Machine-Level Programming I: Basics

Assignment Project Exam Help

15-213/18-213/14-513/15-513/18-613: Introduction to Computer Systems

5th Lecture, September 15, 2020

https://powcoder.com

Add WeChat powcoder

Assignment Announcements

- **Written Assignment 1 available on Canvas**
  - Due Wed, Sept. 16, 11:59pm ET
  - Peer grading due Wed, Sept. 23, 11:59pm ET
  - You will grade 3 submissions using the rubric posted on Canvas
- **Lab 1 available via Autolab**
  - Due Thurs, Sept. 17, 11:59pm ET
  - Read instructions carefully: writeup, bits.c, tests.c
    - Quirky software infrastructure
  - Based on lectures 2, 3, and 4 (CS:APP Chapter 2)
- **Recitations**
  - In person: you have been contacted with your recitation info
  - Online: use the zoom links provided on the Canvas homepage

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Today: Machine Programming I: Basics

- **History of Intel processors and architectures**
- **Assembly Basics: Registers, operands, move**
- **Arithmetic & logical operations**
- **C, assembly, machine code**

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Intel x86 Processors

- **Dominate laptop/desktop/server market**
- **Evolutionary design**
  - Backwards compatible up until 8086, introduced in 1978
  - Added more features as time goes on
- **x86 is a Complex Instruction Set Computer (CISC)**
  - Many different instructions with many different formats
    - But, only small subset encountered with Linux programs
- **Compare: Reduced Instruction Set Computer (RISC)**
  - RISC: *very few* instructions, with *very few* modes for each
  - RISC can be quite fast (but Intel still wins on speed!)
  - Current RISC renaissance (e.g., ARM, RISCV), especially for low-power

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Intel x86 Evolution: Milestones

Name	Date	Transistors	MHz
8086	**1978**	**29K**	**5-10**
▪ First 16-bit Intel processor. Basis for IBM PC & DOS			
▪ 1MB address space			
386	**1985**	**275K**	**16-33**
▪ First 32 bit Intel processor , referred to as IA32			
▪ Added "flat addressing", capable of running Unix			
Pentium 4E	**2004**	**125M**	**2800-3800**
▪ First 64-bit Intel x86 processor, referred to as x86-64			
Core 2	**2006**	**291M**	**1060-3333**
▪ First multi-core Intel processor			
Core i7	**2008**	**731M**	**1600-4400**
▪ Four cores (our shark machines)			

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Intel x86 Processors, cont.

- **Machine Evolution**

386	1985	0.3M
Pentium	1993	3.1M
Pentium/MMX	1997	4.5M
PentiumPro	1995	6.5M
Pentium III	1999	8.2M
Pentium 4	2000	42M
Core 2 Duo	2006	291M
Core i7	2008	731M
Core i7 Skylake	2015	1.9B



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Added Features**
  - Instructions to support multimedia operations
  - Instructions to enable more efficient conditional operations
  - Transition from 32 bits to 64 bits
  - More cores

Intel x86 Processors, cont.

- **Past Generations**

		Process technology
1st Pentium Pro	1995	600 nm
1st Pentium III	1999	250 nm
1st Pentium 4	2000	180 nm
1st Core 2 Duo	2006	65 nm

Process technology dimension = width of narrowest wires (10 nm ≈ 100 atoms wide)

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Recent & Upcoming Generations**

1.	Nehalem	2008	45 nm
2.	Sandy Bridge	2011	32 nm
3.	Ivy Bridge	2012	22 nm
4.	Haswell	2013	22 nm
5.	Broadwell	2014	14 nm
6.	Skylake	2015	14 nm
7.	Kaby Lake	2016	14 nm
8.	Coffee Lake	2017	14 nm
9.	Cannon Lake	2018	10 nm
10.	Ice Lake	2019	10 nm
11.	Tiger Lake	2020?	10 nm

2018 State of the Art: Coffee Lake



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Mobile Model: Core i7**
  - 2.2-3.2 GHz
  - 45 W
- **Desktop Model: Core i7**
  - Integrated graphics
  - 2.4-4.0 GHz
  - 35-95 W
- **Server Model: Xeon E**
  - Integrated graphics
  - Multi-socket enabled
  - 3.3-3.8 GHz
  - 80-95 W

x86 Clones: Advanced Micro Devices (AMD)

- **Historically**
  - AMD has followed just behind Intel
  - A little bit slower, a lot cheaper
- **Then**
  - Recruited top circuit designers from Digital Equipment Corp. and other downward trending companies
  - Built Opteron: tough competitor to Pentium 4
  - Developed x86-64, their own extension to 64 bits
- **Recent Years**
  - Intel got its act together
    - 1995-2011: Lead semiconductor “fab” in world
    - 2018: #2 largest by $$ (#1 is Samsung)
    - 2019: reclaimed #1
  - AMD fell behind
    - Relies on external semiconductor manufacturer GlobalFoundaries
    - ca. 2019 CPUs (e.g., Ryzen) are competitive again

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Intel's 64-Bit History

- **2001: Intel Attempts Radical Shift from IA32 to IA64**
  - Totally different architecture (Itanium, AKA "Itanic")
  - Executes IA32 code only as legacy
  - Performance disappointing
- **2003: AMD Steps in with Evolutionary Solution**
  - x86-64 (now called "AMD64")
- **Intel Felt Obligated to Focus on IA64**
  - Hard to admit mistake or that AMD is better
- **2004: Intel Announces EM64T extension to IA32**
  - Extended Memory 64-bit Technology
  - Almost identical to x86-64!
- **Virtually all modern x86 processors support x86-64**
  - But, lots of code still runs in 32-bit mode

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Our Coverage

- **IA32**
  - The traditional x86
  - For 15/18-213: RIP, Summer 2015
- **x86-64**
  - The standard
  - `shark> gcc hello.c`
  - `shark> gcc -m64 hello.c`
- **Presentation**
  - Book covers x86-64
  - Web aside on IA32
  - We will only cover x86-64

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Today: Machine Programming I: Basics

- History of Intel processors and architectures
- **Assembly Basics: Registers, operands, move**
- Arithmetic & logical operations
- C, assembly, machine code

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Levels of Abstraction

C programmer

```
#include <stdio.h>
int main(){
  int i, n = 10, t1 = 0, t2 = 1, nxt;
  for (i = 1; i <= n; ++i){
    printf("%d, ", t1);
    nxt = t1 + t2;
    t1 = t2;
    t2 = nxt; }
  return 0; }
```

Assignment Project Exam Help

Nice clean layers, but beware…

https://powcoder.com

Assembly programmer

Add WeChat powcoder



Computer Designer



Gates, clocks, circuit layout, …



Definitions

- **Architecture: (also ISA: instruction set architecture) The parts of a processor design that one needs to understand for writing correct machine/assembly code**
  - Examples: instruction set specification, registers
  - **Machine Code**: The byte-level programs that a processor executes
  - **Assembly Code**: A text representation of machine code
- **Microarchitecture: Implementation of the architecture**
  - Examples: cache sizes and core frequency
- **Example ISAs:**
  - Intel: x86, IA32, Itanium, x86-64
  - ARM: Used in almost all mobile phones
  - RISC V: New open-source ISA

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Assembly/Machine Code View



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Programmer-Visible State

- **PC: Program counter**
  - Address of next instruction
  - Called "RIP" (x86-64)
- **Register file**
  - Heavily used program data
- **Condition codes**
  - Store status information about most recent arithmetic or logical operation
  - Used for conditional branching

- **Memory**
  - Byte addressable array
  - Code and user data
  - Stack to support procedures

Assembly Characteristics: Data Types

- **“Integer” data of 1, 2, 4, or 8 bytes**
  - Data values
  - Addresses (untyped pointers)
- **Floating point data of 4, 8, or 10 bytes**
- **(SIMD vector data types of 8, 16, 32 or 64 bytes)**
- **Code: Byte sequences encoding series of instructions**
- **No aggregate types such as arrays or structures**
  - Just contiguously allocated bytes in memory

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

x86-64 Integer Registers

%rax	%eax	%r8	%r8d
%rbx	%ebx	%r9	%r9d
%rcx	%ecx	%r10	%r10d
%rdx	%edx	%r11	%r11d
%rsi	%esi	%r12	%r12d
%rdi	%edi	%r13	%r13d
%rsp	%esp	%r14	%r14d
%rbp	%ebp	%r15	%r15d

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- Can reference low-order 4 bytes (also low-order 1 & 2 bytes)
- Not part of memory (or cache)

Some History: IA32 Registers



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Assembly Characteristics: Operations

- **Transfer data between memory and register**
  - Load data from memory into register
  - Store register data into memory

Assignment Project Exam Help

- **Perform arithmetic function on register or memory data**

https://powcoder.com

- **Transfer control**

Add WeChat powcoder

  - Unconditional jumps to/from procedures
  - Conditional branches
  - Indirect branches

Moving Data

- **Moving Data**

  `movq` *Source, Dest*

- **Operand Types**
  - ***Immediate:*** Constant integer data
    - Example: `$0x400, $-533`
    - Like C constant, but prefixed with `$`
    - Encoded with 1, 2, or 4 bytes
  - ***Register:*** One of 16 integer registers
    - Example: `%rax, %r13`
    - But `%rsp` reserved for special use
    - Others have special uses for particular instructions
  - ***Memory:*** 8 consecutive bytes of memory at address given by register
    - Simplest example: `(%rax)`
    - Various other "addressing modes"

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder



Warning: Intel docs use mov *Dest, Source*

movq Operand Combinations



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Cannot do memory-memory transfer with a single instruction

Simple Memory Addressing Modes

- **Normal (R) Mem[Reg[R]]**
  - Register R specifies memory address
  - Aha! Pointer dereferencing in C

Assignment Project Exam Help

```
movq (%rcx),%rax
```

https://powcoder.com

Add WeChat powcoder

- **Displacement D(R) Mem[Reg[R]+D]**
  - Register R specifies start of memory region
  - Constant displacement D specifies offset

```
movq 8(%rbp),%rdx
```

Example of Simple Addressing Modes

```
void
whatAmI(<type> a, <type> b)
{
      ????
}
```




```
whatAmI:
        movq    (%rdi), %rax
        movq    (%rsi), %rdx
        movq    %rdx, (%rdi)
        movq    %rax, (%rsi)
        ret
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Example of Simple Addressing Modes

```
void swap
    (long *xp, long *yp)
{
  long t0 = *xp;
  long t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
swap:
    movq    (%rdi), %rax
    movq    (%rsi), %rdx
    movq    %rdx, (%rdi)
    movq    %rax, (%rsi)
    ret
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Understanding Swap()

```
void swap
    (long *xp, long *yp)
{
  long t0 = *xp;
  long t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Register	Value
%rdi	xp
%rsi	yp
%rax	t0
%rdx	t1

```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Simple Memory Addressing Modes

- **Normal (R) Mem[Reg[R]]**
  - Register R specifies memory address
  - Aha! Pointer dereferencing in C

Assignment Project Exam Help

```
movq (%rcx),%rax
```

https://powcoder.com

Add WeChat powcoder

- **Displacement D(R) Mem[Reg[R]+D]**
  - Register R specifies start of memory region
  - Constant displacement D specifies offset

```
movq 8(%rbp),%rdx
```

Complete Memory Addressing Modes

- **Most General Form**

  D(Rb,Ri,S) **Mem[Reg[Rb]+S*Reg[Ri]+ D]**

  - D: Constant "displacement" 1, 2, or 4 bytes
  - Rb: Base register: Any of 16 integer registers
  - Ri: Index register: Any, except for `%rsp`
  - S: Scale: 1, 2, 4, or 8 (*why these numbers?*)

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Special Cases**

  (Rb,Ri) **Mem[Reg[Rb]+Reg[Ri]]**

  D(Rb,Ri) **Mem[Reg[Rb]+Reg[Ri]+D]**

  (Rb,Ri,S) **Mem[Reg[Rb]+S*Reg[Ri]]**

Address Computation Examples

%rdx	0xf000
%rcx	0x0100

D(Rb,Ri,S) **Mem[Reg[Rb]+S*Reg[Ri]+ D]**

- D: Constant "displacement" 1, 2, or 4 bytes
- Rb: Base register: Any of 16 integer registers
- Ri: Index register: Any, except for %rsp
- S: Scale: 1, 2, 4, or 8 (*why these numbers?*)

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Expression	Address Computation	Address
0x8(%rdx)		
(%rdx,%rcx)		
(%rdx,%rcx,4)		
0x80(,%rdx,2)		

Address Computation Examples

%rdx	0xf000
%rcx	0x0100

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Expression	Address Computation	Address
0x8(%rdx)	0xf000 + 0x8	0xf008
(%rdx,%rcx)	0xf000 + 0x100	0xf100
(%rdx,%rcx,4)	0xf000 + 4*0x100	0xf400
0x80(,%rdx,2)	2*0xf000 + 0x80	0x1e080

Today: Machine Programming I: Basics

- History of Intel processors and architectures
- Assembly Basics: Registers, operands, move
- **Arithmetic & logical operations**
- C, assembly, machine code

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Address Computation Instruction

- **`leaq` *Src*, *Dst***
  - *Src* is address mode expression
  - Set *Dst* to address denoted by expression

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Uses**
  - Computing addresses without a memory reference
    - E.g., translation of `p = &x[i];`
  - Computing arithmetic expressions of the form x + k*y
    - k = 1, 2, 4, or 8
- **Example**

```
long m12(long x)
{
  return x*12;
}
```

Converted to ASM by compiler:

```
leaq (%rdi,%rdi,2), %rax  # t = x+2*x
salq $2, %rax             # return t<<2
```

Some Arithmetic Operations

- **Two Operand Instructions:**

Format	*Computation*		
`addq`	*Src,Dest*	Dest = Dest + Src	
`subq`	*Src,Dest*	Dest = Dest – Src	
`imulq`	*Src,Dest*	Dest = Dest * Src	
`shlq`	*Src,Dest*	Dest = Dest << Src	***Synonym: salq***
`sarq`	*Src,Dest*	Dest = Dest >> Src	***Arithmetic***
`shrq`	*Src,Dest*	Dest = Dest >> Src	***Logical***
`xorq`	*Src,Dest*	Dest = Dest ^ Src	
`andq`	*Src,Dest*	Dest = Dest & Src	
`orq`	*Src,Dest*	Dest = Dest | Src	

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Watch out for argument order! *Src,Dest***
  (Warning: Intel docs use "op *Dest,Src*")
- **No distinction between signed and unsigned int (why?)**

Quiz Time!

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Check out:

https://canvas.cmu.edu/courses/17808

Some Arithmetic Operations

- **One Operand Instructions**

`incq`	*Dest*	*Dest = Dest + 1*
`decq`	*Dest*	*Dest = Dest – 1*
`negq`	*Dest*	*Dest = – Dest*
`notq`	*Dest*	*Dest = ~Dest*

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **See book for more instructions**
  - Depending how you count, there are 2,034 total x86 instructions
  - (If you count all addr modes, op widths, flags, it's actually 3,683)

Arithmetic Expression Example

```
long arith
(long x, long y, long z)
{
  long t1 = x+y;
  long t2 = z+t1;
  long t3 = x+4;
  long t4 = y * 48;
  long t5 = t3 + t4;
  long rval = t2 * t5;
  return rval;
}
```

```
arith:
   leaq    (%rdi,%rsi), %rax
   addq    %rdx, %rax
   leaq    (%rsi,%rsi,2), %rdx
   salq    $4, %rdx
   leaq    4(%rdi,%rdx), %rcx
   imulq   %rcx, %rax
   ret
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Interesting Instructions

- **`leaq`**: address computation
- **`salq`**: shift
- **`imulq`**: multiplication
  - Curious: only used once…

Understanding Arithmetic Expression Example

```
long arith
(long x, long y, long z)
{
  long t1 = x+y;
  long t2 = z+t1;
  long t3 = x+4;
  long t4 = y * 48;
  long t5 = t3 + t4;
  long rval = t2 * t5;
  return rval;
}
```

```
arith:
   leaq    (%rdi,%rsi), %rax    # t1
   addq    %rdx, %rax           # t2
   leaq    (%rsi,%rsi,2), %rdx
   salq    $4, %rdx             # t4
   leaq    4(%rdi,%rdx), %rcx   # t5
   imulq   %rcx, %rax           # rval
   ret
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z, t4
%rax	t1, t2, rval
%rcx	t5

Today: Machine Programming I: Basics

- History of Intel processors and architectures
- Assembly Basics: Registers, operands, move
- Arithmetic & logical operations
- **C, assembly, machine code**

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder

Turning C into Object Code

- Code in files `p1.c p2.c`
- Compile with command: `gcc –Og p1.c p2.c -o p`
  - Use basic optimizations (`–Og`) [New to recent versions of GCC]
  - Put resulting binary in file `p`



Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Compiling Into Assembly

C Code (sum.c)

```
long plus(long x, long y);

void sumstore(long x, long y,
              long *dest)
{
    long t = plus(x, y);
    *dest = t;
}
```

Generated x86-64 Assembly

```
sumstore:
    pushq   %rbx
    movq    %rdx, %rbx
    call    plus
    movq    %rax, (%rbx)
    popq    %rbx
    ret
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Obtain (on shark machine) with command

```
gcc –Og –S sum.c
```

Produces file `sum.s`

***Warning*: Will get very different results on non-Shark machines (Andrew Linux, Mac OS-X, …) due to different versions of gcc and different compiler settings.**

What it really looks like

```
        .globl  sumstore
        .type   sumstore, @function
sumstore:
.LFB35:
        .cfi_startproc
        pushq   %rbx
        .cfi_def_cfa_offset 16
        .cfi_offset 3, -16
        movq    %rdx, %rbx
        call    plus
        movq    %rax, (%rbx)
        popq    %rbx
        .cfi_def_cfa_offset 8
        ret
        .cfi_endproc
.LFE35:
        .size   sumstore, .-sumstore
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

What it really looks like

```
        .globl  sumstore
        .type   sumstore, @function
sumstore:
.LFB35:
        .cfi_startproc
        pushq   %rbx
        .cfi_def_cfa_offset 16
        .cfi_offset 3, -16
        movq    %rdx, %rbx
        call    plus
        movq    %rax, (%rbx)
        popq    %rbx
        .cfi_def_cfa_offset 8
        ret
        .cfi_endproc
.LFE35:
        .size   sumstore, .-sumstore
```

Things that look weird and are preceded by a '.' are generally directives.

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

```
sumstore:
    pushq   %rbx
    movq    %rdx, %rbx
    call    plus
    movq    %rax, (%rbx)
    popq    %rbx
    ret
```

Assembly Characteristics: Data Types

- **"Integer" data of 1, 2, 4, or 8 bytes**
  - Data values
  - Addresses (untyped pointers)
- **Floating point data of 4, 8, or 10 bytes**
- **(SIMD vector data types of 8, 16, 32 or 64 bytes)**
- **Code: Byte sequences encoding series of instructions**
- **No aggregate types such as arrays or structures**
  - Just contiguously allocated bytes in memory

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Assembly Characteristics: Operations

- **Transfer data between memory and register**
  - Load data from memory into register
  - Store register data into memory

Assignment Project Exam Help

- **Perform arithmetic function on register or memory data**

https://powcoder.com

- **Transfer control**

Add WeChat powcoder

  - Unconditional jumps to/from procedures
  - Conditional branches

Object Code

Code for `sumstore`

```
0x0400595:
    0x53
    0x48
    0x89
    0xd3
    0xe8
    0xf2
    0xff
    0xff
    0xff
    0xff
    0x48
    0x89
    0x03
    0x5b
    0xc3
```

- **Total of 14 bytes**
- **Each instruction 1, 3, or 5 bytes**
- **Starts at address `0x0400595`**

- **Assembler**
  - Translates `.s` into `.o`
  - Binary encoding of each instruction
  - Nearly-complete image of executable code
  - Missing linkages between code in different files
- **Linker**
  - Resolves references between files
  - Combines with static run-time libraries
    - E.g., code for **`malloc`**, **`printf`**
  - Some libraries are *dynamically linked*
    - Linking occurs when program begins execution

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Machine Instruction Example

```
*dest = t;
```

```
movq %rax, (%rbx)
```

```
0x40059e:  48 89 03
```

- **C Code**
  - Store value **t** where designated by **dest**
- **Assembly**
  - Move 8-byte value to memory
    - Quad words in x86-64 parlance
  - Operands:
    - **t:** Register **%rax**
    - **dest:** Register **%rbx**
    - ***dest:** Memory **M[%rbx]**
- **Object Code**
  - 3-byte instruction
  - Stored at address **0x40059e**

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

Disassembling Object Code

Disassembled

```
0000000000400595 <sumstore>:
  400595:  53                   push   %rbx
  400596:  48 89 d3             mov    %rdx,%rbx
  400599:  e8 f2 ff ff ff       callq  400590 <plus>
  40059e:  48 89 03             mov    %rax,(%rbx)
  4005a1:  5b                   pop    %rbx
  4005a2:  c3                   retq
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Disassembler**

  `objdump -d sum`

  - Useful tool for examining object code
  - Analyzes bit pattern of series of instructions
  - Produces approximate rendition of assembly code
  - Can be run on either `a.out` (complete executable) or `.o` file

Alternate Disassembly

Disassembled

```
Dump of assembler code for function sumstore:
   0x0000000000400595 <+0>:  push   %rbx
   0x0000000000400596 <+1>:  mov    %rdx,%rbx
   0x0000000000400599 <+4>:  callq  0x400590 <plus>
   0x000000000040059e <+9>:  mov    %rax,(%rbx)
   0x00000000004005a1 <+12>: pop    %rbx
   0x00000000004005a2 <+13>: retq
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Within gdb Debugger**
  - Disassemble procedure

```
gdb sum
disassemble sumstore
```

Alternate Disassembly

Object Code

```
0x0400595:
    0x53
    0x48
    0x89
    0xd3
    0xe8
    0xf2
    0xff
    0xff
    0xff
    0x48
    0x89
    0x03
    0x5b
    0xc3
```

Disassembled

```
Dump of assembler code for function sumstore:
  0x0000000000400595 <+0>: push   %rbx
  0x0000000000400596 <+1>: mov    %rdx,%rbx
  0x0000000000400599 <+4>: callq  0x400590 <plus>
  0x000000000040059e <+9>: mov    %rax,(%rbx)
  0x00000000004005a1 <+12>:pop    %rbx
  0x00000000004005a2 <+13>:retq
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder

- **Within gdb Debugger**
  - Disassemble procedure

    `gdb sum`

    `disassemble sumstore`
  - Examine the 14 bytes starting at `sumstore`

    `x/14xb sumstore`

What Can be Disassembled?

```
% objdump -d WINWORD.EXE

WINWORD.EXE:     file format pei-i386

No symbols in "WINWORD.EXE".
Disassembly of section .text:

30001000 <.text>:
30001000:
30001001:
30001003:
30001005:
3000100a:
```

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder
Reverse engineering forbidden by
Microsoft End User License Agreement

- Anything that can be interpreted as executable code
- Disassembler examines bytes and reconstructs assembly source

Machine Programming I: Summary

- **History of Intel processors and architectures**
  - Evolutionary design leads to many quirks and artifacts
- **C, assembly, machine code**
  - New forms of visible state: program counter, registers, ...
  - Compiler must transform statements, expressions, procedures into low-level instruction sequences
- **Assembly Basics: Registers, operands, move**
  - The x86-64 move instructions cover wide range of data movement forms
- **Arithmetic**
  - C compiler will figure out different instruction combinations to carry out computation

Assignment Project Exam Help
https://powcoder.com
Add WeChat powcoder