

Assignment Project Exam Help

# Introduction

<https://powcoder.com>

CSC363: Computational Complexity and Computability

Add WeChat powcoder

*Mohammad Mahmoud*

This lecture is co-hosted by one of the TAs:

Paul Zhang  
Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- **Mohammad Mahmoud**



**Cairo University**  
BSc, 2010  
MSc, 2014

Assignment Project Exam Help

Ph.D, 2019  
<https://powcoder.com>



Post-doc

Master's of Statistics



# About the Course

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Course Outline

- You can find it at the Office of the Registrar Timetable page  
<https://student.utm.utoronto.ca/timetable/>  
**Assignment Project Exam Help**
- It includes all information regarding **Office hours, grading, and deadlines**  
<https://powcoder.com>  
**Add WeChat powcoder**
- Also includes a **course description, learning outcomes, and a list of references**

# Assessments

- 5 easy short quizzes (3% each): The first will be on Friday the 22<sup>nd</sup>
- 5 assignments (10% each): The first will be on Friday 29<sup>th</sup>  
<https://powcoder.com>  
Add WeChat powcoder
- No midterm
- No programming
- Final exam (35%). You need to score at least 40% on the exam itself.

Assignment Project Exam Help  
Computability  
<https://powcoder.com>

Add WeChat powcoder

# When we were kids

- Learned how to count: 1,2,3 ...

Assignment Project Exam Help

- Then, how to add + : through counting (oo + ooo = oooooo)  
<https://powcoder.com>

Add WeChat powcoder

- Later, how to multiply x: repeated addition



# It was computation (calculation)

Main characteristics:

Assignment Project Exam Help

- There is a procedure

<https://powcoder.com>

- There is some initial primitive operation/function (e.g. successor)

Add WeChat powcoder

# Now we are older

- Our procedures are now algorithms

Assignment Project Exam Help

- We build algorithms using some primitive functions

<https://powcoder.com>

- We compute functions using algorithms

Add WeChat powcoder

# Strong Intuition

- Most of the time we are comfortable with our intuitive understanding of what an **algorithm** is and what **computable** is.  
Assignment Project Exam Help
- Informally, an **algorithm** is a finite sequence of implementable instructions.  
<https://powcoder.com>  
Add WeChat powcoder
- A function is **computable** if there is an algorithm to compute it.

# Do we need formality?

- That moment when mathematicians realized that they were trying to find an algorithm to solve a problem which is unsolvable by an algorithm.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Hilbert's 10<sup>th</sup> Problem (H10)

- In 1900, David Hilbert published 23 problems. The 10<sup>th</sup> was:

Assignment Project Exam Help

*Given a Diophantine equation with any number of unknown quantities and with rational integral numerical coefficients: To devise a process according to which it can be determined in a finite number of operations whether the equation is solvable in rational integers.*

<https://powcoder.com>

Add WeChat powcoder

# H10 in modern terms

- Find an algorithm which, for any given Diophantine equation, it can decide whether the equation **has** a solution with all unknowns taking integer values.

Assignment Project Exam Help

<https://powcoder.com>

- Note that the algorithm here is meant to be general. In other words, it is the same for any given Diophantine equation.
- Also note that it does not even ask for finding a solution. Just decide if exists or not.

# 70 years after Hilbert's request

- The 23 year old Yuri Matiyasevich proved that THERE IS NO such algorithm

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Remarks

- Yuri just added the final touch to a work built by many others (Martin Davis, Hilary Putnam, and Julia Robinson).

Assignment Project Exam Help

- The feeling that the problem is unsolvable had been around since 1944

<https://powcoder.com>  
Add WeChat powcoder

- That feeling was declared by Emil Leon Post
- H10 is not the first problem of that kind, but it is one we can introduce at the moment without much background



# The need for formality

- Proving unsolvability by an algorithm requires a solid formulation of which processes we can accept as algorithms

Assignment Project Exam Help

- We should be able to create a list of all algorithms  $\{P_e: e \in N\}$   
(algorithms can be thought of as strings, the set of strings is countable)

<https://powcoder.com>

Add WeChat powcoder

- Then show that: for all  $e$ ,  $P_e$  does not solve the given problem.

# Formal Approaches

- One approach is formalizing the definition of *computable function* directly (Kurt Gödel)

Assignment Project Exam Help

- Another approach is “mechanical”: an algorithm is a computer program (Alan Turing, Emil Leon Post)

<https://powcoder.com>  
Add WeChat powcoder

- A computer here is an abstraction of how “any” computer works
- There are several such abstract computer models. We will discuss the Turing Machine in this course.

# Assignment Project Exam Help More about H10

<https://powcoder.com>

I will not be asking you details about this topic. The goal is the big picture and to introduce some knowledge which should ring a bell later in this course. Also to make you look things up and read around the topic.

That being said, many proofs will be omitted.

Some of the content will be hard at first, and that's ok. You will take your time later to digest it. It will grow your muscles.

# Diophantine Equations

- *Diophantine* refers to the mathematician Diophantus of Alexandria (3<sup>rd</sup> century)

Assignment Project Exam Help

- A Diophantine equation is a polynomial equation in more than one unknown in which all the coefficients are integers (in  $\mathbf{Z}$ ).

<https://powcoder.com>

Add WeChat powcoder

Recall:  $\mathbf{Z} = \{\dots, -3, -2, -1, 0, 1, 2, 3, \dots\}$

- We only care about integer solutions

# Diophantine Equations: Examples

- $3x^2 - 2xy - y^2z - 7 = 0$  has the following integer solution

$x=1, y=2, z=-2$   
Assignment Project Exam Help

Indeed,  $3(1)^2 - 2(1)(2) - (2)^2(-2) - 7 = 3 - 4 + 8 - 7 = 0$

<https://powcoder.com>

- $x^2 + y^2 + 1 = 0$  has no integer solutions

Add WeChat powcoder

Careful, this isn't the circle equation

# Diophantine Equation: General Form

- $p(a_1, \dots, a_k, x_1, \dots, x_l) = 0$

Assignment Project Exam Help

where  $p(\dots)$  stands for a polynomial function, the  $x_i$ 's can be the unknowns and the  $a_i$ 's can be some (or all) of the coefficients (parameters of particular interest).

<https://powcoder.com>

Add WeChat powcoder

Example:  $3x^2 - 2xy - y^2z - 7 = 0$  can be  $p(3, -2, -1, x, y, z) = 0$

where  $p(a_1, a_2, a_3, x, y, z) = a_1x^2 + a_2xy + a_3y^2z - 7$

- Or can be  $q(7, x, y, z) = 0$  where

Assignment Project Exam Help  
 $q(a, x, y, z) = 3x^2 - 2xy - y^2z - a$   
<https://powcoder.com>

- It can take many forms Add WeChat powcoder

# Diophantine Sets

- A Diophantine set is a subset  $S$  of  $N^k$  (tuples of natural numbers) for which there exists a Diophantine equation  $p(\bar{x}, \bar{y}) = 0$  such that

Assignment Project Exam Help

$$S = \{\bar{a} : (\exists \bar{m} \in N^l)(p(\bar{a}, \bar{m}) = 0)\}$$

Add WeChat powcoder

- Here  $\bar{x}$  is a tuple of unknowns of length  $k$ , and  $\bar{y}$  is a tuple of unknowns of length  $l$ . Also,  $N = \{0, 1, 2, \dots\}$ .
- We say  $S$  is definable by the formula  $\varphi(\bar{x}) = (\exists \bar{m})(p(\bar{x}, \bar{m}) = 0)$  in  $N$ .



# Diophantine Set: Example

- Consider the set

$$S = \{a \in \mathbb{N} : (\exists m_1, m_2 \in \mathbb{N})(m_1 m_2 + 2m_2 + 2m_1 + 4 - a = 0)\}$$

Assignment Project Exam Help

Here

<https://powcoder.com>

$$p(a, x, y) = xy + 2y + 2x + 4 - a = (x + 2)(y + 2) - a$$

Add WeChat powcoder

- $p(a, x, y) = 0$  iff  $a = (x + 2)(y + 2)$
- $S$  is exactly the set of numbers  $>2$  which are not prime.

- The set  $S$  is basically the set of parameter tuples  $\bar{a}$  for which the Diophantine equation  $p(\bar{a}, \bar{y}) = 0$  has a solution in the **natural** numbers

Assignment Project Exam Help

<https://powcoder.com>

- Recall that when we stated H10, we were talking about integer solutions (not natural)
- In fact, in the statement of H10, if we restrict the problem to finding natural solutions, then the version we get is still equivalent.

Add WeChat powcoder

# H10 (practical version)

- Find an algorithm which, for any given Diophantine equation, it can decide whether the equation has a solution with all unknowns taking natural values. **Assignment Project Exam Help**

<https://powcoder.com>

- Both versions are equivalent in the sense that, if you find an algorithm for one of them, then you can find an algorithm for the other. **Add WeChat powcoder**
- Proving the equivalence is omitted but not hard. It uses a handy fact called **Lagrange's four-square theorem**

# Lagrange's four-square theorem

- *Every natural number is the sum of the squares of four integers*

Assignment Project Exam Help

- Example:  $31 = 5^2 + 2^2 + 1^2 + 1^2$

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help  
Time to Recollect  
<https://powcoder.com>

Short break  
Add WeChat powcoder

# H10 and Diophantine sets

- There is the following connection between Diophantine sets and Hilbert's problem which is:

Assignment Project Exam Help

<https://powcoder.com>

The existence of an algorithm as mentioned in H10

Add WeChat **implies** powcoder

We can 'uniformly' decide membership for any Diophantine set

# Decidability

- We mean by that, there is an algorithm which when given any Diophantine set  $S$  (subset of  $N^k$  say), and any  $\bar{a} \in N^k$ , it can determine if  $\bar{a}$  belongs to  $S$  or not.

<https://powcoder.com>

- In general, a set is *decidable* if there is an algorithm that can decide its membership, e.g., the set of prime numbers.

# What Yuri did

- Yuri filled the last piece of proving that (known as MRDP theorem):

Assignment Project Exam Help

A set is Diophantine iff it is *listable*

<https://powcoder.com>

- Listable means there is an algorithm (program) that lists its elements. In other words, pops its elements one after the other.
- Listable is also known as *computably enumerable (c.e.)*



# Listable vs Decidable

- Every decidable set is listable (easy to prove)

Assignment Project Exam Help

- The converse is not true (easy once we formally settle the definition of an algorithm or that of a computable function)

<https://powcoder.com>  
Add WeChat powcoder

- In other words, there exists a set  $H$  which is listable but not decidable

Assignment Project Exam Help  
Let's trace things back  
<https://powcoder.com>

Add WeChat powcoder

- $H$  is listable but not decidable

Assignment Project Exam Help

- By MRDP,  $H$  is Diophantine but not decidable

<https://powcoder.com>

- The existence of a Diophantine set which is not decidable implies that  $H_{10}$  isn't solvable (Contra-positive).

Add WeChat powcoder

- There is the following connection between Diophantine sets and Hilbert's problem which is:

Assignment Project Exam Help

<https://powcoder.com>  
The existence of an algorithm as mentioned in H10

Add WeChat **implies** powcoder

We can 'uniformly' decide membership for any Diophantine set

Assignment Project Exam Help  
Done with the H10 story  
<https://powcoder.com>

Add WeChat powcoder

# Take this

- Formal Computability is either Gödel computability, or Turing computability. Both can be proved equivalent.
- Turing computability is mechanical: *An algorithm is a Turing Machine (TM)*
- A set is *listable* if it can be listed by a TM
- A set is *decidable* if a TM can decide its membership (compute its characteristic/indicator function)
- Every decidable set is listable but not the other way (intuitively kinda obvious, but the proof is through formal computability)
- This implies that H10 is unsolvable (by MRDP which particularly relies on Gödel computability)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Gödel Computability

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Recall again when we were little kids

- Counting: **successor** operation

Assignment Project Exam Help

- Then addition: repeating the successor

<https://powcoder.com>

- Multiplication: repeating addition

Add WeChat powcoder

- That repetition process can be generally seen as **recursion**



# Mimicking baby math

- Gödel decided to mimic early calculation

Assignment Project Exam Help

- Defined some basic initial functions

<https://powcoder.com>

- Then used some fundamental primitive rules to build with them

Add WeChat powcoder

# Initial Functions

1. The **zero function**:  $\mathbf{0}(n) = 0$  for every  $n$  in  $N$

2. The **successor function**:  $s(n) = n + 1$  for every  $n$  in  $N$   
<https://powcoder.com>

3. The **projection functions**:  $U_i^k$

The  $k$  indicates that its input is a tuple of length  $k$ , and  $i$  means it outputs the  $i$ -th component. More precisely,

$$U_i^k(\bar{m}) = m_i$$

# Reinforcing Intuition

- Note that those initial functions are directly computable by instinct

Assignment Project Exam Help

- The zero function is like erasing, nothingness

<https://powcoder.com>

- The successor is what takes us from nothing to something

Add WeChat powcoder

- The projection is literally choice, ability to distinguish

Assignment Project Exam Help  
What could be simpler?!  
<https://powcoder.com>

Beautiful!  
Add WeChat powcoder

# Primitive Recursive Functions (PRIM)

- Now it is time to build more complex functions
- We think like induction
- Initial Functions are the base
- Assume we have a bunch of functions that have been built
- We describe how to use the latter to build the next ones (one step more complex)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder