

Time Complexity

Assignment Project Exam Help

<https://powcoder.com>

Co-hosted by Paul

Add WeChat powcoder

Time Complexity Class

- Let $f: \mathbb{N} \rightarrow \mathbb{R}^+$ be a function. Define the time complexity class $TIME(f(n))$ to be the collection of all languages that are decidable by an $O(f(n))$ Turing Machine.

Assignment Project Exam Help

<https://powcoder.com>

- The class above is a class of languages. Does this seem to cause loss of generality?
- For example, the sorting problem (or function), can it be regarded as a language?

Add WeChat powcoder

Languages are general enough

- Let's look at the sorting example. Let Sort be the machine that does the sorting

Assignment Project Exam Help

- Sort is a function that takes a tuple as input and outputs a tuple of the same size

<https://powcoder.com>

Add WeChat powcoder

- As we learnt before, a function is a set of ordered pairs. Here, Sort is a subset of $\mathbb{N}^* \times \mathbb{N}^*$.

Every function problem can be turned into a decision problem

- Suppose we are given a tuple $\bar{x} = (x_1, \dots, x_n)$ and that we want to compute $\text{Sort}(\bar{x})$.

Assignment Project Exam Help

- \mathbb{N}^* is c.e., and so we can computably list it, say: $(\bar{y})_1, (\bar{y})_2, \dots$

<https://powcoder.com>

Add WeChat powcoder

- And keep checking: is $(\bar{x}, (\bar{y})_1) \in \text{Sort}$?, is $(\bar{x}, (\bar{y})_2) \in \text{Sort}$?, ... until one of them is Yes

Vice versa

- Every decision problem is a function problem. Why?

Assignment Project Exam Help

- Answer: the characteristic function

<https://powcoder.com>

Add WeChat powcoder

- Note that the transition from a function problem to a decision problem does not necessarily preserve the TIME complexity class

Assignment Project Exam Help

- Function Problem: Consider a machine ~~Solver~~ which can take an equation as an input (say quadratic equations), and outputs solutions.
- Decision Problem: Given an equation and a value x , decide whether x is a solution for the equation or not.

Sort again (thoughts)

- When we listed $(\bar{y})_1, (\bar{y})_2, \dots$ one may chose to do that smartly so the sorted tuple shows up faster

Assignment Project Exam Help

- For example, we could only list tuple of length n

<https://powcoder.com>

Add WeChat powcoder

- With a deeper look, finding a smart way to list the tuples is a process that has its own running time

Assignment Project Exam Help

Break

<https://powcoder.com>

Hope we are comfortable with the fact that complexity theory is developed through decision problems

Add WeChat powcoder

The class P

- $P = \{L: L \text{ is a language decidable by some polytime TM}\}$

Assignment Project Exam Help

- Note that $P = \bigcup_k TIME(n^k)$
<https://powcoder.com>

Add WeChat powcoder

- Why is
$$\bigcup_{k \in \mathbb{N}} TIME(n^k) = \{L: L \text{ is a language decidable by some polytime TM}\}$$

How do we prove equality of sets?

- \subseteq :

Let L be an arbitrary language from $\bigcup_{k \in \mathbb{N}} TIME(n^k)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- \supseteq

Let L be an arbitrary language decidable by some polytime TM

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

The *PATH* problem

- Given a directed graph G and two nodes s, t in G . Consider the following question: Is there a path from s to t ?

Assignment Project Exam Help

- $PATH =$
 $\{(G, s, t): G \text{ is a directed graph that has a directed path from } s \text{ to } t\}$

<https://powcoder.com>

Add WeChat powcoder

- This set (or relation) *PATH* is an example of what we mean by a problem in the context of complexity

Unfolding *PATH*

- The question we first asked is equivalent to the following decision problem

Assignment Project Exam Help
Is $(G, s, t) \in \text{PATH}$?

<https://powcoder.com>

- This question unfolds into:
Add WeChat powcoder
Is G a directed graph?
Are s, t vertices in G ?

Is there a number n , and vertices v_1, v_2, \dots, v_n such that the edges $(s, v_1), (v_1, v_2), \dots, (v_n, t)$ are edges in G ?